

GitHub Tasks.

1. Create a GitHub account.

The screenshot shows a GitHub repository page for 'Spider-Man-01' by user 'mohdparvez1407-ops'. The repository is public and has 1 branch and 0 tags. The commit history shows 3 commits. The files listed are 'a', 'abc', 'b', 'wow', and 'zp', each with a description of the commit and the time it was made.

File	Commit Message	Time
a	added coouple of files	yesterday
abc	added a file abc	18 hours ago
b	added coouple of files	yesterday
wow	added wow file	yesterday
zp	added coouple of files	yesterday

2. Set up MFA (Multi-Factor Authentication) for the GitHub account using a mobile app.

Two-factor authentication (2FA) is now enabled for your GitHub account



You have enabled two-factor authentication using your authenticator app.

Don't get locked out, configure additional authentication methods

Configuring additional authentication methods will help you gain access to your account in case you lose your device and don't have your recovery codes.



Passkeys

Passkeys are webauthn credentials that validate your identity using touch, facial recognition, a device password, or a PIN. They can be used as a password replacement or as a 2FA method.

Add a passkey →



Security keys

Use your device with Touch ID, Windows Hello, etc. or a physical security key (e.g. YubiKey)

Manage



GitHub Mobile

Two-factor authentication

...

Two-factor authentication adds an additional layer of security to your account by requiring more than just a password to sign in. [Learn more about two-factor authentication.](#)

Preferred 2FA method

Set your preferred method to use for two-factor authentication when signing into GitHub.

Authenticator app ↕

Two-factor methods



Authenticator app Configured

Edit

Use an authentication app or browser extension to get two-factor authentication codes when prompted.



SMS/Text message Less secure

Add

Get one-time codes sent to your phone via SMS to complete authentication requests. We strongly advise against using SMS because it is susceptible to interception, does not provide resistance against phishing attacks, and deliverability can be unreliable. It is recommended to use an Authenticator app instead of SMS.

3. Execute all commands shown in the video.

1. Checks the installed Git version.

```
USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app
$ git --version
git version 2.37.1.windows.1

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app
$
```

2. git status → Checks the current working directory and staging area status.

```
USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app
$ git status
fatal: not a git repository (or any of the parent directories): .git

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app
$ |
```

4. Initializes a Git repository in the current directory.

```
USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ ls -a
./ ../ .git/ Dockerfile.txt

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ |
```

5. git config -l → Displays all Git configuration settings.

```
USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git init
Reinitialized existing Git repository in C:/Users/USER/Desktop/hiring-app/.git/

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ ls -a
/  ../ .git/ Dockerfile.txt

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git config -l
git: 'config' is not a git command. See 'git --help'.

The most similar command is
    config

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git config -l
diff.astextplain.textconv=astextplain
filter.lfs.clean=git-lfs clean -- %f
filter.lfs.smudge=git-lfs smudge -- %f
filter.lfs.process=git-lfs filter-process
filter.lfs.required=true
http.sslbackend=openssl
http.sslcainfo=C:/Program Files/Git/mingw64/ssl/certs/ca-bundle.crt
core.autocrlf=true
core.fscache=true
core.symlinks=false
pull.rebase=false
credential.helper=manager-core
credential.https://dev.azure.com.usehttppath=true
init.defaultbranch=master
user.name=mohdparvez1407-ops
user.email=mohdparvez1407@gmail.com
core.repositoryformatversion=0
core.filemode=false
core.bare=false
core.logallrefupdates=true
core.symlinks=false
core.ignorecase=true

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ |
```

6. git config --global user.name "Your Name" → Sets your Git username globally.

7. git config --global user.email [your@email.com](#)

8. git add → Stages files for commit.

```

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git status
On branch master

No commits yet

Untracked files:
  (use "git add <file>..." to include in what will be committed)
      Dockerfile.txt
      a

nothing added to commit but untracked files present (use "git add" to track)

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git add ^C

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git add Dockerfile.txt a

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git status
On branch master

No commits yet

Changes to be committed:
  (use "git rm --cached <file>..." to unstage)
      new file:   Dockerfile.txt
      new file:   a

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$

```

9. git reset → Unstages changes from the staging area.

```

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git reset

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git status
On branch master

No commits yet

Untracked files:
  (use "git add <file>..." to include in what will be committed)
      Dockerfile.txt
      a

nothing added to commit but untracked files present (use "git add" to track)

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ |

```

10. git commit -m "message" → Creates a commit with a message.

```
USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git status
On branch master

No commits yet

Changes to be committed:
  (use "git rm --cached <file>..." to unstage)
        new file:   Dockerfile.txt
        new file:   a
        new file:   b
        new file:   c
        new file:   d

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git commit -m "added files"
[master (root-commit) 8b05b73] added files
 5 files changed, 0 insertions(+), 0 deletions(-)
 create mode 100644 Dockerfile.txt
 create mode 100644 a
 create mode 100644 b
 create mode 100644 c
 create mode 100644 d

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git status
On branch master
nothing to commit, working tree clean

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$
```

11. git log → Displays the commit history.

```
USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git log
commit 8b05b737b997553fd80c0184c877b8b8cbad2aa0 (HEAD -> master)
Author: mohdparvez1407-ops <mohdparvez1407@gmail.com>
Date:   Mon Sep 21 14:21:03 2026 +0530

    added files

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$
```

12. git push -u origin master → Pushes master to GitHub.

13. git remote add origin <URL> → Adds a GitHub remote repository named origin.

14.git remote

```
USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git push -u origin master
Enumerating objects: 3, done.
Counting objects: 100% (3/3), done.
Delta compression using up to 8 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (3/3), 235 bytes | 235.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0
To github.com:mohdparvez1407-ops/Hulk-01.git
 * [new branch]      master -> master
branch 'master' set up to track 'origin/master'.
```

```
USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git remote add origin git@github.com:mohdparvez1407-ops/Hulk-01.git

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git remote -v
origin  git@github.com:mohdparvez1407-ops/Hulk-01.git (fetch)
origin  git@github.com:mohdparvez1407-ops/Hulk-01.git (push)

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git push -u origin master
Enumerating objects: 3, done.
Counting objects: 100% (3/3), done.
Delta compression using up to 8 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (3/3), 235 bytes | 235.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0
To github.com:mohdparvez1407-ops/Hulk-01.git
 * [new branch]      master -> master
branch 'master' set up to track 'origin/master'.

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ |
```

15.git pull → Gets the latest changes from the remote repository.

```

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git pull
remote: Enumerating objects: 4, done.
remote: Counting objects: 100% (4/4), done.
remote: Compressing objects: 100% (2/2), done.
remote: Total 3 (delta 1), reused 0 (delta 0), pack-reused 0 (from 0)
Unpacking objects: 100% (3/3), 931 bytes | 103.00 KiB/s, done.
From github.com:mohdparvez1407-ops/Hulk-01
   8b05b73..1c06c89  master    -> origin/master
Updating 8b05b73..1c06c89
Fast-forward
 new-file | 1 +
 1 file changed, 1 insertion(+)
 create mode 100644 new-file

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ ls
a  b  c  d  new-file

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git push -u origin master
Everything up-to-date
branch 'master' set up to track 'origin/master'.

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git status
On branch master
Your branch is up to date with 'origin/master'.

Changes not staged for commit:
  (use "git add/rm <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        deleted:    Dockerfile.txt

no changes added to commit (use "git add" and/or "git commit -a")

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git add Dockerfile.txt

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git commit -m "message"
[master 30d8876] message
 1 file changed, 0 insertions(+), 0 deletions(-)
 delete mode 100644 Dockerfile.txt

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git push
Enumerating objects: 3, done

```

16. git clone → Copies a remote Git repository to your local system.

```

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git clone git@github.com:mohdparvez1407-ops/Hulk-01.git
Cloning into 'Hulk-01'...
remote: Enumerating objects: 8, done.
remote: Counting objects: 100% (8/8), done.
remote: Compressing objects: 100% (5/5), done.
remote: Total 8 (delta 2), reused 5 (delta 1), pack-reused 0 (from 0)
Receiving objects: 100% (8/8), done.
Resolving deltas: 100% (2/2), done.

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ ls
Hulk-01/  a  b  c  d  new-file

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ cd hiring-app
bash: cd: hiring-app: No such file or directory

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ cd Hulk-01/

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app/Hulk-01 (master)
$ ls
a  b  c  d  new-file

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app/Hulk-01 (master)
$ |

```

```

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git clone git@github.com:mohdparvez1407-ops/Hulk-01.git
Cloning into 'Hulk-01'...
remote: Enumerating objects: 8, done.
remote: Counting objects: 100% (8/8), done.
remote: Compressing objects: 100% (5/5), done.
remote: Total 8 (delta 2), reused 5 (delta 1), pack-reused 0 (from 0)
Receiving objects: 100% (8/8), done.
Resolving deltas: 100% (2/2), done.

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ ls
Hulk-01/  a  b  c  d  new-file

USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ |

```

17. git revert → Undoes a commit by creating a new commit.

```
USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ git clone git@github.com:mohdparvez1407-ops/Hulk-01.git
Cloning into 'Hulk-01'...
remote: Enumerating objects: 8, done.
remote: Counting objects: 100% (8/8), done.
remote: Compressing objects: 100% (5/5), done.
remote: Total 8 (delta 2), reused 5 (delta 1), pack-reused 0 (from 0)
Receiving objects: 100% (8/8), done.
Resolving deltas: 100% (2/2), done.
```

```
USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ ls
Hulk-01/  a  b  c  d  new-file
```

```
USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ cd hiring-app
bash: cd: hiring-app: No such file or directory
```

```
USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app (master)
$ cd Hulk-01/
```

```
USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app/Hulk-01 (master)
$ ls
a  b  c  d  new-file
```

```
USER@DESKTOP-NTBFNKM MINGW64 ~/Desktop/hiring-app/Hulk-01 (master)
$ |
```