


FARO BLINK
AMETEK

From Site to Insights, in a BLINK



↑
9' 11 ⁷/₈"

←→
18' 1 ⁵/₈"



Reality capture for everyone through automated workflows, stunning visuals, and one touch to insights.

Take Control of Reality Capture with Blink

Whether you're in construction, facility management, or surveying, Blink is the affordable, effective, and easy-to-use solution you need to get the job done — accurately and quickly.



Specifications

GENERAL	
Manufacturer Warranty	1 year
Accessories	The Blink Mobility Kit provides a tripod, a QuickMount, a backpack and a QuadLock phone mount kit, specifically designed to deliver best mobility and efficiency
PERFORMANCE	
Data Acquisition	HDR color scans in less than 30 s per position
3D Point Accuracy	4 mm @ 10 m (0.16 in @ 32.8 ft)
Fully Automatic Leveling	0.3 mm over 1 m (0.012 in over 3.28 ft)
IMAGING	
Panoramic Camera System	Dual on-axis HDR camera system with 25 MPx resolution Provides 125 MPx raw image resolution
SCANNING	
Laser Class	Laser Class 1
Field of View	300° vertical / 360° horizontal
Range	0.5 m – 80 m (1.64 ft - 262.5 ft)
3D Points Per Scan	Up to 50 MPts
OPERATION	
Stand-Alone Operation	One-button scan operation
Real Time Position Tracking	Always know where to capture the next scan
Mobile Devices	FARO Stream App for iOS and Android Guides the user through a successful on-site workflow and provides direct sync to cloud processing with FARO Sphere® XG

DATA PROCESSING	
Internal Memory	Up to 1,500 scan positions
Data Transfer	WiFi (2.4 GHz and 5 GHz) USB-C to store data on a thumb drive (high speed thumb drive included)
Desktop Software	FARO SCENE for advanced processing and registration needs
Cloud Software	Fully automated with FARO Sphere XG
POWER	
Power Supply	14.4 V (internal battery)
Capacity	Typical Battery Operation Time: About 3 hours 3 batteries included for a full day of data capture
Battery Charge Time	< 3h
PHYSICAL	
Dimensions	280 mm x 115 mm x 225 mm (11 in x 4.5 in x 8.9 in)
Weight	3.7 kg (8.2 lbs, including battery)
ENVIRONMENTAL	
Operating Temperature	+5°C to +40°C (41°F to 104°F)
Storage Temperature	-10°C to +60°C (14°F to 140°F)
Dust / Humidity	IP 54 / non-condensing

All accuracy specifications are standard deviations, after warm-up and within operating temperature range; unless otherwise noted. Subject to change without prior notice.



FARO / AMETEK
Authorized Distributor

sales@3dgeoscan.com
www.3dgeoscan.com
(+20) 4290191 - 4290192
+20 1050037275
Smouha, Alexandria