Literature Survey Report

CROSS-SPECTRAL DSMAC

Directorate of Artificial Intelligence & Visualisation
Research Centre Imarat (RCI), DRDO
&
Department of Computer Science
Defence Institute of Advanced Technology (DIAT)

Presented by
Mohineet Kaur (25-26-08)
M. Tech (Artificial Intelligence)

Guides
Prof. CRS Kumar
A. Kalidasu (Scientist-F)

1. Title

Lightweight Cross-Modal (RGB–SAR) Scene Matching for Edge Deployment in Cross-Spectral DSMAC.

2. Synopsis

Digital Scene Matching Area Correlation (DSMAC) is a vision-based navigation technique that estimates a vehicle's position by matching onboard sensor imagery with reference maps or stored scene information. It is important for GPS-denied environments because it enables autonomous localization without relying on satellite navigation. The presentation motivates the use of multiple sensing modalities, including RGB and Synthetic Aperture Radar (SAR), to improve robustness under changing environmental and illumination conditions.

The surveyed literature shows a progression from conventional area-based DSMAC correlation to learned feature representations and Transformer-based matching. LoFTR introduced detector-free coarse-to-fine correspondence estimation; Efficient LoFTR addressed computational efficiency; XoFTR extended detector-free matching to visible–thermal cross-modal imagery; Chen et al. addressed SAR–optical registration with co-attention; MatchAnything explored general cross-domain association using segmentation foundation models; and DistillMatch demonstrated knowledge-distillation strategies for lightweight multimodal representation learning.

The proposed research direction is a lightweight RGB–SAR matcher for edge/onboard DSMAC. A strong teacher matcher, based on the MatchAnything–ELoFTR pipeline, is used to establish correspondence quality, after which knowledge is intended to be distilled into a compact student matcher. The final framework is intended to perform matching, geometric verification, position estimation and geolocation while balancing accuracy and computational efficiency.

3. Literature Review

The literature review focuses on methodology/pipeline, principal contribution, limitations and relevance to the proposed RGB–SAR DSMAC problem.

Paper / Year	Methodology / Pipeline	Contribution	Limitations / Gap	Relevance
LoFTR [4] (2021)	CNN features → Transformer self/cross-attention → coarse matching → fine refinement.	Detector-free dense correspondence; effective in low-texture regions.	Computationally intensive; not specifically designed for SAR–optical matching.	Foundation for detector-free matching.
Efficient LoFTR [5] (2024)	CNN → adaptive token selection → efficient Transformer → coarse-to-fine matching.	Improves LoFTR efficiency while retaining strong matching performance.	Still not SAR–RGB specific; Transformer computation remains.	Motivates efficiency-oriented matching.
XoFTR [6] (2024)	Multi-scale CNN → coarse matching → fine matching → sub-pixel refinement.	Extends detector-free matching to visible–thermal cross-modal imagery.	Demonstrated on visible–thermal, not SAR–RGB; no DSMAC localization.	Cross-modal detector-free precedent.
Chen et al. [7] (2023)	DCNN → dense features → CAMM → keypoints/descriptors → matching.	Pair-based SAR–optical registration with modality-aware co-attention.	Keypoint-based and training-dependent; not a complete DSMAC pipeline.	Direct SAR–optical precedent.
MatchAnything [8] (2024)	SAM → object/region proposals → feature learning → cross-domain association.	Generalizable cross-domain visual association using segmentation foundation models.	Designed for object association/tracking, not geometric image registration.	Candidate strong teacher/foundation.
DistillMatch [9] (2024)	VFM teacher → lightweight student → modality information injection → augmentation → matching.	Knowledge distillation for robust cross-modal features with modality-specific information.	Primarily evaluated on visible/infrared-type multimodal data.	Motivates compact student learning.

The main gap identified from the survey is the absence of a lightweight, practical RGB–SAR scene-matching pipeline that simultaneously provides robust cross-modal correspondence, geometric verification and DSMAC-oriented geolocation while meeting edge-deployment constraints.

4. Problem Statement

Reliable scene matching is a critical component of DSMAC navigation in GPS-denied environments. Direct RGB–SAR matching is challenging because the two sensors have substantially different imaging characteristics. Existing methods provide strong solutions for conventional optical matching, visible–thermal cross-modal matching, SAR–optical registration and general cross-domain association, but they do not directly provide a lightweight end-to-end RGB–SAR DSMAC localization solution.

The research problem is therefore to develop a computationally efficient cross-modal RGB–SAR scene matcher capable of producing reliable correspondences, geometrically verifying them and converting the matched scene location into a position estimate suitable for edge/onboard deployment.

5. Objectives

1. Establish a robust RGB–SAR scene-matching and geolocation evaluation pipeline for DSMAC.
2. Evaluate a strong pretrained teacher matcher based on MatchAnything–ELoFTR on geographically aligned RGB–SAR imagery.
3. Develop a compact student matcher through knowledge distillation from the teacher.
4. Preserve cross-modal correspondence and modality-specific information while reducing model complexity and inference latency.
5. Integrate RANSAC-based geometric verification and estimate scene position from the matched patch.
6. Evaluate accuracy, repeatability, correspondence quality, localization error and computational efficiency.
7. Benchmark the resulting student model for edge/onboard deployment.

6. Approach

6.1 Overall Research Strategy

The proposed approach follows a teacher–student framework. A high-capability MatchAnything–ELoFTR teacher is first evaluated/fine-tuned on geographically aligned RGB–SAR data. Its correspondence knowledge is then transferred to a compact student model. The student is trained using supervised and distillation losses, with spatially separate training and testing regions.

6.2 Inference Pipeline

- Input georeferenced RGB and SAR imagery.
- Common ground-resolution alignment, normalization and SAR no-data masking.
- Cross-modal correspondence extraction by the matcher.
- Geometric verification using RANSAC and an inlier-count accept/reject criterion.
- Conversion of the matched patch centre from image coordinates to geographic coordinates.
- Calculation of pixel and geodesic localization error.
- Deployment of the compact student matcher for edge inference.

6.3 Training Pipeline

- Prepare spatially aligned RGB–SAR training pairs.
- Preprocess using common ground resolution, normalization and no-data masking.

- Fine-tune/evaluate the teacher matcher.
- Train the student using supervised loss plus distillation loss.
- Replace the teacher matcher with the compact student during inference.
- Compress/optimize the model and benchmark it on an edge device.

7. Proposed Steps for Implementation

7.1 Dataset and Geospatial Preparation

- ICEYE SAR imagery and Google RGB imagery are used.
- Common geographic coverage is established between the modalities.
- SAR imagery is resampled to the RGB grid.
- CRS and georeferencing are verified.
- SAR no-data regions are masked and percentile normalization is applied.

7.2 Patch Generation

- Generate geographically co-located SAR–RGB patches.
- Use 2048 × 2048 patches for MatchAnything experiments.
- Use smaller patches during student-model experiments.
- Maintain a spatial training/holdout split.

7.3 Baseline Matcher and Geolocation

- Use MatchAnything–ELoFTR as the baseline cross-modal matcher.
- Use sliding RGB search windows where required.
- Perform similarity/affine geometric verification using RANSAC.
- Convert predicted RGB patch centres into latitude/longitude.
- Report matches, inliers, pixel error and localization error.

7.4 Next Implementation Stages

The presentation identifies RGB–SAR student-pair construction, distillation training and edge optimization as the next implementation stages. The planned edge benchmark includes latency, parameter count, accuracy, NN-mAP, repeatability and corner-loss error, with the student compared against the teacher.

8. Preliminary Results

8.1 MatchAnything–ELoFTR

A preliminary RGB–SAR experiment produced a successful localization estimate on the tested scene. The reported SAR centre was approximately latitude 37.32859617 and longitude −6.00007932. The predicted RGB centre produced a localization error of 25.81 pixels, corresponding to approximately 15.44 m. The presentation uses a 10 m threshold as the reference threshold.

8.2 Comparison with Other Matchers

ELoFTR alone produced no reliable match for the reported irrelevant scene; the presentation attributes this to the fact that ELoFTR is not inherently designed for cross-modality matching. SIFT, ORB and RIFT also produced no reliable match in the reported test, with the presentation noting that handcrafted local features lack modality-invariant descriptors.

8.3 Interpretation

The preliminary experiment demonstrates the feasibility of an RGB–SAR matching and geolocation pipeline. However, the reported 15.44 m error is above the 10 m reference threshold. Therefore, the result should be treated as a baseline rather than final DSMAC performance. It motivates the development of a dedicated lightweight SAR–RGB matcher.

9. Summary

- DSMAC provides vision-based localization for GPS-denied environments.
- RGB and SAR can provide complementary information under changing conditions.
- Modern learned matching methods provide stronger correspondence capabilities than conventional handcrafted methods, but cross-modal robustness and efficiency remain challenging.
- MatchAnything–ELoFTR provides a practical baseline for RGB–SAR matching and geolocation evaluation.
- The preliminary test produced a 15.44 m localization error on the reported scene.
- The next stage is a lightweight student matcher trained through knowledge transfer from a strong teacher.
- Final evaluation will emphasize the accuracy–efficiency trade-off required for edge/onboard deployment.

10. Conclusion

The literature survey shows that modern learned feature matching has advanced from conventional image correlation toward detector-free Transformers, modality-aware matching and knowledge transfer. Nevertheless, a gap remains between high-capability general-purpose matchers and the practical requirements of lightweight RGB–SAR DSMAC.

The proposed research addresses this gap through a teacher–student framework in which a strong MatchAnything–ELoFTR matcher supplies correspondence knowledge and a compact student is trained for RGB–SAR matching. The preliminary implementation establishes the feasibility of the matching and geolocation pipeline, while the 15.44 m error indicates that further work is required to reach the 10 m reference target. The intended outcome is a practical accuracy–efficiency trade-off suitable for edge/onboard deployment.

11. References

[1] J. R. Carr and J. S. Sobek, “Digital Scene Matching Area Correlator (DSMAC),” Proc. SPIE 0238, Image Processing for Missile Guidance, 1980, pp. 36–41. doi: 10.1117/12.959130.

[2] G. B. Irani and J. P. Christ, “Image processing for Tomahawk scene matching,” Johns Hopkins APL Technical Digest, vol. 15, no. 3, pp. 250–264, 1994.

[3] S. Kashyap, J. Shivamurthy, and C. R. S. Kumar, “ML Based Solution for DSMAC System in Aerial Navigation,” Springer, 2026, ch. 23.

[4] J. Sun, Z. Shen, Y. Wang, H. Bao, and X. Zhou, “LoFTR: Detector-Free Local Feature Matching with Transformers,” Proc. IEEE/CVF CVPR, 2021, pp. 8922–8931. doi: 10.1109/CVPR46437.2021.00882.

[5] Y. Wang, X. He, S. Peng, D. Tan, and X. Zhou, “Efficient LoFTR: Semi-Dense Local Feature Matching with Sparse-Like Speed,” Proc. IEEE/CVF CVPR, 2024. doi: 10.1109/CVPR52733.2024.02047.

[6] Ö. Tuzcuoğlu, A. Köksal, B. Sofu, S. Kalkan, and A. A. Alatan, “XoFTR: Cross-modal Feature Matching Transformer,” Proc. IEEE/CVF CVPR Workshops, 2024, pp. 4275–4286. doi: 10.1109/CVPRW63382.2024.00431.

[7] J. Chen, H. Xie, L. Zhang, J. Hu, H. Jiang, and G. Wang, “SAR and Optical Image Registration Based on Deep Learning with Co-Attention Matching Module,” Remote Sensing, vol. 15, no. 15, p. 3879, 2023. doi: 10.3390/rs15153879.

[8] S. Li et al., “Matching Anything by Segmenting Anything,” Proc. IEEE/CVF CVPR, 2024, pp. 18963–18973. doi: 10.1109/CVPR52733.2024.01794.

[9] C. Wang, B. Zhao, and Z. Liu, “DistillMatch: Revisiting Self-Knowledge Distillation in Semi-Supervised Medical Image Segmentation,” Proc. IEEE International Conference on Bioinformatics and Biomedicine, 2024, pp. 3778–3783. doi: 10.1109/BIBM62325.2024.10821816.

[10] ICEYE, “ICEYE Synthetic Aperture Radar (SAR) Open Dataset,” ICEYE Open Data Catalog via AWS. Accessed Oct. 6, 2026.

[11] X. Yu, C. Jinyang, H. Zhonghua, et al., “OSDataset2.0: Optical-SAR Image Matching Dataset and Evaluation Benchmark,” Science Data Bank, 2025/2026.

[12] A. A. Neeralgi, R. R. Avarsekar, M. Bhajantri, R. Khatod, U. Kulkarni, and S. M. Nadaf, “Knowledge Distillation Using Deep Learning Techniques: A Survey,” Proc. IEEE Conference on Engineering Informatics, 2024, pp. 1–10. doi: 10.1109/ICEI64305.2024.10912425.

[13] F. Guo, J. Yang, Y. Chen, and B. Yao, “Research on image detection and matching based on SIFT features,” Proc. 3rd International Conference on Control and Robotics Engineering, 2018, pp. 130–134. doi: 10.1109/ICCRE.2018.8376448.

[14] E. Rublee, V. Rabaud, V. Konolige, and G. Bradski, “ORB: An efficient alternative to SIFT or SURF,” Proc. IEEE ICCV, 2011, pp. 2564–2571. doi: 10.1109/ICCV.2011.6126544.

[15] J. Li, Q. Hu, and M. Ai, “RIFT: Multi-modal image matching based on radiation-variation insensitive feature transform,” IEEE Transactions on Image Processing, vol. 29, pp. 3296–3310, 2020. doi: 10.1109/TIP.2020.2992976.

[16] Designation-Systems.net, “M-109 reference,” online resource cited in the presentation.

[17] M. A. Fischler and P. C. Bolles, “Random sample consensus: A paradigm for model fitting with applications to image analysis and automated cartography,” Communications of the ACM, vol. 24, no. 6, pp. 381–395, 1981. doi: 10.1145/358669.358692.