


# MACHINE LEARNING

1. What is the most appropriate no. of clusters for the data points represented by the following dendrogram:



- a) 2
- b) 4
- c) 6
- d) 8

b) 4

2. In which of the following cases will K-Means clustering fail to give good results?

- 1. Data points with outliers
- 2. Data points with different densities
- 3. Data points with round shapes
- 4. Data points with non-convex shapes

Options:

- a) 1 and 2
- b) 2 and 3
- c) 2 and 4
- d) 1, 2 and 4

d) 1, 2 and 4

3. The most important part of is selecting the variables on which clustering is based.

- a) interpreting and profiling clusters
- b) selecting a clustering procedure
- c) assessing the validity of clustering
- d) formulating the clustering problem

d) formulating the clustering problem

4. The most commonly used measure of similarity is the or its square.

- a) Euclidean distance
- b) city-block distance
- c) Chebyshev's distance
- d) Manhattan distance

a) Euclidean distance

5. is a clustering procedure where all objects start out in one giant cluster. Clusters are formed by dividing this cluster into smaller and smaller clusters.

- a) Non-hierarchical clustering
- b) Divisive clustering
- c) Agglomerative clustering
- d) K-means clustering

b) Divisive clustering

6. Which of the following is required by K-means clustering?

- a) Defined distance metric
- b) Number of clusters
- c) Initial guess as to cluster centroids
- d) All answers are correct

d) All answers are correct

7. The goal of clustering is to-

- a) Divide the data points into groups
- b) Classify the data point into different classes
- c) Predict the output values of input data points
- d) All of the above

a) Divide the data points into groups

8. Clustering is a-

- a) Supervised learning
- b) Unsupervised learning
- c) Reinforcement learning
- d) None

Unsupervised learning

9. Which of the following clustering algorithms suffers from the problem of convergence at local optima?

- a) K- Means clustering
- b) Hierarchical clustering
- c) Diverse clustering
- d) All of the above

a) K- Means clustering

10. Which version of the clustering algorithm is most sensitive to outliers?

- a) K-means clustering algorithm
- b) K-modes clustering algorithm
- c) K-medians clustering algorithm
- d) None

a) K-means clustering algorithm  
as its centroid based

11. Which of the following is a bad characteristic of a dataset for clustering analysis-

- a) Data points with outliers
- b) Data points with different densities
- c) Data points with non-convex shapes
- d) All of the above

d) All of the above

12. For clustering, we do not require-

- a) Labeled data
- b) Unlabeled data
- c) Numerical data
- d) Categorical data

a) Labeled data

**Q13 to Q15 are subjective answers type questions, Answers them in their own words briefly.**

13. How is cluster analysis calculated?

Cluster analysis known as classification – it divides the data in the segment for the analysis – makes different group make clusters for analysis.

as we have 3 cluster analysis or we can say unsupervised method – given below

- 1. *k*-means clustering
- 2. Hierarchical clustering
- 3. Diverse clustering

14. How is cluster quality measured?

- 1. Dissimilarity/Similarity metric
- 2. Cluster completeness
- 3. Ragbag
- 4. Small cluster preservation

15. What is cluster analysis and its types?

The process of making a group of abstract objects into classes of similar objects is known as clustering.

Clustering Methods:

- 1. Model-Based Method
- 2. Hierarchical Method
- 3. Constraint-Based Method
- 4. Grid-Based Method
- 5. Partitioning Method
- 6. Density-Based Method