

BHTTP/1: a binary framing for HTTP

Specification, version 1

MUST, SHOULD and MAY are as in RFC 2119 and 8174. Integers are unsigned and big-endian. Sizes are in bytes.


1. Connection

BHTTP/1 runs over one TCP connection, by default on port 9000.

- A client sends all requests of one run on it and MUST NOT open a second; if it closes early, that is an error.
- A client SHOULD wait for each response, but a server MUST accept pipelined requests and answer them in order.
- A server MAY refuse a connection by closing it before reading anything. Otherwise it closes only after a connection error (§6), a body it cannot finish (§4), or a time limit (idle, slow request, or a client not taking frames). Each limit SHOULD be at least 10 s; unknown frames are not activity.
- Unless a body fails or the client stalls, a server never closes with a received request unanswered: no response means not processed.

2. Frame header

Every frame is an 8-byte header followed by Length bytes of payload.



- Length: payload bytes, not counting the header (0 to 16 777 215).
- Type: 0x00 DATA, 0x01 HEADERS. Any other value is unknown (§3).
- Flags: 0x01 END_STREAM marks the last frame of a request or response. Other bits are sent as 0 and ignored.
- Stream ID: the client numbers its requests, usually from 1, each higher than the last (gaps are allowed), and the response uses the same ID. Stream 0 is the connection itself; it carries only unknown frames and the connection-error message (§6). A client that runs out of IDs reports an error.

Example: 00 00 31 01 01 00 00 01 is HEADERS, 49 payload bytes, END_STREAM, stream 1.

3. Unknown frame types

A receiver that meets a frame of unknown type MUST skip it: read and discard exactly Length bytes, then carry on with the next frame. It MUST NOT reply, close the connection or change any request state because of it, whatever its stream or flags; END_STREAM on an unknown frame ends nothing. This holds anywhere, even inside a message, and overrides every other rule (the idle limit of §1 still runs). Types 0xF0–0xFF will never be assigned, so senders can use them to test that peers skip. HTTP/2 has the same rule outside its header blocks (RFC 9113 §4.1).

4. Messages

A request is one HEADERS frame, then zero or more DATA frames on the same stream, with END_STREAM on the last frame. A response has the same shape. A message with no body is a single HEADERS frame with END_STREAM.

- A header block fits in one HEADERS frame of at most 65 535 bytes; receivers MUST accept any such block.
- DATA frames SHOULD be at most 16 384 bytes; receivers MUST accept any Length.
- A response to HEAD carries no DATA, except that a 400 MAY carry its body (a server that cannot decode the block cannot know the method); a HEAD response's content-length is not checked. Any other response with content-length MUST carry exactly that many DATA bytes. In a request, only its syntax is checked.
- A sender that cannot finish a body MUST close the connection without END_STREAM, so the cut is visible.

5. Header block

A HEADERS payload is a list of fields ending at the frame's Length. tag is one byte; len is one or two.

field	= tag [name] value	; name only when tag = 0
name	= len bytes	value = len bytes
len	= 0xxxxxxx	; 0 to 127
	1xxxxxxx xxxxxxxx	; 0 to 32 767

Tag 0 means a literal name follows. Tags 1 to 10 are the names of a plain GET exchange:

tag	name	tag	name	tag	name	tag	name	tag	name
1	:method	3	:status	5	user-agent	7	server	9	content-type
2	:path	4	host	6	accept	8	date	10	content-length

- Literal names are lowercase HTTP token characters (RFC 9110 §5.6.2). `:` is not one, so pseudo-headers are sent by tag only. Senders MUST use the tag for a table name; receivers also accept the other table names as literals.
- Values may hold any byte except NUL, CR and LF. `content-length` is 1 to 18 digits, read as a number. Senders SHOULD use the shortest `len`; receivers accept both forms.
- Pseudo-headers come first. `:method`, `:path`, `:status`, `host` and `content-length` appear once at most (tag or literal).
- A request has one `:method` (a case-sensitive token), one `:path` (`/` first, at most 1024 bytes), no `:status`, and SHOULD have `host`.
- A response has one `:status`, three ASCII digits from 200 to 599, and no `:method` or `:path`.
- A block is malformed if it breaks a rule above (other than a SHOULD or the duty to use tags), uses tags 11 to 255, or overruns its payload.

6. Server

The server cuts `:path` at the first `?` or `#`, decodes `%XX` escapes and looks the path up under its document root; a directory, or a path ending in `/`, means its `index.html`. Every response carries `content-type`, `content-length`, server and date. A found file gets 200 and the file as DATA, an error a short text body, HEAD the headers only. The first matching row decides:

status	when
400	the header block is malformed or over 65 535 bytes, or the path has a bad <code>%</code> escape or <code>%00</code>
405	the method is well-formed but not GET or HEAD
403	the path would lead outside the root, or the file may not be read
404	there is no regular file to serve
500	opening or reading the file failed in some other way

Treatment of symbolic links and dotfiles is left to the server.

These are stream errors: the response goes on the request's stream (after any body is discarded) and the connection stays open. Connection errors, which win over stream errors, mean the frame sequence can no longer be trusted:

- HEADERS on stream 0, or with an ID not higher than every earlier one;
- DATA with no request open, or on another stream;
- a new HEADERS before the open request's `END_STREAM`.

The server answers requests completed before the bad frame, sends a 400 response on stream 0 whose body gives the reason, and closes. On EOF inside a frame or request, it just closes.

7. Client

The client matches responses to its requests in order. A HEADERS frame on stream 0, at any point, starts a connection-error message: the client reads it, reports the reason and stops. Otherwise it closes on a protocol error:

- a HEADERS or DATA frame for any stream but the oldest unanswered request;
- DATA before HEADERS or after `END_STREAM`, a second HEADERS, or DATA in a HEAD response other than a 400;
- a malformed or oversized response block, a `content-length` mismatch, EOF mid-response, or a read timeout.

8. Design notes

HTTP/2's frame header is 9 bytes: Length 24, Type 8, Flags 8, a reserved bit and a 31-bit Stream ID. Its drafts used 8 bytes, like BHTTP/1, until draft 14 (2014) widened Length from 14 to 24 bits so a receiver could opt in to larger frames. The default stayed 2^{14} so one large frame cannot hold up other streams. Flags are defined per frame type, so 8 bits suffice. The Stream ID is a 32-bit word minus the reserved bit, split between client (odd) and server (even). BHTTP/1 uses 24 / 8 / 8 / 24:

- Length 24. v1 senders keep frames small, but receivers already accept any Length, so larger frames need no new header. The width can never change: §3's skipping needs every version to read Length alike.
- Type 8 and Flags 8. Whole bytes need no masking, and the four fields fill two 32-bit words exactly. New frame types are safe for v1 peers (§3); a new flag or tag is not, so a v2 negotiates those first.
- Stream ID 24. v1 answers in order and the server never opens streams, so there is no odd/even split. The ID matches responses to requests and exposes stale frames. At the 19 000 requests a second bserve manages on loopback, 2^{24} IDs last about 15 minutes.

Like HPACK, common names get one-byte tags and the rest is length-prefixed, without a dynamic table or Huffman coding. A stray HTTP/1.1 GET `/` reads as an unknown frame of Length 0x474554 and waits out the idle limit. For v2, a client sends a new HELLO frame with a plain-v1 first request; only a v2 server answers it.