

A nested loop puzzle

Which of the following two code segments is faster? Assume that compiler makes no optimizations.

```
/* FIRST */
for(i=0; i<10; i++)
    for(j=0; j<100; j++)
        //do something
```

```
/* SECOND */
for(i=0; i<100; i++)
    for(j=0; j<10; j++)
        //do something
```

Both code segments provide same functionality, and the code inside the two for loops would be executed same number of times in both code segments.

If we take a closer look then we can see that the SECOND does more operations than the FIRST. It executes all three parts (assignment, comparison and increment) of the for loop more times than the corresponding parts of FIRST

a) The SECOND executes assignment operations (j = 0 or i = 0) 101 times while FIRST executes only 11 times.
 b) The SECOND does 101 + 1100 comparisons (i < 100 or j < 10) while the FIRST does 11 + 1010 comparisons (i < 10 or j < 100).
 c) The SECOND executes 1100 increment operations (i++ or j++) while the FIRST executes 1010 increment operation. Below C++ code counts the number of increment operations executed in FIRST and SECOND, and prints the counts. [sourcecode language="C"]

```
/* program to count number of increment operations in FIRST and SECOND */
#include<iostream> using namespace std;
int main() { int c1 = 0, c2 = 0;
/* FIRST */
for(int i=0; i<10; i++, c1++)
for(int j=0; j<100; j++, c1++); //do something
/* SECOND */
for(int i=0; i<100; i++, c2++)
for(int j=0; j<10; j++, c2++); //do something
cout << " Count in FIRST = " << c1 << endl;
cout << " Count in SECOND = " << c2 << endl;
getchar(); return 0; }
```

Below C++ code counts the number of comparison operations executed by FIRST and SECOND [sourcecode language="C"]

```
/* Program to count the number of comparison operations executed by FIRST and SECOND */
#include<iostream> using namespace std;
int main() { int c1 = 0, c2 = 0;
/* FIRST */
for(int i=0; ++c1&&i<10; i++)
for(int j=0; ++c1&&j<100; j++); //do something
/* SECOND */
for(int i=0; ++c2&&i<100; i++)
for(int j=0; ++c2&&j<10; j++); //do something
cout << " Count fot FIRST " << c1 << endl;
cout << " Count fot SECOND " << c2 << endl;
getchar(); return 0; }
```

Thanks to [Dheeraj](#) for suggesting the solution.

Please write comments if you find any of the answers/codes incorrect, or you want to share more information about the topics discussed above.



Choose from Top 150+ IT Courses & Rise in Your Career!

Big Data, Business Intelligence, Testing, Salesforce, Data Science, DataBase, etc...

FLAT 15% OFF
COUPON CODE: ID15

IntelliPaat
Enroll Now

GATE CS Corner Company Wise Coding Practice

C/C++ Puzzles

Related Posts:

- [Printing source code of a C program itself](#)
- [isalpha\(\) and isdigit\(\) functions in C with example](#)
- [Nested printf \(printf inside printf\) in C](#)
- [Assigning an integer to float and comparison in C/C++](#)
- [Counts of distinct consecutive sub-string of length two using C++ STL](#)
- [auto_ptr, unique_ptr, shared_ptr and weak_ptr](#)
- [Interesting Facts in C Programming](#)
- [Dangling, Void , Null and Wild Pointers](#)

Logged in as **mohitingale5** (Logout)

2.7

Average Difficulty : **2.7/5.0**
Based on **9** vote(s)

Basic

Easy

Medium

Hard

Expert

☐ Add to TODO List

☐ Mark as DONE

Writing code in comment? Please use code.geeksforgeeks.org generate link and share the link here.

Load Comments

@geeksforgeeks, Some rights reserved

[Contact Us!](#)
[Policy](#)

[About Us!](#)

[Advertise with us!](#)

[Privacy](#)