

C function to Swap strings

Let us consider the below program.

```
#include<stdio.h>
void swap(char *str1, char *str2)
{
    char *temp = str1;
    str1 = str2;
    str2 = temp;
}

int main()
{
    char *str1 = "geeks";
    char *str2 = "forgeeks";
    swap(str1, str2);
    printf("str1 is %s, str2 is %s", str1, str2);
    getchar();
    return 0;
}
```

[Run on IDE](#)

Output of the program is *str1 is geeks, str2 is forgeeks*. So the above swap() function doesn't swap strings. The function just changes local pointer variables and the changes are not reflected outside the function.

Let us see the correct ways for swapping strings:

Method 1(Swap Pointers)

If you are [using character pointer for strings](#) (not arrays) then change str1 and str2 to point each other's data. i.e., swap pointers. In a function, if we want to change a pointer (and obviously we want changes to be reflected outside the function) then we need to pass a pointer to the pointer.

```
#include<stdio.h>

/* Swaps strings by swapping pointers */
void swap1(char **str1_ptr, char **str2_ptr)
{
    char *temp = *str1_ptr;
    *str1_ptr = *str2_ptr;
    *str2_ptr = temp;
}

int main()
{
    char *str1 = "geeks";
    char *str2 = "forgeeks";
    swap1(&str1, &str2);
    printf("str1 is %s, str2 is %s", str1, str2);
    getchar();
    return 0;
}
```

This method cannot be applied if strings are stored using character arrays.

Method 2(Swap Data)

If you are using character arrays to store strings then preferred way is to swap the data of both arrays.

```
#include<stdio.h>
#include<string.h>
#include<stdlib.h>

/* Swaps strings by swapping data*/
void swap2(char *str1, char *str2)
{
    char *temp = (char *)malloc((strlen(str1) + 1) * sizeof(char));
    strcpy(temp, str1);
    strcpy(str1, str2);
    strcpy(str2, temp);
    free(temp);
}

int main()
{
    char str1[10] = "geeks";
    char str2[10] = "forgeeks";
    swap2(str1, str2);
    printf("str1 is %s, str2 is %s", str1, str2);
    getchar();
    return 0;
}
```

This method cannot be applied for strings stored in read only block of memory.

Please write comments if you find anything incorrect in the above article, or you want to share more information about the topic discussed above.



amazon.in

[Xiaomi Redmi Note 3 ...](#)
Rs. 9,999.00
(details + delivery)

[KAIRA Xiaomi Redmi ...](#)
Rs. 149.00
(details + delivery)

Related Posts:

- [Linux Kernel Module Programming: Hello World Program](#)
- [Priority Inversion : What the heck !](#)
- [Time Complexity where loop variable is incremented by 1, 2, 3, 4 ..](#)
- [Time Complexity of Loop with Powers](#)
- [Analysis of Algorithms | Set 4 \(Analysis of Loops\)](#)
- [Analysis of Algorithms | Set 3 \(Asymptotic Notations\)](#)
- [NP-Completeness | Set 1 \(Introduction\)](#)
- [Reservoir Sampling](#)

(Login to Rate and Mark)

3

Average Difficulty : **3/5.0**
Based on **26** vote(s)



Add to TODO List



Mark as DONE

Writing code in comment? Please use code.geeksforgeeks.org generate link and share the link here.

Load Comments