

A computer science portal for geeks **Practice** 

GATE CS Placements GeeksQuiz

Google™ Custom Search



Login/Register

# To find sum of two numbers without using operator

Write a C program to find sum of positive integers without using any operator. Only use of printf() is allowed. No other library function can be used.

### Solution

It's a trick question. We can use printf() to find sum of two numbers as printf() returns the number of characters printed. The width field in printf() can be used to find the sum of two numbers. We can use '\*' which indicates the minimum width of output. For example, in the statement "printf("%\*d", width, num);", the specified 'width' is substituted in place of \*, and 'num' is printed within the minimum width specified. If number of digits in 'num' is smaller than the specified 'wodth', the output is padded with blank spaces. If number of digits are more, the output is printed as it is (not truncated). In the following program, add() returns sum of x and y. It prints 2 spaces within the width specified using x and y. So total characters printed is equal to sum of x and y. That is why add() returns x+y.

```
int add(int x, int y)
{
    return printf("%*c%*c", x, ' ', y, ' ');
}
int main()
   printf("Sum = %d", add(3, 4));
   return 0;
```

Run on IDE

Output:

```
Sum = 7
```

The output is seven spaces followed by "Sum = 7". We can avoid the leading spaces by using carriage return. Thanks to krazyCoder and Sandeep for suggesting this. The following program prints output without any leading spaces.

```
int add(int x, int y)
    return printf("%*c%*c", x, '\r', y, '\r');
int main()
    printf("Sum = %d", add(3, 4));
    return 0;
```

Run on IDE

Output:

Sum = 7

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above



## **GATE CS Corner** Company Wise Coding Practice


C/C++ Puzzles

### **Related Posts:**

- strtok() and strtok\_r() functions in C with examples
- C++ Floating Point Manipulation (fmod(), remainder(), remquo() ... in cmath)
- C/C++ program to shutdown a system
- How to pass an array by value in C?
- Programs for printing pyramid patterns in C++
- Pointers in C and C++ | Set 1 (Introduction, Arithmetic and Array)
- Creating a Rainbow using Graphics Programming in C
- Character Classification in C++ : cctype

#### (Login to Rate and Mark)





Writing code in comment? Please usecode geeksforgeeks.org generate link and share the link here.

Load Comments				
@geeksforgeeks, Some rights reserved	Contact Us! Poli	About Us! cy	Advertise with us!	Privacy