

The Linux Kernel API

This documentation is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

For more details see the file COPYING in the source distribution of Linux.

Table of Contents

1. [Driver Basics](#)

1.1. [Driver Entry and Exit points](#)

[module_init](#) -- driver initialization entry point
[module_exit](#) -- driver exit entry point

1.2. [Atomic and pointer manipulation](#)

[atomic_read](#) -- read atomic variable
[atomic_set](#) -- set atomic variable
[atomic_add](#) -- add integer to atomic variable
[atomic_sub](#) -- subtract the atomic variable
[atomic_sub_and_test](#) -- subtract value from variable and test result
[atomic_inc](#) -- increment atomic variable
[atomic_dec](#) -- decrement atomic variable
[atomic_dec_and_test](#) -- decrement and test
[atomic_inc_and_test](#) -- increment and test
[atomic_add_negative](#) -- add and test if negative
[get_unaligned](#) -- get value from possibly mis-aligned location
[put_unaligned](#) -- put value to a possibly mis-aligned location

2. [Data Types](#)

2.1. [Doubly Linked Lists](#)

[list_add](#) -- add a new entry
[list_add_tail](#) -- add a new entry
[list_add_rcu](#) -- add a new entry to rcu-protected list
[list_add_tail_rcu](#) -- add a new entry to rcu-protected list
[list_del](#) -- deletes entry from list.
[list_del_rcu](#) -- deletes entry from list without re-initialization
[list_del_init](#) -- deletes entry from list and reinitialize it.
[list_move](#) -- delete from one list and add as another's head
[list_move_tail](#) -- delete from one list and add as another's tail
[list_empty](#) -- tests whether a list is empty
[list_splice](#) -- join two lists
[list_splice_init](#) -- join two lists and reinitialise the emptied list.
[list_entry](#) -- get the struct for this entry
[list_for_each](#) -- iterate over a list

[list_for_each](#) -- iterate over a list
[list_for_each_prev](#) -- iterate over a list backwards
[list_for_each_safe](#) -- iterate over a list safe against removal of list entry
[list_for_each_entry](#) -- iterate over list of given type
[list_for_each_entry_reverse](#) -- iterate backwards over list of given type.
[list_for_each_entry_safe](#) -- iterate over list of given type safe against removal of list entry
[list_for_each_rcu](#) -- iterate over an rcu-protected list
[list_for_each_safe_rcu](#) -- iterate over an rcu-protected list safe
[list_for_each_entry_rcu](#) -- iterate over rcu list of given type
[list_for_each_continue_rcu](#) -- iterate over an rcu-protected list
[hlist_del_rcu](#) -- deletes entry from hash list without re-initialization
[hlist_for_each_entry](#) -- iterate over list of given type
[hlist_for_each_entry_continue](#) -- iterate over a hlist continuing after existing point
[hlist_for_each_entry_from](#) -- iterate over a hlist continuing from existing point
[hlist_for_each_entry_safe](#) -- iterate over list of given type safe against removal of list entry

3. [Basic C Library Functions](#)

3.1. [String Conversions](#)

[simple_strtoll](#) -- convert a string to a signed long long
[simple_strtoul](#) -- convert a string to an unsigned long
[simple_strtol](#) -- convert a string to a signed long
[simple_strtoul](#) -- convert a string to an unsigned long long
[vsprintf](#) -- Format a string and place it in a buffer
[snprintf](#) -- Format a string and place it in a buffer
[vsprintf](#) -- Format a string and place it in a buffer
[sprintf](#) -- Format a string and place it in a buffer
[vsscanf](#) -- Unformat a buffer into a list of arguments
[sscanf](#) -- Unformat a buffer into a list of arguments

3.2. [String Manipulation](#)

[strcpy](#) -- Copy a NUL terminated string
[strncpy](#) -- Copy a length-limited, NUL-terminated string
[strcat](#) -- Append one NUL-terminated string to another
[strncat](#) -- Append a length-limited, NUL-terminated string to another
[strcmp](#) -- Compare two strings
[strncmp](#) -- Compare two length-limited strings
[strchr](#) -- Find the first occurrence of a character in a string
[strrchr](#) -- Find the last occurrence of a character in a string
[strlen](#) -- Find the length of a string
[strnlen](#) -- Find the length of a length-limited string
[strcspn](#) -- Calculate the length of the initial substring of *s* which does
[strpbrk](#) -- Find the first occurrence of a set of characters
[memset](#) -- Fill a region of memory with the given value
[bcopy](#) -- Copy one area of memory to another
[memcpy](#) -- Copy one area of memory to another
[memmove](#) -- Copy one area of memory to another
[memcmp](#) -- Compare two areas of memory
[memscan](#) -- Find a character in an area of memory.
[strstr](#) -- Find the first substring in a NUL terminated string
[memchr](#) -- Find a character in an area of memory.
[strnicmp](#) -- Case insensitive, length-limited string comparison
[strncpy](#) -- Copy a NUL terminated string into a sized buffer
[strlcat](#) -- Append a length-limited, NUL-terminated string to another
[strspn](#) -- Calculate the length of the initial substring of *s* which only
[strsep](#) -- Split a string into tokens

3.3. [Bit Operations](#)

[set_bit](#) -- Atomically set a bit in memory
[__set_bit](#) -- Set a bit in memory
[clear_bit](#) -- Clears a bit in memory
[__change_bit](#) -- Toggle a bit in memory
[change_bit](#) -- Toggle a bit in memory
[test_and_set_bit](#) -- Set a bit and return its old value
[__test_and_set_bit](#) -- Set a bit and return its old value
[test_and_clear_bit](#) -- Clear a bit and return its old value
[__test_and_clear_bit](#) -- Clear a bit and return its old value
[test_and_change_bit](#) -- Change a bit and return its new value
[test_bit](#) -- Determine whether a bit is set
[find_first_zero_bit](#) -- find the first zero bit in a memory region
[find_first_bit](#) -- find the first set bit in a memory region
[find_next_zero_bit](#) -- find the first zero bit in a memory region
[find_next_bit](#) -- find the first set bit in a memory region
[ffz](#) -- find first zero in word.
[__ffs](#) -- find first bit in word.
[ffs](#) -- find first bit set
[hweight32](#) -- returns the hamming weight of a N-bit word

4. [Memory Management in Linux](#)

4.1. [The Slab Cache](#)

[kmem_cache_create](#) -- Create a cache.
[kmem_cache_shrink](#) -- Shrink a cache.
[kmem_cache_destroy](#) -- delete a cache
[kmem_cache_alloc](#) -- Allocate an object
[__kmalloc](#) -- allocate memory
[__alloc_percpu](#) -- allocate one copy of the object for every present
[kmem_cache_free](#) -- Deallocate an object
[kfree](#) -- free previously allocated memory
[free_percpu](#) -- free previously allocated percpu memory

4.2. [User Space Memory Access](#)

[access_ok](#) -- Checks if a user space pointer is valid
[verify_area](#) -- Obsolete, use [access_ok](#)
[get_user](#) -- Get a simple variable from user space.
[put_user](#) -- Write a simple value into user space.
[__get_user](#) -- Get a simple variable from user space, with less checking.
[__put_user](#) -- Write a simple value into user space, with less checking.
[__copy_to_user](#) -- Copy a block of data into user space, with less checking.
[__copy_from_user](#) -- Copy a block of data from user space, with less checking.
[copy_to_user](#) -- Copy a block of data into user space.
[copy_from_user](#) -- Copy a block of data from user space.
[strlen_user](#) -- Get the size of a string in user space.
[__strncpy_from_user](#) -- Copy a NUL terminated string from userspace, with less checking.
[strncpy_from_user](#) -- Copy a NUL terminated string from userspace.
[clear_user](#) -- Zero a block of memory in user space.
[__clear_user](#) -- Zero a block of memory in user space, with less checking.
[strnlen_user](#) -- Get the size of a string in user space.

5. [The proc filesystem](#)

5.1. [sysctl interface](#)

[register_sysctl_table](#) -- register a sysctl hierarchy
[unregister_sysctl_table](#) -- unregister a sysctl table hierarchy
[proc_dostring](#) -- read a string sysctl
[proc_dointvec](#) -- read a vector of integers
[proc_dointvec_minmax](#) -- read a vector of integers with min/max values
[proc_doulongvec_minmax](#) -- read a vector of long integers with min/max values
[proc_doulongvec_ms_jiffies_minmax](#) -- read a vector of millisecond values with min/max values
[proc_dointvec_jiffies](#) -- read a vector of integers as seconds

6. [The Linux VFS](#)

6.1. [The Directory Cache](#)

[d_invalidate](#) -- invalidate a dentry
[d_find_alias](#) -- grab a hashed alias of inode
[shrink_dcache_sb](#) -- shrink dcache for a superblock
[have_submounts](#) -- check for mounts over a dentry
[shrink_dcache_parent](#) -- prune dcache
[shrink_dcache_anon](#) -- further prune the cache
[d_alloc](#) -- allocate a dcache entry
[d_instantiate](#) -- fill in inode information for a dentry
[d_alloc_root](#) -- allocate root dentry
[d_alloc_anon](#) -- allocate an anonymous dentry
[d_splice_alias](#) -- splice a disconnected dentry into the tree if one exists
[d_lookup](#) -- search for a dentry
[d_validate](#) -- verify dentry provided from insecure source
[d_delete](#) -- delete a dentry
[d_rehash](#) -- add an entry back to the hash
[d_move](#) -- move a dentry
[is_subdir](#) -- is new dentry a subdirectory of old_dentry
[find_inode_number](#) -- check for dentry with name
[__d_drop](#) -- drop a dentry
[d_add](#) -- add dentry to hash queues
[dget](#) -- get a reference to a dentry
[d_unhashed](#) -- is dentry hashed

6.2. [Inode Handling](#)

[clear_inode](#) -- clear an inode
[invalidate_inodes](#) -- discard the inodes on a device
[new_inode](#) -- obtain an inode
[iunique](#) -- get a unique inode number
[ilookup5](#) -- search for an inode in the inode cache
[ilookup](#) -- search for an inode in the inode cache
[iget5_locked](#) -- obtain an inode from a mounted file system
[iget_locked](#) -- obtain an inode from a mounted file system
[__insert_inode_hash](#) -- hash an inode
[remove_inode_hash](#) -- remove an inode from the hash
[iput](#) -- put an inode
[bmap](#) -- find a block number in a file
[update_atime](#) -- update the access time
[inode_update_time](#) -- update mtime and ctime time
[make_bad_inode](#) -- mark an inode bad due to an I/O error
[is_bad_inode](#) -- is an inode errored

6.3. [Registration and Superblocks](#)

[deactivate_super](#) -- drop an active reference to superblock
[generic_shutdown_super](#) -- common helper for ->kill_sb
[sget](#) -- find or create a superblock
[get_super](#) -- get the superblock of a device

6.4. [File Locks](#)

[posix_lock_file](#) -- Apply a POSIX-style lock to a file
[locks_mandatory_area](#) -- Check for a conflicting lock
[__break_lease](#) -- revoke all outstanding leases on file
[lease_get_mtime](#) --
[posix_block_lock](#) -- blocks waiting for a file lock
[posix_unblock_lock](#) -- stop waiting for a file lock
[lock_may_read](#) -- checks that the region is free of locks
[lock_may_write](#) -- checks that the region is free of locks
[locks_mandatory_locked](#) -- Check for an active lock
[fcntl_getlease](#) -- Enquire what lease is currently active
[fcntl_setlease](#) -- sets a lease on an open file
[sys_flock](#) -- flock system call.
[get_locks_status](#) -- reports lock usage in /proc/locks

7. [Linux Networking](#)

7.1. [Socket Buffer Functions](#)

[struct sk_buff](#) -- socket buffer
[skb_queue_empty](#) -- check if a queue is empty
[skb_get](#) -- reference buffer
[kfree_skb](#) -- free an sk_buff
[skb_cloned](#) -- is the buffer a clone
[skb_shared](#) -- is the buffer shared
[skb_share_check](#) -- check if buffer is shared and if so clone it
[skb_unshare](#) -- make a copy of a shared buffer
[skb_peek](#) --
[skb_peek_tail](#) --
[skb_queue_len](#) -- get queue length
[__skb_queue_head](#) -- queue a buffer at the list head
[skb_queue_head](#) -- queue a buffer at the list head
[__skb_queue_tail](#) -- queue a buffer at the list tail
[skb_queue_tail](#) -- queue a buffer at the list tail
[__skb_dequeue](#) -- remove from the head of the queue
[skb_dequeue](#) -- remove from the head of the queue
[skb_insert](#) -- insert a buffer
[skb_append](#) -- append a buffer
[skb_unlink](#) -- remove a buffer from a list
[__skb_dequeue_tail](#) -- remove from the tail of the queue
[skb_dequeue_tail](#) -- remove from the head of the queue
[skb_put](#) -- add data to a buffer
[skb_push](#) -- add data to the start of a buffer
[skb_pull](#) -- remove data from the start of a buffer
[skb_headroom](#) -- bytes at buffer head
[skb_tailroom](#) -- bytes at buffer end
[skb_reserve](#) -- adjust headroom
[skb_trim](#) -- remove end from a buffer
[skb_orphan](#) -- orphan a buffer
[skb_queue_purge](#) -- empty a list
[__skb_queue_purge](#) -- empty a list
[__dev_alloc_skb](#) -- allocate an skbuff for sending

[dev_alloc_skb](#) -- allocate an skbuff for sending
[skb_cow](#) -- copy header of skb when it is required
[skb_padto](#) -- pad an skbuff up to a minimal size
[skb_over_panic](#) -- private function
[skb_under_panic](#) -- private function
[alloc_skb](#) -- allocate a network buffer
[__kfree_skb](#) -- private function
[skb_clone](#) -- duplicate an sk_buff
[skb_copy](#) -- create private copy of an sk_buff
[pskb_copy](#) -- create copy of an sk_buff with private head.
[pskb_expand_head](#) -- reallocate header of sk_buff
[skb_copy_expand](#) -- copy and expand sk_buff
[skb_pad](#) -- zero pad the tail of an skb
[__pskb_pull_tail](#) -- advance tail of skb header

7.2. [Socket Filter](#)

[sk_run_filter](#) -- run a filter on a socket
[sk_chk_filter](#) -- verify socket filter code

8. [Network device support](#)

8.1. [Driver Support](#)

[init_etherdev](#) -- Register ethernet device
[alloc_etherdev](#) -- Allocates and sets up an ethernet device
[alloc_fddidev](#) -- Register FDDI device
[alloc_hippi_dev](#) -- Register HIPPI device
[alloc_trdev](#) -- Register token ring device
[alloc_fcdev](#) -- Register fibre channel device
[dev_add_pack](#) -- add packet handler
[__dev_remove_pack](#) -- remove packet handler
[dev_remove_pack](#) -- remove packet handler
[netdev_boot_setup_check](#) -- check boot time settings
[__dev_get_by_name](#) -- find a device by its name
[dev_get_by_name](#) -- find a device by its name
[__dev_get](#) -- test if a device exists
[__dev_get_by_index](#) -- find a device by its ifindex
[dev_get_by_index](#) -- find a device by its ifindex
[dev_getbyhwaddr](#) -- find a device by its hardware address
[dev_get_by_flags](#) -- find any device with given flags
[__dev_get_by_flags](#) -- find any device with given flags
[dev_alloc_name](#) -- allocate a name for a device
[dev_alloc](#) -- allocate a network device and name
[netdev_state_change](#) -- device changes state
[dev_load](#) -- load a network module
[dev_open](#) -- prepare an interface for use.
[dev_close](#) -- shutdown an interface.
[register_netdevice_notifier](#) -- register a network notifier block
[unregister_netdevice_notifier](#) -- unregister a network notifier block
[call_netdevice_notifiers](#) -- call all network notifier blocks
[dev_queue_xmit](#) -- transmit a buffer
[netif_rx](#) -- post buffer to the network code
[register_gifconf](#) -- register a SIOCGIF handler
[netdev_set_master](#) -- set up master/slave pair
[dev_set_promiscuity](#) -- update promiscuity count on a device
[dev_set_allmulti](#) -- update allmulti count on a device
[dev_ioctl](#) -- network device ioctl

[dev_new_index](#) -- allocate an ifindex
[register_netdevice](#) -- register a network device
[free_netdev](#) -- free network device
[unregister_netdevice](#) -- remove device from the kernel

8.2. [8390 Based Network Cards](#)

[ei_open](#) -- Open/initialize the board.
[ei_close](#) -- shut down network device
[ei_tx_timeout](#) -- handle transmit time out condition
[ei_interrupt](#) -- handle the interrupts from an 8390
[ethdev_init](#) -- init rest of 8390 device struct
[alloc_ei_netdev](#) -- alloc_etherdev counterpart for 8390
[NS8390_init](#) -- initialize 8390 hardware

8.3. [Synchronous PPP](#)

[sppp_input](#) -- receive and process a WAN PPP frame
[sppp_close](#) -- close down a synchronous PPP or Cisco HDLC link
[sppp_open](#) -- open a synchronous PPP or Cisco HDLC link
[sppp_reopen](#) -- notify of physical link loss
[sppp_change_mtu](#) -- Change the link MTU
[sppp_do_ioctl](#) -- Ioctl handler for ppp/hdlc
[sppp_attach](#) -- attach synchronous PPP/HDLC to a device
[sppp_detach](#) -- release PPP resources from a device

9. [Module Support](#)

9.1. [Module Loading](#)

[request_module](#) -- try to load a kernel module
[call_usermodehelper](#) -- start a usermode application

9.2. [Inter Module support](#)

10. [Hardware Interfaces](#)

10.1. [Interrupt Handling](#)

[disable_irq_nosync](#) -- disable an irq without waiting
[disable_irq](#) -- disable an irq and wait for completion
[enable_irq](#) -- enable handling of an irq
[probe_irq_mask](#) -- scan a bitmap of interrupt lines

10.2. [MTRR Handling](#)

[mtrr_add](#) -- Add a memory type region
[mtrr_del](#) -- delete a memory type region

10.3. [PCI Support Library](#)

[pci_bus_max_busnr](#) -- returns maximum PCI bus number of given bus' children
[pci_max_busnr](#) -- returns maximum PCI bus number
[pci_find_capability](#) -- query for devices' capabilities
[pci_bus_find_capability](#) -- query for devices' capabilities
[pci_find_parent_resource](#) -- return resource region of parent bus of given region
[pci_set_power_state](#) -- Set the power state of a PCI device
[pci_save_state](#) -- save the PCI configuration space of a device before suspending
[pci_restore_state](#) -- Restore the saved state of a PCI device

[pci_enable_device_bars](#) -- Initialize some of a device for use
[pci_enable_device](#) -- Initialize device before it's used by a driver.
[pci_disable_device](#) -- Disable PCI device after use
[pci_enable_wake](#) -- enable device to generate PME# when suspended
[pci_release_region](#) -- Release a PCI bar
[pci_request_region](#) -- Reserved PCI I/O and memory resource
[pci_release_regions](#) -- Release reserved PCI I/O and memory resources
[pci_request_regions](#) -- Reserved PCI I/O and memory resources
[pci_set_master](#) -- enables bus-mastering for device dev
[pci_set_mwi](#) -- enables memory-write-invalidate PCI transaction
[pci_clear_mwi](#) -- disables Memory-Write-Invalidate for device dev

10.4. [PCI Hotplug Support Library](#)

[pci_hp_register](#) -- register a hotplug_slot with the PCI hotplug subsystem
[pci_hp_deregister](#) -- deregister a hotplug_slot with the PCI hotplug subsystem
[pci_hp_change_slot_info](#) -- changes the slot's information structure in the core

10.5. [MCA Architecture](#)

10.5.1. [MCA Device Functions](#)

10.5.2. [MCA Bus DMA](#)

11. [The Device File System](#)

[devfs_put](#) -- Put (release) a reference to a devfs entry.
[devfs_mk_symlink](#) --
[devfs_mk_dir](#) -- Create a directory in the devfs namespace.

12. [Security Framework](#)

[register_security](#) -- registers a security framework with the kernel
[unregister_security](#) -- unregisters a security framework with the kernel
[mod_reg_security](#) -- allows security modules to be "stacked"
[mod_unreg_security](#) -- allows a security module registered with mod_reg_security to be unloaded
[capable](#) -- calls the currently loaded security module's capable function with the specified capability

13. [Power Management](#)

[pm_register](#) -- register a device with power management
[pm_unregister](#) -- unregister a device with power management
[pm_unregister_all](#) -- unregister all devices with matching callback
[pm_send](#) -- send request to a single device
[pm_send_all](#) -- send request to all managed devices
[pm_find](#) -- find a device

14. [Block Devices](#)

[blk_queue_prep_rq](#) -- set a prepare_request function for queue
[blk_queue_merge_bvec](#) -- set a merge_bvec function for queue
[blk_queue_make_request](#) -- define an alternate make_request function for a device
[blk_queue_bounce_limit](#) -- set bounce buffer limit for queue
[blk_queue_max_sectors](#) -- set max sectors for a request for this queue
[blk_queue_max_phys_segments](#) -- set max phys segments for a request for this queue
[blk_queue_max_hw_segments](#) -- set max hw segments for a request for this queue
[blk_queue_max_segment_size](#) -- set max segment size for blk_rq_map_sg
[blk_queue_hardsect_size](#) -- set hardware sector size for the queue
[blk_queue_stack_limits](#) -- inherit underlying queue limits for stacked drivers
[blk_queue_segment_boundary](#) -- set boundary rules for segment merging

[blk_queue_dma_alignment](#) -- set dma length and memory alignment
[blk_queue_find_tag](#) -- find a request by its tag and queue
[blk_queue_free_tags](#) -- release tag maintenance info
[blk_queue_init_tags](#) -- initialize the queue tag info
[blk_queue_end_tag](#) -- end tag operations for a request
[blk_queue_start_tag](#) -- find a free tag and assign it
[blk_queue_invalidate_tags](#) -- invalidate all pending tags
[generic_unplug_device](#) -- fire a request queue
[blk_start_queue](#) -- restart a previously stopped queue
[blk_stop_queue](#) -- stop a queue
[blk_run_queue](#) -- run a single device queue
[blk_cleanup_queue](#) -- release a request_queue_t when it is no longer needed
[blk_init_queue](#) -- prepare a request queue for use with a block device
[blk_requeue_request](#) -- put a request back on queue
[blk_insert_request](#) -- insert a special request in to a request queue
[blk_congestion_wait](#) -- wait for a queue to become uncongested
[blk_attempt_remerge](#) -- attempt to remerge active head with next request
[generic_make_request](#) --
[submit_bio](#) --
[process_that_request_first](#) -- process partial request submission
[end_that_request_first](#) -- end I/O on a request
[end_that_request_chunk](#) -- end I/O on a request

15. [Miscellaneous Devices](#)

[misc_register](#) -- register a miscellaneous device
[misc_deregister](#) -- unregister a miscellaneous device

16. [Video4Linux](#)

[video_register_device](#) -- register video4linux devices
[video_unregister_device](#) -- unregister a video4linux device

17. [Sound Devices](#)

[register_sound_special](#) -- register a special sound node
[register_sound_mixer](#) -- register a mixer device
[register_sound_midi](#) -- register a midi device
[register_sound_dsp](#) -- register a DSP device
[register_sound_synth](#) -- register a synth device
[unregister_sound_special](#) -- unregister a special sound device
[unregister_sound_mixer](#) -- unregister a mixer
[unregister_sound_midi](#) -- unregister a midi device
[unregister_sound_dsp](#) -- unregister a DSP device
[unregister_sound_synth](#) -- unregister a synth device

18. [16x50 UART Driver](#)

[uart_update_timeout](#) -- update per-port FIFO timeout.
[uart_get_baud_rate](#) -- return baud rate for a particular port
[uart_get_divisor](#) -- return uart clock divisor
[uart_register_driver](#) -- register a driver with the uart core layer
[uart_unregister_driver](#) -- remove a driver from the uart core layer
[uart_add_one_port](#) -- attach a driver-defined port structure
[uart_remove_one_port](#) -- detach a driver defined port structure
[uart_register_port](#) --
[uart_unregister_port](#) -- de-allocate a port
[register_serial](#) -- configure a 16x50 serial port at runtime
[unregister_serial](#) -- remove a 16x50 serial port at runtime

[serial8250_suspend_port](#) -- suspend one serial port
[serial8250_resume_port](#) -- resume one serial port

19. [Z85230 Support Library](#)

[z8530_interrupt](#) -- Handle an interrupt from a Z8530
[z8530_sync_open](#) -- Open a Z8530 channel for PIO
[z8530_sync_close](#) -- Close a PIO Z8530 channel
[z8530_sync_dma_open](#) -- Open a Z8530 for DMA I/O
[z8530_sync_dma_close](#) -- Close down DMA I/O
[z8530_sync_txdma_open](#) -- Open a Z8530 for TX driven DMA
[z8530_sync_txdma_close](#) -- Close down a TX driven DMA channel
[z8530_describe](#) -- Uniformly describe a Z8530 port
[z8530_init](#) -- Initialise a Z8530 device
[z8530_shutdown](#) -- Shutdown a Z8530 device
[z8530_channel_load](#) -- Load channel data
[z8530_null_rx](#) -- Discard a packet
[z8530_queue_xmit](#) -- Queue a packet
[z8530_get_stats](#) -- Get network statistics

20. [Frame Buffer Library](#)

20.1. [Frame Buffer Memory](#)

[register_framebuffer](#) -- registers a frame buffer device
[unregister_framebuffer](#) -- releases a frame buffer device

20.2. [Frame Buffer Console](#)

[drivers/video/console/fbcon.c](#) -- Document generation inconsistency

20.3. [Frame Buffer Colormap](#)

[fb_alloc_cmap](#) -- allocate a colormap
[fb_dealloc_cmap](#) -- deallocate a colormap
[fb_copy_cmap](#) -- copy a colormap
[fb_set_cmap](#) -- set the colormap
[fb_default_cmap](#) -- get default colormap
[fb_invert_cmaps](#) -- invert all defaults colormaps

20.4. [Frame Buffer Video Mode Database](#)

[fb_find_mode](#) -- finds a valid video mode
[__fb_try_mode](#) -- test a video mode

20.5. [Frame Buffer Macintosh Video Mode Database](#)

[mac_vmode_to_var](#) -- converts vmode/cmode pair to var structure
[mac_var_to_vmode](#) -- convert var structure to MacOS vmode/cmode pair
[mac_map_monitor_sense](#) -- Convert monitor sense to vmode
[mac_find_mode](#) -- find a video mode

20.6. [Frame Buffer Fonts](#)