

Chapter 9: Virtual Memory





Chapter 9: Virtual Memory

- Background
- Demand Paging
- Process Creation
- Page Replacement
- Allocation of Frames
- Thrashing






Background

- **Virtual memory** – separation of user logical memory from physical memory.
 - Only part of the program needs to be in memory for execution.
 - Logical address space can therefore be much larger than physical address space.
 - Allows address spaces to be shared by several processes.
 - Allows for more efficient process creation.






Virtual Memory That is Larger Than Physical Memory






Virtual-address Space





Shared Library Using Virtual Memory





Demand Paging

- Bring a page into memory only when it is needed
 - Less I/O needed
 - Less memory needed
 - Faster response
 - More users

- Page is needed \Rightarrow reference to it
 - invalid reference \Rightarrow abort
 - not-in-memory \Rightarrow bring to memory





Valid-Invalid Bit

- With each page table entry a valid–invalid bit is associated (1 \Rightarrow in-memory, 0 \Rightarrow not-in-memory)
- Initially valid–invalid bit is set to 0 on all entries
- Example of a page table snapshot:

Frame #	valid-invalid bit
	1
	1
	1
	1
	0
⋮	
	0
	0


page table

- During address translation, if valid–invalid bit in page table entry is 0 \Rightarrow page fault





Page Table When Some Pages Are Not in Main Memory






Page Fault

- If there is ever a reference to a page, first reference will trap to OS \Rightarrow page fault
- OS looks at another table to decide:
 - Invalid reference \Rightarrow abort.
 - Just not in memory.
- Get empty frame.
- Swap page into frame.
- Reset tables, validation bit = 1.
- Restart instruction





Steps in Handling a Page Fault





What happens if there is no free frame?

- Page replacement – find some page in memory, but not really in use, swap it out
 - algorithm
 - performance – want an algorithm which will result in minimum number of page faults





Performance of Demand Paging

- Page Fault Rate $0 \leq p \leq 1.0$
 - if $p = 0$ no page faults
 - if $p = 1$, every reference is a fault
- Effective Access Time (EAT)
EAT = $(1 - p) \times \text{memory access}$
 - + p (page fault overhead
 - + [swap page out]
 - + swap page in
 - + restart overhead)






Page Replacement

- Use **modify (dirty) bit** to reduce overhead of page transfers – only modified pages are written to disk
- Page replacement completes separation between logical memory and physical memory – large virtual memory can be provided on a smaller physical memory





Need For Page Replacement






Basic Page Replacement

1. Find the location of the desired page on disk
2. Find a free frame:
 - If there is a free frame, use it
 - If there is no free frame, use a page replacement algorithm to select a **victim** frame
3. Read the desired page into the (newly) free frame. Update the page and frame tables.
4. Restart the process





Page Replacement






Page Replacement Algorithms

- Want lowest page-fault rate
- Evaluate algorithm by running it on a particular string of memory references (reference string) and computing the number of page faults on that string
- In all our examples, the reference string is
1, 2, 3, 4, 1, 2, 5, 1, 2, 3, 4, 5





Graph of Page Faults Versus The Number of Frames





First-In-First-Out (FIFO) Algorithm

- Reference string: 1, 2, 3, 4, 1, 2, 5, 1, 2, 3, 4, 5
- 3 frames (3 pages can be in memory at a time per process)

1	1	4	5
2	2	1	3
3	3	2	4

9 page faults

- 4 frames

1	1	5	4
2	2	1	5
3	3	2	
4	4	3	


10 page faults

- FIFO Replacement – Belady's Anomaly
 - more frames \Rightarrow more page faults






FIFO Page Replacement





FIFO Illustrating Belady's Anomaly





Optimal Algorithm

- Replace page that will not be used for longest period of time
- 4 frames example

1, 2, 3, 4, 1, 2, 5, 1, 2, 3, 4, 5

1	4
2	
3	
4	5


6 page faults

- How do you know this?
- Used for measuring how well your algorithm performs





Optimal Page Replacement





Least Recently Used (LRU) Algorithm

- Reference string: 1, 2, 3, 4, 1, 2, 5, 1, 2, 3, 4, 5

1	5
2	
3	5 4
4	3

- Counter implementation
 - Every page entry has a counter; every time page is referenced through this entry, copy the clock into the counter
 - When a page needs to be changed, look at the counters to determine which are to change





LRU Page Replacement

reference string

7 0 1 2 0 3 0 4 2 3 0 3 2 1 2 0 1 7 0 1

7	7	7	2		2		4	4	4	0			1		1		1		
	0	0	0		0		0	0	3	3			3		0		0		
		1	1		3		3	2	2	2			2		2		7		

page frames





Counting Algorithms

- Keep a counter of the number of references that have been made to each page
- **LFU Algorithm:** replaces page with smallest count
- **MFU Algorithm:** based on the argument that the page with the smallest count was probably just brought in and has yet to be used





Allocation of Frames

- Each process needs *minimum* number of pages
- Example: IBM 370 – 6 pages to handle SS MOVE instruction:
 - instruction is 6 bytes, might span 2 pages
 - 2 pages to handle *from*
 - 2 pages to handle *to*
- Two major allocation schemes
 - fixed allocation
 - priority allocation





Fixed Allocation

- Equal allocation – For example, if there are 100 frames and 5 processes, give each process 20 frames.
- Proportional allocation – Allocate according to the size of process
 - s_i = size of process p_i
 - $S = \sum s_i$
 - m = total number of frames
 - a_i = allocation for $p_i = \frac{s_i}{S} \times m$

$$m = 64$$

$$s_1 = 10$$

$$s_2 = 127$$

$$a_1 = \frac{10}{137} \times 64 \approx 5$$

$$a_2 = \frac{127}{137} \times 64 \approx 59$$





Priority Allocation

- Use a proportional allocation scheme using priorities rather than size
- If process P_i generates a page fault,
 - select for replacement one of its frames
 - select for replacement a frame from a process with lower priority number





Global vs. Local Allocation

- **Global replacement** – process selects a replacement frame from the set of all frames; one process can take a frame from another
- **Local replacement** – each process selects from only its own set of allocated frames





Thrashing


- If a process does not have “enough” pages, the page-fault rate is very high. This leads to:
 - low CPU utilization
 - operating system thinks that it needs to increase the degree of multiprogramming
 - another process added to the system

- **Thrashing** \equiv a process is busy swapping pages in and out





Thrashing (Cont.)



End of Chapter 9

