

BCA – 401: Java Programming

Rahul Kumar Singh

In today's Class we have discussed on Multithreading in Java.

Multitasking:-

Multitasking is a process of executing multiple tasks simultaneously. We use multitasking to utilize the CPU. Multitasking can be achieved in two ways:

- Process-based Multitasking (Multiprocessing)
- Thread-based Multitasking (Multithreading)

1) Process-based Multitasking (Multiprocessing)

- Each process has an address in memory. In other words, each process allocates a separate memory area.
- A process is heavyweight.
- Cost of communication between the process is high.
- Switching from one process to another requires some time for saving and loading registers, memory maps, updating lists, etc.

2) Thread-based Multitasking (Multithreading)


- Threads share the same address space.
- A thread is lightweight.
- Cost of communication between the thread is low.

Note: At least one process is required for each thread.

Thread in java:-

A thread is a lightweight subprocess, the smallest unit of processing. It is a separate path of execution.

Threads are independent. If there occurs exception in one thread, it doesn't affect other threads. It uses a shared memory area.



As shown in the above figure, a thread is executed inside the process. There is context-switching between the threads. There can be multiple processes inside the OS, and one process can have multiple threads.

Note: At a time one thread is executed only.

Multithreading in Java:-

Multithreading in Java is a process of executing multiple threads simultaneously.

As we know that a thread is a lightweight sub-process, the smallest unit of processing. Multiprocessing and multithreading, both are used to achieve multitasking.

However, we use multithreading than multiprocessing because threads use a shared memory area. They don't allocate separate memory area so saves memory, and context-switching between the threads takes less time than process.

Java Multithreading is mostly used in games, animation, etc.

Advantages of Java Multithreading:-


- 1) It **doesn't block the user** because threads are independent and you can perform multiple operations at the same time.
- 2) You can **perform many operations together**, so it **saves time**.
- 3) Threads are **independent**, so it doesn't affect other threads if an exception occurs in a single thread.

Life cycle of a Thread (Thread States):-


A thread goes through various stages in its life cycle. For example, a thread is born, started, runs, and then dies. The following diagram shows the complete life cycle of a thread.

In Java, a thread always exists in any one of the following states. These states are:

- 1) New
- 2) Active
- 3) Blocked / Waiting
- 4) Timed Waiting
- 5) Terminated



Life Cycle of a Thread



Explanation of Different Thread States:-

New:-

A new thread begins its life cycle in the new state. It remains in this state until the program starts the thread. It is also referred to as a born thread.

Whenever a new thread is created, it is always in the new state. For a thread in the new state, the code has not been run yet and thus has not begun its execution.

Active:-

When a thread invokes the `start()` method, it moves from the new state to the active state. The active state contains two states within it: one is runnable, and the other is running.

► Runnable:-

After a newly born thread is started, the thread becomes runnable. A thread in this state is considered to be executing its task.

A thread, that is ready to run is then moved to the runnable state. In the runnable state, the thread may be running or may be ready to run at any given instant of time. It is the duty of the thread scheduler to provide the thread time to run, i.e., moving the thread the running state.

A program implementing multithreading acquires a fixed slice of time to each individual thread. Each and

every thread runs for a short span of time and when that allocated time slice is over, the thread voluntarily gives up the CPU to the other thread, so that the other threads can also run for their slice of time. Whenever such a scenario occurs, all those threads that are willing to run, waiting for their turn to run, lie in the runnable state. In the runnable state, there is a queue where the threads lie.

► **Running:-**

When the thread gets the CPU, it moves from the runnable to the running state. Generally, the most common change in the state of a thread is from runnable to running and again back to runnable.

Blocked or Waiting:-

Sometimes, a thread transitions to the waiting state while the thread waits for another thread to perform a task. A thread transitions back to the runnable state only when another thread signals the waiting thread to continue executing.

Whenever a thread is inactive for a span of time (not permanently) then, either the thread is in the blocked state or is in the waiting state.

For example, a thread (let's say its name is A) may want to print some data from the printer. However, at the same time, the other thread (let's say its name is B) is using the printer to print some data. Therefore, thread A has to wait for thread B to use the printer. Thus, thread A is in the

blocked state. A thread in the blocked state is unable to perform any execution and thus never consume any cycle of the Central Processing Unit (CPU). Hence, we can say that thread A remains idle until the thread scheduler reactivates thread A, which is in the waiting or blocked state.

When the main thread invokes the `join()` method then, it is said that the main thread is in the waiting state. The main thread then waits for the child threads to complete their tasks. When the child threads complete their job, a notification is sent to the main thread, which again moves the thread from waiting to the active state.

If there are a lot of threads in the waiting or blocked state, then it is the duty of the thread scheduler to determine which thread to choose and which one to reject, and the chosen thread is then given the opportunity to run.

Timed Waiting:-

A runnable thread can enter the timed waiting state for a specified interval of time. A thread in this state transitions back to the runnable state when that time interval expires or when the event it is waiting for occurs.

Sometimes, waiting for leads to **starvation**. For example, a thread (its name is A) has entered the critical section of a code and is not willing to leave that critical section. In such a scenario, another thread (its name is B) has to wait forever, which leads to starvation. To avoid such scenario, a

timed waiting state is given to thread B. Thus, thread lies in the waiting state for a specific span of time, and not forever. A real example of timed waiting is when we invoke the `sleep()` method on a specific thread. The `sleep()` method puts the thread in the timed wait state. After the time runs out, the thread wakes up and start its execution from when it has left earlier.

Terminated:-

A runnable thread enters the terminated state when it completes its task or otherwise terminates.

A thread reaches the termination state because of the following reasons:

- When a thread has finished its job, then it exists or terminates normally.
- Abnormal termination: It occurs when some unusual events such as an unhandled exception or segmentation fault.

A terminated thread means the thread is no more in the system. In other words, the thread is dead, and there is no way one can respawn (active after kill) the dead thread.

