

Agents & Graph Nodes — Goals, Responsibilities, Role

Autonomous Social Media Content Studio · reference companion to the architecture deck

THE 5 AGENTS (a prompt + a model call)

Agent	Goal	Responsibilities	Role in the pipeline
Manager <code>write_brief()</code>	Turn raw source material into one shared, self-contained brief every other agent works from.	Condenses arbitrary-length input into a brief under ~150 words. Nothing downstream ever sees the original source — only this brief.	Runs once, first, on a new run. Its output is the only shared context the three writers get.
Platform Writer ×3 <code>write_post()</code>	Produce a publish-ready post for one platform, inside its character limit and house style.	Writes a fresh draft from the brief, or rewrites the old draft against a fix instruction on a revision pass. Never sees the other two platforms' drafts.	Runs 1–3 times per platform (write → self-check → revise loop), plus again if the Consistency Checker flags a contradiction.
Self-Critic <code>self_critique()</code>	Gate quality before a draft ships — decide OK or hand back one concrete fix.	Returns exactly “OK” or one imperative fix sentence. Only runs after the free, deterministic <code>check_length()</code> passes. Shown its own previous note on a revision pass; told to accept on the final attempt unless factually wrong or off-brief.	Its verdict drives <code>after_self_check()</code> — revise (back to Writer) or accept.
Consistency Checker <code>check_consistency()</code>	Catch contradictions across the three finished posts (numbers, dates, claims).	Structured-output comparison of all three accepted drafts against each other and the brief; returns any conflicts found.	Runs once per run, after all three platform branches rejoin — the only agent that ever sees all three drafts together. Triggers a targeted rewrite for any platform in conflict.
Intent Router <code>route_message()</code>	On a second-or-later message in a thread, decide what the user actually means before anything runs.	Structured output (<code>RefineIntent</code>) classifying the message as fresh source (new), or a targeted refine with platform(s) + instruction. Sees the last 5 edits as history.	The one agent with no graph node — lives in <code>main.py</code> , above the graph, deciding whether to invoke the graph at all.

THE 6 GRAPH NODES (a step in the LangGraph workflow — not the same thing as an agent)

Node (agent it runs)	Goal	Responsibilities	Role in the graph
manager <code>Manager</code>	Get the brief written.	Wraps the Manager agent; resets <code>drafts={}</code> ; logs the action/trace entry.	First node after START. Its conditional edge, <code>fan_out()</code> , launches the three parallel platform branches.

Node (agent it runs)	Goal	Responsibilities	Role in the graph
platform (subgraph) – wrapper only	Contain the per-platform write/self-check/accept loop so it can run 3× in parallel.	None of its own — no agent, no model call. Purely a container LangGraph sends Send() calls into.	Sits between manager and consistency; three instances run in the same superstep, one per platform, each its own checkpoint namespace.
write Platform Writer	Get one draft (or revision) on the table for one platform.	Wraps the Platform Writer; checks state["problem"] to pick a fresh draft vs. a revision; increments the attempt counter.	Entry point of the platform subgraph; loops back to itself via self_check → revise, up to MAX_ATTEMPTS = 3.
self_check Self-Critic	Decide if a draft is good enough to ship.	Runs check_length() first (free, deterministic); only escalates to the Self-Critic if length passes; detects a critic repeating its last note.	Feeds after_self_check(), the actual branch decision: revise (→ write) or accept.
accept none – pure state transition	Formally publish one platform's draft into shared state.	No agent, no model call. Tags the draft accepted or accepted_as_is (attempts ran out with an open problem).	Exit point of each platform branch; the three accept outputs merge via merge_drafts() before the outer graph moves on.
consistency Consistency Checker	Reconcile the three finished posts before the run ends.	Wraps the Consistency Checker; rewrites (write_post(fix=...)) any platform flagged with a contradiction.	Last node in the outer graph; runs once after all three branches join; its output is what the API returns.

One asymmetry ties both tables together: **accept** has a node but no agent (it's a pure state transition), while the **Intent Router** has an agent but no node (it has to decide whether to invoke the graph at all, so it sits above it, in main.py). Most nodes wrap exactly one agent — these two don't, and that's where the design lives.