



Incident report analysis

Summary	A DoS attack was recently experienced, which compromised the internal network for about 2 hours after which it was resolved. During the attack, the organization's network services stopped responding because of an incoming flood of ICMP packets. The incident management team responded by blocking incoming ICMP packets, stopping all non-critical network services offline, and restoring critical network services.
Identify	A malicious actor or actors targeted the company with an ICMP flood attack. The entire internal network was affected. All critical network resources needed to be secured and restored to a functioning state.
Protect	The cybersecurity team implemented a new firewall rule to limit the rate of incoming ICMP packets and an IDS/IPS system to filter out some ICMP traffic based on suspicious characteristics.
Detect	The cybersecurity team configured source IP address verification on the firewall to check for spoofed IP addresses on incoming ICMP packets and implemented network monitoring software to detect abnormal traffic patterns.
Respond	For future security events, the cybersecurity team will isolate affected systems to prevent further disruption to the network. They will attempt to restore any critical systems and services that were disrupted by the event. Then, the team will analyze network logs to check for suspicious and abnormal activity. The team will also report all incidents to upper management and appropriate legal authorities, if applicable.
Recover	To recover from a DoS attack by ICMP flooding, access to network services

	need to be restored to a normal functioning state. In the future, external ICMP flood attacks can be blocked at the firewall. Then, all non-critical network services should be stopped to reduce internal network traffic. Next, critical network services should be restored first. Finally, once the flood of ICMP packets have timed out, all non-critical network systems and services can be brought back online.
--	--
