

No.	Questions
	What is Dictionaries?
	Dictionary Length?
	The dict() Constructor
	How to Check if Item Exists?
	Access Item of Dictionary?
	Add Dictionary Items?
	Change Or Update Dictionary Items?
	Remove Dictionary Items?
	Copy Dictionaries?
	Loop Dictionaries?
	Dictionary Methods?

Ques. What is Dictionaries?

- Dictionaries are written with curly **brackets{}**, and have keys and values.
- Dictionary items are **ordered**, **changeable**, and **does not allow duplicates**.
- Dictionaries are **changeable**, meaning that we can change, add or remove items after the dictionary has been created.

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964,  
    "year": 2020,  
    "electric": False,  
    "colors": ["red", "white", "blue"]  
}  
print(thisdict)
```

Output:- {'brand': 'Ford', 'model': 'Mustang', 'year': 2020, 'electric': False, 'colors': ['red', 'white', 'blue']}

Ques. Dictionary Length?

- To determine how many items a dictionary has, use the **len()** function.

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964,  
    "year": 2020  
}  
print(len(thisdict))    # Dictionary Length:- Output:- 3
```

The dict() Constructor

- It is also possible to use the **dict()** constructor to make a dictionary.

```
thisdict = dict(name = "John", age = 36, country = "Norway")  
print(thisdict)  
Output:- {'name': 'John', 'age': 36, 'country': 'Norway'}
```

Check if Key Exists

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
if "model" in thisdict:  
    print("Yes, 'model' is one of the keys in the thisdict dictionary")
```

Output:- Yes, 'model' is one of the keys in the thisdict dictionary

Access Item of Dictionary

Ques. Access Item of Dictionary?

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
  
# Using key name:- We can access the items of a dictionary by referring to its  
**key name**, inside square brackets.  
x = thisdict["model"]  
print(x)    # Output:- Mustang  
  
# using the get() method:- Using the **get()** Method  
x = thisdict.get("model")  
print(x)    # output:- Mustang  
  
# Get **All Keys** of the Dictionary:- The **keys() method** will return a list of  
all the keys in the dictionary.  
x = thisdict.keys()  
print(x)    # Output:- dict_keys(['brand', 'model', 'year'])  
  
# Get **All Values** of the Dictionary and We can change the value of a specific  
item by referring to its key name.  
x = thisdict.values()  
print(x)    # Output:- dict_values(['Ford', 'Mustang', 1964])  
  
# Get **All Items** :- The items() method will return each item in a dictionary,  
as tuples in a list.  
x = thisdict.items()  
print(x)    # Output:- dict_items([('brand', 'Ford'), ('model', 'Mustang'),  
('year', 1964)])
```

Add Dictionary Items

Ques. Add Dictionary Items?

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
  
# Using key:- using key add the items  
thisdict["color"] = "red"  
print(thisdict)    # Output:- {'brand': 'Ford', 'model': 'Mustang', 'year': 1964,  
                             'color': 'red'}  
  
# Using Update() method:- Adding Items using **Update()** Method  
thisdict.update({"color": "red"})  
print(thisdict)    # Output:- {'brand': 'Ford', 'model': 'Mustang', 'year': 1964,  
                             'color': 'red'}
```

Change Or Update Dictionary Items?

Change Or Update Dictionary Items

- Change Values:- We can change the value of a specific item by referring to its **key name**.

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}
```

Using key name:- We can change the value of a specific item by referring to its key name.

```
thisdict["year"] = 2018
```

```
print(thisdict)    # Output:- {'brand': 'Ford', 'model': 'Mustang', 'year': 2018}
```

Using Update method:-

```
thisdict.update({"year": 2020})
```

```
print(thisdict)    # Output:- {'brand': 'Ford', 'model': 'Mustang', 'year': 2020}
```

Remove Dictionary Items?

Ques. Remove Dictionary Items?

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}
```

using pop() method:- The **pop()** method removes the item with the specified **key name**:

```
thisdict.pop("model")  
print(thisdict) # Output:- {'brand': 'Ford', 'year': 1964}
```

using **popitem()** methods:- method removes the last inserted item (in versions before 3.7, a random item is removed instead).

```
thisdict.popitem()  
print(thisdict) # Output:- {'brand': 'Ford', 'model': 'Mustang'}
```

using del method:- Using **del** methods removes the item with the specified **key name**.

```
del thisdict["model"]  
print(thisdict) # Output:- {'brand': 'Ford', 'year': 1964}
```

using del method without key name:- If we **can not define the key name** del method delete the dictionary completely.

The Removing item using del methods keyword can also delete the dictionary completely.

```
del thisdict  
print(thisdict) # Output:- this will cause an error because "thisdict" no longer exists.
```

using clear method:- The Removing item using **clear()** methods method empties the dictionary.

```
thisdict.clear()  
print(thisdict) # output:- Output:- {}
```

Copy Dictionaries?

Ques. Copy Dictionaries?

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
  
# using copy method:-  
mydict = thisdict.copy()  
print(mydict)    # Output:- {'brand': 'Ford', 'model': 'Mustang', 'year': 1964}  
  
# using dict() method:-  
mydict = dict(thisdict)  
print(mydict)    # Output:- {'brand': 'Ford', 'model': 'Mustang', 'year': 1964}
```


Loop Dictionaries?

Ques. Loop Dictionaries?

```
# print Dictionaries by key, value and item
a = {1:12 ,2:11 ,4:16 ,3:14 ,6:15 ,5:13 }
print(sorted(a.keys()))
print(sorted(a.values()))
print(sorted(a.items()))
```

Output:-

```
[1, 2, 3, 4, 5, 6]
[11, 12, 13, 14, 15, 16]
[(1, 12), (2, 11), (3, 14), (4, 16), (5, 13), (6, 15)]
```

- Print **all key names** in the dictionary, one by one.

```
thisdict = {
    "brand": "Ford",
    "model": "Mustang",
    "year": 1964
}
for x in thisdict:
    print(x)
```

Output:-

```
brand
model
year
```

- Print all values in the dictionary, one by one:

```
thisdict = {
    "brand": "Ford",
    "model": "Mustang",
    "year": 1964
}
for x in thisdict:
    print(thisdict[x])
```

Output:-

```
Ford
Mustang
1964
```

- We can use the **keys()** method to return the keys of a dictionary:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
for x in thisdict.keys():  
    print(x)
```

Output:-

brand
model
year

- You can also use the **values()** method to return values of a dictionary:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
for x in thisdict.values():  
    print(x)
```

Output:-

Ford
Mustang
1964

- Loop through both keys and values, by using the **items()** method.

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
for x, y in thisdict.items():  
    print(x, y)
```

Output:-

brand Ford
model Mustang
year 1964

Dictionary Methods?

Ques. Dictionary Methods?

Method	Description
clear()	Removes all the elements from the dictionary
copy()	Returns a copy of the dictionary
get()	Returns the value of the specified key.
pop()	Removes the element with the specified key.
popitem()	Removes the last inserted key-value pair.
fromkeys()	Returns a dictionary with the specified keys and value.
items()	Returns a list containing a tuple for each key value pair.
keys()	Returns a list containing the dictionary's keys.
setdefault()	Returns the value of the specified key. If the key does not exist: insert the key, with the specified value.
update()	Updates the dictionary with the specified key-value pairs.
values()	Returns a list of all the values in the dictionary.

```
car = {
    "brand": "Ford",
    "model": "Mustang",
    "year": 1964
}

# The **clear()** method removes all the elements from a dictionary.
car.clear()
print(car)    # Output:- {}

# The **copy()** method returns a copy of the specified dictionary.
x = car.copy()
print(x)      # Output:- {'brand': 'Ford', 'model': 'Mustang', 'year': 1964}

# The **get()** method returns the value of the item with the **specified key**.
x = car.get("model")
print(x)      # Output:- Mustang
#
x = car.get("price", 15000)
print(x)      # Output:- 15000
```

```
# The **pop()** method removes the specified item from the dictionary.
x = car.pop("model")
print(x)    # output:- Mustang
print(car)  # Output:- {'brand': 'Ford', 'year': 1964}

# The **popitem()** method removes the item that was last inserted into the
dictionary.
x = car.popitem()
print(x)    # Output:- ('year', 1964)
print(car)  # Output:- {'brand': 'Ford', 'model': 'Mustang'}
```

- The **fromkeys()** method returns a dictionary with the specified keys and the specified value.

```
# Example1:-
x = ('key1', 'key2', 'key3')
y = 0
thisdict = dict.fromkeys(x, y)
print(thisdict)

Output:- {'key1': 0, 'key2': 0, 'key3': 0}

# Example2:-
x = ('key1', 'key2', 'key3')
thisdict = dict.fromkeys(x)
print(thisdict)

Output:- {'key1': None, 'key2': None, 'key3': None}
```

- The **items()** method returns a view object. The view object contains the \n key-value pairs of the dictionary, as tuples in a list.

```
car = {
    "brand": "Ford",
    "model": "Mustang",
    "year": 1964
}
x = car.items()
print(x)

Output:- dict_items([('brand', 'Ford'), ('model', 'Mustang'), ('year', 1964)])

# example2:-
car = {
    "brand": "Ford",
    "model": "Mustang",
    "year": 1964
}
```

```
x = car.items()
car["year"] = 2018
print(x)
```

Output:- dict_items([('brand', 'Ford'), ('model', 'Mustang'), ('year', 2018)])

- The **keys()** method returns a view object. The view object contains the keys of the dictionary, as a list.

```
car = {
    "brand": "Ford",
    "model": "Mustang",
    "year": 1964
}
x = car.keys()
print(x)
```

```
car["color"] = "white"
print(x)
```

Output:- dict_keys(['brand', 'model', 'year'])

Output:- dict_keys(['brand', 'model', 'year', 'color'])

- The **setdefault()** method returns the value of the item with the specified key.

```
car = {
    "brand": "Ford",
    "model": "Mustang",
    "year": 1964
}

x = car.setdefault("color", "White")
y = car.setdefault("model", "Bronco")

print(x)
print(y)
```

Output:- White

Output:- Mustang

- The **update()** method inserts the specified items to the dictionary.

```
car = {
    "brand": "Ford",
    "model": "Mustang",
    "year": 1964
}
```

```
car.update({"color": "White"})
print(car)    # Output:- {'brand': 'Ford', 'model': 'Mustang', 'year': 1964,
'color': 'White'}
```

- The **values()** method returns a view object. The view object contains the values of the dictionary, as a list.

```
car = {
    "brand": "Ford",
    "model": "Mustang",
    "year": 1964
}
x = car.values()
print(x)    # Output:- dict_values(['Ford', 'Mustang', 1964])

# Example2:-
car = {
    "brand": "Ford",
    "model": "Mustang",
    "year": 1964
}

x = car.values()
car["year"] = 2018
print(x)    # Output:- dict_values(['Ford', 'Mustang', 2018])
```

