

Table of Contents

No. **Mysql Commomn Questions**

What is database?

what is sql?

What Is DBMS?

What Is RDBMS?

Difference between DBMS & RDBMS?

No. **Mysql User Management**

Create Databse user?

Show Databse user?

Show Current user?

User Password Change?

Drop User?

Grant Privileges to the MySQL New User?

Show Privileges?

REVOKE Privileges?

No. **Database**

Show Database

Create Databse

Rename Database

Drop/Delete Database

Select Database

No. **Tables**

Types of SQL Commands/subsets of SQL?

Data Definition Language (DDL)

Data Manipulation Language (DML)

Data Control Language (DCL)

Transaction Control Language (TCL)

Create TABLE?

No. Tables

show Tables

See the table structure

Alter

ADD a column in the table

Add column after particular field

Add column in first

Add multiple columns in the table

Use table

RENAME column in table?

Delete/Drop table

Select table

UPDATE

DELETE

Change Datatype from alter cmd?

DROP column in table?

TRUNCATE table?

RENAME table name?

Difference between Delete, Truncate & Drop?

Difference b/w DROP and TRUNCATE statements?

No. SQL Comments?

Difference between **CHAR** and **VARCHAR** data types?

Difference between In and Between Operator in SQL?

IN and NOT IN Operator

BETWEEN and NOT BETWEEN Operator?

What is Aggregate function?(sum,avg,max,min,count)

SQL Operators and Clauses

LIKE

INNER JOIN

No. SQL Comments?

OUTER JOIN

IF()

IFNULL

NULLIF

IS NULL and IS NOT NULL

Round()

BETWEEN()

AND

OR

Case

GROUP BY

Having

Limit

ORDER BY

SELECT DISTINCT

With()

WHERE

Wildcard Characters/Like Query

what is Aliases?

What Is Union & Union All

What is Intersect?

What is MINUS?

No. Keys

Primary Key?

Add primary Key?

Delete primary Key?

Unique Key?

ALTER unique key?

Drop unique key?

Foreign Key?

No. Keys

Foreign Key Add/ALTER?

DROP Foreign Key?

Composite Key?

Difference between Primary Key & Unique Key?

Difference between Primary Key & Foreign Key?

No. Joins

What Is Joins?

self join

INNER JOIN

Left JOIN/LEFT OUTER JOIN

Right JOIN

Outer join

CROSS Join

Full Join/FULL OUTER JOIN

Difference between Delete, Truncate & Drop?

What is View?

No. Index

What is Index?

Types of Indexes

Unique Indexes

Show Index

Alter/Modify an Index

Drop Index

Unique Indexes

Cluster Index

Non cluster index

difference between cluster and non cluster index?

No. View

What is View?

Create view

No. View

Show view

Alter view

Deleted view

What is ACID property/SQL TRANSACTIONS?**No. interview_Questions_answers**

What are Constraints in SQL?**No. Sql Query questions**

Check version of the sql?

Current date?

How to copy a table in another table?

How to copy structure of a table but not data?

How to find **Nth** highest salary from a table?

Top Nth Salary?

Find the Highest Salary of Each Department?

How to Find Duplicate values in a Table?

Replace a Column Values from 'male' to 'female' and 'female' to 'male'?

Update remaing days startdate - enddate

Count phone number

<https://www.w3resource.com/sql-exercises/joins-hr/sql-joins-hr-exercise-11.php>

Sql

Ques. What is database?

- A database is an organized collection of data, stored and retrieved digitally from a remote or local computer system. Databases can be vast and complex, and such databases are developed using fixed design and modeling approaches.
- Database is nothing but an organized form of data for easy access, storing, retrieval and managing of data.
- This is also known as structured form of data which can be accessed in many ways.

Ques. What is Sql?

- SQL is stands for **structure query language**.
- It is a database language **used** for database **creation, deletion, fetching** rows and modifying rows etc.
- It is a kind of ANSI standard language, used with all database.

Ques. What Is DBMS?

- A database management system is program that control creation, maintenance and use of a database.
- DBMS can be termed as File Manager that manages data in a database rather than saving it in file systems.

What is RDBMS?

- RDBMS stands for Relational Database Management System. RDBMS store the data into the collection of tables, which is related by common fields between the columns of the table. It also provides relational operators to manipulate the data stored into the tables.

Ques. Difference between DBMS & RDBMS?

DBMS	RDBMS
DBMS applications store data as file	RDBMS applications store data in a tabular form
Normalization is not present in DBMS	Normalization is present in RDBMS
DBMS does not support distributed data hnbase	RDBMS support distributed database

User Management

Create User

```
CREATE USER username@hostname IDENTIFIED BY 'password';  
-- The hostname is optional then  
CREATE USER username IDENTIFIED BY 'password';
```

Show all Users

```
select user from mysql.user;  
+-----+  
| User   |  
+-----+  
| root   |  
| mohits4 |  
+-----+
```

Show Current User

```
SELECT USER();  
OR  
Select current_user();
```

User Password Change

```
SET PASSWORD FOR 'mohits4'@'hostname' = PASSWORD('jtp12345');  
OR  
ALTER USER mohits4@hostname IDENTIFIED BY 'jtp123';
```

Drop User

```
DROP USER mohits4@localhost;  
--can also be used to remove more than one user accounts at once.  
DROP USER john@localhost, peter@localhost;
```

Grant Privileges to the MySQL New User

1. **ALL PRIVILEGES**: It permits all privileges to a new user account.
2. **CREATE**: It enables the user account to create databases and tables.
3. **DROP**: It enables the user account to drop databases and tables.
4. **DELETE**: It enables the user account to delete rows from a specific table.
5. **INSERT**: It enables the user account to insert rows into a specific table.
6. **SELECT**: It enables the user account to read a database.
7. **UPDATE**: It enables the user account to update table rows.

☐ Note:- Sometimes, you want to flush all the privileges of a user account for changes occurs immediately

```
FLUSH PRIVILEGES;
```

```
-- If you want to give all privileges to a newly created user, execute the following command.
```

```
GRANT ALL PRIVILEGES ON * . * TO username@hostname;
```

```
-- If you want to give specific privileges to a newly created user, execute the following command.
```

```
GRANT CREATE, SELECT, INSERT ON * . * TO username@hostname;
```

Show Privileges

```
SHOW GRANTS for mohits4;  
SHOW GRANTS FOR 'local_user'@'localhost';
```

REVOKE Privileges

```
REVOKE ALL PRIVILEGES ON *.* FROM 'mohits4'@'hostname';  
-- If you want to remove specific privileges to a newly created user  
REVOKE SELECT ON *.* FROM 'mohits4'@'hostname';  
-- Revoke **all privileges** on a specific **database**:  
REVOKE ALL PRIVILEGES ON database_name.* FROM 'mohits4'@'hostname';  
-- Revoke **SELECT privilege** on a **specific** **table**:  
REVOKE SELECT ON database_name.table_name FROM 'mohits4'@'hostname';
```


Database

Show Database

```
SHOW DATABASES/SCHEMAS;
SHOW DATABASES [LIKE 'pattern' | WHERE expr];
SHOW DATABASES LIKE 'test%';
SELECT * FROM sys.databases;
EXEC sp_databases;
+-----+
| Database          |
+-----+
| employeesdb       |
| profile_fastapi   |
+-----+
```

Create Database

```
CREATE DATABASE databasename;
```

Rename Database

```
RENAME DATABASE old_database_name TO new_database_name
(OR)
ALTER DATABASE old_database MODIFY NAME = new_database
```

Drop Database

```
DROP DATABASE/SCHEMA database_name;

-- DROP DATABASE IF EXISTS Statement
DROP DATABASE IF EXISTS DatabaseName;

-- Deleting Multiple Databases
DROP DATABASE testDB3, testDB4;
```

Select Database

```
USE YourDatabaseName;
```

Tables

Types of SQL Commands/subsets of SQL?

- DDL (Data Definition Language):
 - **CREATE:** Creates a new table or database.
 - **ALTER:** Modifies an existing database object.
 - **DROP:** Deletes an entire table, database, or other objects.
 - **TRUNCATE:** Removes all records from a table, deleting the space allocated for the records.
- DML (Data Manipulation Language):
 - **SELECT:** Retrieves data from the database.
 - **INSERT:** Adds new data to a table.
 - **UPDATE:** Modifies existing data within a table.
 - **DELETE:** Removes data from a table.
- DCL (Data Control Language):
 - **GRANT:** Gives users access privileges to the database.
 - **REVOKE:** Removes access privileges given with the GRANT command.
- TCL (Transaction Control Language):
 - **COMMIT:** Saves all changes made in the current transaction.
 - **ROLLBACK:** Restores the database to the last committed state.
 - **SAVEPOINT:** Sets a savepoint within a transaction.
 - **SET TRANSACTION:** Places a name on a transaction.

Tables commands

Create table

```
CREATE TABLE table_name(  
  id int NOT NULL AUTO_INCREMENT,  
  name varchar(45) NOT NULL,  
  occupation varchar(35) NOT NULL,  
  age int NOT NULL,  
  PRIMARY KEY (id)  
);
```

Show tables

```
SHOW TABLES;  
+-----+  
| Tables_in_employee123 |
```

```
+-----+
| employee_table |
+-----+
```

See the table structure

```
DESCRIBE employee_table;
```

```
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra      |
+-----+-----+-----+-----+-----+-----+
| id         | int(11)   | NO   | PRI | NULL    | auto_increment |
| name       | varchar(45) | NO   |     | NULL    |              |
| occupation | varchar(35) | NO   |     | NULL    |              |
| age        | int(11)   | NO   |     | NULL    |              |
+-----+-----+-----+-----+-----+-----+
```

Alter

- ALTER TABLE lets you add columns to a table in a database.

```
ALTER TABLE table_name ADD column_name datatype;
(OR)
ALTER TABLE table_name
ADD new_column_name datatype
[ FIRST | AFTER column_name ];
```

ADD a column in the table

```
ALTER TABLE employee_table ADD cus_age varchar(40) NOT NULL;
```

```
DESCRIBE employee_table;
```

```
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra      |
+-----+-----+-----+-----+-----+-----+
| id         | int(11)   | NO   | PRI | NULL    | auto_increment |
| name       | varchar(45) | NO   |     | NULL    |              |
| occupation | varchar(35) | NO   |     | NULL    |              |
| age        | int(11)   | NO   |     | NULL    |              |
| cus_age    | varchar(40) | NO   |     | NULL    |              |
+-----+-----+-----+-----+-----+-----+
```

Add column after particular field

```
ALTER TABLE employee_table ADD after_occupation varchar(40) NOT NULL AFTER occupation;
```

Field	Type	Null	Key	Default	Extra
id	int(11)	NO	PRI	NULL	auto_increment
name	varchar(45)	NO		NULL	
occupation	varchar(35)	NO		NULL	
after_occupation	varchar(40)	NO		NULL	
age	int(11)	NO		NULL	
cus_age	varchar(40)	NO		NULL	

Add column in first

```
ALTER TABLE employee_table ADD COLUMN unique_id INT(11) NOT NULL FIRST;
```

Field	Type	Null	Key	Default	Extra
unique_id	int(11)	NO		NULL	
id	int(11)	NO	PRI	NULL	auto_increment
name	varchar(45)	NO		NULL	
occupation	varchar(35)	NO		NULL	
after_occupation	varchar(40)	NO		NULL	
age	int(11)	NO		NULL	
cus_age	varchar(40)	NO		NULL	

Add multiple columns in the table

```
ALTER TABLE employee_table
  ADD COLUMN unique_id1 INT(11) NOT NULL FIRST,
  ADD COLUMN unique_id2 INT(11) NOT NULL FIRST;
```

Field	Type	Null	Key	Default	Extra
unique_id2	int(11)	NO		NULL	
unique_id1	int(11)	NO		NULL	
unique_id	int(11)	NO		NULL	
id	int(11)	NO	PRI	NULL	auto_increment
name	varchar(45)	NO		NULL	
occupation	varchar(35)	NO		NULL	
after_occupation	varchar(40)	NO		NULL	
age	int(11)	NO		NULL	
cus_age	varchar(40)	NO		NULL	

```
+-----+-----+-----+-----+-----+-----+  
  
-- add enum column  
  
ALTER TABLE table_name ADD field_name enum('0','1') NOT NULL DEFAULT '0' after  
password;
```

Change Datatype from alter cmd

```
ALTER TABLE employee_table MODIFY unique_id4 VARCHAR(40) NULL;  
OR  
ALTER TABLE employee_table MODIFY COLUMN unique_id4 VARCHAR(40) NULL;
```

DROP column in table

```
ALTER TABLE employee_table DROP COLUMN unique_id4;
```

[↑ Back to top](#)

Use table

```
use database_name;
```

Delete/Drop table

```
DROP TABLE table_name;
```

RENAME column in table

```
RENAME old_table_name To new_table_name;  
OR  
RENAME table old_table_name TO new_table_name;  
OR  
ALTER TABLE old_table_name RENAME TO new_table_name;
```

SELECT

- SELECT statements are used to fetch data from a database. Every query will begin with SELECT.

```
SELECT * FROM table_name;    -- fetch Full data  
SELECT column_name FROM table_name;    -- fetch particular column
```

Insert table

```
INSERT INTO table_name  
(column1,column2,column3,...)  
VALUES  
( 'value1', 'value2', 'value3', ... );
```

UPDATE

- UPDATE statements allow you to edit rows in a table.

```
UPDATE table_name  
SET some_column = some_value  
WHERE some_column = some_value;  
--  
Update customer set name="mohit" where id =1;
```

DELETE

- DELETE is a DML(Data Manipulation Language) command and is used when we specify the row (tuple) that we want to remove or delete from the table or relation. The DELETE command can contain a WHERE clause.

```
DELETE FROM table_name  
WHERE some_column = some_value;
```

Truncate

- A truncate SQL statement is used to remove all rows (complete data) from a table.
- TRUNCATE is a DDL(Data Definition Language) command and is used to delete all the rows or tuples from a table. Unlike the DELETE command, the TRUNCATE command does not contain a WHERE clause.

```
TRUNCATE TABLE table_name;
```

Ques. Difference between Delete, Truncate & Drop?

Delete	Truncate	Drop
Delete is a DML command	Truncate is DDL command	
We can use where clause in delete command	We cannot use where clause with truncate	
Delete statement is used to delete a row from a table	Truncate statement is used to remove all the row from a table	Remove table and data
You can rollback data after using delete statement	It is not possible to rollback after using TRUNCATE statement.	Can't rollback
Delete is slower	Truncate is faster	

Ques. Difference b/w DROP and TRUNCATE statements?

- **Drop Table:-**
 - Table structure will be dropped
 - Relationship will be dropped
 - Integrity constraints will be dropped
 - Access privileges will also be dropped
- **TRUNCATE Table:-**
 - On the other hand when we TRUNCATE a table, the table structure remains the same, so you will not face any of the above problems.

SQL Comments?

- There are typically two main types of SQL comments:

1. **Single-line Comments:** Started with two dashes (--)

```
-- This is a single-line comment  
SELECT * FROM employees; -- Retrieve all employee records
```

2. **Multi-line Comments:** Started with /* and ended with */

```
/* This is a  
   multi-line comment  
   explaining the query */  
SELECT id, name, email FROM employees;
```


Ques. Difference between CHAR and VARCHAR data types?

- Both of these data types are used for characters.
- **CHAR data** type is used to store **fixed-length** character strings. When VARCHAR data type is used to store **variable-length** character strings.
- char occupies all the space and if space is remaining, then it fill all the blank space with "space". But in case of varchar, It takes only the required length & release remaining.

```
Char -> 10      | R | A | M | space | space | sapce | space | space | space |
space |
Varchar -> 10   | R | A | M |   |   |   |   |   |   |
| R | A | M |
```

- varchar is better than Char in term of space.
- char perform is better than varchar.
- Char max 256 characters, varchar 65535 characters.

Ques. Difference between In and Between Operator in SQL?

- BETWEEN operator is used to **select a range of data between two values** while The IN operator allows you to **specify multiple values**.
- The BETWEEN operator selects a range of data between two values. The values can be numbers, text,etc.

ID	NAME	mark
1	Ramesh	89
2	Khilan	81
3	kaushik	73
3	kaushik	67
4	Chaitali	52

-- between

```
SELECT * FROM emp WHERE marks BETWEEN 50 AND 80
```

ID	NAME	mark
3	kaushik	73
3	kaushik	67
4	Chaitali	52

-- In

```
SELECT * FROM emp WHERE marks IN (89,73)
```

ID	NAME	mark
1	Ramesh	89
3	kaushik	73

Ques. IN and NOT IN Operator?

IN Operator

- The IN operator is a shorthand for multiple OR conditions, It reduces the use of multiple OR conditions in SELECT, INSERT, UPDATE, and DELETE queries.
- The IN operator is used to retrieves results when the specified value matches any value in a set of values or is returned by a subquery.
- This operator allows us to specify multiple values along with the WHERE clause.

```
select * from customers
```

cust_id	cust_name	city	occupation
1	Peter	London	Business
2	Joseph	Texas	Doctor
3	Mark	New Delhi	Engineer
4	Michael	New York	Scientist
5	Alexander	Maxico	Student

```
mysql> SELECT * FROM customer WHERE occupation IN ('Doctor', 'Scientist', 'Engineer');
```

cust_id	cust_name	city	occupation
2	Joseph	Texas	Doctor
3	Mark	New Delhi	Engineer
4	Michael	New York	Scientist

NOT IN Operator

- selects all customers that are located in "Texas", or "New York":

```
SELECT * FROM Customers WHERE city NOT IN ('Texas', 'New York');
```

Output:-

cust_id	cust_name	city	occupation
1	Peter	London	Business
3	Mark	New Delhi	Engineer
5	Alexander	Maxico	Student

Ques. BETWEEN and NOT BETWEEN Operator?

BETWEEN

- The BETWEEN operator selects values within a given range. The values can be numbers, text, or dates.
- The BETWEEN operator is inclusive: begin and end values are included.

```
SELECT column_name(s) FROM table_name  
WHERE column_name BETWEEN value1 AND value2;
```

NOT BETWEEN

- To display the products outside the range of the previous example, use NOT BETWEEN:

```
SELECT column_name(s) FROM table_name  
WHERE column_name NOT BETWEEN value1 AND value2;
```

What is Aggregate function?

```
-- Sum() :- The SUM() function returns the total sum of a numeric column.  
SELECT SUM(column_name) FROM table_name;  
  
-- AVG() :- The AVG() function returns the average value of a numeric column.  
SELECT AVG(column_name) FROM table_name;  
  
-- MAX() :- The MAX() function returns the largest value of the selected column.  
SELECT MAX(column_name) FROM table_name;  
  
-- Min() :- The MIN() function returns the smallest value of the selected column.  
SELECT MIN(column_name) FROM table_name;  
  
-- count() :- The COUNT() function returns the number of rows that matches a  
specified criterion.  
SELECT COUNT(column_name) FROM table_name;
```

SQL Operators and Clauses

Truncate

- A truncate SQL statement is used to **remove all rows** (complete data) from a table.
- TRUNCATE is a **DDL**(Data Definition Language) command and is used to delete all the rows or tuples from a table. Unlike the DELETE command, the TRUNCATE command does not contain a WHERE clause.

```
TRUNCATE TABLE table_name;
```

LIKE

- LIKE is a special operator used with the WHERE clause to search for a specific pattern in a column.

```
SELECT column_name(s)
FROM table_name
WHERE column_name LIKE pattern;
```

INNER JOIN

- An inner join will combine rows from different tables if the join condition is true.

```
SELECT column_name(s)
FROM table_1
JOIN table_2
ON table_1.column_name = table_2.column_name;
```

OUTER JOIN

- An outer join will combine rows from different tables even if the join condition is not met. Every row in the left table is returned in the result set, and if the join condition is not met, then NULL values are used to fill in the columns from the right table.

```
SELECT column_name(s)
FROM table_1
LEFT JOIN table_2
ON table_1.column_name = table_2.column_name;
```

IF()

```
SELECT IF(200>350, 'YES', 'NO'); -- Output:- NO
SELECT IF(251 = 251, ' Correct', 'Wrong'); -- Output:- Correct
```

```
--  
SELECT salary, IF(salary>3000,"Mature","Immature") As Result FROM employee;  
+-----+-----+  
| salary | Result |  
+-----+-----+  
| 2957.00 | Immature |  
| 3100.00 | Mature   |  
+-----+-----+
```

```
SELECT IF(STRCMP('Rinky Ponting','Yuvraj Singh')=0, 'Correct', 'Wrong');
```

IFNULL()

- If the first expression is not NULL, it will return the first expression, which is 'Hello' value.

```
SELECT IFNULL("Hello", "javaTpoint");    # Output:- Hello
```

```
SELECT IFNULL(NULL,5);    # Output:- 5
```

```
+-----+-----+-----+
| emp_name | cellphone | homephone |
+-----+-----+-----+
| mohit    | 2531452   | NULL      |
| Krishna  | NULL      | 345634634 |
| shivani  | 551113    | NULL      |
| akshra   | NULL      | 6574576   |
| abhinav  | NULL      | 674576457 |
+-----+-----+-----+
```

```
SELECT emp_name, IFNULL(cellphone, homephone) phone FROM student_contact;
```

```
+-----+-----+
| emp_name | phone      |
+-----+-----+
| mohit    | 2531452    |
| Krishna  | 345634634  |
| shivani  | 551113     |
| akshra   | 6574576    |
| abhinav  | 674576457  |
+-----+-----+
```


NULLIF()

- The NULLIF function accepts two expressions, and if the first expression is equal to the second expression, it returns the NULL. Otherwise, it returns the first expression.

```
SELECT NULLIF("javaTpoint", "javaTpoint"); # Output:- NULL
```

```
SELECT NULLIF("Hello", "404"); # Output:- Hello
```

cust_id	cust_name	occupation	income	qualification
1	John Miller	Developer	20000	Btech
2	Mark Robert	Engineer	40000	Btech
3	Reyan Watson	Scientist	60000	MSc
4	Shane Trump	Businessman	10000	MBA
5	Adam Obama	Manager	80000	MBA
6	Rincky Ponting	Cricketer	200000	Btech

```
SELECT cust_name, occupation, qualification, NULLIF (qualification,"Btech") result
FROM customer;
```

Output:-

cust_name	occupation	qualification	result
John Miller	Developer	Btech	NULL
Mark Robert	Engineer	Btech	NULL
Reyan Watson	Scientist	MSc	MSc
Shane Trump	Businessman	MBA	MBA
Adam Obama	Manager	MBA	MBA
Rincky Ponting	Cricketer	Btech	NULL

IS NULL and IS NOT NULL

- IS NULL and IS NOT NULL are operators used with the WHERE clause to test for empty values.

```
SELECT column_name(s)
FROM table_name
WHERE column_name IS NULL;
```

ROUND()

- The ROUND() function is used to round a numeric value to a specified number of decimal places.*
- syntax:- syntax:- ROUND(number, decimal_places)

```
SELECT ROUND(123.4567, 2); -- Returns 123.46
SELECT ROUND(123.4567, 0); -- Returns 123
SELECT ROUND(123.4567, -1); -- Returns 120 (rounds to the nearest 10)

-- example:-
SELECT ROUND(salary, 2) AS rounded_salary FROM employees;
```

BETWEEN()

- The BETWEEN operator is used to filter the result set within a certain range. The values can be numbers, text or dates.

```
SELECT column_name(s) FROM table_name
WHERE column_name BETWEEN value_1 AND value_2;
```

AND

- AND is an operator that **combines two conditions. Both conditions must be true** for the row to be included in the result set.
- The MySQL AND Condition (also called the AND Operator) is used to test two or more conditions in a SELECT, INSERT, UPDATE, or DELETE statement.

```
SELECT column_name(s)
FROM table_name
WHERE column_1 = value_1
      AND column_2 = value_2;

SELECT * FROM contacts
WHERE state = 'California'
      AND contact_id > 3000;
```

OR

- OR is an operator that filters the result set to only include rows where either condition is true.

```
SELECT column_name
FROM table_name
WHERE column_name = value_1
      OR column_name = value_2;
```

Case

- CASE statements are used to create different outputs (usually in the SELECT statement). It is SQL's way of handling if-then logic.

```
SELECT column_name,
CASE
  WHEN condition THEN 'Result_1'
  WHEN condition THEN 'Result_2'
  ELSE 'Result_3'
END
FROM table_name;
```

GROUP BY

- GROUP BY is a clause in SQL that is only used with aggregate functions. It is used in collaboration with the SELECT statement to arrange identical data into groups.

```
SELECT column_name, COUNT(*)
FROM table_name
GROUP BY column_name;
```

HAVING

- HAVING was added to SQL because the WHERE keyword could not be used with aggregate functions.

```
SELECT column_name, COUNT(*)
FROM table_name
GROUP BY column_name
HAVING COUNT(*) > value;
```

LIMIT

- LIMIT is a clause that lets you specify the maximum number of rows the result set will have.

```
SELECT column_name(s)
FROM table_name
LIMIT number;
```

ORDER BY

- ORDER BY is a clause that indicates you want to sort the result set by a particular column either alphabetically or numerically.

```
SELECT column_name
FROM table_name
ORDER BY column_name ASC | DESC;
```

SELECT DISTINCT

- SELECT DISTINCT specifies that the statement is going to be a query that returns unique values in the specified column(s).

```
SELECT DISTINCT column_name
FROM table_name;
```

With

- WITH clause lets you store the result of a query in a temporary table using an alias. You can also define multiple temporary tables using a comma and with one instance of the WITH keyword.
- The WITH clause is also known as common table expression (CTE) and subquery factoring.

```
WITH temporary_name AS (
    SELECT *
    FROM table_name)
SELECT *
FROM temporary_name
WHERE column_name operator value;
```

WHERE

- WHERE is a clause that indicates you want to filter the result set to include only rows where the following condition is true.

```
SELECT column_name(s)
FROM table_name
```

```
WHERE column_name operator value;
```

Keys

Primary Key?

- A PRIMARY KEY is a column or combination of columns that uniquely identifies each record in a database table.
- A Primary Key column cannot have Null values.
- A table can have only one primary key per table.
- When multiple fields are used as a primary key, they are called a composite key.

```
-- Create Primary Key
CREATE TABLE Students (
    student_id INT AUTO_INCREMENT PRIMARY KEY,
    name VARCHAR(50),
    email VARCHAR(100)
);
-- (OR)
CREATE TABLE Students (
    student_id INT AUTO_INCREMENT,
    name VARCHAR(50),
    email VARCHAR(100),
    PRIMARY KEY (student_id)
);

-- Create Primary Key with multiple column
CREATE TABLE Order_Items (
    order_id INT,
    product_id INT,
    quantity INT,
    PRIMARY KEY (order_id, product_id) -- Multiple columns as primary key
);
```

Add primary Key

```
-- if primary key doesn't exists in the created table
ALTER TABLE table_name ADD PRIMARY KEY (Id)

-- For multiple column
ALTER table Employee ADD constraints PK_Employee PRIMARY KEY (column_name1,
column_name2);
-- (OR)
ALTER TABLE table_name ADD PRIMARY KEY (column1, column2);

-- Adding Primary Key with Auto-Increment
ALTER TABLE table_name MODIFY column_name INT AUTO_INCREMENT PRIMARY KEY;
```

Delete primary Key

```
ALTER TABLE table_name DROP PRIMARY KEY;

-- For multiple column
ALTER TABLE Employee DROP CONSTRAINT PK_Employee;
-- (OR)
ALTER TABLE table_name DROP PRIMARY KEY;
```

Ques. What Is Unique Key?

- A Unique Key is a constraint that ensures all values in a column or a combination of columns are unique across all records in a table.
- The Unique and Primary Key constraints both provide a guarantee for a column or set of columns.
- A Primary Key consist automatically has a unique constraint define on it.
 - Defining unique key

```
-- Single Column Unique Key
CREATE TABLE Students (
    student_id INT PRIMARY KEY,
    email VARCHAR(100) UNIQUE
);

-- Multiple Column Unique Key
CREATE TABLE Employees (
    id INT PRIMARY KEY,
    first_name VARCHAR(50),
    last_name VARCHAR(50),
    UNIQUE (first_name, last_name)
);
```

ALTER unique key

```
-- Single Column
ALTER table Employee ADD UNIQUE(column name);
-- (OR)
ALTER TABLE table_name ADD CONSTRAINT constraint_name UNIQUE (column_name);

-- Multiple Columns
ALTER TABLE table_name ADD CONSTRAINT constraint_name UNIQUE (column1, column2);
```

Drop unique key

```
ALTER TABLE Employee DROP CONSTRAINT Employee_ID;
-- (OR)
ALTER TABLE table_name DROP INDEX constraint_name;
```


Ques. What Is Foreign Key?

- A foreign key is a key used to link two tables together. This is something called a reference key.
- A column or set of columns in a table that references the PRIMARY KEY of another table.
- Foreign key is a column or a combination of columns whose values match a primary key in a different table.
- The relationship between two tables matches the primary key in one of the tables with a foreign key in the second table.

```
-- create Customers table
CREATE TABLE Customers (
  id INTEGER PRIMARY KEY,
  name VARCHAR(100),
  age INTEGER
);
```

```
-- create Products table
CREATE TABLE Products (
  customer_id INTEGER ,
  name VARCHAR(100),
  FOREIGN KEY (customer_id)
  REFERENCES Customers(id)
);
```

-- Here, the customer_id column in the Products table references the id column in the Customers table.

```
-- One-to-One:- Each record in one table connects to single record in another
CREATE TABLE Employee (
  emp_id INT PRIMARY KEY,
  passport_number INT,
  FOREIGN KEY (passport_number)
  REFERENCES Passport(passport_number)
);
```

-- One-to-Many:- One record in parent table can relate to multiple records in child table

```
CREATE TABLE Orders (
  order_id INT PRIMARY KEY,
  customer_id INT,
  FOREIGN KEY (customer_id)
  REFERENCES Customers(customer_id)
);
```

-- Many-to-Many:- Multiple records in both tables can relate to each other

```
CREATE TABLE StudentCourses (
  student_id INT,
  course_id INT,
  PRIMARY KEY (student_id, course_id),
```

```
FOREIGN KEY (student_id) REFERENCES Students(student_id),  
FOREIGN KEY (course_id) REFERENCES Courses(course_id)  
);
```

Adding Foreign Key to Existing Table?

```
-- if primary key doesn't exists in the created table  
ALTER TABLE Employee ADD FOREIGN KEY (department_id) REFERENCES  
Department(department_id);  
(OR)  
ALTER TABLE `bookings` ADD CONSTRAINT `advance_bookings_user_id_foreign` FOREIGN  
KEY (`user_id`) REFERENCES `users` (`id`) ON DELETE CASCADE ON UPDATE CASCADE  
  
-- For multiple column  
ALTER TABLE Employee ADD CONSTRAINT FK_dept_id FOREIGN KEY (department_id)  
REFERENCES Department(department_id);
```

DROP a Foreign Key from the table

```
-- For single column/multiple column  
ALTER TABLE Employee DROP FOREIGN KEY FK_dept_id;
```

Ques. What is Composite Key?

- Composite key is combination of two or more columns that can uniquely identify each row in the table.
- composite key is also a primary key, but the difference is that it is made by the combination of more than one column to identify the particular row in the table.
- A composite key cannot be null.

```
CREATE TABLE student
(rollNumber INT,
name VARCHAR(30),
class VARCHAR(30),
section VARCHAR(1),
mobile VARCHAR(10),
PRIMARY KEY (rollNumber, mobile));
```

Types of Composite Keys

1. Composite Primary Key

```
CREATE TABLE StudentCourses (
    student_id INT,
    course_id INT,
    semester VARCHAR(10),
    PRIMARY KEY (student_id, course_id, semester)
);
```

2. Composite Unique Key

```
CREATE TABLE Employees (
    first_name VARCHAR(50),
    last_name VARCHAR(50),
    department VARCHAR(50),
    UNIQUE (first_name, last_name, department)
);
```

Ques. Difference between Primary Key & Unique Key?

Primary Key	Unique Key
A table can have only one primary key	A table can have more than one unique key
It does not allow null values	Allows null values
Primary key Can be made foreign key into another table	In SQL server, unique key Can be made foreign key into another table
By default it adds a clustered index	By default it adds a unique non-clustered index
Primary key support auto increment value.	Unique constraint does not support auto increment value.

Ques. Difference between Primary Key & Foreign Key?

Primary Key	Foreign Key
A table can have only one primary key	A table can have more than one foreign key
Primary key uniquely identified a record in the table	Foreign key is a field in the table that is primary key in another table
It does not allow null values	Allows null values
Duplicate not allowed	Duplicate allowed
Primary key support auto increment value	Foreign key do not automatically create an index.

Joins

Ques. What Is Joins?

- A JOIN is a method used to combine rows from two or more tables based on a related column between them.
- MySQL JOINS are used with SELECT statement.

Many types of MySQL joins:

1. Self Join
2. Inner Join
3. Left JOIN
4. Right JOIN
5. Full Join
6. Outer Join
7. Cross Join

Self Join

- A self join connects a table to itself. Used when you want to compare rows within the same table.

Customers table:

ID	NAME	AGE	ADDRESS	SALARY
1	Ramesh	32	Ahmedabad	2000.00
2	Khilan	25	Delhi	1500.00
3	kaushik	23	Kota	2000.00
4	Chaitali	25	Mumbai	6500.00
5	Hardik	27	Bhopal	8500.00
6	Komal	22	MP	4500.00
7	Muffy	24	Indore	10000.00

-- Example

```
SELECT c1.NAME AS Customer1, c2.NAME AS Customer2, c1.SALARY FROM Customers c1
JOIN Customers c2 ON c1.SALARY = c2.SALARY AND c1.ID < c2.ID;
```

-- Output:

Customer1	Customer2	SALARY
Ramesh	kaushik	2000.00

INNER JOIN

- The MySQL Inner Join is used to returns only those results from the tables that **match** the specified condition and hides other rows and columns.
- Inner join: Inner join return rows when there is at least one match of rows between the tables.

Customers table:

ID	NAME	AGE	ADDRESS	SALARY
1	Ramesh	32	Ahmedabad	2000.00
2	Khilan	25	Delhi	1500.00
3	kaushik	23	Kota	2000.00
4	Chaitali	25	Mumbai	6500.00
5	Hardik	27	Bhopal	8500.00
6	Komal	22	MP	4500.00
7	Muffy	24	Indore	10000.00

Order table:

OID	DATE	CUSTOMER_ID	AMOUNT
101	2009-11-20 00:00:00	2	1560
103	2008-05-20 00:00:00	4	2060

```
SELECT customers.name, customers.age, customers.salary, order.date
FROM customers INNER JOIN order
ON customers.id = order.CUSTOMER_ID;
```

NAME	AGE	SALARY	DATE
Khilan	25	1500.00	2009-11-20 00:00:00
Chaitali	25	6500.00	2008-05-20 00:00:00

-- Example 2

Order table:

OID	DATE	CUSTOMER_ID	AMOUNT
102	2009-10-08 00:00:00	3	3000
100	2009-10-08 00:00:00	3	1500
101	2009-11-20 00:00:00	2	1560
103	2008-05-20 00:00:00	4	2060

-- Output:-

```
SQL> SELECT ID, NAME, AMOUNT, DATE FROM CUSTOMERS
INNER JOIN ORDERS
ON CUSTOMERS.ID = ORDERS.CUSTOMER_ID;
```

ID	NAME	AGE	AMOUNT
3	kaushik	23	3000
3	kaushik	23	1500
2	Khilan	25	1560
4	Chaitali	25	2060

Left JOIN/LEFT OUTER JOIN

- The LEFT JOIN keyword returns all records from the left table (the table listed first), and the matching records (if any) from the right table (table2).

CUSTOMERS Table

ID	NAME	AGE	ADDRESS	SALARY
1	Ramesh	32	Ahmedabad	2000.00
2	Khilan	25	Delhi	1500.00
3	kaushik	23	Kota	2000.00
4	Chaitali	25	Mumbai	6500.00
5	Hardik	27	Bhopal	8500.00
6	Komal	22	MP	4500.00
7	Muffy	24	Indore	10000.00

Orders Table

OID	DATE	CUSTOMER_ID	AMOUNT
102	2009-10-08 00:00:00	3	3000
100	2009-10-08 00:00:00	3	1500
101	2009-11-20 00:00:00	2	1560
103	2008-05-20 00:00:00	4	2060

```
SQL> SELECT ID, NAME, AMOUNT, DATE FROM CUSTOMERS LEFT JOIN ORDERS
      ON CUSTOMERS.ID = ORDERS.CUSTOMER_ID;
```

Result:-

ID	NAME	AMOUNT	DATE
1	Ramesh	NULL	NULL
2	Khilan	1560	2009-11-20 00:00:00
3	kaushik	3000	2009-10-08 00:00:00
3	kaushik	1500	2009-10-08 00:00:00
4	Chaitali	2060	2008-05-20 00:00:00
5	Hardik	NULL	NULL
6	Komal	NULL	NULL
7	Muffy	NULL	NULL

Right JOIN

- The RIGHT JOIN keyword returns **all records** from the **right table** (table2), and the **matching records** (if any) from the **left table** (table1).

-- Customers Table

ID	NAME
1	Ramesh
2	Khilan
3	Kaushik

-- Orders Table

OrderID	CustomerID
101	2
102	3
103	4

-- RIGHT JOIN Result

```
SELECT Customers.NAME, Orders.OrderID FROM Customers RIGHT JOIN Orders  
ON Customers.ID = Orders.CustomerID;
```

NAME	OrderID
Khilan	101
Kaushik	102
NULL	103

Outer join

- Returns all rows from both tables, Matching and non-matching rows.
- NULL values where no match exists

```
SELECT column_list
FROM table1
FULL OUTER JOIN table2 ON table1.column = table2.column;
```

```
-- Example query
employees:
```

employee_id	employee_name	department_id
1	John Smith	101
2	Mary Johnson	102
3	Sam Brown	103

```
departments:
```

department_id	department_name
101	HR
102	Finance
104	Marketing

```
SELECT employees.employee_id, employees.employee_name, departments.department_name
FROM employees
FULL OUTER JOIN departments ON employees.department_id =
departments.department_id;
```

employee_id	employee_name	department_name
1	John Smith	HR
2	Mary Johnson	Finance
3	Sam Brown	NULL
NULL	NULL	Marketing

CROSS Join

- The CROSS JOIN keyword returns all records from both tables (table1 and table2).
- If you have a Products table with 3 products and a Colors table with 2 colors, a CROSS JOIN would return a result set with 6 combinations (3 * 2):

```
-- Products table
| ProductID | ProductName |
| ----- | -
```

ProductID	ProductName
1	T-Shirt
2	Jeans

```
-- Colors table
| ColorID | Color |
| ----- | -
```

ColorID	Color
1	Red
2	Blue

```
-- Output:-
SELECT Products.ProductName, Colors.Color
FROM Products
CROSS JOIN Colors;
```

ProductName	Color
T-Shirt	Red
T-Shirt	Blue
Jeans	Red
Jeans	Blue

Full Join/FULL OUTER JOIN

- A FULL JOIN (also called a FULL OUTER JOIN) returns all rows when there is a match in either left (table1) or right (table2) table. It returns all records from both tables, and the result set will have NULL values for columns where there is no match.

Key Points:

- Rows from both tables are included even if there is no match.
- If there is no match, the columns from the table that doesn't have a match will contain NULL.
- This join is useful when you want to retrieve all records, whether or not there's a match in both tables.

-- Employees Table:

EmployeeID	EmployeeName	DepartmentID
1	John	10
2	Jane	20
3	Mike	30
4	Sara	NULL

-- Departments Table:

DepartmentID	DepartmentName
10	HR
20	IT
30	Sales
40	Marketing

-- Output:-

```
SELECT Employees.EmployeeID, Employees.EmployeeName, Employees.DepartmentID,  
Departments.DepartmentName  
FROM Employees  
FULL JOIN Departments  
ON Employees.DepartmentID = Departments.DepartmentID;
```

EmployeeID	EmployeeName	DepartmentID	DepartmentName
1	John	10	HR
2	Jane	20	IT
3	Mike	30	Sales
4	Sara	NULL	NULL
NULL	NULL	40	Marketing

Index

What is Index?

- An index is used to enhance the performance of SQL Queries. It allows the database to find data quickly and efficiently by using Row ID, avoiding full table scans.
- Indexes can be created on one or more columns of a table.
- Index allows the database application to find data fast, without reading the whole table.
- An index can be created in a table to find data more quickly and efficiently.
- **How It Works:-** Behind the scenes, an index is usually implemented as a B-tree or similar structure.

Types of Indexes?

1. **Single-column index:-** on one column

```
CREATE INDEX idx_product_id ON Sales (product_id);
```

2. **Composite/Multi-column indexes:** on multiple columns

```
CREATE INDEX idx_dept_salary ON employees(department, salary);
```

3. **Unique Index:-**

```
CREATE UNIQUE INDEX idx_email_unique ON employees(email);
```

4. **Full-Text Index :-** Designed for efficient text search in large text fields (e.g., for searching keywords in articles, product descriptions, etc.)

```
CREATE FULLTEXT INDEX idx_description ON products(description);
```

Show Index

```
show index from table_name
```

Unique Indexes

- A Unique Index is a database index that ensures the uniqueness of values in one or more columns of a database table.

- This index ensures that no two rows in the Employees table have the same employee_id(Column_name), which maintains data integrity and prevents duplicate entries.
- The SQL Unique Index ensures that no two rows in the indexed columns of a table have the same values (no duplicate values allowed).

```
* Behind the scenes, when a new record is inserted, the database would:
  * Check the Index: It looks up the email in the index (which could be a B-tree
  or hash table) to find if that email already exists.
  * The database will search the index, and it will quickly identify whether the
  email you're trying to insert is already in the table.
  * Check for Duplicates:
    * For example, if we try to insert a new row:
    * INSERT INTO users (Name, Email) VALUES ('David', 'alice@example.com');
    * The database will search the unique index for the email alice@example.com.
  Since this email already exists in the index, the insert will fail with an error
  like:
    "Duplicate entry 'alice@example.com' for key 'idx_unique_email'".
```

```
-- Single column unique index
CREATE UNIQUE INDEX idx_email ON users(email);

-- Composite unique index
CREATE UNIQUE INDEX idx_name_age ON employees(last_name, first_name);
```

Alter/Modify an Index

```
-- Rename Index name
ALTER TABLE table_name
RENAME INDEX old_index_name TO new_index_name;

-- Modify Index name
ALTER TABLE table_name DROP INDEX existing_index,
ADD INDEX new_index (column1, column2);

-- Rebuild Index
ALTER INDEX index_name
ON table_name REBUILD;

-- Reorganize Index
ALTER INDEX index_name
ON table_name REORGANIZE;

-- Disable Index
ALTER INDEX index_name
ON table_name DISABLE;

-- Change Index Properties
```

```
ALTER INDEX index_name
ON table_name
SET (
    STATISTICS_NORECOMPUTE = OFF,
    ALLOW_ROW_LOCKS = ON,
    ALLOW_PAGE_LOCKS = ON
);
```

Drop Index

```
Drop index index_name on table_name
(OR) DROP INDEX table_name.index_name;

-- DROP INDEX with IF EXISTS
DROP INDEX IF EXISTS index_name
ON table_name;

ALTER TABLE table_name DROP CONSTRAINT constraint_name;
```

Cluster Index

- A clustered index is an index where the data in the table is physically stored in the order of the indexed column. In other words, the rows of the table are sorted on disk based on the values in the indexed column. A table can have only one clustered index because the data can only be sorted in one way.
- **Example:** If you create a clustered index on the EmployeeID column, the table rows will be stored on disk in ascending order of EmployeeID. The clustered index itself dictates the physical arrangement of the data.
- jab kisi table par hum primary key lagate hai to wo cluster index ban jata hai.

Non cluster index

- A non-clustered index is an index where the data in the table is stored independently of the index. It creates a separate structure that contains the indexed column(s) and pointers to the actual rows in the table. A table can have multiple non-clustered indexes, allowing for efficient lookups on different columns without changing the physical order of the data.
- **Example:** If you create a non-clustered index on the Department column, the index will store the department values along with pointers to the corresponding rows in the table, but the table data itself remains in its original order.
- table mai jis column par select command sabse jyda chalte hai to us column par hum non cluster index bna lete hai.

Ques. What is the difference between cluster and non cluster index?

Cluster index

Non cluster index

Cluster index	Non cluster index
Data rows are stored in the order of the index.	Data rows are not sorted in any particular order.
Only one clustered index per table.	Multiple non-clustered indexes can exist per table.
Created by default for the primary key.	Must be explicitly created (e.g., for specific queries).

View

What is View?

- A view is a **virtual table** based on the result set of a SELECT query.
- It does not store data itself but provides a way to look at data from one or more tables in a structured and reusable manner.
- It **behaves** like a **table** but **doesn't store** the **data physically**.

Create view

```
Create view view_name As  
Select column1, column2  
From table_name  
Where [condition];
```

Show view

```
SELECT * FROM view_name;
```

Alter view

- CREATE OR REPLACE VIEW Syntax

```
CREATE OR REPLACE VIEW view_name AS  
SELECT column1, column2, ...  
FROM table_name  
WHERE condition;
```

Deleted view

- A view is **deleted** with the **DROP VIEW statement**.

```
DROP VIEW view_name  
DROP VIEW IF EXISTS view_name;
```

Ques. What is ACID property/SQL TRANSACTIONS?

- A transaction in SQL is a **sequence** of one or more SQL operations that are executed as a single unit.
- The goal of a transaction is to ensure that either all operations succeed or none of them do, maintaining the consistency of the database. Think of it like: "Do everything, or do nothing."
- (Transaction एक तरह का ब्लॉक है जिसमें कई SQL statements (जैसे INSERT, UPDATE, DELETE) एक साथ execute होते हैं। इसका मतलब है: या तो सारे काम पूरे होंगे, या कोई भी नहीं होगा।)

ACID Properties

1. **A - Atomicity:-** If all operations in a transaction succeed, the changes are saved to the database; if any operation fails, the entire transaction is rolled back.
2. **C - Consistency:-** Ensures that after a transaction, the data in the database is still correct and follows all rules.
3. **I - Isolation:-** Makes sure that when many transactions run at the same time, they don't interfere with each other.(Ensures that concurrent transactions do not affect each other. The final result should be the same as if transactions were run sequentially.)
4. **D - Durability:-** Once a transaction is committed, it is permanently saved in the database—even in case of system failure or crashes.

```
BEGIN TRANSACTION;
```

```
UPDATE accounts SET balance = balance - 100 WHERE account_id = 1;
```

```
UPDATE accounts SET balance = balance + 100 WHERE account_id = 2;
```

```
COMMIT;
```

```
-- If any of those updates fail (e.g., account not found), you can use:
```

```
ROLLBACK;
```

Wildcard Characters/Like Query

Ques. Wildcard Characters?

- Wildcard characters are used with the **LIKE operator**. The LIKE operator is **used** in a **WHERE** clause to search for a specified pattern in a column.

Symbol	Description
%	Represents zero or more characters
_	Represents a single character

Some Example

LIKE Operator	Description
WHERE CustomerName LIKE 'a%'	Finds any values that starts with "a"
WHERE CustomerName LIKE '%a'	Finds any values that ends with "a"
WHERE CustomerName LIKE '%or%'	Finds any values that have "or" in any position
WHERE CustomerName LIKE '_r%'	Finds any values that have "r" in the second position
WHERE CustomerName LIKE 'a_%_ %'	Finds any values that starts with "a" and are at least 3 characters in length
WHERE ContactName LIKE 'a%o'	Finds any values that starts with "a" and ends with "o"

```
SELECT * FROM Customers WHERE City LIKE 'ber%';
```

Aliases?

- AS is a keyword in SQL that allows you to rename a column or table using an alias.
- Aliases are used to give a table, or a column in a table, a temporary name.
- An alias is created with the **AS** keyword.

Alias Column Syntax:-

```
SELECT column_name AS alias_name FROM table_name;

-- Basic Column Alias
SELECT first_name AS name, last_name AS surname FROM employees;

-- Using quotes for aliases with spaces
SELECT
    first_name AS 'Employee First Name',
    last_name AS 'Employee Last Name',
    salary AS 'Monthly Compensation'
FROM
    employees;

-- Without AS keyword
SELECT first_name name, last_name surname FROM employees;

-- Simple Table Alias
SELECT e.first_name, e.last_name, d.department_name
FROM employees e JOIN departments d
ON e.department_id = d.department_id;

-- Calculation with Alias
SELECT
    product_name,
    price * quantity AS total_value,
    (price * quantity) * 1.1 AS total_with_tax
FROM products;

-- Concatenation Alias
SELECT
    CONCAT(first_name, ' ', last_name) AS full_name,
    email AS contact_email
FROM customers;

-- Subquery with Alias
SELECT
    (SELECT AVG(salary) FROM employees) AS avg_salary,
    (SELECT MAX(salary) FROM employees) AS max_salary;
```

```
-- Aggregate Function Aliases
SELECT
    department_id,
    AVG(salary) AS average_salary,
    COUNT(*) AS employee_count,
    MAX(salary) AS highest_salary
FROM employees
GROUP BY department_id;

-- Conditional Aliases
SELECT
    first_name,
    last_name,
    CASE
        WHEN salary < 50000 THEN 'Junior'
        WHEN salary BETWEEN 50000 AND 100000 THEN 'Mid-Level'
        ELSE 'Senior'
    END AS salary_category
FROM employees;
```

Ques. What Is Union & Union All?

- Both UNION and UNION ALL Operator combine rows from result sets into a single result set.

UNION

- The union operator **combines** the results of two or more select statements by **removing duplicate rows**.
- The columns and the data types must be the same in select statements.

```
+---+-----+
| ID | NAME      |
+---+-----+
|  1 | Ramesh    |
|  2 | Khilan    |
|  3 | kaushik   |
+---+-----+
```

```
+---+-----+
| ID | NAME      |
+---+-----+
|  3 | kaushik   |
|  4 | Mohit     |
|  5 | abhay     |
+---+-----+
```

```
Select Column1, Column2, Column3 from Table A
UNION
Select Column1, Column2, Column3 from Table B
```

```
+---+-----+
| ID | NAME      |
+---+-----+
|  1 | Ramesh    |
|  2 | Khilan    |
|  3 | kaushik   |
|  4 | Mohit     |
|  5 | abhay     |
+---+-----+
```

UNION ALL

- The UNION operator selects only distinct values by default. To **allow duplicate values**, use UNION ALL

```
Select Column1, Column2, Column3 from Table A
UNION ALL
Select Column1, Column2, Column3 from Table B
```

ID	NAME
1	Ramesh
2	Khilan
3	kaushik
3	kaushik
4	Mohit
5	abhay

Ques. Difference between Union & Union All?

Union	Union All
Union removes duplicate rows.	Union All does not remove the duplicate rows.
Union uses a distinct sort	Union All does not use a distinct sort
Union can't work with a column that has a text data type.	Union All can work with all data type column.

What is Intersect?

- The INTERSECT statement will return only those rows that are **identical/common** to both of the SELECT statements from two or more tables

```
-- Employees
| EmpID | EmpName | Department |
| -----|-----|-----|
| 1      | Alice   | HR         |
| 2      | Bob     | IT         |
| 3      | Charlie | Finance    |
| 4      | David   | IT         |
| 5      | Eve     | Marketing  |

-- Managers
| EmpID | EmpName | Department |
| -----|-----|-----|
| 2      | Bob     | IT         |
| 4      | David   | IT         |
| 6      | Frank   | Sales      |
| 7      | Grace   | Marketing  |

-- Output
SELECT EmpID, EmpName, Department FROM Employees
INTERSECT
SELECT EmpID, EmpName, Department FROM Managers;
| EmpID | EmpName | Department |
| -----|-----|-----|
| 2      | Bob     | IT         |
| 4      | David   | IT         |
```

What is MINUS?

- MINUS operator will return only those rows which are **unique** in only first SELECT query and not those rows which are common to both first and second SELECT queries.

```
-- Employees
| EmpID | EmpName | Department |
| -----|-----|-----|
| 1      | Alice   | HR         |
| 2      | Bob     | IT         |
| 3      | Charlie | Finance    |
| 4      | David   | IT         |
| 5      | Eve     | Marketing  |

-- Managers
| EmpID | EmpName | Department |
| -----|-----|-----|
| 2      | Bob     | IT         |
| 4      | David   | IT         |
| 6      | Frank   | Sales      |
| 7      | Grace   | Marketing  |

-- output:-
SELECT EmpID, EmpName, Department FROM Employees
MINUS
SELECT EmpID, EmpName, Department FROM Managers;
| EmpID | EmpName | Department |
| -----|-----|-----|
| 1      | Alice   | HR         |
| 3      | Charlie | Finance    |
| 5      | Eve     | Marketing  |
```


Sql Query questions

Ques. Check version of the sql?

```
select version()
```

Current date?

```
select GETDATE();
```

Ques. How to copy a table in another table?

```
CREATE TABLE EMP1 AS (SELECT * FROM EMP); //constraint will not copied.
```

Ques. How to copy structure of a table but not data?

```
CREATE TABLE STD AS (SELECT * FROM EMP WHERE EMPNO=-1);
```

Nth highest salary?

- Using the LIMIT Clause
 - The limit clause has two components, the **First component** is to skip a number of rows from the top and the **second component** is to display the number of rows we want.

```
-- Syntex:- Using Limit
Select DISTINCT Salary from table_name order by Salary DESC limit n-1,1;
(OR) SELECT DISTINCT salary FROM employees ORDER BY salary DESC LIMIT 1 OFFSET N-1;

+-----+-----+
| emp_name | salary |
+-----+-----+
| JONAS    | 2957.00 |
+-----+-----+
```

```
-- Example:- 4th Highest salary using limit
Select DISTINCT emp_name, salary from Employee order by salary DESC limit 3,1;
```

```
-- Using Subquery:- 3rd highest salary
SELECT MAX(salary) AS ThirdHighestSalary FROM Employee WHERE salary < (SELECT
MAX(salary) FROM Employee WHERE salary < (SELECT MAX(salary) FROM Employee));

+-----+
| MAX(salary) |
+-----+
|      2957.00 |
+-----+
```

Top N Salary?

```
-- Using Limit
SELECT salary FROM employee ORDER BY salary DESC LIMIT 4

+-----+-----+
| emp_name | salary |
+-----+-----+
| KAYLING  | 6000.00 |
| FRANK    | 3100.00 |
| SCARLET  | 3100.00 |
| JONAS    | 2957.00 |
| BLAZE    | 2750.00 |
+-----+-----+
```

```
-- In Oracle
SELECT SAL FROM(SELECT DISTINCT SAL FROM EMP WHERE SAL IS NOT NULL ORDER BY SAL
DESC)WHERE ROWNUM <6;
```

Find the Highest Salary of Each Department?

-- Employee table:

id	name	salary	departmentId
1	Joe	85000	1
2	Henry	80000	2
3	Sam	60000	2
4	Max	90000	1
5	Janet	69000	1
6	Randy	85000	1
7	Will	70000	1
8	Mohit	90000	1

-- Department table:

id	name
1	IT
2	Sales

-- for single table

```
SELECT dep_id, max(salary) FROM `employee` GROUP BY dep_id;
```

dep_id	max(salary)
1001	6000.00
2001	3100.00
2244	6000.00
3001	2750.00

-- for two table

```
select max(employee.salary) AS salary, department.name from employee JOIN
department WHERE employee.departmentId = department.id GROUP BY department.name;
```

salary	name
90000	IT
80000	Sales

-- Find the Highest Salary of Each Department with name

```
SELECT dep_id, emp_name, salary FROM employee WHERE (dep_id,salary) IN (SELECT
dep_id, MAX(salary) FROM employee GROUP BY dep_id);
```

dep_id	emp_name	salary
2244	Mohit	6000.00
3001	BLAZE	2750.00
2001	SCARLET	3100.00
1001	KAYLING	6000.00
2001	FRANK	3100.00

-- Find the Highest Salary of Each Department with name from two table

```
SELECT department.name AS dep_name, employee.name AS emp_name, employee.salary AS
```

```

salary
FROM employee JOIN department
ON employee.departmentId = department.id
JOIN(
SELECT departmentId, max(salary) AS max_salary
from employee GROUP BY departmentId
) AS dept_max ON employee.departmentId = dept_max.departmentId AND employee.salary
= dept_max.max_salary

```

```

+-----+-----+-----+
| dep_name | emp_name | salary |
+-----+-----+-----+
| Sales    | Henry    | 80000  |
| IT       | Max      | 90000  |
| IT       | Mohit    | 90000  |
+-----+-----+-----+

```

```

-- Find the Highest Salary of Each Department with name Using SubQuery
SELECT department.name AS dep_name, employee.name AS emp_name, employee.salary AS
salary
FROM employee
JOIN department ON employee.departmentId = department.id
WHERE (employee.departmentId, employee.salary) IN (
    SELECT departmentId, MAX(salary)
    FROM employee
    GROUP BY departmentId
);

```

```

+-----+-----+-----+
| dep_name | emp_name | salary |
+-----+-----+-----+
| Sales    | Henry    | 80000  |
| IT       | Max      | 90000  |
| IT       | Mohit    | 90000  |
+-----+-----+-----+

```

How to Find Duplicate values in a Table?

```

select Email, count(Email) as total_email from Person group by Email HAVING
COUNT(Email) > 1;

```

```

+-----+-----+
| Email  | total_email |
+-----+-----+
| a@b.com | 2           |
| c@d.com | 5           |
+-----+

```

Replace a Column Values from 'male' to 'female' and 'female' to 'male'

```
UPDATE empdata
SET GENDER = CASE
    WHEN GENDER='male' THEN 'female'
    WHEN GENDER='female' THEN 'male'
END;
(OR)
UPDATE EMPDATA
SET gender = CASE
    gender WHEN 'male' THEN 'female'
           WHEN 'female' THEN 'male'
    ELSE gender
END;
```

Update remaing days startdate - enddate

```
UPDATE advance_bookings
SET remaining_days = DATEDIFF('2025-01-31', CURDATE()), end_date = '2025-01-31'
WHERE id = 4529;

-- End date dynamic
UPDATE advance_bookings
SET remaining_days = DATEDIFF(end_date, CURDATE()), end_date = end_date
WHERE id = 4529;
```

Count phone number

```
SELECT phone, count(phone) as total_phone FROM `users` WHERE role_id = 4 group by
phone having count(phone) > 1;
```