

No.	Questions
	What is Dictionaries?
	Dictionary Length?
	The dict() Constructor
	How to Check if Item Exists?
	Access Item of Dictionary?
	Add Dictionary Items?
	Change Or Update Dictionary Items?
	Remove Dictionary Items?
	Copy Dictionaries?
	Loop Dictionaries?
	Dictionary Methods?
	Nested Dictionaries?

	How to Merging Or Adding two Dictionaries?
	Combine two dictionary adding values for common keys?
	What will the output of following Program?
	Sort in dictionary with key, Value and Items
	Can we use tuple as keys inside python dictionary?
	Can we use lists as keys inside python dictionary?
	What is enumerate function inside a dictionary?
	How can combine two dictionaries together?
	Find Unique dictionary from list by id?

Ques. What is Dictionaries?

- Dictionaries are written with curly **brackets{}**, and have keys and values.
- Dictionary items are **ordered**, **changeable**, and **does not allow duplicates**.
- Dictionaries are **changeable**, meaning that we can change, add or remove items after the dictionary has been created.

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964,  
    "year": 2020,  
    "electric": False,  
    "colors": ["red", "white", "blue"]  
}  
print(thisdict)
```

Output:- {'brand': 'Ford', 'model': 'Mustang', 'year': 2020, 'electric': False, 'colors': ['red', 'white', 'blue']}

Ques. Dictionary Length?

- To determine how many items a dictionary has, use the **len()** function.

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964,  
    "year": 2020  
}  
print(len(thisdict))    # Dictionary Length:- Output:- 3
```

The dict() Constructor

- It is also possible to use the **dict()** constructor to make a dictionary.

```
thisdict = dict(name = "John", age = 36, country = "Norway")  
print(thisdict)  
Output:- {'name': 'John', 'age': 36, 'country': 'Norway'}
```

Check if Key Exists

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
if "model" in thisdict:  
    print("Yes, 'model' is one of the keys in the thisdict dictionary")
```

Output:- Yes, 'model' is one of the keys in the thisdict dictionary

Access Item of Dictionary

Ques. Access Item of Dictionary?

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
  
# Using key name:- We can access the items of a dictionary by referring to its  
**key name**, inside square brackets.  
x = thisdict["model"]  
print(x)    # Output:- Mustang  
  
# Using the **get()** Method  
x = thisdict.get("model")  
print(x)    # output:- Mustang  
  
# Get **All Keys** of the Dictionary:- The **keys() method** will return a list of  
all the keys in the dictionary.  
x = thisdict.keys()  
print(x)    # Output:- dict_keys(['brand', 'model', 'year'])  
  
# Get **All Values** of the Dictionary and We can change the value of a specific  
item by referring to its key name.  
x = thisdict.values()  
print(x)    # Output:- dict_values(['Ford', 'Mustang', 1964])  
  
# Get **All Items** :- The items() method will return each item in a dictionary,  
as tuples in a list.  
x = thisdict.items()  
print(x)    # Output:- dict_items([('brand', 'Ford'), ('model', 'Mustang'),  
('year', 1964)])
```

Add Dictionary Items

Ques. Add Dictionary Items?

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
  
# Using key:- using key add the items  
thisdict["color"] = "red"  
print(thisdict)    # Output:- {'brand': 'Ford', 'model': 'Mustang', 'year': 1964,  
                             'color': 'red'}  
  
# Using Update() method:- Adding Items using **Update()** Method  
thisdict.update({"color": "red"})  
print(thisdict)    # Output:- {'brand': 'Ford', 'model': 'Mustang', 'year': 1964,  
                             'color': 'red'}
```

Change Or Update Dictionary Items?

Change Or Update Dictionary Items

- Change Values:- We can change the value of a specific item by referring to its **key name**.

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}
```

Using key name:- We can change the value of a specific item by referring to its key name.

```
thisdict["year"] = 2018
```

```
print(thisdict)    # Output:- {'brand': 'Ford', 'model': 'Mustang', 'year': 2018}
```

Using Update method:-

```
thisdict.update({"year": 2020})
```

```
print(thisdict)    # Output:- {'brand': 'Ford', 'model': 'Mustang', 'year': 2020}
```

Remove Dictionary Items?

Ques. Remove Dictionary Items?

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}
```

using pop() method:- The **pop()** method removes the item with the specified **key name**:

```
thisdict.pop("model")  
print(thisdict) # Output:- {'brand': 'Ford', 'year': 1964}
```

using **popitem()** methods:- method removes the last inserted item (in versions before 3.7, a random item is removed instead).

```
thisdict.popitem()  
print(thisdict) # Output:- {'brand': 'Ford', 'model': 'Mustang'}
```

using del method:- Using **del** methods removes the item with the specified **key name**.

```
del thisdict["model"]  
print(thisdict) # Output:- {'brand': 'Ford', 'year': 1964}
```

using del method without key name:- If we **can not define the key name** del method delete the dictionary completely.

The Removing item using del methods keyword can also delete the dictionary completely.

```
del thisdict  
print(thisdict) # Output:- this will cause an error because "thisdict" no longer exists.
```

using clear method:- The Removing item using **clear()** methods method empties the dictionary.

```
thisdict.clear()  
print(thisdict) # output:- Output:- {}
```

Copy Dictionaries?

Ques. Copy Dictionaries?

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
  
# using copy method:-  
mydict = thisdict.copy()  
print(mydict)    # Output:- {'brand': 'Ford', 'model': 'Mustang', 'year': 1964}  
  
# using dict() method:-  
mydict = dict(thisdict)  
print(mydict)    # Output:- {'brand': 'Ford', 'model': 'Mustang', 'year': 1964}
```


Loop Dictionaries?

Ques. Loop Dictionaries?

```
# print Dictionaries by key, value and item
a = {1:12 ,2:11 ,4:16 ,3:14 ,6:15 ,5:13 }
print(sorted(a.keys()))
print(sorted(a.values()))
print(sorted(a.items()))
```

Output:-

```
[1, 2, 3, 4, 5, 6]
[11, 12, 13, 14, 15, 16]
[(1, 12), (2, 11), (3, 14), (4, 16), (5, 13), (6, 15)]
```

- Print **all key names** in the dictionary, one by one.

```
thisdict = {
    "brand": "Ford",
    "model": "Mustang",
    "year": 1964
}
for x in thisdict:
    print(x)
```

Output:-

```
brand
model
year
```

- Print all values in the dictionary, one by one:

```
thisdict = {
    "brand": "Ford",
    "model": "Mustang",
    "year": 1964
}
for x in thisdict:
    print(thisdict[x])
```

Output:-

```
Ford
Mustang
1964
```

- We can use the **keys()** method to return the keys of a dictionary:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
for x in thisdict.keys():  
    print(x)
```

Output:-

brand
model
year

- You can also use the **values()** method to return values of a dictionary:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
for x in thisdict.values():  
    print(x)
```

Output:-

Ford
Mustang
1964

- Loop through both keys and values, by using the **items()** method.

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
for x, y in thisdict.items():  
    print(x, y)
```

Output:-

brand Ford
model Mustang
year 1964

Dictionary Methods?

Ques. Dictionary Methods?

Method	Description
clear()	Removes all the elements from the dictionary
copy()	Returns a copy of the dictionary
get()	Returns the value of the specified key.
pop()	Removes the element with the specified key.
popitem()	Removes the last inserted key-value pair.
fromkeys()	Returns a dictionary with the specified keys and value.
items()	Returns a list containing a tuple for each key value pair.
keys()	Returns a list containing the dictionary's keys.
setdefault()	Returns the value of the specified key. If the key does not exist: insert the key, with the specified value.
update()	Updates the dictionary with the specified key-value pairs.
values()	Returns a list of all the values in the dictionary.

```
car = {
    "brand": "Ford",
    "model": "Mustang",
    "year": 1964
}

# The **clear()** method removes all the elements from a dictionary.
car.clear()
print(car)    # Output:- {}

# The **copy()** method returns a copy of the specified dictionary.
x = car.copy()
print(x)      # Output:- {'brand': 'Ford', 'model': 'Mustang', 'year': 1964}

# The **get()** method returns the value of the item with the **specified key**.
x = car.get("model")
print(x)      # Output:- Mustang
#
x = car.get("price", 15000)
print(x)      # Output:- 15000
```

```
# The **pop()** method removes the specified item from the dictionary.
x = car.pop("model")
print(x)    # output:- Mustang
print(car)  # Output:- {'brand': 'Ford', 'year': 1964}

# The **popitem()** method removes the item that was last inserted into the
dictionary.
x = car.popitem()
print(x)    # Output:- ('year', 1964)
print(car)  # Output:- {'brand': 'Ford', 'model': 'Mustang'}
```

- The **fromkeys()** method returns a dictionary with the specified keys and the specified value.

```
# Example1:-
x = ('key1', 'key2', 'key3')
y = 0
thisdict = dict.fromkeys(x, y)
print(thisdict)

Output:- {'key1': 0, 'key2': 0, 'key3': 0}

# Example2:-
x = ('key1', 'key2', 'key3')
thisdict = dict.fromkeys(x)
print(thisdict)

Output:- {'key1': None, 'key2': None, 'key3': None}
```

- The **items()** method returns a view object. The view object contains the \n key-value pairs of the dictionary, as tuples in a list.

```
car = {
    "brand": "Ford",
    "model": "Mustang",
    "year": 1964
}
x = car.items()
print(x)

Output:- dict_items([('brand', 'Ford'), ('model', 'Mustang'), ('year', 1964)])

# example2:-
car = {
    "brand": "Ford",
    "model": "Mustang",
    "year": 1964
}
```

```
x = car.items()
car["year"] = 2018
print(x)
```

Output:- dict_items([('brand', 'Ford'), ('model', 'Mustang'), ('year', 2018)])

- The **keys()** method returns a view object. The view object contains the keys of the dictionary, as a list.

```
car = {
    "brand": "Ford",
    "model": "Mustang",
    "year": 1964
}
x = car.keys()
print(x)
```

```
car["color"] = "white"
print(x)
```

Output:- dict_keys(['brand', 'model', 'year'])

Output:- dict_keys(['brand', 'model', 'year', 'color'])

- The **setdefault()** method returns the value of the item with the specified key.

```
car = {
    "brand": "Ford",
    "model": "Mustang",
    "year": 1964
}

x = car.setdefault("color", "White")
y = car.setdefault("model", "Bronco")

print(x)
print(y)
```

Output:- White

Output:- Mustang

- The **update()** method inserts the specified items to the dictionary.

```
car = {
    "brand": "Ford",
    "model": "Mustang",
    "year": 1964
}
```

```
car.update({"color": "White"})
print(car)    # Output:- {'brand': 'Ford', 'model': 'Mustang', 'year': 1964,
'color': 'White'}
```

- The **values()** method returns a view object. The view object contains the values of the dictionary, as a list.

```
car = {
    "brand": "Ford",
    "model": "Mustang",
    "year": 1964
}
x = car.values()
print(x)    # Output:- dict_values(['Ford', 'Mustang', 1964])

# Example2:-
car = {
    "brand": "Ford",
    "model": "Mustang",
    "year": 1964
}

x = car.values()
car["year"] = 2018
print(x)    # Output:- dict_values(['Ford', 'Mustang', 2018])
```

Nested Dictionaries

Ques. Nested Dictionaries?

A dictionary can contain dictionaries, this is called nested dictionaries.

```
myfamily = {  
    "child1" : {  
        "name" : "Emil",  
        "year" : 2004  
    },  
    "child2" : {  
        "name" : "Tobias",  
        "year" : 2007  
    },  
    "child3" : {  
        "name" : "Linus",  
        "year" : 2011  
    }  
}
```

```
print(myfamily)
```

Output:-

```
{'child1': {'name': 'Emil', 'year': 2004}, 'child2': {'name': 'Tobias', 'year':  
2007}, 'child3': {'name': 'Linus', 'year': 2011}}
```

Example2:-

```
child1 = {  
    "name" : "Emil",  
    "year" : 2004  
}  
child2 = {  
    "name" : "Tobias",  
    "year" : 2007  
}  
child3 = {  
    "name" : "Linus",  
    "year" : 2011  
}
```

```
myfamily = {  
    "child1" : child1,  
    "child2" : child2,  
    "child3" : child3  
}
```

```
print(myfamily)
```

Output:-

```
{'child1': {'name': 'Emil', 'year': 2004}, 'child2': {'name': 'Tobias', 'year': 2007}, 'child3': {'name': 'Linus', 'year': 2011}}
```

- Access Items in Nested Dictionaries

```
myfamily = {  
    "child1" : {  
        "name" : "Emil",  
        "year" : 2004  
    },  
    "child2" : {  
        "name" : "Mohit",  
        "year" : 2007  
    },  
    "child3" : {  
        "name" : "Linus",  
        "year" : 2011  
    }  
}  
  
print(myfamily["child2"]["name"])  
Output:- Mohit
```


Dictionaries Questions

Ques. How to Merging Or Adding two Dictionaries?

- Using **update()** method

```
dict_1 = {'John': 15, 'Rick': 10, 'Misa' : 12 }  
dict_2 = {'Bonnie': 18, 'Rick': 20, 'Matt' : 16 }
```

```
dict_1.update(dict_2)  
print(dict_1)
```

Output:- {'John': 15, 'Rick': 20, 'Misa': 12, 'Bonnie': 18, 'Matt': 16}

- Using ****** operator:- The simplest way to merge two dictionaries in python is by using the unpack operator(**)

```
dict_1 = {'John': 15, 'Rick': 20, 'Misa' : 12 }  
dict_2 = {'Bonnie': 18, 'Rick': 10, 'Matt' : 16 }  
dict_3 = {'Stefan': 19, 'Riya': 14, 'Lora': 17}  
dict_4 = {**dict_1, **dict_2, **dict_3}  
print (dict_4)
```

Output:- {'John': 15, 'Rick': 10, 'Misa': 12, 'Bonnie': 18, 'Matt': 16, 'Stefan': 19, 'Riya': 14, 'Lora': 17}

- Using for loop

```
dict1 = {'Alexandra' : 27, 'Shelina' : 22, 'James' : 29, 'Peterson' : 30 }  
dict2 = {'Jasmine' : 19, 'Maria' : 26, 'Helena' : 30 }  
dict3 = dict1.copy()
```

```
for key, value in dict2.items():  
    dict3[key] = value
```

```
print(dict3)
```

Output:- {'Alexandra': 27, 'Shelina': 22, 'James': 29, 'Peterson': 30, 'Jasmine': 19, 'Maria': 26, 'Helena': 30}

- Unpacking the second dictionary

```
dict_1={'John': 15, 'Rick': 10, 'Misa' : 12 }  
dict_2={'Bonnie': 18, 'Rick': 20, 'Matt' : 16 }  
dict_3=dict(dict_1,**dict_2)  
print (dict_3)
```

```
Output:- {'John': 15, 'Rick': 20, 'Misa': 12, 'Bonnie': 18, 'Matt': 16}
```

- Using collection.ChainMap() method

```
from collections import ChainMap
dict_1={'John': 15, 'Rick': 10, 'Misa' : 12 }
dict_2={'Bonnie': 18, 'Rick': 20, 'Matt' : 16 }
dict_3 = ChainMap(dict_1, dict_2)
print(dict_3)
print(dict(dict_3))

Output:-
ChainMap({'John': 15, 'Rick': 10, 'Misa': 12}, {'Bonnie': 18, 'Rick': 20, 'Matt': 16})
{'Bonnie': 18, 'Rick': 10, 'Matt': 16, 'John': 15, 'Misa': 12}
```

- Using itertools.chain()

```
import itertools
dict_1={'John': 15, 'Rick': 10, 'Misa': 12}
dict_2={'Bonnie': 18, 'Rick': 20, 'Matt': 16}
dict_3=itertools.chain(dict_1.items(),dict_2.items())
#Returns an iterator object
print (dict_3)
print(dict(dict_3))

Output:-
<itertools.chain object at 0x7f34fd841220>
{'John': 15, 'Rick': 20, 'Misa': 12, 'Bonnie': 18, 'Matt': 16}
```

- Using dictionary comprehension

```
dict_1={'John': 15, 'Rick': 10, 'Misa': 12}
dict_2={'Bonnie': 18, 'Rick': 20, 'Matt': 16}
dict_3={k:v for d in (dict_1,dict_2) for k,v in d.items()}
print (dict_3)

Output:- {'John': 15, 'Rick': 20, 'Misa': 12, 'Bonnie': 18, 'Matt': 16}
```

- Add values of common keys

```
dict_1 = {'John': 15, 'Rick': 10, 'Misa': 12}
dict_2 = {'Bonnie': 18, 'Rick': 20, 'Matt': 16}
```

```
def mergeDictionary(dict_1, dict_2):
    dict_3 = {**dict_1, **dict_2}
    for key, value in dict_3.items():
        if key in dict_1 and key in dict_2:
            dict_3[key] = [value, dict_1[key]]
    return dict_3
```

```
dict_3 = mergeDictionary(dict_1, dict_2)
print(dict_3)
```

Output:-

```
{'John': 15, 'Rick': [20, 10], 'Misa': 12, 'Bonnie': 18, 'Matt': 16}
```

- Using Zip function

```
d = {'k1': 1, 'k2': 2}
```

```
keys = ['k1', 'k3', 'k4']
```

```
values = [100, 3, 4]
```

```
d.update(zip(keys, values))
print(d)
```

Output:- {'k1': 100, 'k2': 2, 'k3': 3, 'k4': 4}

Ques. Combine two dictionary adding values for common keys?

- Using collections.Counter()

```
from collections import Counter
# initializing two dictionaries
dict1 = {'a': 12, 'for': 25, 'c': 9}
dict2 = {'Geeks': 100, 'geek': 200, 'for': 300}
```

```
res = Counter(dict1) + Counter(dict2)
print(res)
```

Output:- Counter({'for': 325, 'geek': 200, 'Geeks': 100, 'a': 12, 'c': 9})

- Naive method

```
dict1 = {'a': 12, 'for': 25, 'c': 9}
dict2 = {'Geeks': 100, 'geek': 200, 'for': 300}
# adding the values with common key
for key in dict2:
    if key in dict1:
        dict2[key] = dict2[key] + dict1[key]
```

```
print(dict2)
```

Output:- {'Geeks': 100, 'geek': 200, 'for': 325}

Ques. What will the output of following Program?

```
dictlang = {'c#': 6, 'GO': 89, 'python': 4, 'Rust':10, 'Apple':51, 'apple':21}
```

```
for i in sorted(dictlang):
    print (dictlang[i])
```

Output:-

```
51
89
10
21
6
4
```

Ques. Sort in dictionary with key, Value and Items.

- more sorted:- <https://www.golinuxcloud.com/python-sort-dictionary-by-key/>

```
dict = {6:'George' ,2:'John' ,1:'Potter' ,9:'Micheal' ,7:'Robert' ,8:'Gayle'}
```

```
b = sorted(dict.keys())
print("Sorted keys",b)
```

```
d = sorted(dict.values())
print("Sorted Values",d)
```

```
c = sorted(dict.items())
print("Sorted Values",c)
```

Output:-

```
Sorted keys [1, 2, 6, 7, 8, 9]
Sorted Values ['Gayle', 'George', 'John', 'Micheal', 'Potter', 'Robert']
Sorted Values [(1, 'Potter'), (2, 'John'), (6, 'George'), (7, 'Robert'), (8, 'Gayle'), (9, 'Micheal')]
```

- sort dictionary by key using for loop with **sorted()**

```
mydict_1 = {'key5': 'value5', 'key3': 'value3', 'key1': 'value1', 'key2': 'value2'}
new_dict = {}
sorted_value = sorted(mydict_1.keys())
```

```
for i in sorted_value:
    for key, value in mydict_1.items():
        if key == i:
            new_dict[key] = value

print(new_dict)
```

Ques. Can we use tuple as keys inside python dictionary?

- Yes, tuple can be used as key inside python dictionary, only if it contains only string, number or tuple. If a tuple contains any mutable datatype inside it like list, it can not be used as keys.

Ques. Can we use lists as keys inside python dictionary?

- No, python list can not be used as keys inside python dictionary, as they are mutable in nature.

Ques. What is enumerate function inside a dictionary?

- You can use the enumerate function with dictionary to get position index and corresponding index at the same time.

```
for i in enumerate(dict1):
    print(i)
```

```
#output
(0, 'name')
(1, 'age')
(2, 'city')
```

Ques. What is zip function in python dictionary and how can you use it?

How can combine two dictionaries together?

```
questions = ['name', 'location', 'favorite language']
answers = ['Codersdaily', 'Indore', 'Python']
for q, a in zip(questions, answers):
    print('What is your {0}? It is {1}.'.format(q, a))
```

Find Unique dictionary from list by id?

```
a = [  
    {'id':1,'name':'john', 'age':34},  
    {'id':1,'name':'john', 'age':34},  
    {'id':2,'name':'hanna', 'age':30},  
]  
  
b = {x['id']:x for x in a}.values()  
  
print(b)
```

Output:-

```
dict_values([{'id': 1, 'name': 'john', 'age': 34}, {'id': 2, 'name': 'hanna',  
'age': 30}])
```

