10. Perform the following Query

1. **Display the names of employees from department number 10 with salary greater than that of any employee working in other departments.**

```
MariaDB [vijendra0862]> SELECT empno, ename, deptno, sal
    -> FROM employee
    -> WHERE deptno = 10
    -> AND sal > ANY (
    ->     SELECT sal
    ->     FROM employee
    ->     WHERE deptno != 10
    -> );
+-------+--------+--------+------+
| empno | ename  | deptno | sal  |
+-------+--------+--------+------+
|  7934 | MILLER |     10 | 1430 |
+-------+--------+--------+------+
1 row in set (0.001 sec)
```

2. **Display the names of employee from department number 10 with salary greater than that of all employee working in other departments.**

```
MariaDB [vijendra0862]> SELECT empno, ename, deptno, sal
    -> FROM employee
    -> WHERE deptno = 10
    -> AND sal > ALL (
    ->     SELECT sal
    ->     FROM employee
    ->     WHERE deptno != 10
    -> );
Empty set (0.002 sec)
```

3. **Display the details of employees who are in sales dept and grade is**

```
MariaDB [vijendra0862]> SELECT e.empno, e.ename, e.deptno, e.sal
    -> FROM employee e
    -> JOIN department d ON e.deptno = d.Deptno
    -> JOIN salgrade s ON e.sal BETWEEN s.losal AND s.hisal
    -> WHERE d.name = 'SALES'
    -> AND s.grade = 3;
+-------+--------+--------+------+
| empno | ename  | deptno | sal  |
+-------+--------+--------+------+
|  7499 | ALLEN  |     30 | 1600 |
|  7844 | TURNER |     30 | 1500 |
+-------+--------+--------+------+
2 rows in set (0.010 sec)
```

4. **Display those who are not managers and who are managers anyone.**

```
MariaDB [vijendra0862]> SELECT empno, ename, job
    -> FROM employee
    -> WHERE empno NOT IN (
    ->     SELECT DISTINCT mgr
    ->     FROM employee
    ->     WHERE mgr IS NOT NULL
    -> );
+-------+--------+----------+
| empno | ename  | job      |
+-------+--------+----------+
|  7369 | SMITH  | CLERK    |
|  7499 | ALLEN  | SALESMAN |
|  7521 | WARD   | SALESMAN |
|  7654 | MARTIN | SALESMAN |
|  7844 | TURNER | SALESMAN |
|  7876 | ADAMS  | CLERK    |
|  7900 | JAMES  | CLERK    |
|  7934 | MILLER | CLERK    |
+-------+--------+----------+
8 rows in set (0.002 sec)
```

5. **Display those employees whose manager name is jones.**

```
MariaDB [vijendra0862]> SELECT e.empno, e.ename, e.deptno, e.sal
    -> FROM employee e
    -> JOIN employee m ON e.mgr = m.empno
    -> WHERE m.ename = 'JONES';
+-------+-------+--------+------+
| empno | ename | deptno | sal  |
+-------+-------+--------+------+
|  7788 | SCOTT |     40 | 3300 |
|  7902 | FORD  |     20 | 3300 |
+-------+-------+--------+------+
2 rows in set (0.002 sec)
```

6. **Display ename who are working in sales dept.**

```
MariaDB [vijendra0862]> SELECT e.ename
    -> FROM employee e
    -> JOIN department d ON e.deptno = d.Deptno
    -> WHERE UPPER(d.name) = 'SALES';
+--------+
| ename  |
+--------+
| ALLEN  |
| WARD   |
| MARTIN |
| BLAKE  |
| TURNER |
| JAMES  |
+--------+
6 rows in set (0.002 sec)
```

7. **Display employee name, deptname, salary and comm. For those sal in between 2000 to 5000 while location is Mumbai.**

```
MariaDB [vijendra0862]> SELECT e.ename, d.name AS deptname, e.sal, e.comm
    -> FROM employee e
    -> JOIN department d ON e.deptno = d.Deptno
    -> WHERE e.sal BETWEEN 2000 AND 5000
    -> AND UPPER(d.LOCATION) = 'MUMBAI';
+-------+----------+------+------+
| ename | deptname | sal  | comm |
+-------+----------+------+------+
| BLAKE | SALES    | 3135 | NULL |
+-------+----------+------+------+
1 row in set (0.001 sec)
```

8. **Display those employees whose salary greater than his manager salary.**

```
MariaDB [vijendra0862]> SELECT e.empno, e.ename, e.sal, m.ename AS manager, m.sal AS mgr_sal
    -> FROM employee e
    -> JOIN employee m ON e.mgr = m.empno
    -> WHERE e.sal > m.sal;
+-------+-------+------+---------+---------+
| empno | ename | sal  | manager | mgr_sal |
+-------+-------+------+---------+---------+
|  7788 | SCOTT | 3300 | JONES   |    3273 |
|  7902 | FORD  | 3300 | JONES   |    3273 |
+-------+-------+------+---------+---------+
2 rows in set (0.002 sec)
```

9. **Display those employees who are working in the same dept where his manager is working**

```
MariaDB [vijendra0862]> SELECT e.empno, e.ename, e.deptno
    -> FROM employee e
    -> JOIN employee m ON e.mgr = m.empno
    -> WHERE e.deptno = m.deptno;
+-------+--------+--------+
| empno | ename  | deptno |
+-------+--------+--------+
|  7369 | SMITH  |     20 |
|  7499 | ALLEN  |     30 |
|  7521 | WARD   |     30 |
|  7566 | JONES  |     20 |
|  7654 | MARTIN |     30 |
|  7782 | CLARK  |     20 |
|  7844 | TURNER |     30 |
|  7900 | JAMES  |     30 |
|  7902 | FORD   |     20 |
+-------+--------+--------+
9 rows in set (0.010 sec)
```

10 Display grade and employees name for the dept no 10 or 30 but grade is not 4, while joined the company before 31-dec-82.

```
MariaDB [vijendra0862]> SELECT e.ename, s.grade
    -> FROM employee e
    -> JOIN salgrade s
    -> ON e.sal BETWEEN s.losal AND s.hisal
    -> WHERE e.deptno IN (10, 30)
    -> AND s.grade <> 4
    -> AND e.hiredate < '1982-12-31';
+--------+-------+
| ename  | grade |
+--------+-------+
| ALLEN  |     3 |
| WARD   |     2 |
| MARTIN |     2 |
| BLAKE  |     5 |
| TURNER |     3 |
| JAMES  |     1 |
| MILLER |     3 |
+--------+-------+
7 rows in set (0.002 sec)
```