COMPUTER NETWORKS

TEAM NETWORKS

Department of Computer Science and Engineering

COMPUTER NETWORKS

Transport Layer

TEAM NETWORKS

Department of Computer Science and Engineering

PES UNIVERSITY

CELEBRATING 50 YEARS

Transport Layer - Roadmap

3.1 Transport-layer Services

3.2 Multiplexing and Demultiplexing

3.3 Connectionless Transport: UDP

UDP: User Datagram Protocol

- "no frills," "bare bones" Internet transport protocol
- "best effort" service, UDP segments may be:
  - lost
  - delivered out-of-order to app
- *connectionless:*
  - no handshaking between UDP sender, receiver
  - each UDP segment handled independently of others

Why is there a UDP?

- **no connection** establishment (which can add RTT delay)
- **no connection state** at sender, receiver (buffer, seq, ack, c-c parameters)
- **small header size** (8 vs 20 bytes)
- **no congestion control**
  - UDP can blast away as fast as desired!
  - can function in the face of congestion

UDP: User Datagram Protocol [RFC 768]

- UDP use:
  - streaming multimedia apps (loss tolerant, rate sensitive)
  - DNS
  - SNMP
  - HTTP/3
- if reliable transfer needed over UDP (e.g., HTTP/3):
  - add needed reliability at application layer
  - add congestion control at application layer

Popular Internet Applications using TCP/UDP

Application	Application-Layer Protocol	Underlying Transport Protocol
Electronic mail	SMTP	TCP
Remote terminal access	Telnet	TCP
Web	HTTP	TCP
File transfer	FTP	TCP
Remote file server	NFS	Typically UDP
Streaming multimedia	typically proprietary	UDP or TCP
Internet telephony	typically proprietary	UDP or TCP
Network management	SNMP	Typically UDP
Name translation	DNS	Typically UDP

UDP: User Datagram Protocol [RFC 768]

INTERNET STANDARD

RFC 768

J. Postel
ISI
28 August 1980

User Datagram Protocol

Introduction

This User Datagram Protocol (UDP) is defined to make available a datagram mode of packet-switched computer communication in the environment of an interconnected set of computer networks. This protocol assumes that the Internet Protocol (IP) [1] is used as the underlying protocol.

This protocol provides a procedure for application programs to send messages to other programs with a minimum of protocol mechanism. The protocol is transaction oriented, and delivery and duplicate protection are not guaranteed. Applications requiring ordered reliable delivery of streams of data should use the Transmission Control Protocol (TCP) [2].

Format

```
 0      7 8     15 16    23 24    31
+--------+--------+--------+--------+
|     Source      |   Destination   |
|      Port       |      Port       |
+--------+--------+--------+--------+
|                 |                 |
|     Length      |    Checksum     |
+--------+--------+--------+--------+
|
|          data octets ...
+---------------- ...
```

UDP: Transport Layer Actions



UDP: Transport Layer Actions

UDP sender actions:

- is passed an application-layer message
- determines UDP segment header fields values
- creates UDP segment
- passes segment to IP



UDP: Transport Layer Actions



UDP receiver actions:

- receives segment from IP
- checks UDP checksum header value
- extracts application-layer message
- demultiplexes message up to application via socket

UDP: segment header



UDP segment format

UDP Checksum

Goal: detect “errors” (e.g., flipped bits) in transmitted segment

	1st number	2nd number	sum
Transmitted:	5	6	11
Received:	4	6	11

receiver-computed checksum ≠ sender-computed checksum (as received)

!

UDP Checksum

Goal: detect errors (*i.e.,* flipped bits) in transmitted segment

sender:

- treat contents of UDP segment (including UDP header fields and IP addresses) as sequence of 16-bit integers
- checksum: addition (one's complement sum) of segment content
- checksum value put into UDP checksum field

receiver:

- compute checksum of received segment
- check if computed checksum equals checksum field value:
  - Not equal - error detected
  - Equal - no error detected. *But maybe errors nonetheless?* More later ….

Internet Checksum: example

example: add two 16-bit integers

		1	1	1	0	0	1	1	0	0	1	1	0	0	1	1	0
		1	1	0	1	0	1	0	1	0	1	0	1	0	1	0	1
wraparound	1	1	0	1	1	1	0	1	1	1	0	1	1	1	0	1	1
sum		1	0	1	1	1	0	1	1	1	0	1	1	1	1	0	0
checksum		0	1	0	0	0	1	0	0	0	1	0	0	0	0	1	1

Note: when adding numbers, a carryout from the most significant bit needs to be added to the result

* Check out the online interactive exercises for more examples: http://gaia.cs.umass.edu/kurose_ross/interactive/

Internet Checksum: Weak protection!

example: add two 16-bit integers

		1	1	1	0	0	1	1	0	0	1	1	0	0	1	1	0
		1	1	0	1	0	1	0	1	0	1	0	1	0	1	0	1
wraparound	1	1	0	1	1	1	0	1	1	1	0	1	1	1	0	1	1
sum		1	0	1	1	1	0	1	1	1	0	1	1	1	1	0	0
checksum		0	1	0	0	0	1	0	0	0	1	0	0	0	0	1	1

0 1

1 0

Even though numbers have changed (bit flips), *no* change in checksum!

Internet Checksum: example

example: add three 16-bit integers

	0	1	1	0	0	1	1	0	0	1	1	0	0	0	0	0
	0	1	0	1	0	1	0	1	0	1	0	1	0	1	0	1
	1	0	0	0	1	1	1	1	0	0	0	0	1	1	0	0
sum	0	1	0	0	1	0	1	0	1	1	0	0	0	0	1	0
checksum	1	0	1	1	0	1	0	1	0	0	1	1	1	1	0	1

Note: when adding numbers, a carryout from the most significant bit needs to be added to the result

* Check out the online interactive exercises for more examples: http://gaia.cs.umass.edu/kurose_ross/interactive/

Suggested Readings

- UDP – RFC 768 https://tools.ietf.org/html/rfc768
- Networking - DNS and UDP https://youtu.be/vuyQ1PW6AwY

Q&A

Thank You
For Your Attention

THANK YOU

Department of Computer Science and Engineering