



DESIGN AND ANALYSIS OF ALGORITHMS

The Knapsack Problem

Reetinder Sidhu

Department of Computer Science and Engineering

DESIGN AND ANALYSIS OF ALGORITHMS

The Knapsack Problem

Reetinder Sidhu

Department of Computer Science and
Engineering

THE KNAPSACK PROBLEM

UNIT 5: Limitations of Algorithmic Power and Coping with the Limitations

- Dynamic Programming
 - ▶ Computing a Binomial Coefficient
 - ▶ **The Knapsack Problem**
 - ▶ Memory Functions
 - ▶ Warshall's and Floyd's Algorithms
- Limitations of Algorithmic Power
 - ▶ Lower-Bound Arguments
 - ▶ Decision Trees
 - ▶ P, NP, and NP-Complete, NP-Hard Problems
- Coping with the Limitations
 - ▶ Backtracking
 - ▶ Branch-and-Bound. Architecture (microprocessor instruction set)

Concepts covered

- The Knapsack Problem
 - ▶ Introduction
 - ▶ Recurrence
 - ▶ Example

- Given
 - ▶ n items of integer weights : $w_1 \quad w_2 \quad \dots \quad w_n$
values : $v_1 \quad v_2 \quad \dots \quad v_n$
 - ▶ knapsack of capacity W (integer $W > 0$)
- Find the most valuable subset of items such that sum of their weights does not exceed W

THE KNAPSACK PROBLEM

Knapsack Recurrence

- To design a dynamic programming algorithm, we need to derive a recurrence relation that expresses a solution to an instance of the knapsack problem in terms of solutions to its smaller subinstances
- Consider the smaller knapsack problem where number of items is i ($i \leq n$) and the knapsack capacity is j ($j \leq W$)
- Then

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j - w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j-w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12
2	1	10
3	3	20
4	2	15

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j - w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12

	capacity j				
i	1	2	3	4	5
1					
2					
3					
4					

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j - w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12

	capacity j				
i	1	2	3	4	5
1	0				
2					
3					
4					

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j-w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12

	capacity j				
i	1	2	3	4	5
1	0	12			
2					
3					
4					

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j - w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12

	capacity j				
i	1	2	3	4	5
1	0	12	12		
2					
3					
4					

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j-w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12

	capacity j				
i	1	2	3	4	5
1	0	12	12	12	
2					
3					
4					

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j - w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12

	capacity j				
i	1	2	3	4	5
1	0	12	12	12	12
2					
3					
4					

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j-w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12
2	1	10

	capacity j				
i	1	2	3	4	5
1	0	12	12	12	12
2					
3					
4					

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j-w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12
2	1	10

	capacity j				
i	1	2	3	4	5
1	0	12	12	12	12
2	10				
3					
4					

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j-w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12
2	1	10

	capacity j				
i	1	2	3	4	5
1	0	12	12	12	12
2	10	12			
3					
4					

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j-w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12
2	1	10

	capacity j				
i	1	2	3	4	5
1	0	12	12	12	12
2	10	12	22		
3					
4					

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j-w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12
2	1	10

	capacity j				
i	1	2	3	4	5
1	0	12	12	12	12
2	10	12	22	22	22
3					
4					

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j-w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12
2	1	10
3	3	20

	capacity j				
i	1	2	3	4	5
1	0	12	12	12	12
2	10	12	22	22	22
3					
4					

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j-w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12
2	1	10
3	3	20

	capacity j				
i	1	2	3	4	5
1	0	12	12	12	12
2	10	12	22	22	22
3	10				
4					

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j - w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12
2	1	10
3	3	20

	capacity j				
i	1	2	3	4	5
1	0	12	12	12	12
2	10	12	22	22	22
3	10	12			
4					

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j - w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12
2	1	10
3	3	20

	capacity j				
i	1	2	3	4	5
1	0	12	12	12	12
2	10	12	22	22	22
3	10	12	22		
4					

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j-w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12
2	1	10
3	3	20

	capacity j				
i	1	2	3	4	5
1	0	12	12	12	12
2	10	12	22	22	22
3	10	12	22	30	
4					

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j-w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12
2	1	10
3	3	20

	capacity j				
i	1	2	3	4	5
1	0	12	12	12	12
2	10	12	22	22	22
3	10	12	22	30	32
4					

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j - w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12
2	1	10
3	3	20
4	2	15

	capacity j				
i	1	2	3	4	5
1	0	12	12	12	12
2	10	12	22	22	22
3	10	12	22	30	32
4					

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j-w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12
2	1	10
3	3	20
4	2	15

	capacity j				
i	1	2	3	4	5
1	0	12	12	12	12
2	10	12	22	22	22
3	10	12	22	30	32
4	10				

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j-w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12
2	1	10
3	3	20
4	2	15

	capacity j				
i	1	2	3	4	5
1	0	12	12	12	12
2	10	12	22	22	22
3	10	12	22	30	32
4	10	15			

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j - w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12
2	1	10
3	3	20
4	2	15

	capacity j				
i	1	2	3	4	5
1	0	12	12	12	12
2	10	12	22	22	22
3	10	12	22	30	32
4	10	15	25		

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j - w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12
2	1	10
3	3	20
4	2	15

	capacity j				
i	1	2	3	4	5
1	0	12	12	12	12
2	10	12	22	22	22
3	10	12	22	30	32
4	10	15	25	30	

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j-w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12
2	1	10
3	3	20
4	2	15

	capacity j				
i	1	2	3	4	5
1	0	12	12	12	12
2	10	12	22	22	22
3	10	12	22	30	32
4	10	15	25	30	37

What is the maximum value that can be stored in a knapsack of capacity 6?

THE KNAPSACK PROBLEM

Example

$$F(i, j) = \begin{cases} \max(F(i-1, j), v_i + F(i-1, j-w_i)) & \text{if } j - w_i \geq 0 \\ F(i-1, j) & \text{if } j - w_i < 0 \end{cases}$$

Dynamic Programming Example

item i	weight w_i	value v_i
1	2	12
2	1	10
3	3	20
4	2	15

What is the maximum value that can be stored in a knapsack of capacity 6?

	capacity j				
i	1	2	3	4	5
1	0	12	12	12	12
2	10	12	22	22	22
3	10	12	22	30	32
4	10	15	25	30	37

Given above 6 items, maximum value that can be stored in a knapsack of capacity 5 is

37

THE KNAPSACK PROBLEM

Complexity

- Space complexity: $\Theta(nW)$
- Time complexity: $\Theta(nW)$
- Time to compose optimal solution: $O(n)$

THE KNAPSACK PROBLEM

Think About It



THE KNAPSACK PROBLEM

Think About It

- Write pseudocode of the bottom-up dynamic programming algorithm for the knapsack problem

THE KNAPSACK PROBLEM

Think About It

- Write pseudocode of the bottom-up dynamic programming algorithm for the knapsack problem
- True or False:
 - ① A sequence of values in a row of the dynamic programming table for the knapsack problem is always nondecreasing?

THE KNAPSACK PROBLEM

Think About It

- Write pseudocode of the bottom-up dynamic programming algorithm for the knapsack problem
- True or False:
 - ① A sequence of values in a row of the dynamic programming table for the knapsack problem is always nondecreasing?
 - ② A sequence of values in a column of the dynamic programming table for the knapsack problem is always nondecreasing?