```python
n = int(input("Enter number of processes: "))
tq = int(input("Enter Time Quantum: "))
pid = []
at = []
bt = []
rt = []
for i in range(n):
    pid.append(input(f"Enter PID for P{i+1}: "))
    at.append(int(input("Arrival Time: ")))
    bt.append(int(input("Burst Time: ")))
    rt.append(bt[i])

ct = [0] * n
tat = [0] * n
wt = [0] * n
time = 0
queue = []
visited = [0] * n
completed = 0
while completed < n:
    # Add processes that have arrived
    for i in range(n):
        if at[i] <= time and visited[i] == 0:
            queue.append(i)
            visited[i] = 1

    if not queue:
        time += 1
        continue
```

```python
        time += 1
        continue

    i = queue.pop(0)

    if rt[i] > tq:
        time += tq
        rt[i] -= tq
    else:
        time += rt[i]
        rt[i] = 0
        ct[i] = time
        completed += 1
    for j in range(n):
        if at[j] <= time and visited[j] == 0:
            queue.append(j)
            visited[j] = 1
    if rt[i] > 0:
        queue.append(i)
for i in range(n):
    tat[i] = ct[i] - at[i]
    wt[i] = tat[i] - bt[i]
print("\nPID\tAT\tBT\tCT\tTAT\tWT")
for i in range(n):
    print(f"{pid[i]}\t{at[i]}\t{bt[i]}\t{ct[i]}\t{tat[i]}\t{wt[i]}")
```

```
Enter number of processes: 3
Enter Time Quantum: 5
Enter PID for P1: A
Arrival Time: 1
Burst Time: 9
Enter PID for P2: B
Arrival Time: 2
Burst Time: 16
Enter PID for P3: C
Arrival Time: 3
Burst Time: 12

PID AT  BT  CT  TAT WT
A   1   9   20  19  10
B   2   16  38  36  20
C   3   12  37  34  22
```