

<https://www.baeldung.com/java-memory-management-interview-questions>

<https://www.softwaretestinghelp.com/garbage-collection-in-java/>

Q1. What Does the Statement “Memory Is Managed in Java” Mean?

Memory is the key resource an application requires to run effectively and like any resource, it is scarce. As such, its allocation and deallocation to and from applications or different parts of an application require a lot of care and consideration.

However, in Java, a developer does not need to explicitly allocate and deallocate memory – the JVM and more specifically the Garbage Collector – has the duty of handling memory allocation so that the developer doesn't have to.

This is contrary to what happens in languages like C where a programmer has direct access to memory and literally references memory cells in his code, creating a lot of room for memory leaks.

Q2. What Is Garbage Collection and What Are Its Advantages?

Garbage collection is the process of looking at heap memory, identifying which objects are in use and which are not, and deleting the unused objects.

An in-use object, or a referenced object, means that some part of your program still maintains a pointer to that object. An unused object, or unreferenced object, is no longer referenced by any part of your program. So the memory used by an unreferenced object can be reclaimed.

The biggest advantage of garbage collection is that it removes the burden of manual memory allocation/deallocation from us so that we can focus on solving the problem at hand.

Q3. Are There Any Disadvantages of Garbage Collection?

Yes. Whenever the garbage collector runs, it has an effect on the application's performance. This is because all other threads in the application have to be stopped to allow the garbage collector thread to effectively do its work.

Depending on the requirements of the application, this can be a real problem that is unacceptable by the client. However, this problem can be greatly reduced or even eliminated through skillful optimization and garbage collector tuning and using different GC algorithms.

Q4. What Is the Meaning of the Term “Stop-The-World”?

When the garbage collector thread is running, other threads are stopped, meaning the application is stopped momentarily. This is analogous to house cleaning or fumigation where occupants are denied access until the process is complete.

Depending on the needs of an application, “stop the world” garbage collection can cause an unacceptable freeze. This is why it is important to do garbage

collector tuning and JVM optimization so that the freeze encountered is at least acceptable.

Q5. What Are Stack and Heap? What Is Stored in Each of These Memory Structures, and How Are They Interrelated?

The stack is a part of memory that contains information about nested method calls down to the current position in the program. It also contains all local variables and references to objects on the heap defined in currently executing methods.

This structure allows the runtime to return from the method knowing the address whence it was called, and also clear all local variables after exiting the method. Every thread has its own stack.

The heap is a large bulk of memory intended for allocation of objects. When you create an object with the *new* keyword, it gets allocated on the heap. However, the reference to this object lives on the stack.

Q6. What Is Generational Garbage Collection and What Makes It a Popular Garbage Collection Approach?

Generational garbage collection can be loosely defined as the strategy used by the garbage collector where the heap is divided into a number of sections called generations, each of which will hold objects according to their “age” on the heap.

Whenever the garbage collector is running, the first step in the process is called marking. This is where the garbage collector identifies which pieces of

memory are in use and which are not. This can be a very time-consuming process if all objects in a system must be scanned.

As more and more objects are allocated, the list of objects grows and grows leading to longer and longer garbage collection time. However, empirical analysis of applications has shown that most objects are short-lived.

With generational garbage collection, objects are grouped according to their “age” in terms of how many garbage collection cycles they have survived. This way, the bulk of the work spread across various minor and major collection cycles.

Today, almost all garbage collectors are generational. This strategy is so popular because, over time, it has proven to be the optimal solution.

Q7. Describe in Detail How Generational Garbage Collection Works

To properly understand how generational garbage collection works, it is important to first **remember how Java heap is structured** to facilitate generational garbage collection.

The heap is divided up into smaller spaces or generations. These spaces are Young Generation, Old or Tenured Generation, and Permanent Generation.

The **young generation hosts most of the newly created objects**. An empirical study of most applications shows that majority of objects are quickly short lived and therefore, soon become eligible for collection. Therefore, new objects start their journey here and are only “promoted” to the old generation space after they have attained a certain “age”.

The term “**age**” in generational garbage collection **refers to the number of collection cycles the object has survived**.

The young generation space is further divided into three spaces: an Eden space and two survivor spaces such as Survivor 1 (s1) and Survivor 2 (s2).

The **old generation hosts objects that have lived in memory longer than a certain “age”**. The objects that survived garbage collection from the young generation are promoted to this space. It is generally larger than the young generation. As it is bigger in size, the garbage collection is more expensive and occurs less frequently than in the young generation.

The **permanent generation or more commonly called, *PermGen*, contains metadata required by the JVM** to describe the classes and methods used in the application. It also contains the string pool for storing interned strings. It is populated by the JVM at runtime based on classes in use by the application. In addition, platform library classes and methods may be stored here.

First, **any new objects are allocated to the Eden space**. Both survivor spaces start out empty. When the Eden space fills up, a minor garbage collection is triggered. Referenced objects are moved to the first survivor space. Unreferenced objects are deleted.

During the next minor GC, the same thing happens to the Eden space. Unreferenced objects are deleted and referenced objects are moved to a survivor space. However, in this case, they are moved to the second survivor space (S2).

In addition, objects from the last minor GC in the first survivor space (S1) have their age incremented and are moved to S2. Once all surviving objects have been moved to S2, both S1 and Eden space are cleared. At this point, S2 contains objects with different ages.

At the next minor GC, the same process is repeated. However this time the survivor spaces switch. Referenced objects are moved to S1 from both Eden and S2. Surviving objects are aged. Eden and S2 are cleared.

After every minor garbage collection cycle, the age of each object is checked. Those that have reached a certain arbitrary age, for example, 8, are promoted from the young generation to the old or tenured generation. For all subsequent minor GC cycles, objects will continue to be promoted to the old generation space.

This pretty much exhausts the process of garbage collection in the young generation. Eventually, a major garbage collection will be performed on the old generation which cleans up and compacts that space. For each major GC, there are several minor GCs.

Q8. When Does an Object Become Eligible for Garbage Collection? Describe How the Gc Collects an Eligible Object?

An object becomes eligible for Garbage collection or GC if it is not reachable from any live threads or by any static references.

The most straightforward case of an object becoming eligible for garbage collection is if all its references are null. Cyclic dependencies without any live external reference are also eligible for GC. So if object A references object B and object B references Object A and they don't have any other live reference then both Objects A and B will be eligible for Garbage collection.

Another obvious case is when a parent object is set to null. When a kitchen object internally references a fridge object and a sink object, and the kitchen object is set to null, both fridge and sink will become eligible for garbage collection alongside their parent, kitchen.

Q9. How Do You Trigger Garbage Collection from Java Code?

You, as Java programmer, can not force garbage collection in Java; it will only trigger if JVM thinks it needs a garbage collection based on Java heap size.

Before removing an object from memory garbage collection thread invokes `finalize()` method of that object and gives an opportunity to perform any sort of cleanup required. You can also invoke this method of an object code, however, there is no guarantee that garbage collection will occur when you call this method.

Additionally, there are methods like `System.gc()` and `Runtime.gc()` which is used to send request of Garbage collection to JVM but it's not guaranteed that garbage collection will happen.

Q10. What Happens When There Is Not Enough Heap Space to Accommodate Storage of New Objects?

If there is no memory space for creating a new object in Heap, Java Virtual Machine throws *OutOfMemoryError* or more specifically *java.lang.OutOfMemoryError* heap space.

Q11. Is It Possible to «Resurrect» an Object That Became Eligible for Garbage Collection?

When an object becomes eligible for garbage collection, the GC has to run the *finalize* method on it. The *finalize* method is guaranteed to run only once, thus the GC flags the object as finalized and gives it a rest until the next cycle.

In the *finalize* method you can technically “resurrect” an object, for example, by assigning it to a *static* field. The object would become alive again and non-eligible for garbage collection, so the GC would not collect it during the next cycle.

The object, however, would be marked as finalized, so when it would become eligible again, the finalize method would not be called. In essence, you can turn this “resurrection” trick only once for the lifetime of the object. Beware that this ugly hack should be used only if you really know what you're doing — however, understanding this trick gives some insight into how the GC works.

Q12. Suppose We Have a Circular Reference (Two Objects That Reference Each Other). Could Such Pair of Objects Become Eligible for Garbage Collection and Why?

Yes, a pair of objects with a circular reference can become eligible for garbage collection. This is because of how Java's garbage collector handles circular references. It considers objects live not when they have any reference to them, but when they are reachable by navigating the object graph starting from some garbage collection root (a local variable of a live thread or a static field). If a pair of objects with a circular reference is not reachable from any root, it is considered eligible for garbage collection.

#3) Permanent Generation Till Java 7 there used to be a Permanent Generation (Perm Gen). The Perm Gen held metadata was used by JVM. JVM used this metadata to describe classes and methods used in the application. The Perm Gen was removed in Java 8.

Java 8 Garbage Collection: Perm Gen And Metaspace

We have already mentioned about Perm Gen space that was present till Java 7. However, now in Java 8, the JVM represents the class metadata using the native memory called “Metaspace”.

Apart from Metaspace, there is a new flag called “MaxMetaspaceSize” that limits the memory used for class metadata. If no value is specified for MaxMetaspaceSize, then the Metaspace resizes it at runtime according to the application demand.

When class metadata space reaches MaxMetaspaceSize, the Metaspace GC is triggered. When there is excessive Metaspace GC, it indicates memory leak of classes, classloaders, etc. as well as inadequate sizing.

Garbage Collection Algorithms In Java

There are various ways in which the Garbage Collection is performed. In this section, we will present four such ways or algorithms for Garbage Collection in Java.

Serial GC

Serial GC is the simplest GC algorithm. It mainly works on small heap sizes and single-threaded systems. While working, Serial GC freezes all the applications.

To turn on Serial GC, we can use the following JVM Option.

```
java -xx:+UseSerialGC -jar Application.java
```

The above command can be given in the command line. Here Application.java is a file for which serial GC is to be enabled.

Throughput/Parallel GC

THE Parallel GC algorithm is the default one in JDK 8. This algorithm uses multiple threads to scan the heap space and compaction. This algorithm is suitable mostly for applications that can handle thread pauses and optimize the CPU overhead.

One disadvantage of parallel GC is that while performing minor or full GC, the algorithm pauses the application threads.

The CMS Collector

The CMS stands for “**Concurrent Mark Sweep**”. This algorithm makes use of multiple **concurrent** threads to scan the heap (**mark**) to identify unused objects and recycle (**sweep**) them. The CMS collector has a mode Stop-The-World (STW).

The collector goes in this mode in two scenarios:

- When objects belonging to the old generation can be reached from static variables or thread entry points. So this mode is on during the initialization of initial root markings.
- When the algorithm is running concurrently, the application changes the state and forces the collector to go back to make sure that the correct objects are marked.

The CMS collector however may suffer from “promotion failures”. So what is a promotional failure? If the objects from the young generation space are moved to the old generation, and the collector has not made enough space for these objects in the old generation heap space then a promotional failure will occur.

To prevent promotional failure, we may provide more background threads to the collector or provide more heap size to the old generation.

The G1 Collector

The G1 Collector is the “Garbage-First” Collector. It is designed for heap sizes of more than 4GB. Based on the heap size, it divides the heap size into regions of sizes ranging from 1MB to 32MB.

G1 collector marks the objects depending on the liveness of the objects throughout the heap. After this marking phase, G1 is aware of the empty regions. Thus it collects the unreachable objects from these regions thereby freeing a large amount of space. Hence it is named as Garbage-First as it collects regions containing garbage first.

It also meets the user-defined pause time target by using a pause prediction model by selecting the number of regions to collect depending on the specified pause time target.

IMPORTANT:- In Java8, the default GC is Parallel GC, while on Java 11 the default is G1 GC.

Daemon Thread in Java

Daemon thread in Java is a service provider thread that provides services to the user thread. Its life depends on the mercy of user threads i.e. when all the user threads dies, JVM terminates this thread automatically.

There are many java daemon threads running automatically e.g. gc, finalizer etc.