
R1 interface: Application Protocols for R1 Services

Copyright © 2026 by the O-RAN ALLIANCE e.V.

The copying or incorporation into any other work of part or all of the material available in this specification in any form without the prior written permission of O-RAN ALLIANCE e.V. is prohibited, save that you may print or download extracts of the material of this specification for your personal use, or copy the material of this specification for the purpose of sending to individual third parties for their information provided that you acknowledge O-RAN ALLIANCE as the source of the material and that you inform the third party that these conditions apply to them and that they must comply with them.

O-RAN ALLIANCE e.V., Buschkauler Weg 27, 53347 Alfter, Germany

Register of Associations, Bonn VR 11238, VAT ID DE321720189

Contents

Foreword.....	7
Modal verbs terminology.....	7
1 Scope.....	8
2 References.....	8
2.1 Normative references.....	8
2.2 Informative references.....	9
3 Definition of terms, symbols and abbreviations.....	10
3.1 Terms.....	10
3.2 Symbols.....	10
3.3 Abbreviations.....	11
4 Application protocol for the R1 services.....	12
4.1 Introduction.....	12
4.2 Version conventions for the present document.....	12
5 RESTful R1 service APIs.....	12
5.1 Overview.....	12
5.2 Versioning of RESTful R1 service APIs.....	13
5.3 URI structure and supported content formats.....	13
5.4 General considerations for RESTful R1 service APIs.....	14
5.4.1 Usage of HTTP header fields.....	14
5.4.2 Handling of large query results.....	14
5.4.3 Error reporting.....	14
6 Service management and exposure services.....	15
6.1 Service registration API.....	15
6.1.1 Introduction.....	15
6.1.2 API version.....	15
6.1.3 Resource structure and methods.....	15
6.1.4 Service operations.....	15
6.1.5 Resources.....	19
6.1.6 Custom operations without associated resources.....	21
6.1.7 Notifications.....	21
6.1.8 Data model.....	21
6.1.9 Error Handling.....	21
6.2 Service discovery API.....	22
6.2.1 Introduction.....	22
6.2.2 API version.....	22
6.2.3 Resource structure and methods.....	22
6.2.4 Service operations.....	22
6.2.5 Resources.....	23
6.2.6 Custom operations without associated resources.....	24
6.2.7 Notifications.....	24
6.2.8 Data model.....	24
6.2.9 Error Handling.....	24
6.3 Service events subscription API.....	25
6.3.1 Introduction.....	25
6.3.2 API version.....	25
6.3.3 Resource structure and methods.....	25
6.3.4 Service operations.....	25
6.3.5 Resources.....	28
6.3.6 Custom operations without associated resources.....	29
6.3.7 Notifications.....	29
6.3.8 Data Model.....	29
6.3.9 Error Handling.....	30

6.4	Bootstrap API	30
6.4.1	Introduction	30
6.4.2	API version	30
6.4.3	Resource structure and methods	30
6.4.4	Service Operations	30
6.4.5	Resources	31
6.4.6	Custom operation without associated resources.	32
6.4.7	Notifications	32
6.4.8	Data Model	32
6.4.9	Error Handling	33
7	Data management and exposure services	34
7.1	Data registration API	34
7.1.1	Introduction	34
7.1.2	API version	34
7.1.3	Resource structure and methods	34
7.1.4	Service Operations	35
7.1.4	Service Operations	38
7.1.5	Resources	39
7.1.6	Custom operation without associated resources.	43
7.1.7	Notifications	43
7.1.8	Data Model	43
7.1.9	Error Handling	46
7.2	Data discovery API	46
7.2.1	Introduction	46
7.2.2	API version	46
7.2.3	Resource structure and methods	46
7.2.4	Service operations	47
7.2.5	Resources	48
7.2.6	Custom operation without associated resources.	50
7.2.7	Notifications	51
7.2.8	Data Model	51
7.2.9	Error Handling	51
7.3	Data access API	52
7.3.1	Introduction	52
7.3.2	API version	52
7.3.3	Resource structure and methods	52
7.3.4	Service Operations	53
7.3.5	Resources	58
7.3.6	Custom operation without associated resources.	62
7.3.7	Notifications	63
7.3.8	Data Model	64
7.3.9	Error Handling	66
7.4	HTTP based Push data API	68
7.4.1	Introduction	68
7.4.2	API version	68
7.4.3	Resource structure and methods	68
7.4.4	Service Operations	68
7.4.5	Resources	69
7.4.6	Custom operation without associated resources.	69
7.4.7	Notifications	69
7.4.8	Data Model	70
7.4.9	Error Handling	70
7.5	HTTP based Pull data API	70
7.5.1	Introduction	70
7.5.2	API version	70
7.5.3	Resource structure and methods	70
7.5.4	Service Operations	71
7.5.5	Resources	72
7.5.6	Custom operation without associated resources.	73

7.5.7	Notifications	73
7.5.8	Data Model	73
7.5.9	Error Handling	73
7.6	Data offer API	74
7.6.1	Introduction	74
7.6.2	API version	74
7.6.3	Resource structure and methods	74
7.6.4	Service Operations	75
7.6.5	Resources	77
7.6.6	Custom operation without associated resources.	79
7.6.7	Notifications	80
7.6.8	Data Model	82
7.6.9	Error Handling	85
8	RAN OAM related services.	85
8.1	Configuration management API	85
8.1.1	Introduction	85
8.1.2	API version	85
8.1.3	Resource structure and methods	85
8.1.4	Service operations	86
8.1.5	Resources	88
8.1.6	Custom operations without associated resources.	88
8.1.7	Notifications	88
8.1.8	Data model	89
8.1.9	Error Handling	89
8.2	Fault management API	89
8.2.1	Introduction	89
8.2.2	API version	89
8.2.3	Resource structure and methods	90
8.2.4	Service operations	90
8.2.5	Resources	92
8.2.6	Custom operations without associated resources	93
8.2.7	Notifications	93
8.2.8	Data model	93
8.2.9	Error Handling	94
8.3	Configuration schema information API.	94
8.3.1	Introduction	94
8.3.2	API version	94
8.3.3	Resource structure and methods	94
8.3.4	Service operations	95
8.3.5	Resources	96
8.3.6	Custom operations without associated resources	98
8.3.7	Notifications	98
8.3.8	Data model	98
8.3.9	Error Handling	99
9.	A1 related services	100
9.1	A1 policy management API	100
9.1.1	Introduction	100
9.1.2	API version	100
9.1.3	Resource structure and methods	100
9.1.4	Service operations	101
9.1.5	Resources	112
9.1.6	Custom operation without associated resources	121
9.1.7	Notifications	121
9.1.8	Data Model	122
9.1.9	Error Handling	126
10.	AI/ML workflow services	127
10.1	AI/ML model registration API	127
10.1.1	Introduction	127

10.1.2	API version	127
10.1.3	Resource structure and methods	127
10.1.4	Service operations.....	128
10.1.5	Resources.....	131
10.1.6	Custom operation without associated resources.	134
10.1.7	Notifications	134
10.1.8	Data Model	134
10.1.9	Error Handling	136
10.2	AI/ML model discovery API.....	137
10.2.1	Introduction.....	137
10.2.2	API version	137
10.2.3	Resource structure and methods	137
10.2.4	Service operations.....	137
10.2.5	Resources.....	139
10.2.6	Custom operation without associated resources	141
10.2.7	Notifications	141
10.2.8	Data Model	141
10.2.9	Error Handling	142
10.3	AI/ML model training API.....	142
10.3.1	Introduction.....	142
10.3.2	API version	142
10.3.3	Resource structure and methods	143
10.3.4	Service operations.....	143
10.3.5	Resources.....	147
10.3.6	Custom operation without associated resources.	149
10.3.7	Notificationss.....	150
10.3.8	Data Model	150
10.3.9	Error Handling.....	151
10.4	AI/ML model deployment API	151
10.4.1	Introduction.....	151
10.4.2	API version	151
10.4.3	Resource structure and methods	152
10.4.4	Service operations.....	153
10.4.5	Resources.....	155
10.4.6	Custom operation without associated resources.	156
10.4.7	Notifications	156
10.4.8	Data Model	157
10.5	Void.....	157
Annex A (normative): OpenAPI specifications.....		158
A.1	General	158
A.1.1	Overview	158
A.1.2	Common schemas for general use	158
A.2	Service management and exposure service	161
A.2.1	Service registration API.....	161
A.2.2	Service discovery API	163
A.2.3	Service events subscription API	165
A.2.4	Bootstrap API	166
A.3	Data management and exposure service.....	167
A.3.1	Data registration API	167
A.3.2	Data discovery API.....	173
A.3.3	Data access API	175
A.3.4	HTTP based Push data API	180
A.3.5	HTTP based Pull data API.....	180
A.3.6	Data offer API.....	181
A.4	RAN OAM related services.....	184
A.4.1	Configuration management API	184
A.4.2	Fault management API	185
A.4.3	Configuration schema information API.....	185
A.5	A1 related service.....	188

A.5.1	A1 policy management API.....	188
A.6	AI/ML workflow service.....	195
A.6.1	AI/ML model registration API.....	195
A.6.2	AI/ML model discovery API	199
A.6.3	AI/ML model training API	202
A.6.4	AI/ML model deployment API.....	205
Annex B (normative): Common data types for R1 service APIs.....		207
B.1	Introduction	207
B.2	Common data types for Generic Usage.....	207
B.2.1	Introduction.....	207
B.2.2	Simple data types	207
B.2.3	Enumeration.....	207
B.2.4	Structured data types.....	207
B.2.5	Re-used data types	209
B.3	Common data types for Service management and exposure	209
B.3.1	Introduction.....	209
B.3.2	Simple data types	209
B.3.3	Enumerations	209
B.3.4	Structured data types.....	209
B.3.5	Re-used data types	209
B.4	Common data types for Data Management and Exposure	210
B.4.1	Introduction.....	210
B.4.2	Simple data types	210
B.4.3	Enumerations	211
B.4.4	Structured data types.....	211
B.4.5	Re-used data types	212
B.5	Common data types for RAN OAM related services	212
B.5.1	Introduction.....	212
B.5.2	Simple data types	212
B.5.3	Enumerations	212
B.5.4	Structured data types.....	212
B.5.5	Re-used data types	212
Annex (informative): Bibliography		214
Annex (informative): Change history.....		215

Foreword

This Technical Specification (TS) has been produced by WG2 of the O-RAN ALLIANCE. It is part of a TS-family covering the WG2: R1 Interface Specifications.

The content of the present document is subject to continuing work within O-RAN and may change following formal O-RAN approval. Should the O-RAN ALLIANCE modify the contents of the present document, it will be re-released by O-RAN with an identifying change of version date and an increase in version number as follows:

version xx.yy.zz

where:

- xx: the first digit-group is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc. (the initial approved document will have xx=01). Always 2 digits with leading zero if needed.
- yy: the second digit-group is incremented when editorial only changes have been incorporated in the document. Always 2 digits with leading zero if needed.
- zz: the third digit-group included only in working versions of the document indicating incremental changes during the editing process. External versions never include the third digit-group. Always 2 digits with leading zero if needed.

Modal verbs terminology

In the present document “**shall**”, “**shall not**”, “**should**”, “**should not**”, “**may**”, “**need not**”, “**will**”, “**will not**”, “**can**” and “**cannot**” are to be interpreted as described in clause 3.2 of the O-RAN Drafting Rules (Verbal forms for the expression of provisions).

“**must**” and “**must not**” are **NOT** allowed in O-RAN deliverables except when used in direct citation.

1 Scope

The present document specifies the Application Protocols for R1 Services.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies. In the case of a reference to a 3GPP document, a non-specific reference implicitly refers to the latest version of that document in Release 18, or the latest 3GPP release prior to Release 18 that includes that document.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, O-RAN cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] 3GPP TS 29.501 (v16.0): “5G System; Principles and Guidelines for Services Definition; (“3GPP TS 29.501”).
- [2] 3GPP TS 29.500: “5G System; Technical Realization of Service Based Architecture; Stage 3“. (“3GPP TS 29.500“)
- [3] OpenAPI: “OpenAPI 3.0.3 Specification“,

NOTE: Available at : <http://spec.openapis.org/oas/v3.0.3.html>

- [4] ETSI GS NFV-SOL 013 Rel3: “Protocols and Data Models; Specification of common aspects for RESTful NFV MANO APIs“.
- [5] O-RAN.WG2.TS.R1GAP: “R1 General Aspects and Principles“ (“R1GAP“).
- [6] O-RAN.WG2.TS.R1UCR: “R1 Use Cases and Requirements“ (“R1UCR“).
- [7] O-RAN.WG2.TS.R1TP: “Transport Protocols for R1 services“(“R1TP“).
- [8] IETF RFC 3986: “Uniform Resource Identifier (URI): Generic Syntax“.
- [9] 3GPP TS 29.222 (v18.6.0): “Common API Framework for 3GPP Northbound APIs. (“3GPP TS 29.222“)
- [10] IETF RFC 7807: “Problem Details for HTTP APIs“.
- [11] Semantic Versioning 2.0.0.

NOTE: Available at : <https://semver.org>.

- [12] IETF RFC 8259: “The JavaScript Object Notation (JSON) Data Interchange Format“.
- [13] IETF RFC 4229: “HTTP Header Field Registrations“.
- [14] json-schema 2020-12,

NOTE: Available at: “<https://json-schema.org/specification-links.html#2020-12>“.

- [15] Kafka Documentation

NOTE : Available at : “<https://kafka.apache.org/documentation.html>“.

- [16] W3C REC-xmlschema-1-20010502 : “XML Schema Part 1 : Structures“,

NOTE : Available at : <https://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>.

[17] W3C REC-xmlschema-2-20010502 : “XML Schema Part 2 : Datatypes“,

NOTE : Available at : <https://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>.

[18] W3C REC-xml-names-19990114: “Namespaces in XML“

NOTE: Available at : <http://www.w3.org/TR/1999/REC-xml-names-19990114>.

[19] IETF RFC 1035: “DOMAIN NAMES - IMPLEMENTATION AND SPECIFICATION“.

[20] 3GPP TS 28.532: “Management and orchestration; Generic management services“. (“3GPP TS 28.532“).

[21] 3GPP TS 28.622: “ Generic Network Resource Model (NRM) Integration Reference Point (IRP); Information Service (IS)“ (“3GPP TS 28.622“)

[22] 3GPP TS 28.623 (v17.9.0): “Generic Network Resource Model (NRM) Integration Reference Point (IRP); Solution Set (SS) definitions“. (“3GPP TS 28.623“).

[23] O-RAN.WG2.TS.A1AP: “A1 Interface: Application Protocol“ (“A1AP“).

[24] O-RAN.WG2.TS.A1TD: “A1 interface: Type Definitions“ (“A1TD“).

[25] IETF RFC 9110: “HTTP Semantics“.

[26] 3GPP TS 28.111: " Management and orchestration;Fault Management (FM) (“3GPP TS 28.111“).

[27] Protocol Buffers Documentation.

NOTE: Available at : “<https://protobuf.dev/>“.

[28] Avro Documentation.

NOTE: Available at : “<https://avro.apache.org/docs/>“.

[29] 3GPP TS 32.158: " Management and orchestration;Design rules for REpresentational State Transfer (REST) Solution Sets (SS) (“3GPP TS 32.158“).

[30] CloudEvents- version1.0 (“CloudEvents“)

NOTE: Available at : “spec/cloudevents/spec.md at v1.0.2 · cloudevents/spec · GitHub”

[31] HTTP Protocol Binding for CloudEvents - Version 1.0.2 (“HTTP-CloudEvents“)

NOTE: Available at : “spec/cloudevents/bindings/http-protocol-binding.md at v1.0.2 · cloudevents/spec · GitHub”.

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies. In the case of a reference to a 3GPP document, a non-specific reference implicitly refers to the latest version of that document in Release 18, or the latest 3GPP release prior to Release 18 that includes that document.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, O-RAN cannot guarantee their long-term validity.

The following referenced documents are not necessary for the application of the present document, but they assist the user with regard to a particular subject area.

[i.1] W3C REC-xmlschema-0-20010502: “XML Schema Part 0: Primer“

NOTE: Available at : <https://www.w3.org/TR/2001/REC-xmlschema-0-20010502/>.

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

API Consumer: The Service Consumer consuming one or more services using APIs.

NOTE: The Service Consumer role is introduced in R1GAP [5].

API Producer: The Service Producer that offers its services for consumption via APIs.

NOTE: The Service Producer role is introduced in R1GAP [5].

DME type: data type managed and exposed by the DME services and identified by a data type identifier.

3.2 Symbols

Void

3.3 Abbreviations

For the purposes of the present document, the follow abbreviations apply:

API	Application programming interface
FQDN	Fully qualified domain name
IOC	Information Object Class

4 Application protocol for the R1 services

4.1 Introduction

The present document contains a realization for the procedures identified in R1GAP [5]. It is based on transport protocols as defined in R1TP [7]. This definition of the R1 Application Protocols (R1AP) defined in the present document is based on the 3GPP service framework for network functions specified in 3GPP TS 29.501 [1].

4.2 Version conventions for the present document

The version number of the present document follows the “xx.yy” versioning scheme. There could be implications for the interoperability between rApps and R1 service API implementations in SMO/Non-RT RIC framework that are based on different versions of the present document.

An incremented “xx” version field of the present document could indicate that a new major feature (e.g., a new R1 service) has been added or that an incompatible change has been made to one or more R1 service APIs. An incremented “yy” version field could indicate that an optional feature has been added, a technical issue has been fixed, or that clarifications or editorial corrections have been made.

The version conventions for RESTful R1 service APIs are defined in clause 5.2.

5 RESTful R1 service APIs

5.1 Overview

The design of the RESTful R1 service APIs is based on the procedures and requirements defined in R1UCR [6] and R1GAP [5], and on the protocol design framework as specified in 3GPP TS 29.501 [1].

The API version of a service API includes a pre-release version (e.g., “-alpha.1”) if the service API is under development.

The present document defines the protocols for the R1 service APIs listed in table 5.1-1.

Table 5.1-1: RESTful R1 service APIs and their versions defined in the present document.

R1 Services	Service API	API Version
Service management and exposure services	Service registration	1.2.0
	Service discovery	1.2.0
	Service events subscription	1.2.0
	Bootstrap	1.0.1
Data management and exposure services	Data registration	2.0.0-alpha.3
	Data discovery	2.0.1
	Data access	2.0.0-alpha.3
	HTTP based push data	1.0.0
	HTTP based pull data	1.0.0
	Data offer	2.0.0-alpha.1
RAN OAM-related services	Configuration management	1.0.0-alpha.1
	Fault management	1.0.0
	Configuration schema information	1.0.1
A1-related services	A1 policy management	1.0.1
AI/ML workflow services	AI/ML model registration	1.0.1
	AI/ML model discovery	1.1.1
	AI/ML model training	1.0.0-alpha.2
	AI/ML model deployment	1.0.0-alpha.2

5.2 Versioning of RESTful R1 service APIs

Each RESTful R1 service API is versioned independently. The API version number defined in the present document contains three numerical fields following a MAJOR.MINOR.PATCH pattern, and may contain a pre-release version field, according to SemVer [11].

The API version number held by an implementation may additionally include a build metadata field, according to SemVer [11], to indicate a specific deployment. The content of this field is implementation specific; it is provided by the deployment. The <apiVersion> path segment used in URI structures indicate the MAJOR field of the API version number. The full API version number is visible in the “version” field of the “info” object of each OpenAPI document in Annex A, as well as in the ServiceAPIDescription information communicated during service registration and service discovery (see annex B.3.4.1).

To indicate the full API version the API Consumer intends to use, the API Consumer may include the “Version” HTTP header (see IETF RFC 4229 [13]) in an HTTP request, in which case the header shall contain the version identifier as defined above. It is optional to include the build metadata field.

The API Producer shall include in the response the “Version” HTTP header signalling the used API version, including the build metadata if available. If the build metadata have been omitted in the request, the API Producer shall use the combination of MAJOR, MINOR, PATCH, and pre-release indicator as requested and the highest supported value for the build metadata field for that combination, if available. In case the API Consumer has not sent a “Version” header in the request, the API Producer shall use the latest available version, and signal it in the “Version” header.

NOTE: In case multiple versions are supported by an API Producer under the URI for a major version, this allows the API Consumer to request a particular version. This mechanism is referred to as “microversioning”.

If the API version signalled by the API Consumer in the “Version” request header is not supported by the API Producer, the API Producer shall respond with a “406 Not Acceptable” error and may include in the response payload body a Problem Details structure providing more information on the cause of the error.

5.3 URI structure and supported content formats

This clause specifies the URI prefix and the supported content formats applicable to the RESTful R1 service APIs.

All resource URIs of the APIs shall have the following prefix:

{apiRoot}/<apiName>/<apiVersion>/

The request URIs used in HTTP requests from the API Consumer towards the API Producer shall have the resource URI structure defined in clause 4.4.1 of 3GPP TS 29.501 [1], i.e.:

{apiRoot}/<apiName>/<apiVersion>/<apiSpecificResourceUriPart>

with the following components:

- The {apiRoot} shall be set as described in 3GPP TS 29.501[1], clause 4.4.1; however, the restrictions w.r.t the operator specific FQDN of the host portion defined there do not apply.
- The <apiName> indicates the API name of the service interface in an abbreviated form. It is defined in the clause specifying the corresponding RESTful R1 service API.
- The <apiVersion> indicates the major version (see clause 5.2) of the API and is defined in the clause specifying the corresponding RESTful R1 serviceAPI.
- Each <apiSpecificResourceUriPart> represents a specific resource of the API. It is defined in the corresponding RESTful R1 service API for each one of the defined resources.

For HTTP requests and responses that have message content, the content format JSON (see IETF RFC 8259 [12]) shall be supported. The JSON format shall be signalled by the content type “application/json”.

All resource URIs of the API shall comply with the URI syntax as defined in IETF RFC 3986 [8]. An implementation that dynamically generates resource URI parts (individual path segments, sequences of path segments that are separated by “/”, query parameter values) shall ensure that these parts only use the character set that is allowed by IETF RFC 3986 [8] for these parts.

5.4 General considerations for RESTful R1 service APIs

5.4.1 Usage of HTTP header fields

HTTP headers are components of the headers section of the HTTP request and response messages. The usage of HTTP header fields shall follow the definitions in ETSI GS NFV-SOL 013 [4], clause 4.2.

5.4.2 Handling of large query results

The handling of large query results shall be supported by RESTful R1 service APIs as specified in ETSI GS NFV-SOL 013 [4], clause 5.4.2.

5.4.3 Error reporting

In RESTful interfaces, application errors are mapped to HTTP errors. Since HTTP error information is generally not enough to discover the root cause of the error, additional application specific error information is typically delivered in the message content based on the ProblemDetails data type.

HTTP error responses shall be supported as specified in 3GPP TS 29.501 [1], clause 4.8. Protocol errors and application errors specified in 3GPP TS 29.500 [2], table 5.2.7.1-1, shall be supported for an HTTP method if the corresponding HTTP status codes are specified as mandatory for that HTTP method in 3GPP TS 29.500 [2], table 5.2.7.1-1.

If an HTTP method is not defined for a particular resource in the present document, that method is not supported. When that method is requested on the resource, the API Producer shall return a “405 Method Not Allowed” response. The message content may include a ProblemDetails structure.

6 Service management and exposure services

6.1 Service registration API

6.1.1 Introduction

This API allows the API Consumer to manage registrations of service APIs based on the procedures for “Registration of services” defined in R1GAP [5].

6.1.2 API version

For the service registration API as specified in the present document, the MAJOR version field shall be 1, the MINOR version field shall be 2 and the PATCH version field shall be 0 (see 3GPP TS 29.501 [1] for a definition of the version fields). Consequently, the <apiVersion> URI path segment shall be set to “v1”.

6.1.3 Resource structure and methods

The request URIs used in HTTP requests from the API Consumer towards the API Producer shall have the resource URI structure as defined for the CAPIF_Publish_Service_API (see 3GPP TS 29.222 [9], for Figure 8.2.2.1-1 in Clause 8.2.2).

Table 6.1.3-1 lists the individual resources defined for the API, the applicable HTTP methods as defined in 3GPP TS 29.222 [9], clause 8.2) and the associated service operations.

Table 6.1.3-1: Resources and methods overview of the service registration API

Resource Name 3GPP TS 29.222 [9]	Resource URI 3GPP TS 29.222 [9]	HTTP method 3GPP TS 29.222 [9]	Service Operation
APF published APIs	/{apfld}/service-apis	POST	Register service API
		GET	Query service APIs
Individual APF published API	/{apfld}/service-apis/{serviceApId}	PUT	Update registered service API
		DELETE	Deregister service API
		PATCH	Partial update registered service API

6.1.4 Service operations

6.1.4.1 Register service API

6.1.4.1.1 Operation definition

A Service Producer uses the Register service API operation as API Consumer to register with the API Producer service APIs for services it is capable of producing.

The operation is based on HTTP POST.

```
@startuml
autonumber
participant "API Consumer" as cons
participant "API Producer" as prod
cons ->> prod : POST .../{apfId}/service-apis (ServiceAPIDescription)
```

```

prod -->> cons : 201 Created (ServiceAPIDescription)
@enduml

```



Figure 6.1.4.1.1-1: Register service API operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP POST request to the API Producer. The target URI shall identify the resource (`.../{apfId}/service-apis/`) under which the new registration is requested to be created. The message content shall carry a `ServiceAPIDescription` structure. The API Producer shall process the message content received in the HTTP POST message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall generate the service API identifier and construct the URI for the created resource. The API Producer shall return the HTTP POST response. On success “201 Created” shall be returned. The “Location” header shall be present and shall carry the URI of the new registration resource. The message content shall carry the registered service API description. On failure, the appropriate error code shall be returned, and the message response body may contain additional error information.

6.1.4.1.2 Referenced procedures.

6.1.4.1.2.1 Register service procedure

The Register service API operation illustrated in figure 6.1.4.1.1-1 is based on the Register service procedure defined in R1GAP [5].

6.1.4.2 Update registered service API.

6.1.4.2.1 Operation definition

A Service Producer uses the Update registered service API operation as API Consumer to update a complete service API registration with the API Producer.

The operation is based on HTTP PUT.

```

@startuml
autonumber
participant "API Consumer" as cons
participant "API Producer" as prod
cons ->> prod : PUT .../{apfId}/service-apis/{serviceApiId} (ServiceAPIDescription)
prod -->> cons : 200 OK (ServiceAPIDescription)
@enduml

```





Figure 6.1.4.2.1-1: Update registered service API operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP PUT request to the API Producer. The target URI shall identify the resource ($\dots/{apfId}/service-apis/{serviceApiId}$). The message content shall carry an updated service API description. The API Producer shall determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP PUT response. On success “200 OK” shall be returned. The message content shall carry the updated service API description. On failure, the appropriate error code shall be returned, and the message response body may contain additional error information.

6.1.4.2.2 Referenced procedures.

6.1.4.2.2.1 Update service registration procedure

The Update registered service API operation illustrated in figure 6.1.4.2.1-1 is based on the Update service registration procedure defined in R1GAP [5].

6.1.4.3 Deregister service API

6.1.4.3.1 Operation definition

A Service Producer uses the Deregister service API operation as API Consumer to deregister a service with the API Producer

The operation is based on HTTP DELETE.

```

@startuml
autonumber
participant "API Consumer" as cons
participant "API Producer" as prod
cons ->> prod : DELETE .../{apfId}/service-apis/{serviceApiId}
prod -->> cons : 204 No Content
@enduml
  
```



Figure 6.1.4.3.1-1: Deregister service API operation.

The service operation is as follows:

1. To deregister a service, The API Consumer shall send an HTTP DELETE. request to the API Producer . The target URI shall identify the resource to be deleted (.../{apfId}/service-apis/{serviceApiId}. The API Producer shall process the message content received in the HTTP DELETE message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP DELETE response. On success “204 No Content“ shall be-returned. On failure, the appropriate error code shall be returned, and the message response body may contain additional error information.

6.1.4.3.2 Referenced procedures

6.1.4.3.2.1 Deregister service procedure

The Deregister service API operation illustrated in figure 6.1.4.3.1-1 is based on the Deregister service procedure defined in R1GAP [5].

6.1.4.4 Partially update registered service API

6.1.4.4.1 Operation definition

A Service Producer uses the Partially update registered service API operation as API Consumer to partially update a service API registration with the API Producer.

The operation is based on HTTP PATCH.

```
@startuml
autonumber
participant "API Consumer" as cons
participant "API Producer" as prod
cons ->> prod : PATCH.../{apfId}/service-apis/{serviceApiId} (ServiceAPIDescriptionPatch)
prod -->> cons : 200 OK (ServiceAPIDescription)
@enduml
```




Figure 6.1.4.4.1-1: Partial update registered service API operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP PATCH request to the API Producer. The target URI shall identify the resource (.../{apfId}/service-apis/{serviceApiId}. The message content shall carry a service API description patch structure. The API Producer shall determine if the request sent by the API Consumer is authorized or not. If so, the API Producer shall process the message content received in the HTTP PATCH message.
2. The API Producer shall return the HTTP PATCH response. On success “200 OK“ shall be returned. The message content shall carry the updated service API description. On failure, the appropriate error code shall be returned, and the message response body may contain additional error information.

6.1.4.4.2 Referenced procedures.

6.1.4.4.2.1 Update service registration procedure

The Update registered service API operation illustrated in figure 6.1.4.2.1-1 is based on the Update service registration procedure defined in R1GAP [5].

6.1.4.5 Query service APIs

6.1.4.5.1 Operation definition

The API Consumer uses the Query service APIs operation to retrieve the service API descriptions that are registered with the API Producer.

The operation is based on HTTP GET.

```
@startuml
autonumber
participant "API Consumer" as cons
participant "API Producer" as prod
cons ->> prod : GET .../{apfId}/service-apis
prod -->> cons : 200 OK array(ServiceAPIDescription)
@enduml
```



Figure 6.1.4.5.1-1: Query service API operation

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer. The target URI shall identify the resource (.../{apfId}/service-apis). The message content shall be empty. The API producer shall process the HTTP GET message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the "200 OK" on success and the message content shall carry a list requested service API description. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

6.1.4.5.2 Referenced procedures

6.1.4.5.2.1 Query register service procedure

The Query service APIs operation illustrated in figure 6.1.4.5.1-1 is based on the query registered service procedure defined in R1GAP [5].

6.1.5 Resources

6.1.5.1 Overview

This clause defines the resources for the service registration API based on 3GPP TS 29.222 [9].

6.1.5.2 Resource: "APF published APIs"

This resource is defined in 3GPP TS 29.222 [9], clause 8.2 with the following URI:

{apiRoot}/published-apis/<apiVersion>/{apfId}/service-apis

By consuming this API, an rApp takes the role of the APF (API publishing function).

In addition to the provisions in 3GPP TS 29.222 [9], clause 8.1, the following shall apply:

- The value of the {apfId} resource URI variable shall be set to the rAppId of the rApp that performs the service registration.

6.1.5.2.1 Resource Standard Methods

6.1.5.2.1.1 POST

This method shall support the URI query parameters, request data, response data structures and response codes specified in 3GPP TS 29.222 [9], clause 8.2.2.2.3.1.

6.1.5.2.1.2 GET

This method shall support the URI query parameters, request data structures, response data structures, and response codes specified in 3GPP TS 29.222 [9], clause 8.2.2.2.3.2.

6.1.5.2.2 Resource Custom Operations

None

6.1.5.3 Resource: "Individual APF published API"

This resource is defined in 3GPP TS 29.222 [9], clause 8.2.2.3 with the following URI:

{apiRoot}/published-apis/<apiVersion>/{apfId}/service-apis/{serviceApiId}

By consuming this API, an rApp takes the role of the APF (API publishing function).

In addition to the provisions in 3GPP TS 29.222 [9], clause 8.2, the following shall apply:

- The value of the {apfId} resource URI variable shall be set to the rAppId of the rApp that performed the service registration.

6.1.5.3.1 Resource Standard Methods

6.1.5.3.1.1 PUT

This method shall support the URI query parameters, request data structures, response data structures and response codes specified in 3GPP TS 29.222 [9], clause 8.2.2.3.3.2.

6.1.5.3.1.2 DELETE

This method shall support the URI query parameters, request data, response data structures and response codes specified in 3GPP TS 29.222 [9], clause 8.2.2.3.3.3.

6.1.5.3.1.3 PATCH

This method shall support the URI query parameters, request data structures, response data structures and response codes specified in 3GPP TS 29.222 [9], clause 8.2.2.3.3.4.

6.1.5.3.2 Resource Custom Operations

None.

6.1.6 Custom operations without associated resources.

None.

6.1.7 Notifications

None

6.1.8 Data model

6.1.8.1 General

The application data model is defined in 3GPP TS 29.222 [9], clause 8.2.4. In addition, the adaptations specified in clause B.3 apply to this API.

6.1.8.2 Structured data types

None.

6.1.8.3 Simple data types and enumerations

None.

6.1.8.4 Re-used data types

The re-used data types are defined in clause B.3

6.1.8.5 Service-specific registration information

None.

6.1.9 Error Handling

6.1.9.1 General

HTTP error handling is applicable for this API as specified in 3GPP TS 29.222 [9], clause 7.7 .

6.1.9.2 Protocol Errors

Protocol error handling shall be supported as specified in 3GPP TS 29.222 [9], clause 8.1.5.2 .

6.1.9.3 Application Errors

Application error handling shall be supported as specified in 3GPP TS 29.222 [9], clause 8.2.5.3.

6.2 Service discovery API

6.2.1 Introduction

This API allows the API Consumer to perform service discovery based on the service discovery procedures defined in R1GAP [5]. The API is based on the CAPIF_Discover_Service_API as specified in 3GPP TS 29.222 [9].

6.2.2 API version

For the service discovery API as specified in the present document, the MAJOR version field shall be 1, the MINOR version field shall be 2 and the PATCH version field shall be 0 (see 3GPP TS 29.501 [1] for a definition of the version fields). Consequently, the <apiVersion> URI path segment shall be set to “v1”.

6.2.3 Resource structure and methods

The request URIs used in HTTP requests from the API Consumer towards the API Producer shall have the resource URI structure as defined for the CAPIF_Discovery_Service_API (see 3GPP TS 29.222 [9], Figure 8.1.2.1-1 in clause 8.1.2)

Table 6.2.3-1 lists the individual resources defined for the API and the applicable HTTP methods as defined in 3GPP TS 29.222 [9], clause 8.1 of) and the associated service operations.

Table 6.2.3-1: Resources and methods overview of the service discovery API

Resource Name 3GPP TS 29.222 [9]	Resource URI 3GPP TS 29.222 [9]	HTTP method 3GPP TS 29.222 [9]	Service Operation
All published service APIs	.../allServiceAPIs	GET	Query service APIs

6.2.4 Service operations

6.2.4.1 Query service APIs

6.2.4.1.1 Operation definition

The API Consumer uses the Query service APIs operation to discover service APIs information.

The operation is based on HTTP GET as per figure 6.2.4.1.1-1. The HTTP GET response contains information about all services that the API Consumer is authorized to access and that match the filtering criteria.

```
@startuml
autonumber
participant "API Consumer" as cons
participant "API Producer" as prod

cons ->> prod : GET .../allServiceAPIs
prod -->> cons : 200 OK (DiscoveredAPIs)
@enduml
```




Figure 6.2.4.1.1-1: Query service APIs operation

This service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer. The target URI shall identify the resource (.../allServiceAPIs) and may also contain that includes the rApp identifier and optional filtering criteria. The API Producer shall process the service discovery details received in the HTTP GET message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP GET response. On success “200 OK“ shall be returned and the message content shall carry a list of service profiles that the API Consumer is authorized to access and that match the filtering criteria, if provided. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

6.2.4.1.2 Referenced procedures

6.2.4.1.2.1 Discovery services procedure

The Query service APIs operation illustrated in figure 6.2.4.1.1-1 is based on the Discover services procedure as defined in R1GAP [5].

6.2.5 Resources

6.2.5.1 Overview

This clause defines the resource for the Service discovery API based on 3GPP TS 29.222 [9].

6.2.5.2 Resource: "All published service APIs"

This resource is defined in 3GPP TS 29.222 [9], clause 8.1 with the following URI:

{apiRoot}/service-apis /<apiVersion>/allserviceapis

In addition to the provisions in 3GPP TS 29.222 [9], clause 8.1, the following shall apply:

- 1) In the GET method, the URI query parameters “api-name“ and “api-version“ are relevant in the context of the SME services and shall be supported by the API Producer to allow filtering the query by name and/or version of the service API. The API Consumer may provide these parameters. The following parameters are not applicable in the context of the SME services and therefore need not be supported: comm-type, protocol, aef-id, data-format, api-cat, preferred-aef-loc, supported-features, api-supported-features.
- 2) In the GET method, the URI query parameter “api-invoker-id“ shall carry the rAppId of the rApp that performs the service discovery.

6.2.5.2.1 Resource Standard Methods

6.2.5.2.1.1 GET

This method shall support the URI query parameters, response data structures and response codes specified in 3GPP TS 29.222 [9], clause 8.1.2.2.3.1 .

6.2.5.2.2 Resource Custom Operations

None.

6.2.6 Custom operations without associated resources

None.

6.2.7 Notifications

None.

6.2.8 Data model

6.2.8.1 General

The application data model is defined in 3GPP TS 29.222 [9], clause 8.1.4, apply to this API. In addition, the adaptations specified in clause B.3 apply to this API.

6.2.8.2 Structured data types

None.

6.2.8.3 Simple data types and enumerations

None.

6.2.8.4 Re-used data types

The re-used data types are defined in clause B.3.

6.2.8.5 Service-specific registration information

None.

6.2.9 Error Handling

6.2.9.1 General

HTTP error handling is applicable for this API as specified in 3GPP TS 29.222 [9], clause 7.7 .

6.2.9.2 Protocol Errors

Protocol error handling shall be supported as specified in 3GPP TS 29.222 [9], clause 8.1.5.2 .

6.2.9.3 Application Errors

Application error handling shall be supported as specified in 3GPP TS 29.222 [9], clause 8.2.5.3 .

6.3 Service events subscription API

6.3.1 Introduction

This API allows the API Consumer to subscribe to and unsubscribe from service event notifications as specified in R1GAP [5]. The API is based on the CAPIF_Events_API as specified in 3GPP TS 29.222 [9].

6.3.2 API version

For the service events subscription API as specified in the present document, the MAJOR version field shall be 1, the MINOR version field shall be 2 and the PATCH version field shall be 0 (see 3GPP TS 29.501 [1], clause 4.3.1.1, for a definition of the version fields). Consequently, the <apiVersion> URI part segment shall be set to “v1”.

6.3.3 Resource structure and methods

The request URIs used in HTTP requests from the API Consumer towards the API Producer shall have the resource URI structure as defined for the CAPIF_Events_API (see 3GPP TS 29.222 [9], Figure 8.3.2.1-1 in clause 8.3.1).

Table 6.3.3-1 lists the individual resources defined for the API and the applicable HTTP methods as defined in 3GPP TS 29.222 [9], clause 8.3.1, and the associated service operations.

Table 6.3.3-1: Resources and methods overview of the service subscription API

Resource Name 3GPP TS 29.222 [9]	Resource URI 3GPP TS 29.222 [9]	HTTP method 3GPP TS 29.222 [9]	Service Operation
CAPIF Events Subscriptions	/{subscriberId}/subscriptions	POST	Subscribe service events
Individual CAPIF Events Subscription	/{subscriberId}/subscriptions/{subscriptionId}	DELETE	Unsubscribe service events

6.3.4 Service operations

6.3.4.1 Subscribe service events.

6.3.4.1.1 Operation definition

The API Consumer uses the subscribe service events API operation to subscribe to service event notifications.

The operation is based on HTTP POST.

```
@startuml
autonumber
participant "API Consumer" as cons
participant "API Producer" as prod
cons ->> prod : POST ../{subscriberId}/subscriptions/ (EventSubscription)
prod -->> cons : 201 Created (subscriptionId)
@enduml
```



Figure 6.3.4.1.1-1: Subscribe service events APIs operation.

This service operation is as follows:

1. The API Consumer shall send an HTTP POST request to the API Producer. The target URI shall identify the resource (“.../{subscriberId}/subscriptions/”) under which the new subscription is requested to be created. The message content shall carry a EventSubscription structure. The API Producer shall process the request received in the HTTP POST message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return HTTP POST response. On success “201 Created” shall be returned. The “Location” HTTP header shall be present and shall carry the URI for the newly created resource i.e., subscription identifier. The message content shall carry a EventSubscription structure that represents the new resource. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

6.3.4.1.2 Referenced procedures.

6.3.4.1.2.1 Subscribe service availability.

The Subscribe service events operation illustrated in figure 6.3.4.1.1-1 is based on the Subscribe service availability procedure defined in R1GAP [5].

6.3.4.2 Unsubscribe service events.

6.3.4.2.1 Operation definition

The API Consumer uses the unsubscribe service events operation to unsubscribe from service event notifications.

The operation is based on HTTP DELETE.

```

@startuml
autonumber
participant "API Consumer" as cons
participant "API Producer" as prod
cons ->> prod : DELETE.../{subscriberId}/subscriptions/{subscriptionId}
prod -->> cons : 204 No Content
@enduml
  
```



Figure 6.3.4.2.1-1: Unsubscribe service events operation.

This service operation is as follows:

1. The API Consumer shall send an HTTP DELETE request to the API Producer. . The target URI shall identify the resource (“.../{subscriberId}/subscriptions/{subscriptionId}”). The message content shall be empty. The API Producer shall process the request received in the HTTP DELETE message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP DELETE response. On success “204 No Content” shall be returned. The message content shall be empty. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

6.3.4.2.2 Referenced procedures.

6.3.4.2.2.1 Unsubscribe service availability.

The Unsubscribe service events operation illustrated in figure 6.3.4.3.1-1 is based on the Unsubscribe service availability procedure defined in R1GAP [5].

6.3.4.3 Notification service API

6.3.4.3.1 Operation definition

The API Producer sends notifications to all subscribed API Consumers.

The operation is based on HTTP POST.

```

@startuml
autonumber
participant "API Consumer" as cons
participant "API Producer" as prod
prod ->> cons : POST.../Event notification {callback URI}
@enduml
  
```




Figure 6.3.4.3.1-1: Notification service API operation

This service operation is as follows:

1. The API Producer shall send an HTTP POST request to the API Consumer. The target URI (“.../Eventnotification“) shall contain the call back URI received in the subscription request to notify the generated events to all the subscribed API Consumers.

6.3.4.3.2 Referenced procedures.

6.3.4.3.2.1 Notify service availability changes.

The Notification service API operation illustrated in figure 6.3.4.3.1-1 is based on the Notify service availability changes procedure defined in R1GAP [5].

6.3.5 Resources

6.3.5.1 Overview

This clause defines the resource for the Service events subscription API based on 3GPP TS 29.222 [9].

6.3.5.2 Resource: "CAPIF Events Subscriptions"

This resource is defined in 3GPP TS 29.222 [9], clause 8.3, with the following URI:

{apiRoot}/capif-events/<apiVersion>/{subscriberId}/subscriptions

This resource shall support the resource URI variables defined in 3GPP TS 29.222 [9], table 8.3.2.2.2-1.

6.3.5.2.1 Resource Standard Methods

6.3.5.2.1.1 POST

This method shall support the URI query parameters, request data, response data structures and response codes specified in 3GPP TS 29.222 [9], clause 8.3.2.2.3.1.

6.3.5.2.2 Resource Custom Operations

None

6.3.5.3 Resource: "Individual CAPIF Events Subscription"

This resource is defined in 3GPP TS 29.222 [9], clause 8.3, with the following URI:

{apiRoot}/capif-events/<apiVersion>/{subscriberId}/subscriptions/{subscriptionId}

This resource shall support the resource URI variables defined in 3GPP TS 29.222 [9], table 8.3.2.3.2-1.

6.3.5.3.1 Resource Standard Methods

6.3.5.3.1.1 DELETE

This method shall support the URI query parameters, request data, response data structures and response codes specified in 3GPP TS 29.222 [9], clause 8.3.2.3.3.1.

6.3.5.3.1.2 PUT

This method shall support the URI query parameters, request data, response data structures and response codes specified in 3GPP TS 29.222 [9], clause 8.3.2.3.3.2.

6.3.5.3.1.2 PATCH

This method shall support the URI query parameters, request data, response data structures and response codes specified in 3GPP TS 29.222 [9], clause 8.3.2.3.3.3.

6.3.5.3.2 Resource Custom Operations

None.

6.3.6 Custom operations without associated resources.

None.

6.3.7 Notifications

6.3.7.1 General

The delivery of notification shall conform to 3GPP TS 29.222 [9], clause 8.3.3.1.

6.3.7.2 Event Notification

6.3.7.2.1 Description

Event Notifications is used by the API Producer to notify all the subscribed API Consumers. The API Consumers shall subscribe to Event Notifications via the Individual CAPIF Events Subscription resource.

6.3.7.2.2 Notification definition

This method shall support the request data structures, URI query parameters and the response data structures as specified in 3GPP TS 29.222 [9], clause 8.3.3.2.2.

6.3.8 Data Model

6.3.8.1 General

The application data model is defined in 3GPP 29.222 [9], clause 8.3.4. In addition, the adaptations specified in clause B.3 of the present document and the data types listed in 3GPP TS 29.222 [9], clause 7.2, also apply to this API.

6.3.8.2 Structured data types

None.

6.3.8.3 Simple data types and enumerations

None.

6.3.8.4 Re-used data types

The re-used data types are defined in clause B.3.

6.3.8.5 Service-specific registration information

None.

6.3.9 Error Handling

General error responses are defined in 3GPP TS 29.222 [9], clause 7.7.

6.4 Bootstrap API

6.4.1 Introduction

This API allows the API Consumer to discover the entry points into the Service management and exposure services and the related token endpoints as defined in R1GAP [5].

6.4.2 API version

For the Bootstrap API as specified in the present document, the MAJOR version field shall be 1, the MINOR version field shall be 0 and the PATCH version field shall be 0 (see 3GPP TS 29.501 [1] for a definition of the version fields). Consequently, the <apiVersion> URI path segment shall be set to “v1”.

6.4.3 Resource structure and methods

The request URIs used in HTTP requests from the API Consumer towards the API Producer shall have the resource URI structure as defined in clause 5.2. The <apiName> resource URI variable shall be “bootstrap”. The <apiSpecificResourceUriPart> for each resource shall be set as described in clause 6.4.5.

Figure 6.4.3-1 shows the overall resource URI structure defined for the bootstrap API.




Figure 6.4.3-1: Resource URI structure of the Bootstrap API

Table: 6.4.3-1 1 lists the individual resources defined for the API, the applicable HTTP methods, and the associated service operations.

Table 6.1.3-1: Resource and methods overview of the Bootstrap API

Resource name	Resource URI	HTTP method	Service Operation
Bootstrap info	.../bootstrap-info/	GET	Query bootstrap information

6.4.4 Service Operations

6.4.4.1 Query bootstrap information

6.4.4.1.1 Operation definition

The API Consumer uses this operation to retrieve bootstrap information .

The operation to query bootstrap information based on HTTP GET.

```
@startuml
autonumber
```

```
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: GET .../bootstrap-info
Producer -->> Consumer: 200 OK (BootstrapInformation)
@enduml
```




Figure 6.4.4.1.1-1: Query bootstrap information operation

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer. The target URI shall identify the resource (.../bootstrap-info). The message content shall be empty.
2. The API Producer shall return the HTTP response. On success, "200 OK" shall be returned. The message content shall carry the BootstrapInformation. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

6.4.4.1.2 Referenced procedures.

6.4.4.1.2.1 Discover bootstrap procedure

The Query bootstrap operation illustrated in figure 6.4.4.1.1-1. is based on the Discover bootstrap procedure defined for the Service management and exposure services in R1GAP [5].

6.4.5 Resources

6.4.5.1 Overview

The following clause defines the resources for the Bootstrap API.

6.4.5.2 Resource: "Bootstrap info"

6.4.5.2.1 Description

The resource represents the bootstrap information for service management and exposure services.

Only the methods defined in clause 6.4.5.2.3 shall be supported by this resource.

6.4.5.2.2 Resource Definition

Resource URI: {apiRoot}/bootstrap/<apiVersion>/bootstrap-info

The resource URI variables supported by the resource is defined in Table 6.4.5.2.2-1.

Table 6.4.5.2.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.2
apiVersion	See clause 6.4.2

6.4.5.2.3 Resource Standard Methods

6.4.5.2.3.1 GET

This method shall support the URI query parameters specified in table 6.4.5.2.3.1-1, the request data structure specified in table 6.4.5.2.3.12 and the response data structure and response code specified in 6.4.5.2.3.1-3.

Table 6.4.5.2.3.1-1: URI query parameters supported by the GET method on this resource.

Name	Data type	P	Cardinality	Description	Applicability
N/A					

Table 6.4.5.2.3.1-2: Data structures supported by the GET request body on this resource.

Data Type	P	Cardinality	Description
N/A			A GET request has no message content

Table 6.4.5.2.3.1-3: Data structures supported by the GET response body on this resource.

Data Type	P	Cardinality	Response codes	Description
BootstrapInformation	M	1	200 OK	The bootstrap information has been queried successfully by the rApp and the response contains a BootstrapInformation structure as a representation of the query resource.
ProblemDetails	O	0..1	4xx/5xx	The operation has failed, and the message content may contain Problem description details.

6.4.5.2.4 Resource Custom Operations

None.

6.4.6 Custom operation without associated resources.

None.

6.4.7 Notifications

None.

6.4.8 Data Model

6.4.8.1 Structured data types

6.4.8.1.1 Overview

The following clauses define the structured data types and their attributes to be used by the bootstrap API.

6.4.8.1.2 Data type: BootstrapInformation

The BootstrapInformation data type represents entry point information for the Service management and exposure services. It contains the attributes defined in table 6.4.8.1.2-1.

Table 6.4.8.1.2-1: Definition of type BootstrapInformation

Attribute Name	Data type	P	Cardinality	Description
apiEndpoints	array(ApiEndpointInformation)	M	1..N	Information about the API.

6.4.8.1.3 Data type: ApiEndpointInformation

The ApiEndpointInformation data type represents entry point information for a single API. It contains the attributes defined in table 6.4.8.1.3-1.

Table 6.4.8.1.3-1: Definition of type ApiEndpointInformation

Attribute Name	Data type	P	Cardinality	Description
apiName	string	M	1	Name of API , as defined in the URI structure as <apiName>. The following values shall be supported “service-apis” for discovery and “published-apis” for service registration.
tokenEndPoint	InterfaceDescription	C	0..1	InterfaceDescription as defined in clause B.3.5, Token endpoint shall be provided if the API requires authorization over OAuth2.0
apiEndPoint	InterfaceDescription	M	1	InterfaceDescription as defined in clause B.3.5, End point of the API

6.4.8.2 Simple data types and enumerations

None

6.4.8.3 Re-used data types

None

6.4.8.4 Service-specific registration information

None.

6.4.9 Error Handling

6.4.9.1 General

In addition to the general provisions in clause 5.4.3, the requirements in the following clauses are applicable for Bootstrap API.

6.4.9.2 Protocol Errors

No specific protocol errors are defined in the present document.

6.4.9.3 Application Errors

No additional application errors defined in the present document.

7 Data management and exposure services

7.1 Data registration API

7.1.1 Introduction

This API enables the API Consumer to register DME type production capabilities based on the data registration service procedure defined in R1GAP [5].

7.1.2 API version

For the data registration API as specified in the present document, the MAJOR version field shall be 2, the MINOR version field shall be 0 and the PATCH version field shall be 0 (see 3GPP TS 29.501 [1] for a definition of the version fields). Consequently, the <apiVersion> URI path segment shall be set to “v2”.

The API is under development and consequently the API version shall include the pre-release version “alpha.2”.

7.1.3 Resource structure and methods

The request URIs used in HTTP requests from the API Consumer towards the API Producer shall have the resource URI structure as defined in clause 5.2. The <apiName> resource URI variable shall be “dataregistration”. The <apiSpecificResourceUriPart> for each resource shall be set as described in clause 7.1.5.

Figure 7.1.3-1 shows the overall resource URI structure defined for the data registration API.




Figure 7.1.3-1: Resource URI structure of the Data registration API

Table: 7.1.3-1 lists the individual resources defined for the API, the applicable HTTP methods, and the associated service operations.

Table 7.1.3-1: Resource and methods overview of the Data registration API

Resource name	Resource URI	HTTP method	Service Operation
Registered DME type production capabilities	.../production- capabilities	POST	Register DME type
Individual registered DME type production capability	.../production-capabilities/{registrationId}	DELETE	Deregister DME type
		PUT	Update DME type
		GET	Query DME type
All subscribed data jobs	.../production-capabilities/{registrationId}/data-jobs	GET	Query data jobs

7.1.4 Service Operations


7.1.4.1 Register DME type

7.1.4.1.1 Operation definition

The API Consumer uses this operation to register DME type production capabilities.

The operation to register the capability to produce a DME type is based on HTTP POST.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: POST .../production-capabilities (DmeTypeRelatedCapabilities)
Producer -->> Consumer: 201 Created (DmeTypeRelatedCapabilities)
@enduml
```


Figure 7.1.4.1.1 -1: Register DME type operation

The service operation is as follows:

1. The API Consumer shall send an HTTP POST request to the API Producer. The target URI shall identify the resource (.../production-capabilities) under which the new registration is requested to be created. The message content shall carry a DmeTypeRelatedCapabilities structure.
2. The API Producer shall generate the registration identifier and construct the URI for the created resource. The API Producer shall return the HTTP POST response. On success, "201 Created" shall be returned. The "Location" header shall be present and shall carry the URI of the new registration resource. The message content shall carry a DmeTypeRelatedCapabilities structure that represents the new resource. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

7.1.4.1.2 Referenced procedures.

7.1.4.1.2.1 Register DME type procedure

The Register DME type operation illustrated in figure 7.1.4.1.1-1. is based on the Register DME type procedure defined for the Data registration service in R1GAP [5].

7.1.4.2 Deregister DME type.

7.1.4.2.1 Operation definition

The API Consumer uses this operation to deregister DME type production capabilities.

The operation to deregister the capability to produce a DME type is based on HTTP DELETE.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: DELETE .../production-capabilities/{registrationId}
Producer -->> Consumer: 204 No Content
@enduml
```




Figure 7.1.4.2.1-1: Deregister DME type operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP DELETE request to the API Producer. The target URI shall identify the resource to be deleted (.../production-capabilities/{registrationId}).
2. The API Producer shall return the HTTP DELETE response. On success, "204 No Content" shall be returned and the response message content shall be empty. On failure, the appropriate error code shall be returned, and the message response content may contain additional error information.

7.1.4.2.2 Referenced procedures.

7.1.4.2.2.1 Deregister DME type procedure.

The Deregister DME type operation illustrated in figure 7.1.4.2.1-1 is based on the Deregister DME type procedure defined for the Data registration service in R1GAP [5].

7.1.4.3 Update DME type

7.1.4.3.1 Operation definition

The API Consumer uses this operation to update the registration of production capabilities related to a DME type.

The operation to update the registration of production capability related to a DME type is based on HTTP PUT.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: PUT .../production-capabilities/{registrationId}
(DmeTypeRelatedCapabilities)
Producer -->> Consumer: 200 OK (DmeTypeRelatedCapabilities)
@enduml
```




Figure 7.1.4.3.1 -1: Update DME type operation

The service operation is as follows:

1. The API Consumer shall send an HTTP PUT request to the API Producer. The target URI shall identify the resource (.../production-capabilities/{registrationId}). The message content shall carry an updated DmeTypeRelatedCapabilities structure. The API producer shall process the HTTP PUT message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP response. On success, “200 OK“ shall be returned. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

7.1.4.3.2 Referenced procedures.

7.1.4.3.2.1 Update DME type procedure

The Update DME type operation illustrated in figure 7.1.4.4.1-1. is based on the Update DME type procedure defined for the Data registration service in R1GAP [5].

7.1.4.4 Query DME type

7.1.4.4.1 Operation definition

The API Consumer uses this operation to query the registration of production capability information on a specific DME type that it has previously registered.

The operation to query the registration of production capability is based on HTTP GET.

```

@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: GET .../production-capabilities/{registrationId}
Producer -->> Consumer: 200 OK (DmeTypeRelatedCapabilities)
@enduml
  
```




Figure 7.1.4.4.1 -1: Query DME type operation

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer. The target URI shall identify the resource (.../production-capabilities/{registrationId}). The message content shall be empty. The API producer shall process the HTTP GET message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP response. On success, “200 OK“ shall be returned. The message content shall carry the queried production capability information. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

7.1.4.4.2 Referenced procedures.

7.1.4.4.2.1 Query DME type procedure

The Query DME type operation illustrated in figure 7.1.4.4.1-1. is based on the Query DME type procedure defined for the Data registration service in R1GAP [5].

7.1.4 Service Operations

7.1.4.5 Query data jobs

7.1.4.5.1 Operation definition

The API Consumer uses this operation to query all the data jobs information associated with a specific DME type that it has previously registered.

The operation to Query data jobs is based on HTTP GET.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: GET .../production-capabilities/{registrationId}/data-jobs
Producer -->> Consumer: 200 OK (array(DataJobInfo))
@enduml
```




Figure 7.1.4.5.1-1: Query All data job operation

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer. The target URI shall identify the resource (.../production-capabilities/{registrationId}/data-jobs). The message content shall be empty. The API producer shall process the HTTP GET message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP response. On success, “200 OK“ shall be returned. The message content shall carry an array of DatajobInfo. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

7.1.4.5.2 Referenced procedures.

7.1.4.5.2.1 Query data subscription information procedure

The Query data jobs operation illustrated in figure 7.1.4.5.1-1. is based on the Query data subscription information procedure defined for the Data registration service in R1GAP [5].

7.1.5 Resources

7.1.5.1 Overview

The following clause defines the resources for the Data registration API.

7.1.5.2 Resource: "Registered DME type production capabilities"

7.1.5.2.1 Description

The resource represents the registered capabilities of an API Consumer to produce DME types.

Only the methods defined in clause 7.1.5.2.3 shall be supported by this resource.

7.1.5.2.2 Resource Definition

Resource URI: {**apiRoot**}/**data-registration**/**<apiVersion>**/**production-capabilities**

The resource URI variables supported by the resource are defined in Table 7.1.5.2.2-1.

Table 7.1.5.2.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.2
apiVersion	See clause 7.1.2

7.1.5.2.3 Resource Standard Methods

7.1.5.2.3.1 POST

This method shall support the request data structure specified in the table 7.1.5.2.3.1-1 and the response data structure and response code specified in the table 7.1.5.2.3.1-2, and the HTTP headers specified in table 7.1.5.2.3.1-3.

Table 7.1.5.2.3.1-1: Data structures supported by the POST request body on this resource.

Data Type	P	Cardinality	Description
DmeTypeRelatedCapabilities	M	1	Registered capabilities of a Data Producer related to a DME type

Table 7.1.5.2.3.1-2: Data structures supported by the POST response body on this resource.

Data Type	P	Cardinality	Response codes	Description
DmeTypeRelatedCapabilities	M	1	201 Created	The operation was successful, and the message content of the POST response contains a DmeTypeProdCapRegistration structure as a representation of the created resource.
ProblemDetails	O	0..1	4xx/5xx	The operation has failed, and the message content may contain Problem description details.

Table 7.1.5.2.3.1-3: Headers supported by the 201 Response Code on this resource.

Name	Data type	P	Cardinality	Description
Location	string	M	1	Contains the URI of the newly created "Individual registered DME type production capability" resource, as defined in clause 7.1.5.3, with the registrationId in the URI.

7.1.5.2.4 Resource Custom Operations

None

7.1.5.3 Resource: "Individual registered DME type production capability"

7.1.5.3.1 Description

The resource represents an individual registered DME type production capability.

Only the methods defined in clause 7.1.5.3.3 shall be supported by this resource.

7.1.5.3.2 Resource Definition

Resource URI: **{apiRoot}/data-registrations/<apiVersion>/production-capabilities/{registrationId}**

The resource URI variables supported by the resource are defined in Table 7.1.5.3.2-1.

Table 7.1.5.3.2-1: Resource URI variables for the resource.

Name	Definition
apiRoot	See clause 5.2
apiVersion	See clause 7.1.2
registrationId	The related DME type production capabilities registration identifier

7.1.5.3.3 Resource Standard Methods

7.1.5.3.3.1 DELETE

This method shall support the request data structure specified in table 7.1.5.3.3.1-1 and the response data structure and response code specified in 7.1.5.3.3.1-2.

Table 7.1.5.3.3.1-1: Data structures supported by the DELETE request body on this resource.

Data type	P	Cardinality	Description
N/A			A DELETE request has no message content

Table 7.1.5.3.3.1-2: Data structures supported by the DELETE response body on this resource.

Data type	P	Cardinality	Response codes	Description
N/A			204 No Content	The DME type production capability registration associated with the registrationId has been deleted successfully. The message content shall be empty.
ProblemDetails	O	0..1	4xx/5xx	The operation has failed, and the message content may contain Problem description details.

7.1.5.3.3.2 PUT

This method shall support the request data structure specified in the table 7.1.5.3.3.2-1 and the response data structure and response code specified in the table 7.1.5.3.3.2-2.

Table 7.1.5.3.3.2-1: Data structures supported by the PUT request body on this resource.

Data Type	P	Cardinality	Description
DmeTypeRelatedCapabilities	M	1	Updated DME type production capability information

Table 7.1.5.2.3.2-2: Data structures supported by the PUT response body on this resource.

Data Type	P	Cardinality	Response codes	Description
DmeTypeRelatedCapabilities	M	1	200 OK	The DME type production capability registration associated with the registrationId has been updated successfully and the response contain the DmeTypeProdCapRegistration as a representation of the updated resource.
ProblemDetails	O	0..1	4xx/5xx	The operation has failed, and the message content may contain Problem description details.

7.1.5.3.3.3 GET

This method shall support the request data structure specified in the table 7.1.5.3.3.3-1 and the response data structure and response code specified in the table 7.1.5.3.3.3-2.

Table 7.1.5.3.3.3-1: Data structures supported by the GET request body on this resource.

Data Type	P	Cardinality	Description
N/A			A GET request has no message content

Table 7.1.5.2.3.3-2: Data structures supported by the GET response body on this resource.

Data Type	P	Cardinality	Response codes	Description
DmeTypeRelatedCapabilities	M	1	200 OK	The DME type production capability registration associated with the registrationId has been queried successfully and the response contain the DmeTypeProdCapRegistration as a representation of the query resource.
ProblemDetails	O	0..1	4xx/5xx	The operation has failed, and the message content may contain Problem description details.

7.1.5.3.4 Resource Custom Operations

None.

7.1.5.4 Resource: "All subscribed data jobs"

7.1.5.4.1 Description

The resource represents all data job information associated with DME type registration identifier.

Only the methods defined in clause 7.1.5.4.3 shall be supported by this resource.

7.1.5.4.2 Resource Definition

Resource URI: **{apiRoot}/data-registrations/<apiVersion>/production-capabilities/{registrationId}/data-jobs**

The resource URI variables supported by the resource are defined in Table 7.1.5.4.2-1.

Table 7.1.5.4.2-1: Resource URI variables for the resource.

Name	Definition
apiRoot	See clause 5.2.
apiVersion	See clause 7.1.2.
registrationId	The related DME type production capabilities registration identifier.

7.1.5.4.3 Resource Standard Methods

7.1.5.4.3.1 GET

This method shall support the request data structure specified in the table 7.1.5.4.3.1-1 and the response data structure and response code specified in the table 7.1.5.4.3.1-2.

Table 7.1.5.4.3.1-1: Data structures supported by the GET request body on this resource.

Data Type	P	Cardinality	Description
N/A			A GET request has no message content.

Table 7.1.5.4.3.1-2: Data structures supported by the GET response body on this resource.

Data Type	P	Cardinality	Response codes	Description
array(DataJobInfo)	M	0..N	200 OK	Provides information for the data job as per clause 7.3.8.1.2
ProblemDetails	O	0..1	4xx/5xx	The operation has failed, and the message content may contain Problem description details.

7.1.5.4.4 Resource Custom Operations

None.

7.1.6 Custom operation without associated resources.

None.

7.1.7 Notifications

None.

7.1.8 Data Model

7.1.8.1 Structured data types

7.1.8.1.1 Overview

The following clauses define the structured data types and their attributes to be used by the service API.

7.1.8.1.2 Data type: DmeTypeRelatedCapabilities

The DmeTypeRelatedCapabilities data type represents capabilities of a data provider entity (such as Data Producer, SME functions) related to providing data instances of a DME type for collection or consumption. It contains the attributes defined in table 7.1.8.1.2-1.

Table 7.1.8.1.2-1: Definition of type DmeTypeRelatedCapabilities.

Attribute Name	Data type	P	Cardinality	Description
dmeTypeDefinition	DmeTypeDefinition	M	1	Information of the DME type.
dataAccessEndpoint	InterfaceDescription	O	0..1	Endpoint to which to send the data request or data subscription for data instances of this DME type. This attribute shall be provided in data registration requests and responses related to data registration. It may be provided in data discovery responses. If this information is not provided, the data access endpoint can be discovered by means outside the scope of the of the DME services.
dataDeliveryMode	array(DataDeliveryMode)	M	1..N	Supported modes for data delivery for this DME type, i.e. one time (data request) or continuous (data subscription) or both.
constraints	object	O	0..1	When this data structure is used for registration, this attribute represents producer constraints related to the DME type based on the dataProductionSchema. When this data structure is used for discovery, this attribute represents constraints applicable to the consumption of data instances of this DME type based on the dataProductionSchema

7.1.8.1.3 Data type: DmeTypeDefinition

The DmeTypeDefinition data type represents information about a DME type. It contains the attributes defined in table 7.1.8.1.3-1.

Table 7.1.8.1.3-1: Definition of type DmeTypeDefinition.

Attribute Name	Data type	P	Cardinality	Description
dmeTypeIid	DmeTypeIidStruct	M	1	The identifier of the DME type being registered.
metadata	Metadata	M	1	Metadata that can be used in discovering the DME type.
dataProductionSchema	object	O	0..1	Schema that defines the information necessary to formulate a data request or data subscription. If this attribute is not present, the schema is assumed to be known from the DME type definition that is referenced by dmeTypeIid (see note).
dataDeliverySchemas	array (DeliverySchema)	M	1.. N	List of delivery schemas supported by the producer for the DME type being registered (see note).
dataDeliveryMechanisms	array (DataDeliveryMechanism)	M	1.. N	see clause B.4.4.2
NOTE: The schemas for data production and data delivery are DME type specific and are not defined in the present version of the document.				

7.1.8.1.4 Data type: Metadata

The Metadata data type contains the attributes defined in table 7.1.8.1.4-1 and the set of metadata attributes may be extended by deployments.

Table 7.1.8.1.4-1: Definition of type Metadata.

Attribute Name	Data type	P	Cardinality	Description
dataCategory	array(string)	M	1.. N	Defines the category of the DME type e.g., PM counters.
rat	array(string)	O	0.. N	Defines the radio access technology e.g., 5G.

7.1.8.1.5 Data type: DeliverySchema

The DeliverySchema data type contains the attributes defined in table 7.1.8.1.5-1.

Table 7.1.8.1.5-1: Definition of type DeliverySchema.

Attribute Name	Data type	P	Cardinality	Description
type	SchemaTypes	M	1	Type of the schema.
deliverySchemaId	string	M	1	A Data Producer may support one or more delivery schemas and for each supported schema type a delivery schema identifier is assigned. A Data Consumer uses this attribute while creating a data job and request to deliver the data using specific schema type which is identified by this attribute.
schema	string	O	0..1	The schema serialized to string. If this attribute is not present, the schema is assumed to be known from the DME type definition that is referenced by the DME type identifier.

7.1.8.2 Simple data types and enumerations

7.1.8.2.1 Introduction

This clause defines simple data types and enumerations that can be referenced from data structures defined in the previous clauses.

7.1.8.2.2 Simple data types

No simple data types are defined in this version of the specification.

7.1.8.2.3 Enumeration

7.1.8.2.3.1 Enumeration: SchemaTypes

Table 7.1.8.3.3.1-1: Enumeration SchemaTypes.

Enumeration value	Description
JSON_SCHEMA	Following JSON Schema 2020-12 [14].
XML_SCHEMA	Following XML Schema [16], [17], [18] and [i.1].
PROTOBUF_SCHEMA	Following PROTOBUF Schema [27].
AVRO_SCHEMA	Following AVRO Schema [28].

7.1.8.3 Re-used data types

None.

7.1.8.4 Service-specific registration information

None.

7.1.9 Error Handling

7.1.9.1 General

In addition to the general provisions in clause 5.4.3, the requirements in the following clauses are applicable for the Data Registration API.

7.1.9.2 Protocol Errors

No specific protocol errors are defined in the present document.

7.1.9.3 Application Errors

No additional application errors defined in the present document.

7.2 Data discovery API

7.2.1 Introduction

This API enables the API Consumer to discover the available DME types based on the data discovery service procedures defined in R1GAP [5].

7.2.2 API version

For the data discovery API as specified in the present document, the MAJOR version field shall be 2, the MINOR version field shall be 0 and the PATCH version field shall be 0 (see 3GPP TS 29.501 [1] for a definition of the version fields). Consequently, the `<apiVersion>` URI path segment shall be set to “v2”.

7.2.3 Resource structure and methods

The request URIs used in HTTP requests from the API Consumer towards the API Producer shall have the resource URI structure as defined in clause 5.2. The `<apiName>` resource URI variable shall be “datadiscovery”. The `<apiSpecificResourceUriPart>` for each resource shall be set as described in clause 7.2.5.

Figure 7.2.3-1 shows the overall resource URI structure defined for the data discovery API.




Figure 7.2.3-1: Resource URI structure of the Data discovery API

Table 7.2.3-1 lists the individual resources defined for the API, the applicable HTTP methods, and the associated service operations.

Table 7.2.3-1: Resources and methods overview of the Data discovery API

Resource name	Resource URI	HTTP method	Service Operation
All DME types	.../dme-types	GET	Discover DME types
Individual DME types	.../dme-types/{dmeTypeId}	GET	Query capabilities related to a DME type

7.2.4 Service operations

7.2.4.1 Discover DME types.

7.2.4.1.1 Operation definition

The API Consumer uses this operation to discover the available DME types.

The operation to discover the DME types is based on HTTP GET.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: GET .../dme-types
Producer -->> Consumer: 200 OK (array(DmeTypeRelatedCapabilities))
@enduml
```




Figure 7.2.4.1.1 -1: Discover DME types operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer. The target URI shall identify the resource (.../dme-types) and may also contain query parameters to discover the available DME types.
2. The API Producer shall return the HTTP GET response. On success, "200 OK" shall be returned and the message content shall carry an array of Dme type related capabilities. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

7.2.4.1.2 Referenced procedures.

7.2.4.1.2.1 Discover DME types procedure.

The Discover DME types operation illustrated in figure 7.2.4.1.1-1 is based on the Discover DME types procedure defined for the Data discovery service in R1GAP [5].

7.2.4.2 Query DME type information

7.2.4.2.1 Operation definition

The API Consumer uses this operation to query for information about a specific DME type identified by a DME type identifier.

The operation to query for information about a specific DME type is based on HTTP GET.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: GET .../dme-types/{dmeTypeId}
Producer -->> Consumer: 200 OK (DmeTypeRelatedCapabilities)
@enduml
```




Figure 7.2.4.2.1-2: Query DME type information operation

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer. The target URI shall identify the resource (.../dme-types/{dmeTypeId}) and the message content shall be empty.
2. The API Producer shall return the HTTP GET response. On success, "200 OK" shall be returned and the message content shall carry capability information related to the DME type identified by {dmeTypeId}. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

7.2.4.2.2 Referenced procedures.

7.2.4.2.2.1 Query DME type information procedure

The Query DME type operation illustrated in figure 7.2.4.2.1-1 is based on the Query DME type information procedure defined for the Data discovery service in R1GAP [5].

7.2.5 Resources

7.2.5.1 Overview

The following clause defines the resources for the Data discovery API.

7.2.5.2 Resource: "All DME types"

7.2.5.2.1 Description

The resource represents the available DME types. Only the methods defined in clause 7.2.5.2.3 shall be supported by this resource.

7.2.5.2.2 Resource Definition

Resource URI: {apiRoot}/data-discovery/<apiVersion>/dme-types

The resource URI variables supported by the resource are defined in Table 7.2.5.2.2-1.

Table 7.2.5.2.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.2 .
apiVersion	See clause 7.2.2.

7.2.5.2.3 Resource Standard Methods

7.2.5.2.3.1 GET

This method shall support the URI query parameters specified in table 7.2.5.2.3.1-1, the request data structure specified in the table 7.2.5.2.3.1-2 and the response data structure and response code specified in the table 7.2.5.2.3.1-3.

Table 7.2.5.2.3.1-1: URI query parameters supported by the GET method on this resource.

Name	Data type	P	Cardinality	Description	Applicability
identity-namespace	string	O	0..1	Identity namespace, which shall match the “namespace” part of the “dmeTypeId” attribute. (See NOTE1)	
identity-name	string	O	0..1	Identity name, which shall match the “name” part of the “dmeTypeId” attribute. (See NOTE1).	
data-category	array(string)	O	0..N	Set of data category entries, all of which shall match entries of the “dataCategory” attribute. (See NOTE1 and NOTE 2).	
NOTE 1: If multiple query parameters are provided these shall be combined with AND when evaluating the query.					
NOTE 2: The encoding of query parameter for array of string shall follow the guideline defined in 3GPP TS 29.501 [1] clause 5.3.13.					

Table 7.2.5.2.3.1-2: Data structures supported by the GET request body on this resource.

Data Type	P	Cardinality	Description
N/A			There is no object in the message content of the GET request

Table 7.2.5.2.3.1-3: Data structures supported by the GET response body on this resource.

Data Type	P	Cardinality	Response codes	Description
array (DmeTypeRelatedCapabilities)	M	0.. N	200 OK	The operation was successful. The message content of the GET response carries an array of DmeTypeRelatedCapabilities structures.
ProblemDetails	O	0..1	4xx/5xx	The operation has failed, and the message content may contain Problem description details.

7.2.5.2.4 Resource Custom Operations

None.

7.2.5.3 Resource: "Individual DME type"

7.2.5.3.1 Description

The resource represents a DME type.

7.2.5.3.2 Resource Definition

Resource URI: {apiRoot}/data-discovery/<apiVersion>/dme-types/{dmeTypeId}

The resource URI variables supported by the resource are defined in Table 7.2.5.3.2-1.

Table 7.2.5.3.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.2
apiVersion	See clause 7.2.2
dmeTypeId	DME type identifier identifying a DME type

7.2.5.3.3 Resource Standard Methods

7.2.5.3.3.1 GET

This method shall support the URI query parameters specified in table 7.2.5.3.3.1-1, the request data structure specified in table 7.2.5.3.3.1-2 and the response data structure and response code specified in 7.2.5.3.3.1-3.

Table 7.2.5.2.3.1-1: URI query parameters supported by the GET method on this resource.

Name	Data type	P	Cardinality	Description	Applicability
N/A					

Table 7.2.5.3.3.1-2: Data structures supported by the GET request body on this resource.

Data type	P	Cardinality	Description
N/A			The message content of a GET request is empty.

Table 7.2.5.3.3.1-3: Data structures supported by the GET response body on this resource.

Data type	P	Cardinality	Response codes	Description
DmeTypeRelatedCapabilities	M	1	200 OK	The operation was successful. The message content a DmeTypeRelatedCapabilities structure.
ProblemDetails	O	0..1	4xx/5xx	The operation has failed, and the message content may contain Problem description details.

7.2.5.3.4 Resource Custom Operations

None.

7.2.6 Custom operation without associated resources.

None.

7.2.7 Notifications

None.

7.2.8 Data Model

7.2.8.1 Structured data types

7.2.8.1.1 Overview

The following clause defines the structured data types and their attributes to be used by the service API.

For this service API, no structured data types are defined in the present document.

7.2.8.2 Simple data types and enumerations

7.2.8.2.1 Introduction

The following clause defines simple data types and enumerations that can be referenced from data structures defined in the previous clauses.

7.2.8.2.2 Simple data types

For this service API, no simple data types are defined in the present document.

7.2.8.2.3 Enumerations

For this service API, no enumerations are defined in the present document.

7.2.8.3 Re-used data types

None.

7.2.8.4 Service-specific registration information

None.

7.2.9 Error Handling

7.2.9.1 General

In addition to the general provisions in clause 5.4.3, the requirements in the following clauses are applicable for the Data Discovery API.

7.2.9.2 Protocol Errors

No specific protocol errors are defined in the present document.

7.2.9.3 Application Errors

No additional application errors defined in the present document.

7.3 Data access API

7.3.1 Introduction

This API enables the API Consumer to request or subscribe data instances based on the Data request service and Data subscription service procedures defined in R1GAP [5]. The API definition applies to both scenarios when rApp is the Service Consumer and when DME is the Service Consumer, respectively.

7.3.2 API version

For the Data access API as specified in the present document, the MAJOR version field shall be 2, the MINOR version field shall be 0 and the PATCH version field shall be 0 (see 3GPP TS 29.501 [1] for a definition of the version fields). Consequently, the `<apiVersion>` URI path segment shall be set to “v2”.

The API is under development and consequently the API version shall include the pre-release version “alpha.3”.

7.3.3 Resource structure and methods

The request URIs used in HTTP requests from the API Consumer towards the API Producer shall have the resource URI structure as defined in clause 5.2. The `<apiName>` resource URI variable shall be “data-access”. The `<apiSpecificResourceUriPart>` for each resource shall be set as described in clause 7.3.5.

Figure 7.3.3-1 shows the overall resource URI structure defined for the Data access API.




Figure 7.3.3-1: Resource URI structure of the Data access API

Table 7.3.3-1 lists the individual resources defined for the API, the applicable HTTP methods, and the associated service operations.

Table 7.3.3-1: Resources and methods overview of the data access API

Resource name	Resource URI	HTTP method	Service Operation
All data jobs	.../data-jobs	POST	Create an individual data job
		GET	Query data job identifiers
Individual data job	.../data-jobs/{dataJobId}	DELETE	Cancel data job
		PUT	Update data job
		GET	Query data job
Individual data job status	.../data-jobs/{dataJobId}/status	GET	Query data Job status

7.3.4 Service Operations

7.3.4.1 Create data job

7.3.4.1.1 Operation definition

The API Consumer uses Create data job operation to create the job for data request or subscription. A data job can be either for data request or data subscription.

NOTE: An API Producer supporting the Data access API shall support at least one type of the services, data request (one time delivery mode) or data subscription (continuous delivery mode). The mean for communicating the service support capabilities with API Consumers is not specified in this version of the specification.

The operations are based on HTTP POST.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: POST .../data-jobs (DataJobInfo)
Producer -->> Consumer: 201 Created (DataJobInfo)
@enduml
```


Figure 7.3.4.1.1-1: Create data job operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP POST request to the API Producer. The target URI shall identify the resource (.../data-jobs) under which the new data job is to be created. The message content shall carry a DataJobInfo.
2. The API Producer shall return the HTTP POST response. On success, "201 Created" shall be returned. The Location header shall be present and shall carry the URI of the new data job resource with dataJobId assigned by the service producer. The message content shall carry a DataJobInfo representing the created data job. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

7.3.4.1.2 Referenced procedures

7.3.4.1.2.1 Request data procedure

The Create data job operation illustrated in figure 7.3.4.1.1-1 is based on the Request data procedure defined for the Data request service in R1GAP [5].

7.3.4.1.2.2 Subscribe data procedure

The Create data job operation illustrated in figure 7.3.4.1.1-1 is based on the Subscribe data procedure defined for the Data subscription service in R1GAP [5].

7.3.4.2 Cancel data job

7.3.4.2.1 Operation definition

The API Consumer uses Cancel data job operation to cancel a data job.

The operations are based on HTTP DELETE.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: DELETE ../data-jobs/{dataJobId}
Producer -->> Consumer: 204 No Content
@enduml
```




Figure 7.3.4.2.1-3: Cancel data job operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP DELETE request to API Producer. The target URI shall identify the resource (.../data-jobs/{dataJobId}).
2. The API Producer shall return the HTTP DELETE response. On success, "204 No Content" shall be returned. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

7.3.4.2.2 Referenced procedures

7.3.4.2.2.1 Cancel data request procedure

The Cancel data job operation illustrated in figure 7.3.4.2.1-1 is based on the cancel data request procedure defined for the Data request service in R1GAP [5].

7.3.4.2.2.2 Unsubscribe data procedure

The Cancel data job operation illustrated in figure 7.3.4.2.1-1 is based on the Unsubscribe data procedure defined for the Data subscription service in R1GAP [5].

7.3.4.3 Notify data availability

7.3.4.3.1 Operation definition

The API Producer uses this operation to notify data availability related to a data subscription.

The operation is based on HTTP POST.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Producer ->> Consumer: POST {dataAvailabilityNotificationUri}
(Notification(DataAvailabilityNotification))
Consumer -->> Producer: 204 No Content
@enduml
```




Figure 7.3.4.3.1-4: Notify data availability operation.

The service operation is as follows:

1. The API Producer shall send an HTTP POST request to API Consumer. The target URI (dataAvailabilityNotificationUri) identifies the address where to send the notifications. The message content shall carry a Notification message that includes a DataAvailabilityNotification payload.
2. The API Consumer shall return the HTTP POST response. On success, "204 No Content" shall be returned. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

7.3.4.3.2 Referenced procedures

7.3.4.3.2.1 Notify data availability procedure

The Notify data availability operation illustrated in figure 7.3.4.3.1-1 is based on the Notify data availability procedure defined for the Data subscription service in R1GAP [5].

7.3.4.4 Update data job

7.3.4.4.1 Operation definition

The API Consumer uses this operation to update the created job for data subscription.

The operation to update a data job is based on HTTP PUT.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: PUT ...../data-jobs/{dataJobId} (DataJobInfo)
Producer -->> Consumer: 200 OK (DataJobInfo)
@enduml
```




Figure 7.3.4.4.1 -1: Update data job operation

The service operation is as follows:

1. The API Consumer shall send an HTTP PUT request to the API Producer. The target URI shall identify the resource (.../data-jobs/{dataJobId}). The message content shall carry an update DataJobInfo structure. The API Producer shall process the HTTP PUT message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP response. On success, "200 OK" shall be returned. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.
3. The API Producer shall reject the update data job with "405 Method Not Allowed" if the dataJobId in the target URI is associated with delivery mode "ONE_TIME".

NOTE: Updating the Data Job can introduce discontinuities in the produced data that are specific to the DME type and/or Data Producer.

7.3.4.4.2 Referenced procedures

7.3.4.3.2.1 Update data job procedure

The Update data job operation illustrated in figure 7.3.4.4.1-1. is based on the Update data subscription procedure defined for the Data subscription service in R1GAP [5].

7.3.4.5 Query data job

7.3.4.5.1 Operation definition

The API Consumer uses this operation to query the created job.

The operation to query the data job is based on HTTP GET.

```

@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: GET ...../data-jobs/{dataJobId}
Producer -->> Consumer: 200 OK (DataJobInfo)
@enduml
  
```




Figure 7.3.4.5.1 -1: Query data job operation

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer. The target URI shall identify the resource (...../data-jobs/{dataJobId}). The message content shall be empty. The API producer shall process the HTTP GET message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP response. On success, “200 OK“ shall be returned. The message content shall carry the queried data job information. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

7.3.4.5.2 Referenced procedures.

7.3.4.5.2.1 Query data job procedure

The Query data job operation illustrated in figure 7.3.4.5.1-1. is based on the Query data subscription procedure defined for the Data subscription service in R1GAP [5].

7.3.4.6 Query data job status

7.3.4.6.1 Operation definition

The API Consumer uses this operation to query the data job status.

The operation to query the data job is based on HTTP GET.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: GET ...../data-jobs/{dataJobId}/status
Producer -->> Consumer: 200 OK (DataJobStatusInfo)
@enduml
```



Figure 7.3.4.6.1 -1: Query data job status operation

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer. The target URI shall identify the resource (...../data-jobs/{dataJobId}/status). The message content shall be empty. The API producer shall process the HTTP GET message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP response. On success, “200 OK“ shall be returned. The message content shall carry the queried data job status information. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

7.3.4.6.2 Referenced procedures.

7.3.4.6.2.1 Query data job procedure

The Query data job status operation illustrated in figure 7.3.4.6.1-1. is based on the Query data subscription status procedure defined for the Data subscription service in R1GAP [5].

7.3.4.7 Query data job identifiers

7.3.4.7.1 Operation definition

The API Consumer uses Query data job identifiers operation to get the data job identifiers for all the jobs that are created for the specific API consumer. A data job can be either for data request or data subscription.

The operations are based on HTTP GET.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: GET .../data-jobs
Producer -->> Consumer: 200 OK (array(dataJobId))
@enduml
```




Figure 7.3.4.7.1 -1: Query data job operation

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer. The target URI shall identify the resource (...../data-jobs/). The message content shall be empty. The API producer shall process the HTTP GET message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP response. On success, "200 OK" shall be returned. The message content shall carry an array of data job identifiers (dataJobId) created by the API Consumer. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

7.3.4.7.2 Referenced procedures.

7.3.4.7.2.1 Query data job identifiers procedure

The Query data job identifiers operation illustrated in figure 7.3.4.7.1-1. is based on the Query data subscription procedure defined for the Data subscription service in R1GAP [5].

7.3.5 Resources

7.3.5.1 Overview

This clause defines the resources for the Data access API.

7.3.5.2 Resource: "All data jobs"

7.3.5.2.1 Description

The resource All data jobs represents all data jobs created by a particular consumer.

Only the methods defined in clause 7.3.5.2.3 shall be supported by these resources.

7.3.5.2.2 Resource Definition

Resource URI: **{apiRoot}/data-access/<apiVersion>/data-jobs**

The resource URI variables supported by the resource are defined in Table 7.3.5.2.2-1.

Table 7.3.5.2.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.2.
apiVersion	See clause 7.3.2.

7.3.5.2.3 Resource Standard Methods

7.3.5.2.3.1 POST

This method shall support the request data structure specified in the table 7.3.5.2.3.1-1, and the response data structure and response code specified in the table 7.3.5.2.3.1-2.

Table 7.3.5.2.3.1-1: Data structures supported by the POST request body on this resource.

Data Type	P	Cardinality	Description
DataJobInfo	M	1	Provides information for the data job to be created.

Table 7.3.5.2.3.1-2: Data structures supported by the POST response body on this resource.

Data Type	P	Cardinality	Response codes	Description
DataJobInfo	M	1	201 Created	The operation was successful. The message content of the POST response contains a DataJobInfo representing the created resource.
ProblemDetails	O	0..1	4xx/5xx	The operation was unsuccessful. Detailed problem description may be carried in the response message content.

Table 7.3.5.2.3.1-3: Headers supported by the 201-response code this resource.

Name	Data type	P	Cardinality	Description
Location	String	M	1	Contains the URI of the newly created resource as defined in clause 7.3.5.2.2.

7.3.5.2.3.2 GET

This method shall support the request data structure specified in table 7.3.5.2.3.2 -1 and the response data structure and response code specified in 7.3.5.2.3.2 -2.

Table 7.3.5.2.3.2-1: Data structure supported by the GET request body on this resource.

Data type	P	Cardinality	Description
N/A			There is no object in the message content of a GET request.

Table 7.3.5.2.3.2-2: Data structures supported by the HTTP GET response body on this resource

Data type	P	Cardinality	Response codes	Description
array(dataJobId)	M	0..N	200 OK	All data job identifiers.
ProblemDetails	O	0..1	4xx/5xx	Detailed problem description.

7.3.5.2.4 Resource Custom Operations

None.

7.3.5.3 Resource: "Individual data job"

7.3.5.3.1 Description

The resource Individual data job represents an individual data job for a data request or data subscription.

Only the methods defined in clause 7.3.5.3.3 shall be supported by these resources.

7.3.5.3.2 Resource Definition

Resource URI: {apiRoot}/data-access/<apiVersion>/data-jobs/{dataJobId}

The resource URI variables supported by the resource are defined in Table 7.3.5.3.2-1.

Table 7.3.5.3.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.2.
apiVersion	See clause 7.3.2.
dataJobId	The data job identifier assigned by the Service Producer.

7.3.5.3.3 Resource Standard Methods

7.3.5.3.3.1 DELETE

This method shall support the request data structure specified in table 7.3.5.3.3.1-1 and the response data structure and response code specified in 7.3.5.3.3.1-2.

Table 7.3.5.3.3.1-1: Data structures supported by the DELETE request body on this resource.

Data type	P	Cardinality	Description
N/A			There is no object in the message content of a DELETE request.

Table 7.3.5.3.3.1-2: Data structures supported by the DELETE response body on this resource.

Data type	P	Cardinality	Response codes	Description
N/A			204 No content	The operation was successful. The data request has been cancelled.
ProblemDetails	O	0..1	4xx/5xx	The operation was unsuccessful. Detailed problem description may be carried in the response message content.

7.3.5.3.3.2 PUT

This method shall support the request data structure specified in table 7.3.5.3.3.2-1 and the response data structure and response code specified in 7.3.5.3.3.2-2.

Table 7.3.5.3.3.2-1: Data structure supported by the PUT request body on this resource.

Data type	P	Cardinality	Description
DataJobInfo	M	1	Provides update data job information.

Table 7.3.5.3.3.2-2: Data structure supported by the PUT response body on this resource.

Data type	P	Cardinality	Response code	Description
DataJobInfo	M	1	200 OK	The operation was successful. Data job information updated successfully.
ProblemDetails	O	0..1	4xx/5xx	The operation was unsuccessful. Detailed problem description may be carried in the response message content.

7.3.5.3.3.3 GET

This method shall support the request data structure specified in table 7.3.5.3.3.3-1 and the response data structure and response code specified in 7.3.5.3.3.3-2.

Table 7.3.5.3.3.3-1: Data structure supported by the GET request body on this resource.

Data type	P	Cardinality	Description
N/A			There is no object in the message content of a GET request.

Table 7.3.5.3.3.3-2: Data structure supported by the GET response body on this resource.

Data type	P	Cardinality	Response code	Description
DataJobInfo	M	1	200 OK	The operation was successful.
ProblemDetails	O	0..1	4xx/5xx	The operation was unsuccessful. Detailed problem description may be carried in the response message content.

7.3.5.3.4 Resource Custom Operations

None.

7.3.5.4 Resource: "Individual data job status"

7.3.5.4.1 Description

The resource Individual data job status represents an individual data job status for a data request or data subscription.

Only the methods defined in clause 7.3.5.4.3 shall be supported by these resources.

7.3.5.4.2 Resource Definition

Resource URI: **{apiRoot}/data-access/<apiVersion>/data-jobs/{dataJobId}/status**

The resource URI variables supported by the resource are defined in Table 7.3.5.4.2-1.

Table 7.3.5.4.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.2.
apiVersion	See clause 7.3.2.
dataJobId	The data job identifier assigned by the Service Producer.

7.3.5.4.3 Resource Standard Methods

7.3.5.4.3.1 GET

This method shall support the request data structure specified in table 7.3.5.4.3.3-1 and the response data structure and response code specified in 7.3.5.4.3.3-2.

Table 7.3.5.4.3.3-1: Data structure supported by the GET request body on this resource.

Data type	P	Cardinality	Description
N/A			There is no object in the message content of a GET request.

Table 7.3.5.4.3.3-2: Data structure supported by the GET response body on this resource.

Data type	P	Cardinality	Response code	Description
DataJobSatatusInfo	M	1	200 OK	The operation was successful.
ProblemDetails	O	0..1	4xx/5xx	The operation was unsuccessful. Detailed problem description may be carried in the response message content.

7.3.5.4.4 Resource Custom Operations

None.

7.3.6 Custom operation without associated resources.

None.

7.3.7 Notifications

7.3.7.0 General

Table 7.3.7.0-1: Notifications overview

Notification	Callback URI	HTTP method or custom operation	Description (service operation)
Data Availability Notification	{dataAvailabilityNotificationUri}	POST	Notify data availability

7.3.7.1 Notify data availability.

7.3.7.1.1 Description

The notification informs the receiver about the availability of data for a data subscription and provides details about how to access them.

7.3.7.1.2 Target URI

This callback URI is provided in the attribute “dataAvailabilityNotificationUri” when creating a data job for data subscription.

7.3.7.1.3 Standard Methods

7.3.7.1.3.1 POST

This method shall support the request data structures specified in table 7.3.7.1.3.1-1 and the response data structure and response codes specified in table 7.3.7.1.3.1-2.

The use of the method shall conform to the structured content mode of CloudEvents as specified in HTTP-CloudEvents [31], i.e. the “Content-Type” HTTP request header shall be set to “application/cloudevents+json”.

Table 7.3.7.1.3.1-1: Data structures supported by the HTTP POST request body on this resource.

Data type	P	Cardinality	Description
Notification	M	1	To notify data availability, the notification structure defined in clause B.2.4.5 shall be used, with the “type” attribute set to “org.o-ran.DME.DATA_AVAILABILITY” and the “data” attribute containing a “DataAvailabilityNotification” structure defined in clause 7.3.8.1.5.

Table 7.3.7.1.3.1-2: Data structures supported by the HTTP POST response body on this resource.

Data type	P	Cardinality	Response codes	Description
N/A			204 No content	Confirmation of received notification
ProblemDetails	O	0..1	4xx/5xx	The operation was unsuccessful. Detailed problem description may be carried in the response message content.

7.3.8 Data Model

7.3.8.1 Structured data types

7.3.8.1.1 Overview

The following clauses define the data type and attributes to be used in the resource representation.

7.3.8.1.2 Data type: DataJobInfo

The DataJobInfo contains the attributes defined in table 7.3.8.1.2-1.

Table 7.3.8.1.2-1: Definition of type DataJobInfo

Attribute Name	Data type	P	Cardinality	Description
dataDeliveryMode	DataDeliveryMode	M	1	See clause 7.3.8.2.3.1.
dmeTypeld	DmeTypeld	M	1	See clause B.4.2.
productionJobDefinition	object	M	1	Job description based on the DME type specific dataProductionSchema.
dataDeliveryMethod	DataDeliveryMethod	M	1	See clause B.4.3.1.
dataDeliverySchemaId	string	M	1	A delivery schema identifier provided by a Data Producer during the data registration procedure.
pullDeliveryDetailsHttp	PullDeliveryDetailsHttp	C	0..1	See clause 7.3.8.1.3 (See NOTE 1).
dataAvailabilityNotificationUri	Uri	C	0..1	Callback URI for data availability notifications (See NOTE 2).
pushDeliveryDetailsHttp	PushDeliveryDetailsHttp	C	0..1	See clause 7.3.8.1.4 (See NOTE 3).
streamingConfigurationKafka	StreamingConfigurationKafka	C	0..1	See clause 7.3.8.1.6 (See NOTE 4).
dataJobInfoStatus	ProcessMonitor	C	0..1	ProcessMonitor datatype is specified in 3GPPTS 28.622 [21] clause 4.3.43. (See NOTE 5)
NOTE 1: If dataDeliveryMethod is PULL_HTTP and dataDeliveryMode is ONE_TIME, the pullDeliveryDetailsHttp attribute shall be present in the Create data job response.				
NOTE 2: If dataDeliveryMethod is PULL_HTTP, and dataDeliveryMode is CONTINUOUS, the dataAvailabilityNotificationUri attribute shall be present in the Create data job request and Create data job response.				
NOTE 3: If dataDeliveryMethod is PUSH_HTTP, the pushDeliveryDetailsHttp attribute shall be present in the Create data job request and Create data job response.				
NOTE 4: If dataDeliveryMethod is STREAMING_KAFKA, the streamingConfigurationKafka attribute shall be present in the Create data job request sent by the DME as API Consumer and in the Create data job response sent by the DME as API Producer. If the streamingConfigurationKafka attribute is present in the Create data job request, it shall be present in the corresponding Create data job response.				
NOTE 5: When API Consumer requesting the datajob, the dataJobInfoStatus shall not present in the request. When API Producer creating a data job the response shall include the DataJobInfo with dataJobInfoStatus.				

7.3.8.1.3 Data type: PullDeliveryDetailsHttp

The PullDeliveryDetailsHttp data type signals how to pull data using the HTTP protocol. It contains the attributes defined in table 7.3.8.1.3-1.

Table 7.3.8.1.3-1: Definition of type PullDeliveryDetailsHttp

Attribute Name	Data type	P	Cardinality	Description
dataPullUri	Uri	M	1	URI which data can be pulled from.

7.3.8.1.4 Data type: PushDeliveryDetailsHttp

The PushDeliveryDetailsHttp data type signals how to push data using the HTTP protocol. It contains the attributes defined in table 7.3.8.1.4-1.

Table 7.3.8.1.4-1: Definition of type PushDeliveryDetailsHttp

Attribute Name	Data type	P	Cardinality	Description
dataPushUri	Uri	M	1	URI to which data can be pushed.

7.3.8.1.5 Data type: DataAvailabilityNotification

The DataAvailabilityNotification contains the attributes defined in table 7.3.8.1.5-1.

Table 7.3.8.1.5-1: Definition of type DataAvailabilityNotification

Attribute Name	Data type	P	Cardinality	Description
dataJobId	string	M	1	Data job identifier.
pullDeliveryDetailsHttp	PullDeliveryDetailsHttp	C	0..1	See clause 7.3.8.2.3.2. If the dataDeliveryMechanism attribute of the data job identified by the dataJobId attribute is PULL_HTTP, this attribute shall be included. Otherwise, it shall be absent.

7.3.8.1.6 Data type: StreamingConfigurationKafka

The StreamingConfigurationKafka data type signals a data streaming configuration for the Kafka protocol. It contains the attributes defined in table 7.3.8.1.6-1.

Table 7.3.8.1.6-1: Definition of type StreamingConfigurationKafka

Attribute Name	Data type	P	Cardinality	Description
topicName	string	M	1	Name of the Kafka topic.
kafkaBootstrapServers	array (ServerAddressWithPort)	M	1.. N	See clause 7.3.8.1.7.

7.3.8.1.7 Data type: ServerAddressWithPort

The ServerAddressWithPort contains the attributes defined in table 7.3.8.1.7-1.

Table 7.3.8.1.7-1: Definition of type ServerAddressWithPort

Attribute Name	Data type	P	Cardinality	Description
hostname	string	M	1	hostname shall follow DNS naming convention as defined in IETF RFC 1035.
portAddress	integer	M	1	Port address, e.g., 9092.

7.3.8.2 Simple data types and enumerations

7.3.8.2.1 Introduction

This clause defines simple data types and enumerations that can be referenced from data structures defined in the previous clauses.

7.3.8.2.2 Simple data types

None.

7.3.8.2.3 Enumerations

7.3.8.2.3.1 Enumeration: DataDeliveryMode

This indicates whether the data instance is created in a one-time data delivery (data request) or continuously (data subscription).

Table 7.3.8.2.3.1-1: Enumeration type of DataDeliveryMode

Enumerations Value	Description
ONE_TIME	indicate the data job to be created is for on-time data delivery, i.e., for data request.
CONTINUOUS	indicate the data job to be created is for continuous data delivery, i.e., for data subscription.

7.3.8.2.3.2 Void

7.3.8.3 Re-used data types

None.

7.3.8.4 Service-specific registration information

The following structure defines the content of the “serviceCapabilities” attribute in the “ServiceProperties” data type (see clause B.3.4.2) for registration and discovery of this service.

Table 7.3.8.4-1: Definition of the service-specific registration information

Attribute Name	Data type	P	Cardinality	Description
supportedDataDeliveryModes	array(DataDeliveryMode)	M	1..N	Indicates whether one-time or continuous data delivery, or both, are supported by the service.

7.3.9 Error Handling

7.3.9.1 General

For the Data access API, HTTP error responses shall be supported as specified in 3GPP TS 29.501 [1]. Protocol errors and application errors specified in 3GPP TS 29.500 [2], table 5.2.7.2-1, shall be supported for an HTTP method if the corresponding HTTP status codes are specified as mandatory for that HTTP method in 3GPP TS 29.500 [2], table 5.2.7.1-1.

In addition, the requirements in the following clauses are applicable for the Data access API.

7.3.9.2 Protocol Errors

No specific protocol errors are defined in the present document.

7.3.9.3 Application Errors

No additional application errors defined in the present document.

7.4 HTTP based Push data API

7.4.1 Introduction

This API enables the API Producer to push data to the API Consumer based on the Push data service procedures defined in R1GAP [5]. The API definition applies to both scenarios when rApp is the Service Consumer and when DME is the Service Consumer, respectively.

7.4.2 API version

For the Push data API as specified in the present document, the MAJOR version field shall be 1, the MINOR version field shall be 0 and the PATCH version field shall be 0 (see 3GPP TS 29.501 [1] for a definition of the version fields).

7.4.3 Resource structure and methods

The resource URI is a callback URI provided when creating a data job or data offer.

7.4.4 Service Operations

7.4.4.1 Push data

7.4.4.1.1 Operation definition

The API Producer uses Push data operation to push data payload to the API Consumer.

The operation is based on HTTP POST.

```
@startuml
autonumber
Participant "API Producer" as Producer
Participant "API Consumer" as Consumer
Producer ->> Consumer: POST {dataPushUri}(data payload)
Consumer -->> Producer: 204 No Content
@enduml
```




Figure 7.4.4.1.1-1: Push data operation

The service operation is as follows:

1. The API Producer shall send an HTTP POST request to the API Consumer. The target URI (dataPushUri) identifies the destination for pushing data to. The message content shall carry the data payload. The Content-Type header shall be present and set to the exact media type of the data payload.
2. The API Consumer shall return the HTTP POST response. On success, "204 No Content" shall be returned. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

7.4.4.1.2 Referenced procedures.

7.4.4.1.2.1 Push data procedure

The Push data operation illustrated in figure 7.4.4.1.1-1 is based on the Push data procedure defined for the Push data service in R1GAP [5].

7.4.5 Resources

7.4.5.1 Overview

This clause defines the resources for the Push data API.

7.4.5.2 Resource: "Push delivery URI"

7.4.5.2.1 Description

The resource represents the destination for pushing data to.

7.4.5.2.2 Resource Definition

The resource URI is a callback URI provided in the "PushDeliveryDetailsHttp" data structure when creating a data job for data subscription or a data offer.

7.4.5.2.3 Resource Standard Methods

7.4.5.2.3.1 POST

The method shall support carrying the data payload in the request body. The format of the data payload and Content-Type header are determined by the data message schema.

The method shall support the response data structures and response codes specified in table 7.4.5.2.3.1-1.

Table 7.4.5.2.3.1-1: Data structures supported by the HTTP POST response body on this resource.

Data type	P	Cardinality	Response codes	Description
N/A			204 No content	Confirmation of received data delivery.
ProblemDetails	O	0..1	4xx/5xx	The operation was unsuccessful. Detailed problem description may be carried in the response message content.

7.4.5.2.4 Resource Custom Operations

None.

7.4.6 Custom operation without associated resources.

None.

7.4.7 Notifications

None.

7.4.8 Data Model

7.4.8.1 Structured data types

None.

7.4.8.2 Simple data types and enumerations

None.

7.4.8.3 Re-used data types

None.

7.4.8.4 Service-specific registration information

None.

7.4.9 Error Handling

7.4.9.1 General

For the Push data API, HTTP error responses shall be supported as specified in 3GPP TS 29.501 [1]. Protocol errors and application errors specified in 3GPP TS 29.500 [2], table 5.2.7.2-1, shall be supported for an HTTP method if the corresponding HTTP status codes are specified as mandatory for that HTTP method in 3GPP TS 29.500 [2], table 5.2.7.1-1.

In addition, the requirements in the following clauses are applicable for the Push data API.

7.4.9.2 Protocol Errors

No specific protocol errors are defined in the present document.

7.4.9.3 Application Errors

No additional application errors defined in the present document.

7.5 HTTP based Pull data API

7.5.1 Introduction

This API enables the API Consumer to pull data from the API Producer based on the Pull data service procedures defined in R1GAP [5]. The API definition applies to both scenarios when rApp is the Service Consumer and when DME is the Service Consumer, respectively.

7.5.2 API version

For the Pull data API as specified in the present document, the MAJOR version field shall be 1, the MINOR version field shall be 0 and the PATCH version field shall be 0 (see 3GPP TS 29.501 [1] for a definition of the version fields).

7.5.3 Resource structure and methods

The resource URI is a target URI provided when creating a data job for data request or a data offer, or when notifying the data availability for data subscription.

7.5.4 Service Operations

7.5.4.1 Pull data.

7.5.4.1.1 Operation definition

The API Consumer uses Pull data operation to pull data payload from the API Producer.

The operation is based on HTTP GET.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: GET {dataPullUri}
alt data ready
Producer -->> Consumer: 200 OK (data payload)
else data not ready
Producer -->> Consumer: 202 Accepted
end
@enduml
```




Figure 7.5.4.1.1-1: Pull data operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer. The target URI (dataPullUri) identifies the destination for pulling data from.
2. The API Producer shall return the HTTP GET response. On success, “200 OK“ shall be returned, the message content shall carry the data payload. The Content-Type header shall be present and set to the exact media type of the data payload.
3. If the data payload is not ready yet, “202 Accepted“ shall be returned, with the Retry-After header optionally provided to indicate how long the API Consumer should wait before making a follow-up request. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

7.5.4.1.2 Referenced procedures.

7.5.4.1.2.1 Pull data procedure

The Pull data operation illustrated in figure 7.5.4.1.1-1 is based on the Retrieve data procedure defined for the Pull data service in R1GAP [5].

7.5.5 Resources

7.5.5.1 Overview

This clause defines the resources for the Pull data API.

7.5.5.2 Resource: "Pull delivery URI"

7.5.5.2.1 Description

The resource represents the destination for pulling data from.

7.5.5.2.2 Resource Definition

The resource URI is a target URI provided in the "PullDeliveryDetailsHttp" data structure when creating a data job for data request or a data offer, or when notifying the data availability for data subscription.

7.5.5.2.3 Resource Standard Methods

7.5.5.2.3.1 GET

This method shall support the request data structures specified in table 7.5.5.2.3.1-1 the response data structures and response codes specified in table 7.5.5.2.3.1-2 and the HTTP response headers as defined in table 7.5.5.2.3.1-3.

Table 7.5.5.2.3.1-1: Data structures supported by the HTTP GET request body on this resource.

Data type	P	Cardinality	Description
NA			There is no object in the message content of a GET request.

Table 7.5.5.2.3.1-2: Data structures supported by the HTTP GET response body on this resource.

Data type	P	Cardinality	Response codes	Description
N/A			200 OK	Carry data payload in the response body.
N/A			202 Accepted	Data payload is not ready, retry later and the response body shall be empty.
ProblemDetails	O	0..1	4xx/5xx	The operation was unsuccessful. Detailed problem description may be carried in the response message content.

The method shall support carrying the data payload in the response body of the "200OK" response. The format of the data payload and Content-Type header are determined by the data message schema.

Table 7.5.5.2.3.1-3: Headers supported by the 202 Response code on this resource

Name	Data type	P	Cardinality	Description
Retry-After	string	O	0..1	Indicates to the API Consumer the length of the time interval to wait until sending the next request, or the point in time when such request should earliest be sent. The format is defined in IETF RFC 9110 [25].

7.5.5.2.4 Resource Custom Operations

None.

7.5.6 Custom operation without associated resources.

None.

7.5.7 Notifications

None.

7.5.8 Data Model

7.5.8.1 Structured data types

None.

7.5.8.2 Simple data types and enumerations

None.

7.5.8.3 Re-used data types

None.

7.5.8.4 Service-specific registration information

None.

7.5.9 Error Handling

7.5.9.1 General

For the Pull data API, HTTP error responses shall be supported as specified in clause 4.8 of 3GPP TS 29.501 [1]. Protocol errors and application errors specified in 3GPP TS 29.500 [2], table 5.2.7.2-1, shall be supported for an HTTP method if the corresponding HTTP status codes are specified as mandatory for that HTTP method in 3GPP TS 29.500 [2], table 5.2.7.1-1.

In addition, the requirements in the following clauses are applicable for the Pull data API.

7.5.9.2 Protocol Errors

No specific protocol errors are defined in the present document.

7.5.9.3 Application Errors

No additional application errors defined in the present document.

7.6 Data offer API

7.6.1 Introduction

This API enables an API Consumer to trigger the API Producer to collect a data instance produced by the API Consumer and to store it for later consumption, based on the procedures for managing a data offer defined in R1GAP [5]. The API definition applies to the scenario when a Data Producer is the Service Consumer and the DME framework is the Service Producer.

7.6.2 API version

For the Data offer API as specified in the present document, the MAJOR version field shall be 2, the MINOR version field shall be 0 and the PATCH version field shall be 0 (see 3GPP TS 29.501 [1] for a definition of the version fields). Consequently, the <apiVersion> URI path segment shall be set to “v2”.

The API is under development and consequently the API version shall include the pre-release version “alpha.1”.

7.6.3 Resource structure and methods

The request URIs used in HTTP requests from the API Consumer towards the API Producer shall have the resource URI structure as defined in clause 5.2. The <apiName> resource URI variable shall be “data-offer”. The <apiSpecificResourceUriPart> for each resource shall be set as described in clause 7.6.5.

Figure 7.6.3-1 shows the overall resource URI structure defined for the Data offer API.




Figure 7.6.3-1: Resource URI structure of the Data offer API

Table 7.6.3-1 lists the individual resources defined for the API, the applicable HTTP methods, and the associated service operations.

Table 7.6.3-1: Resource and methods overview of the Data offer API

Resource name	Resource URI	HTTP method	Service Operation
All data offers	.../offers	POST	Create an individual data offer
Individual data offer	.../offers/{dataOfferId}	DELETE	Cancel data offer

7.6.4 Service Operations

7.6.4.1 Create data offer

7.6.4.1.1 Operation definition

The API Consumer uses the Create data offer operation to create a data offer.

The operation is based on HTTP POST.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer -->> Producer: POST .../offers (DataOfferInfo)
Producer -->> Consumer: 201 Created (DataOfferInfo)
@enduml
```



Figure 7.6.4.1.1-1: Create data offer operation

The service operation is as follows:

1. The API Consumer shall send an HTTP POST request to the API Producer. The target URI shall identify the resource (.../offers) under which the new data offer is to be created. The message content shall carry a DataOfferInfo structure.
2. The API Producer shall return the HTTP POST response. On success, "201 Created" shall be returned. The Location header shall be present and shall carry the URI of the new data offer resource with dataOfferId assigned by the API producer. The message content shall carry a DataOfferInfo representing the created data offer. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

7.6.4.1.2 Referenced procedures.

7.6.4.1.2.1 Create data offer procedure

The Create data offer operation illustrated in figure 7.6.4.1.1-1 is based on the Create data offer procedure defined for the Data offer service in R1GAP [5].

7.6.4.2 Cancel data offer

7.6.4.2.1 Operation definition

The API Consumer uses the Cancel data offer operation to cancel a data offer, i.e. to indicate to the API Producer that it has stopped the delivery of data for the data offer.

The operation is based on HTTP DELETE.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer -->> Producer: DELETE .../offers/{dataOfferId}
```

```

Producer -->> Consumer: 204 No Content
@enduml

```




Figure 7.6.4.2.1-1: Cancel data offer operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP DELETE request to the API Producer. The target URI shall identify the resource (.../offers/{dataOfferId}).
2. The API Producer shall return the HTTP DELETE response. On success, “204 No Content” shall be returned. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

NOTE: For some data delivery methods, due to race conditions, residual produced data can arrive at the API Producer even after having received the HTTP DELETE request. The API Producer should be robust against this situation.

7.6.4.2.2 Referenced procedures.

7.6.4.2.2.1 Cancel data offer procedure.

The Cancel data offer operation illustrated in figure 7.6.4.2.1-1 is based on the cancel data offer procedure defined for the Data offer service in R1GAP [5].

7.6.4.3 Notify data offer termination

7.6.4.3.1 Operation definition

The API Producer uses this operation to notify the API Consumer that it has stopped collecting the offered data. The API Consumer stops producing data.

The operation is based on HTTP POST.

```

@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Producer ->> Consumer: POST {dataOfferTerminationNotificationUri} Notification(
(DataOfferTerminationNotification)
Consumer -->> Consumer: Stop producing data
Consumer -->> Producer: 204 No Content
@enduml

```




Figure 7.6.4.3.1-1: Notify data offer termination

The service operation is as follows:

1. The API Producer shall send an HTTP POST request to the API Consumer. The target URI (dataOfferTerminationNotificationUri which was provided during data offer creation) identifies the address where to send the notifications. The message content shall carry a Notification message that includes a DataOfferTerminationNotification payload.
2. The API Producer shall stop producing data.
3. The API Consumer shall return the HTTP POST response. On success, “204 No Content” shall be returned. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

NOTE: For some data delivery methods, due to race conditions, residual produced data can arrive at the API Producer even after having received the “204 No Content” response. The API Producer should be robust against this situation.

7.6.4.3.2 Referenced procedures.

7.6.4.3.2.1 Notify data offer termination procedure.

The Notify data offer termination operation illustrated in figure 7.6.4.3.1-1 is based on the Notify data offer termination procedure defined for the Data offer service in R1GAP [5].

7.6.5 Resources

7.6.5.1 Overview

This clause defines the resources for the Data offer API.

7.6.5.2 Resource: "All data offers"

7.6.5.2.1 Description

The resource All data offers represents all data offers created by a particular consumer.

Only the methods defined in clause 7.6.5.2.3 shall be supported by these resources.

7.6.5.2.2 Resource Definition

Resource URI: {apiRoot}/data-offer/<apiVersion>/offers

The resource URI variables supported by the resource are defined in Table 7.6.5.2.2-1.

Table 7.6.5.2.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.3.
apiVersion	See clause 7.6.2.

7.6.5.2.3 Resource Standard Methods

7.6.5.2.3.1 POST

This method shall support the request data structure specified in the table 7.6.5.2.3.1-1, and the response data structure and response code specified in the table 7.6.5.2.3.1-2.

Table 7.6.5.2.3.1-1: Data structures supported by the POST request body on all data jobs.

Data Type	P	Cardinality	Description
DataOfferInfo	M	1	Provides information for the data job to be created.

Table 7.6.5.2.3.1-2: Data structures supported by the POST response body on all data jobs.

Data Type	P	Cardinality	Response codes	Description
DataOfferInfo	M	1	201 Created	The operation was successful. The message content of the POST response contains a DataOfferInfo representing the created resource.
ProblemDetails	O	0..1	4xx/5xx	The operation was unsuccessful. Detailed problem description may be carried in the response message content.

Table 7.6.5.2.3.1-3: Headers supported by the 201-response code on the resource.

Name	Data type	P	Cardinality	Description
Location	String	M	1	Contains the URI of the newly created resource as defined in clause 7.6.5.3.2.

7.6.5.2.4 Resource Custom Operations

None.

7.6.5.3 Resource: "Individual data offer"

7.6.5.3.1 Description

The resource Individual data offer represents an individual data offer.

The methods defined in clause 7.6.5.3.3 shall be supported by this resource.

7.6.5.3.2 Resource Definition

Resource URI: {apiRoot}/data-offer /<apiVersion>/offers/{dataOfferId}

The resource URI variables supported by the resource is defined in Table 7.6.5.3.2-1.

Table 7.6.5.3.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.3.
apiVersion	See clause 7.6.2.
dataOfferId	The data offer identifier assigned by the Service Producer.

7.6.5.3.3 Resource Standard Methods

7.6.5.3.3.1 DELETE

This method shall support the request data structure specified in table 7.6.5.3.3.1-1 and the response data structure and response code specified in 7.6.5.3.3.1-2.

Table 7.6.5.3.3.1-1: Data structure supported by the DELETE request body on this resource.

Data type	P	Cardinality	Description
N/A			There is no object in the message content of a DELETE request.

Table 7.6.5.3.3.1-2: Data structure supported by the DELETE response body on this resource.

Data type	P	Cardinality	Response codes	Description
N/A			204 No content	The operation was successful. The data offer has been cancelled.
ProblemDetails	O	0..1	4xx/5xx	The operation was unsuccessful. Detailed problem description may be carried in the response message content.

7.6.5.3.4 Resource Custom Operations

None.

7.6.6 Custom operation without associated resources.

None.

7.6.7 Notifications

7.6.7.0 General

Table 7.6.7.0-1: Notifications overview

Notification	Callback URI	HTTP method or custom operation	Description (service operation)
Data Offer Termination Notification	{dataOfferTerminationNotificationUri}	POST	Notify data offer termination
Data Offer Data Availability Notification	{dataAvailabilityNotificationUri}	POST	Notify availability of data for a data offer Deviating from the general callback pattern, the {dataAvailabilityNotificationUri} is a local URI addressing an endpoint at the API producer side.

7.6.7.1 Notify data offer termination

7.6.7.1.1 Description

The notification informs the Data Producer as API Consumer that the sender of the notification, i.e. the Api Producer, does not intend to collect the data instance related to the data offer from the Data Producer any longer. The Data Producer shall stop data production when receiving this notification.

7.6.7.1.2 Target URI

The target URI is a callback URI that has been provided in the attribute “dataOfferTerminationNotificationUri” when creating the related data offer.

7.6.7.1.3 Standard Methods

7.6.7.1.3.1 POST

This method shall support the request data structures specified in table 7.6.7.1.3.1-1 and the response data structure and response codes specified in table 7.6.7.1.3.1-2.

The use of the method shall conform to the structured content mode of CloudEvents as specified in HTTP-CloudEvents [31], i.e. the “Content-Type” HTTP request header shall be set to “application/cloudevents+json”.

Table 7.6.7.1.3.1-1: Data structures supported by the HTTP POST request body on this resource.

Data type	P	Cardinality	Description
Notification	M	1	To notify data offer termination, the notification structure defined in clause B.2.4.5 shall be used, with the “type” attribute set to “org.o-ran.DME.DATA_OFFER_TERMINATION” and the “data” attribute containing a “DataOfferTerminationNotification” structure defined in clause 7.6.8.1.3.

Table 7.6.7.1.3.1-2: Data structures supported by the HTTP POST response body on this resource.

Data type	P	Cardinality	Response codes	Description
N/A			204 No content	Confirmation of received notification.
ProblemDetails	O	0..1	4xx/5xx	The operation was unsuccessful. Detailed problem description may be carried in the response message content.

7.6.7.2 Notify data offer data availability

7.6.7.2.1 Description

The notification, which is sent by the Data Producer as API Consumer, informs the Data Consumer as API Producer about the availability of data for a data offer and provides details about how to access them.

NOTE: Due to the special nature of a data offer, this pattern deviates from the usual notification pattern where the notification is sent by the API Producer to the API consumer.

7.6.7.2.2 Target URI

The target URI is local URI in API Producer's URI space that has been provided in the attribute "dataAvailabilityNotificationUri" in the response to the request that has created the related data offer.

7.6.7.2.3 Standard Methods

7.6.7.2.3.1 POST

This method shall support the request data structures specified in table 7.6.7.2.3.1-1 and the response data structure and response codes specified in table 7.6.7.2.3.1-2.

The use of the method shall conform to the structured content mode of CloudEvents as specified in HTTP-CloudEvents [31], i.e. the "Content-Type" HTTP request header shall be set to "application/cloudevents+json".

Table 7.6.7.2.3.1-1: Data structures supported by the HTTP POST request body on this resource.

Data type	P	Cardinality	Description
Notification	M	1	To notify data offer termination, the notification structure defined in clause B.2.4.5 shall be used, with the "type" attribute set to "org.o-ran.DME.DATA_OFFER_TERMINATION" and the "data" attribute containing a "DataOfferTerminationNotification" structure defined in clause 7.6.8.1.3.

Table 7.6.7.2.3.1-2: Data structures supported by the HTTP POST response body on this resource.

Data type	P	Cardinality	Response codes	Description
N/A			204 No content	Confirmation of received notification.
ProblemDetails	O	0..1	4xx/5xx	The operation was unsuccessful. Detailed problem description may be carried in the response message content.

7.6.8 Data Model

7.6.8.1 Structured data types

7.6.8.1.1 Overview

The following clauses define the data types and attributes to be used in the resource representation.

7.6.8.1.2 Data type: DataOfferInfo

The DataOfferInfo contains the attributes defined in table 7.6.8.1.2-1.

Table 7.6.8.1.2-1: Definition of type DataOfferInfo

Attribute Name	Data type	P	Cardinality	Description
dataDeliveryMode	DataDeliveryMode	M	1	See clause 7.3.8.2.3.1
dmeTypeld	DmeTypeld	M	1	See clause B.4.2
productionJobDefinition	object	M	1	Job definition based on the DME type specific dataProductionSchema
dataDeliveryMethods	array (DataDeliveryMethod)	M	1..N	Data delivery method(s), see clause B.4.3.1(NOTE 1).
dataDeliverySchemalds	array (string)	M	1..N	Delivery schema identifiers (NOTE 1).
pullDeliveryDetailsHttp	PullDeliveryDetailsHttp	C	0..1	Access details for HTTP Pull delivery of the data, managed by the API Consumer, see clause 7.3.8.1.3. The API Consumer shall provide this attribute in the HTTP request to create a data offer if the value "PULL_HTTP" is included in "dataDeliveryMechanisms". The API Producer shall include this attribute in HTTP responses if it has chosen "PULL_HTTP" data delivery.
dataAvailabilityNotificationUri	Uri	C	0..1	Callback URI to receive data availability notifications, managed by the API Producer. The API Consumer shall not include this attribute in the HTTP request to create a data offer. The API Producer shall include this attribute in HTTP responses if it has chosen "PULL_HTTP" data delivery in "CONTINUOUS" delivery mode.
dataOfferTerminationNotificationUri	Uri	M	1	Callback URI to receive data offer termination notifications, managed by the API Consumer.
pushDeliveryDetailsHttp	PushDeliveryDetailsHttp	C	0..1	Access details for HTTP Push delivery of the data, managed by the API Producer, see clause 7.3.8.1.4. The API Consumer shall not provide this attribute in the HTTP request to create a data offer. The API Producer shall include this attribute in HTTP responses if it has chosen "PUSH_HTTP" data delivery.
streamingConfigurationKafka	StreamingConfigurationKafka	C	0..1	Konfiguration to stream data over a Kafka bus, see clause 7.3.8.1.6. This attribute shall not be present in the HTTP request to create a data offer. If the value "STREAMING_KAFKA" is included in "dataDeliveryMechanisms", this attribute shall be included in HTTP responses.

NOTE 1: In the HTTP request to create a data offer, the API Consumer shall include all items it supports. In HTTP responses, the API Producer shall include the single item that has been chosen from the alternatives proposed during data offer creation.

7.6.8.1.3 Data type: DataOfferTerminationNotification

The DataOfferTerminationNotification contains the attributes defined in table 7.6.8.1.3-1.

Table 7.6.8.1.3-1: Definition of type DataOfferTerminationNotification

Attribute Name	Data type	P	Cardinality	Description
dataOfferId	string	M	1	Identifier of the data offer to be terminated.

7.6.8.1.4 Data type: DataOfferDataAvailabilityNotification

The DataOfferDataAvailabilityNotification contains the attributes defined in table 7.6.8.1.4-1.

Table 7.6.8.1.4-1: Definition of type DataofferDataAvailabilityNotification

Attribute Name	Data type	P	Cardinality	Description
dataOfferId	string	M	1	Identifier of the data offer to be terminated.
pullDeliveryDetailsHttp	PushDeliveryDetailsHttp	C	1	Access details for HTTP Push delivery of the data, managed by the API Producer, see clause 7.3.8.1.4. The API Consumer shall not provide this attribute in the HTTP request to create a data offer. The API Producer shall include this attribute in HTTP responses if it has chosen "PUSH_HTTP" data delivery.

7.6.8.2 Simple data types and enumerations

None.

7.6.8.3 Re-used data types

Table 7.6.8.3-1 specified data types re-used from the Data Access API.

Table 7.6.8.3-1 Re-used data types

Data type	Reference	Comments
DataDeliveryMethod	Clause B.4.3.1	
PullDeliveryDetailsHttp	Clause 7.3.8.1.3	
PushDeliveryDetailsHttp	Clause 7.3.8.1.4	
DataAvailabilityNotification	Clause 7.6.8.1.4	
StreamingConfigurationKafka	Clause 7.3.8.1.6	

7.6.8.4 Service-specific registration information

None.

7.6.9 Error Handling

7.6.9.1 General

For the Data offer API, HTTP error responses shall be supported as specified in clause 4.8 of 3GPP TS 29.501 [1]. Protocol errors and application errors specified in 3GPP TS 29.500 [2], table 5.2.7.2-1, shall be supported for an HTTP method if the corresponding HTTP status codes are specified as mandatory for that HTTP method in 3GPP TS 29.500 [2], table 5.2.7.1-1.

In addition, the requirements in the following clauses are applicable for the Data offer API.

7.6.9.2 Protocol Errors

No specific protocol errors are defined in the present document.

7.6.9.3 Application Errors

No additional application errors defined in the present document.

8 RAN OAM related services.

8.1 Configuration management API

8.1.1 Introduction

This API allows the API Consumer to request managing configuration data based on the procedures for “Configuration management (CM) service” defined in R1GAP [5].

8.1.2 API version

For the Configuration management API as specified in the present document, the MAJOR version field shall be 1, the MINOR version field shall be 0 and the PATCH version field shall be 0 (see 3GPP TS 29.501 [1] for a definition of the version fields). Consequently, the <apiVersion> URI variable shall be set to “v1”.

The Configuration management API is under development and consequently the API version shall include the pre-release version “alpha.1”.

8.1.3 Resource structure and methods

The request URIs used in HTTP requests from the API Consumer towards the API Producer shall have the resource URI structure as defined for the Generic provisioning management service API (see 3GPP TS 28.532 [20], Figure 12.1.1.3.1.1-1 in Clause 12.1.1.3.1.1).

Table 8.1.3-1 lists the individual resources defined for the API, the applicable HTTP methods as defined in 3GPP TS 28.532 [20], clause 12.1.1, and the associated service operations. Table 8.1.3-1 lists the individual resources defined for the API, the applicable HTTP methods, and the associated service operations.

Table 8.1.3-1: Resources and methods overview of the configuration management API

Resource Name 3GPP TS 28.532 [20]	Resource URI 3GPP TS 28.532 [20]	HTTP method 3GPP TS 28.532 [20]	Service Operation
MOI	.../{URI-LDN-first part}/{class Name}={id}	GET	Read configuration data.
		PATCH	Write configuration changes.

NOTE: CM service procedures related to M-Plane nodes, such as O-RUs, are not currently supported in this API resource structure and can be defined in future releases.

8.1.4 Service operations


8.1.4.1 Read configuration data

8.1.4.1.1 Operation definition

A Service Consumer uses the Read configuration data API operation as API Consumer to read configuration with the API Producer.

The operation is based on HTTP GET as per figure 8.1.4.1.1-1. The HTTP GET response contains configuration data that the API Consumer has requested.

```
@startuml
autonumber
participant "API Consumer" as cons
participant "API Producer" as prod
cons ->> prod : GET .../{URI-LDN-first part}/{className}={id}
prod -->> cons : 200 OK (Configuration Data)
@enduml
```


Figure 8.1.4.1.1-1: Read configuration data operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer that includes the Node Identifier and optional query criteria. The API Producer shall process the read information received in the HTTP GET message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP GET response. On success “200 OK“ shall be returned and the message content shall carry configuration data. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

8.1.4.1.2 Referenced procedures

8.1.4.1.2.1 Reading configuration data procedure

The procedure for reading configuration data API operation illustrated in figure 8.1.4.1.1-1 is based on Read Configuration procedure defined in R1GAP [5].

8.1.4.2 Write configuration changes

8.1.4.2.1 Operation definition

A Service Consumer uses the Write configuration changes API operation as API Consumer to write configuration with the API Producer.

The operation is based on HTTP PATCH as per figure 8.1.4.2.1-1. The HTTP PATCH response contains configuration data that the API Consumer has requested.

```
@startuml
autonumber
participant "API Consumer" as cons
participant "API Producer" as prod
cons ->> prod : PATCH ../{URI-LDN-first part}/{className}={id}
prod -->> cons : 200 OK (Configuration Data)
@enduml
```



Figure 8.1.4.2.1-1: Write configuration changes operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP PATCH request to the API Producer that includes the Node Identifier and optional query criteria along with payload which includes attribute identifiers, attribute values and modify operator as part of modification list defined in 3GPP TS 28.532 [20] clause 11.1.1.3.2. The API Producer shall process the write configuration changes information received in the HTTP PATCH message and determine if the request sent by the API consumer is authorized or not.
2. The API Producer shall return the HTTP PATCH response. On success "200 OK" shall be returned and the message content shall carry configuration data. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

NOTE: Response format to represent "partial success" is not specified in the present document.

8.1.4.1.2 Referenced procedures.

8.1.4.1.2.1 Writing configuration change procedure.

The procedure for writing configuration data API operation illustrated in figure 8.1.4.2.1-1 is based on write Configuration procedure defined in R1GAP [5] .

8.1.5 Resources

8.1.5.1 Overview

This clause defines the resources for the Configuration management (CM) service API based on the RESTful HTTP-based solution set for the Generic provisioning management service defined in 3GPP TS 28.532 [20], clause 12.1.1.

The Configuration management (CM) service Producer take the role of the Generic provisioning MnS Producer defined in 3GPP TS 28.532 [20] . By consuming this API, an rApp as Configuration management (CM) service Consumer takes the role of the Generic provisioning MnS Consumer defined in 3GPP TS 28.532 [20].

8.1.5.2 Resource: "MOI"

8.1.5.2.1 Description

The MOI resource represents a managed object instance, or a tree of these, containing the configuration data .

8.1.5.2.2 Resource definition

The resource URI structure of the provisioning MnS is defined in 3GPP TS 28.532 [20], as per clause 12.1.1.3.1.1, with the following URI:

{apiRoot}/ProvMnS/<apiVersion>/{URI-LDN-first-part}/{className}={id}

The resource URI variables are specified in 3GPP TS 28.532 [20], clause 12.1.1.3.2.1.2.

NOTE: HTTP methods GET and PATCH shall only be used.

8.1.5.2.3 Resource standard methods

8.1.5.2.3.1 GET

This method shall support the URI query parameters, request data structures, response data structures and response codes specified in 3GPP TS 28.532 [20], clause 12.1.1.3.2.1.3.2.

8.1.5.2.3.2 PATCH

This method shall support the URI parameters, request data structures, response data structures and response codes specified in 3GPP TS 28.532 [20], clause 12.1.1.3.2.1.3.3.

8.1.5.2.3 Resource custom operations

None.

8.1.6 Custom operations without associated resources.

None.

8.1.7 Notifications

NOTE: The notifications are not specified in present version of the document.

8.1.8 Data model

8.1.8.1 General

The application data model is defined in 3GPP TS 28.532 [20], clause 12.1.1.4, apply to this API.

8.1.8.2 Structured data types

None.

8.1.8.3 Simple data types and enumerations

None.

8.1.8.4 Re-used data types

None.

8.1.8.5 Service-specific registration information

None.

8.1.9 Error Handling

8.1.9.1 General

HTTP error handling is applicable for this API as specified in 3GPP TS 28.532 [20], clause A.1.1.

8.1.9.2 Protocol Errors

No specific protocol errors are defined in the present document.

8.1.9.3 Application Errors

No specific protocol errors are defined in the present document.

8.2 Fault management API

8.2.1 Introduction

This API allows the API Consumer to read information about alarms and to acknowledge alarms based on the procedures for the “Fault management (FM) service” defined in R1GAP [5]. The API is based on the AlarmList IOC as specified in 28.111 [26], clause 7.3.2. .

8.2.2 API version

For the fault management API as specified in the present document, the MAJOR version field shall be 1, the MINOR version field shall be 0 and the PATCH version field shall be 0 (see 3GPP TS 29.501 [1] for a definition of the version fields). Consequently, the <apiVersion> URI variable shall be set to “v1”.

8.2.3 Resource structure and methods

The request URIs used in HTTP requests from the API Consumer towards the API Producer shall have the resource URI structure as defined for the Generic provisioning management service API (see 3GPP TS 28.532 [20], figure 12.1.1.3.1.1-1 in clause 12.1.1.3.1.1).

Table 8.2.3-1 lists the individual resources defined for the API, the applicable HTTP methods as defined in 3GPP TS 28.532 [20], clause 12.1.1, and the associated service operations.

Table 8.2.3-1: Resources and methods overview of the fault management API

Resource Name 3GPP TS 28.532 [20]	Resource URI 3GPP TS 28.532 [20]	HTTP method 3GPP TS 28.532 [20]	Service Operation
Alarm list	.../{URI-LDN-first part}/{className}={id}/ AlarmList={alarmListId}	GET	Query alarms.
		PATCH	Change alarm acknowledgement status.

NOTE: FM service procedures related to M-Plane nodes, such as O-RUs, are not currently supported in this API resource structure and can be defined in future releases.

8.2.4 Service operations

8.2.4.1 Query alarms

8.2.4.1.1 Operation definition

A Service Consumer uses the Query alarms API operation as API Consumer to query alarm information from the API Producer.

The operation is based on HTTP GET as per figure 8.2.4.1.1-1. The HTTP GET response contains a list of alarm records matching the query of the API Consumer.

```
@startuml
autonumber
participant "API Consumer" as cons
participant "API Producer" as prod
cons ->> prod : GET .../{URI-LDN-first part}/{className}={id}/AlarmList={alarmListId}
prod -->> cons : 200 OK (Alarm List)
@enduml
```




Figure 8.2.4.1.1-1: Query alarms operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer that includes either “SubNetwork“ or “ManagedElement“ as the class name, the related object instance identifier, the alarm list identifier, and optional

query criteria. The API Producer shall process the information received in the HTTP GET message and determine if the request sent by the API Consumer is authorized or not.

2. The API Producer shall return the HTTP GET response. On success “200 OK” shall be returned and the message content shall carry the representation of the alarm list. If query criteria were given, the content of the alarm entries in the returned alarm list shall match the query criteria. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

8.2.4.1.2 Referenced procedures

8.2.4.1.2.1 Query alarms procedure

The procedure for querying alarm information illustrated in figure 8.2.4.1.1-1 is based on the Query Alarms procedure defined in R1GAP [5].

8.2.4.2 Change alarm acknowledgement state

8.2.4.2.1 Operation definition

A Service Consumer uses the Change alarm acknowledgement state API operation as API Consumer to acknowledge or unacknowledge one or more alarms with the API Producer.

The operation is based on HTTP PATCH as per figure 8.2.4.2.1-1.

```
@startuml
autonumber
participant "API Consumer" as cons
participant "API Producer" as prod
cons -->> prod : PATCH .../{URI-LDN-first part}/{className}={id}/AlarmList={alarmListId} (Alarm Update Information)
alt success, no information returned
    prod -->> cons : 204 No Content
else success, updated information returned
    prod -->> cons : 200 OK (Alarm List)
else error
    prod -->> cons : Error response
end
end
@enduml
```




Figure 8.2.4.2.1-1: Change alarm acknowledgement state operation.

The service operation is as follows:

1. The API Consumer shall send a PATCH request to the API Producer that includes in the resource URI either “SubNetwork” or “ManagedElement” as the class name, the related object instance identifier, and the alarm list

identifier. Further, it shall include in the message content information about which alarms to be updated as well as information about the actual alarm acknowledgements / unacknowledgments. The API Producer shall process the information received in the HTTP PATCH message and determine if the request sent by the API Consumer is authorized or not.

2. The API Producer shall return the HTTP PATCH response.
3. On success, the API Producer should return a “204 No Content” response message with empty message content.
4. On success, the API Producer may alternatively return a “200 OK” response message with the representation of updated alarm list in the message content.
5. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

8.2.4.2.2 Referenced procedures

8.2.4.2.2.1 Change alarm acknowledgement state procedure

The procedure for changing the acknowledgement state of one or more alarms illustrated in figure 8.2.4.2.1-1 is based on the Change alarm acknowledgement state procedure defined in R1GAP [5].

8.2.5 Resources

8.2.5.1 Overview

This clause defines the resources for the Fault management (FM) service API based on the RESTful HTTP-based solution set for the Generic provisioning management service defined in 3GPP TS 28.532 [20], clause 12.1.1.

The Fault management (FM) service Producer take the role of the Generic provisioning MnS Producer defined in 3GPP TS 28.532 [20]. By consuming this API, an rApp as Fault management (FM) service Consumer takes the role of the Generic provisioning MnS Consumer defined in 3GPP TS 28.532 [20].

8.2.5.2 Resource: "Alarm list"

8.2.5.2.1 Description

The “Alarm list” resource represents a list of alarms related to either a subnetwork or a managed element. It allows to query alarms and to change the acknowledgement state of alarms.

8.2.5.2.2 Resource definition

The resource URI structure of the alarm list as managed by the Generic provisioning MnS is defined as per 3GPP TS 28.532 [20], clause 12.1.1.3.1.1, for the AlarmList IOC as defined in 3GPP TS 28.111 [26], clause 7.3.2, with the following URI:

{apiRoot}/ProvMnS/<apiVersion>/{URI-LDN-first-part}/{className}={id}/AlarmList={alarmListId}

The resource URI variables supported by the resource are defined in Table 8.2.5.2.2-1.

Table 8.2.5.2.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.2.
apiVersion	See clause 8.2.2.
URI-LDN-first-part	See 3GPP TS 28.532 [20], clause 12.1.1.3.2.1.2.
className	Name of the object class (IOC) of the managed object instance to which the alarm list is attached. Shall be either “SubNetwork” or “ManagedElement” as defined in 3GPP TS 28.622 [21], clause 4.3.26.1.
id	Identifier of the managed object instance to which the alarm list is attached.
alarmListId	Identifier of the managed object instance which is the alarm list.

8.2.5.2.3 Resource standard methods

8.2.5.2.3.1 GET

This method shall support the URI query parameters, HTTP headers, response data structures and response codes specified in 3GPP TS 28.532 [20], clause 12.1.1.3.2.1.3.2.

EXAMPLE 1: This request queries the whole alarm list: GET /SubNetwork=SN123/AlarmList=AL123 HTTP/1.1.

EXAMPLE 2: This request queries a single alarm: GET /SubNetwork=SN123/AlarmList=AL123?fields=/attributes/alarmRecords/ALARM456 HTTP/1.1.

NOTE: Selection of alarm records in the query based on then values of other alarm attributes than alarm identifier is not supported in the present version.

8.2.5.2.3.2 PATCH

This method shall support the URI query parameters, HTTP headers, response data structures and response codes specified in 3GPP TS 28.532 [20], clause 12.1.1.3.2.1.3.3.

To change the alarm state, the patch payload shall contain values for the “ackState“ attribute (“ACKNOWLEDGED“ or “UNACKNOWLEDGED“) and the “ackUserId“ attribute and may contain a value for the “ackSystemId“ attribute, as defined in 3GPP TS 28.111 [26], clause 7.3.1.2.

8.2.5.3.3 Resource custom operations

None.

8.2.6 Custom operations without associated resources

None.

8.2.7 Notifications

None.

8.2.8 Data model

8.2.8.1 General

The application data model is defined in 3GPP TS 28.111 [26], clause Annex A.1.3. The key IOCs for this API are SubNetwork, ManagedElement and AlarmList.

8.2.8.2 Structured data types

None.

8.2.8.3 Simple data types and enumerations

None.

8.2.8.4 Re-used data types

None.

8.2.8.5 Service-specific registration information

None.

8.2.9 Error Handling

8.2.9.1 General

HTTP error handling is applicable for this API as specified in 3GPP TS 28.111 [26], clause A.1.3.

8.2.9.2 Protocol Errors

No specific protocol errors are defined in the present document.

8.2.9.3 Application Errors

No specific protocol errors are defined in the present document.

8.3 Configuration schema information API.

8.3.1 Introduction

This API enables the API Consumer to retrieve configuration schema information based on the procedure defined in R1GAP [5].

8.3.2 API version

For the configuration schema information API as specified in the present document, the MAJOR version field shall be 1, the MINOR version field shall be 0 and the PATCH version field shall be 0 (see clause 4.3.1.1 of 3GPP TS 29.501 [1] for a definition of the version fields). Consequently, the <apiVersion> URI path segment shall be set to "v1".

8.3.3 Resource structure and methods

The request URIs used in HTTP requests from the API Consumer towards the API Producer shall have the resource URI structure as defined in clause 5.2. The <apiName> resource URI variable shall be "ran-oam-cm-schema-info". The <apiSpecificResourceUriPart> for each resource shall be set as described in clause 8.3.5.

Figure 8.3.3-1 shows the overall resource URI structure defined for the retrieving configuration information API.




Figure 8.3.3-1: Resource URI structure of the configuration schemas information API

Table: 8.3.3-1 lists the individual resources defined for the API, the applicable HTTP methods, and the associated service operations.

Table 8.3.3-1 Resource and methods overview of the configuration schemas information API

Resource Name	Resource URI	HTTP method	Service Operation
All schema information	.../schemas	GET	Get all schema information
Individual schema information	.../schemas/{schemald}	GET	Get Individual schema information

8.3.4 Service operations

8.3.4.1 Get all schema information

8.3.4.1.1 Operation definition

An API consumer uses the Get all schema information operation to get Schemas.

```
@startuml
autonumber
participant "API Consumer" as cons
participant " API Producer " as prod
cons ->>prod: GET .../schemas
prod-->> cons : 200 OK (array(Schema))
@enduml
```




Figure 8.3.4.1.1-1 Get all schema information operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to API Producer. The target URI shall identify the resource (.../schemas). The API Producer shall process the request received in the HTTP GET message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP GET response. On success "200 OK" shall be returned and the message content shall carry an array of schema. On failure, the appropriate error code shall be returned, and the message response body may contain additional error information.

8.3.4.1.2 Referenced procedures

8.3.4.1.2.1 Get schemas procedure

The Get all schema information operation illustrated in figure 8.3.4.1.1-1 is based on Get schemas procedure defined in R1GAP [5].

8.3.4.2 Get Individual schema information

8.3.4.2.1 Operation definition

An API consumer uses the Get Individual schema information to get one or more schemas of interest for a schemaId.

```
@startuml
autonumber
participant "API Consumer" as cons
participant "API Producer" as prod
cons->>prod: GET .../schemas/{schemaId}
prod-->>cons: 200 OK (Schema)
@enduml
```




Figure 8.3.4.2.1-1 retrieving specific schema API operation.

The service operation is as follows:

- 1) The API Consumer shall send an HTTP GET request to API Producer. The target URI shall identify the resource (.../schemas/{schemaId}), the message content shall be empty. The API Producer shall process the request received in the HTTP GET message and determine if the request sent by the API Consumer is authorized or not.
- 2) The API Producer shall return the HTTP GET response. On success "200 OK" shall be returned and the message content shall carry the Schema matching the API Consumer HTTP GET request URI and schemaId . On failure, the appropriate error code shall be returned, and the message response body may contain additional error information.

8.3.4.2.2 Referenced procedures

8.3.4.2.2.1 Get Schemas procedure

The Get individual schema information operation illustrated in figure 8.3.4.2.1-1 is based on Get schemas procedure defined in R1GAP [5].

8.3.5 Resources

8.3.5.1 Overview

This clause defines the resources for the retrieving configuration schemas API.

8.3.5.2 Resource : " All schema information"

8.3.5.2.1 Description

The resource represents a collection of configuration schema information.

Only the methods defined in clause 8.3.3 shall be supported by this resource.

8.3.5.2.2 Resource Definition

Resource URI: **{apiRoot}/ran-oam-cm-schema-info/<apiVersion>/schemas**

The resource URI variables supported by the resource is defined in table 8.3.5.2.2-1.

Table 8.3.5.2.2-1: Resource URI variables

Name	Definition
apiRoot	See clause 5.2
apiVersion	See clause 8.3.2

8.3.5.2.3 Resource Standard Methods

8.3.5.2.3.1 HTTP GET

This method shall support the request data structure specified in table 8.3.5.2.3.1 -1 and the response data structures and response codes specified in 8.3.5.2.3.1 -2.

Table 8.3.5.2.3.1-1: Data structure supported by the GET request body on this resource.

Data type	P	Cardinality	Description
N/A			There is no object in the message content of a GET request.

Table 8.3.5.2.3.1-2: Data structures supported by the GET Response Body on this resource.

Data Type	P	Cardinality	Response codes	Description
array(Schema)	O	0..N	200 OK	The results with the schema information
ProblemDetails	O	0..1	4xx/5xx	The operation has failed, and the message content may contain Problem description details.

8.3.5.2.4 Resource Custom Operations

None

8.3.5.3 Resource: "Individual schema information"

8.3.5.3.1 Description

The resource represents a schema definition.

Only the methods defined in clause 8.3.3 shall be supported by this resource.

8.3.5.3.2 Resource Definition

Resource URI: **{apiRoot}/ran-oam-cm-schema-info/<apiVersion>/schemas/{schemaId}**

The resource URI variables supported by the resource is defined in the table 8.3.5.3.2-1.

Table 8.3.5.3.2-1: Resource URI variables

Name	Definition
apiRoot	See clause 5.2
apiVersion	See clause 8.3.2
schemald	Where schemald = "name" (for latest revision or if revision is not available) or "name@revision" for a specific revision.

8.3.5.3.3 Resource Standard Methods

8.3.5.3.3.1 HTTP GET

This method shall support the request data structure specified in table 8.3.5.3.3.1 -1 and the response data structures and response codes specified in 8.3.5.3.3.1 -2.

Table 8.3.5.3.3.1-1: Data structure supported by the GET request body on this resource.

Data type	P	Cardinality	Description
N/A			There is no object in the message content of a GET request.

Table 8.3.5.3.3.1-2: Data structures supported by the GET Response Body on this resource.

Data Type	P	Cardinality	Response codes	Description
Schema	M	1	200 OK	The results with the schema information matching the request
ProblemDetails	O	0..1	4xx/5xx	The operation has failed, and the message content may contain Problem description details.

8.3.5.3.4 Resource Custom Operations

None.

8.3.6 Custom operations without associated resources

None

8.3.7 Notifications

None

8.3.8 Data model

The following clause specifies the application data model supported by the retrieving configuration schemas API.

8.3.8.1 Data Type: Schema

The Schema data type contains the attributes defined in table 8.3.8.1.1-1.

Table 8.3.8.1.1-1: Definition of type Schema

Attribute Name	Data type	P	Cardinality	Description
name	string	M	1	The unique name of the schema
revision	string	C	0..1	The unique revision of the schema (See NOTE 3)
location	Uri	M	1	Location of where to find the schema content
type	SchemaType	M	1	See clause 8.3.8.2.3.1. (See NOTE 2).
namespace	string	O	0..1	The namespace of the schema, (See NOTE 1).
features	Array(string)	O	0..N	List of supported features (See NOTE 1).
deviations	Array(string)	O	0..N	List of schema deviation(s) (See NOTE 1).
NOTE 1: Only applicable if type is YANG.				
NOTE 2: This data type is designed to provide extensibility. As specified in clause 8.3.8.2.3.1, Only YANG is supported in the present version of the present document.				
NOTE 3 : this attribute is required for YANG.				

8.3.8.2 Simple data types and enumerations

8.3.8.2.1 Introduction

The following clause defines simple data types and enumerations that can be referenced from data structures defined in the previous clauses.

8.3.8.2.2 Simple data types

None.

8.3.8.2.3 Enumerations

8.3.8.2.3.1 Enumeration: SchemaTypes

Table 8.3.8.2.3.1-1: Enumeration SchemaTypes.

Enumeration value	Description
YANG	YANG schema

8.3.8.3 Re-used data types

None.

8.3.9 Error Handling

8.3.9.1 General

In addition to the general provisions in clause 5.4.3, the requirements in the following clauses are applicable for the retrieving configuration schema API.

8.3.9.2 Protocol Errors

No specific protocol errors are defined in the present document.

8.3.9.3 Application Errors

No specific protocol errors are defined in the present document.

9. A1 related services

9.1 A1 policy management API

9.1.1 Introduction

This API allows the API Consumer to Query policy types and create, query, update and delete A1 policies based on the procedures for “A1 policy management” defined in R1GAP [5].

9.1.2 API version

For the A1 policy management API as specified in the present document, the MAJOR version field shall be 1, the MINOR version field shall be 0, and the PATCH version field shall be 0 (see 3GPP TS 29.501 [1] for a definition of the version fields). Consequently, the <apiVersion> URI path segment shall be set to “v1”.

9.1.3 Resource structure and methods

The request URIs used in HTTP requests from the API Consumer towards the API Producer shall have the resource URI structure as defined in clause 5.2. The <apiName> resource URI variable shall be “a1-policy-managment”. The <apiSpecificResourceUriPart> for each resource shall be set as described in clause 9.1.5.

Figure 9.1.3-1 shows the overall resource URI structure defined for the A1 policy management API for querying policy types and policies, for life cycle management of policies, and for subscriptions to A1 policy status notifications.




Figure 9.1.3-1: Resource URI structure of the A1 policy management API.

Table 9.1.3-1 lists the individual resources defined for the API, the applicable HTTP methods, and the associated service operations.

Table 9.1.3-1: Resources and methods overview of the A1 policy management API

Resource name	Resource URI	HTTP method	Service Operation
All A1 policy types	.../policy-types	GET	Query A1 policy type identifiers.
Individual A1 policy type	.../policy-types/{policyTypeId}	GET	Query A1 policy type.
All A1 policies	.../policies	GET	Query A1 policy identifiers.
		POST	Create A1 policy.
Individual A1 policy	.../policies/{policyId}	GET	Query A1 policy.
		PUT	Update A1 policy.
		DELETE	Delete A1 policy.
Individual A1 policy status	.../policies/{policyId}/status	GET	Query A1 policy status.
All A1 policy status subscriptions	.../policies/subscriptions	POST	Subscribe A1 policy status.
Individual A1 policy status subscription	.../policies/subscriptions/{subscriptionId}	PUT	Update A1 policy status subscription.
		GET	Query A1 policy status subscription.
		DELETE	Unsubscribe A1 policy status.
Policy status change notifications	{notificationDestination}	POST	Notify A1 policy status changes.

9.1.4 Service operations


9.1.4.1 Query A1 policy type identifiers

9.1.4.1.1 Operation definition

The API Consumer uses this operation to query available A1 policy type identifiers.

The operation to query available A1 policy type identifiers is based on HTTP GET.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: GET .../policy-types
Producer -->> Consumer : 200 OK (array(PolicyTypeInfoInformation))
@enduml
```


Figure 9.1.4.1.1-1: Query A1 policy type identifiers operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer. The target URI shall identify the resource “/policy-types” and optionally query parameters, the message content shall be empty. The API Producer shall process

the request received in the HTTP GET message and determine if the request sent by the API Consumer is authorized or not.

2. The API Producer shall return the HTTP GET response. On success, “200 OK” shall be returned. The message content shall carry an array of policy type information representing available policy types and for each policy type identifier the Near-RT RIC identifiers of those Near-RT RICs that support the related A1 policy type. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

NOTE: The behavior of the query parameters is specified in table 9.1.5.2.3.1-3.

9.1.4.1.2 Referenced procedures.

9.1.4.1.2.1 Query A1 policy type identifiers procedure

The Query A1 policy type identifiers API operation illustrated in figure 9.1.4.1.1-1 is based on the Query A1 policy type identifiers procedure defined in R1GAP [5].

9.1.4.2 Query A1 policy type

9.1.4.2.1 Operation definition

The API Consumer uses this operation to query an A1 policy type.

The Query A1 policy type operation is based on HTTP GET.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: GET .../policy-types/{policyTypeId}
Producer ->> Consumer: 200 OK (PolicyTypeObject)
@enduml
```




Figure 9.1.4.2.1-1: Query A1 policy type operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer. The target URI shall identify the policy type to be read based on the policyTypeId under the resource “/policy-types“. The message content shall be empty. The API Producer shall process the request received in the HTTP GET message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP GET response. On success, “200 OK” shall be returned. The message content shall carry a PolicyTypeObject representing the read policy type. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

9.1.4.2.2 Referenced procedures.

9.1.4.2.2.1 Query A1 policy type procedure

The Query A1 policy type API operation illustrated in figure 9.1.4.2.1-1 is based on the Query A1 policy type procedure defined in R1GAP [5].

9.1.4.3 Query A1 policy identifiers

9.1.4.3.1 Operation definition

The API Consumer uses this operation to query A1 policy identifiers.

The operation to query A1 policy identifiers is based on HTTP GET.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: GET ../policies
Producer ->> Consumer: 200 OK (array(PolicyInformation))
@enduml
```




Figure 9.1.4.3.1-1: Query A1 policy identifiers operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer. The target URI shall identify the resource “/policies” and optionally query parameters. The message content shall be empty. The API Producer shall process the HTTP GET message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP GET response. On success, “200 OK” shall be returned. The message content shall carry an array of policy information which includes Near-RT RIC identifiers where A1 policies exist and for each Near-RT RIC identifier the policy identifiers of those policies that exist in that Near-RT RIC. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

NOTE: The behavior of the query parameters is specified in table 9.1.5.2.3.1-3.

9.1.4.3.2 Referenced procedures.

9.1.4.3.2.1 Query A1 policy identifiers procedure

The Query A1 policy identifiers API operation illustrated in figure 9.1.4.3.1-1 is based on the Query A1 policy identifiers procedure defined in R1GAP [5].

9.1.4.4 Create A1 policy

9.1.4.4.1 Operation definition

The API Consumer uses this operation to create an A1 policy.

The Create A1 policy operation is based on HTTP POST.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: POST .../policies(PolicyObjectInformation)
Producer ->> Consumer : 201 Created(PolicyObjectInformation)
@enduml
```




Figure 9.1.4.4.1-1: Create A1 policy operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP POST request to the API Producer. The target URI shall identify the resource “/policies” under which the A1 policy shall be created. The message content shall carry a PolicyObjectInformation which includes a nearRtRid and a PolicyObject. The API Producer shall process the HTTP POST message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP POST response. On success, “201 Created” shall be returned. The message content shall carry the PolicyObjectInformation, and the “Location” HTTP header shall be present and shall carry the URI for the newly created service resource with policyId assigned by the API Producer. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

9.1.4.4.2 Referenced procedures.

9.1.4.4.2.1 Create A1 policy procedure.

The Create A1 policy API operation illustrated in figure 9.1.4.4.1-1 is based on the Create A1 policy procedure defined in R1GAP [5].

9.1.4.5 Query A1 policy

9.1.4.5.1 Operation definition

The API Consumer uses this operation to query an A1 policy.

The Query A1 policy operation is based on HTTP GET.


```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: GET ../policies/{policyId}
Producer ->> Consumer : 200 OK (PolicyObject)
@enduml
```




Figure 9.1.4.5.1-1: Query A1 policy operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer. The target URI shall identify the policy to be read based on the policyId under the resource “/policies“. The message content shall be empty. The API Producer shall process the HTTP GET message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP GET response. On success, “200 OK“ shall be returned. The message content shall carry a PolicyObject representing the read policy. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

9.1.4.5.2 Referenced procedures.

9.1.4.5.2.1 Query A1 policy procedure

The Query A1 policy API operation illustrated in figure 9.1.4.5.1-1 is based on the Query A1 policy procedure defined in R1GAP [5].

9.1.4.6 Update A1 policy

9.1.4.6.1 Operation definition

The API Consumer uses this operation to update an A1 policy.

The Update A1 policy operation is based on HTTP PUT.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: PUT../policies/{policyId} (PolicyObject)
Producer ->> Consumer : 200 OK (PolicyObject)
@enduml
```




Figure 9.1.4.6.1-1: Update A1 policy operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP PUT request to the API Producer. The target URI shall identify the policy to be updated based on the policyId under the resource “/policies“. The message content shall contain a PolicyObject. The API Producer shall process the HTTP PUT message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP PUT response. On success, “200 OK“ shall be returned. The message content shall carry a PolicyObject representing the updated policy. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

9.1.4.6.2 Referenced procedures.

9.1.4.6.2.1 Update A1 policy procedure

The Update A1 policy API operation illustrated in figure 9.1.4.6.1-1 is based on the Update A1 policy procedure defined in R1GAP [5].

9.1.4.7 Delete A1 policy

9.1.4.7.1 Operation definition

The API Consumer uses this operation to delete an A1 policy.

The Delete A1 policy operation is based on HTTP GET.

```

@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: DELETE.../policies/{policyId}
Producer ->> Consumer : 204 No Content
@enduml
  
```




Figure 9.1.4.7.1-1: Delete A1 policy operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP DELETE request to the API Producer. The target URI shall identify the policy to be deleted based on the policyId under the resource “/policies“. The message content shall be empty. The API Producer shall process the HTTP DELETE message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP DELETE response. On success, “204 No Content“ shall be returned. The message content shall be empty. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

9.1.4.7.2 Referenced procedures.

9.1.4.7.2.1 Delete A1 policy procedure.

The Delete A1 policy API operation illustrated in figure 9.1.4.7.1-1 is based on the Delete A1 policy procedure defined in R1GAP [5].

9.1.4.8 Query A1 policy status

9.1.4.8.1 Operation definition

The API Consumer uses this operation to query A1 policy status.

The operation to query A1 policy status is based on HTTP GET.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: GET .../policies/{policyId}/status
Producer -->> Consumer: 200 OK (PolicyStatusObject)
@enduml
```




Figure 9.1.4.8.1-1: Query A1 policy status operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer. The target URI shall identify the resource “.../policies/{policyId}/status“. The message content shall be empty. The API Producer shall process the HTTP GET message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP GET response. On success, “200 OK“ shall be returned. The message content shall carry a PolicyStatusObject representing the status of the A1 policy. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

9.1.4.8.1 Referenced procedures

9.1.4.8.1.1 Query A1 policy status procedure

The Query A1 policy status operation illustrated in figure 9.1.4.8.1-1 is based on the Query A1 policy enforcement status procedure defined in R1GAP [5].

9.1.4.9 Subscribe A1 policy status

9.1.4.9.1 Operation definition

The API Consumer uses this operation to subscribe to notifications for status changes of A1 policies.

The operation to subscribe to A1 policy status is based on HTTP POST.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: POST .../policies/subscriptions (PolicyStatusSubscription)
Producer ->> Consumer : 201 Created (PolicyStatusSubscription)
@enduml
```



Figure 9.1.4.9.1-1: Subscribe to A1 policy status operation

The service operation is as follows:

1. The API Consumer shall send an HTTP POST request to the API Producer. The target URI shall identify the resource “/policies/subscriptions” under which the new subscription is requested to be created. The message content shall carry a PolicyStatusSubscription structure. The API Producer shall process the request received in the HTTP POST message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP POST response. On success, “201 Created” shall be returned. The location header shall be present and shall carry the URI of new subscription resource with subscriptionId assigned by the API producer. The message content shall carry a PolicyStatusSubscription structure that represents the new resource. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

9.1.4.9.2 Referenced procedures

9.1.4.9.2.1 Subscribe A1 policy status procedure

The Subscribe A1 policy status operation illustrated in figure 9.1.4.9.1-1 is based on the Subscribe A1 policy status procedure defined in R1GAP [5].

9.1.4.10 Update A1 policy status subscription

9.1.4.10.1 Operation definition

The API Consumer uses this operation to update a subscription for A1 policy status notifications.

The operation to update an individual A1 policy status subscription is based on HTTP PUT.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: PUT .../policies/subscriptions/{subscriptionId}\n(PolicyStatusSubscription)
Producer ->> Consumer: 200 OK (PolicyStatusSubscription)
@enduml
```




Figure 9.1.4.10.1-1: Update A1 policy status subscription operation

The service operation is as follows:

1. The API Consumer shall send an HTTP PUT request to the API Producer. The target URI shall identify the resource (.../policies/subscriptions/{subscriptionId}). The message content shall carry the updated PolicyStatusSubscription structure. The API Producer shall process the request received in the HTTP PUT message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP PUT response. On success, "200 OK" shall be returned. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

9.1.4.10.2 Referenced procedures.

9.1.4.10.2.1 Update A1 policy status subscription procedure

The Update A1 policy status subscription operation illustrated in figure 9.1.4.10.1-1 is based on the Update A1 policy status procedure defined in R1GAP [5].

9.1.4.11 Query A1 policy status subscription

9.1.4.11.1 Operation definition

The API Consumer uses this operation to query a subscription for A1 policy status.

The operation to query an individual A1 policy status subscription is based on HTTP GET.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: GET .../policies/subscriptions/{subscriptionId}
Producer ->> Consumer: 200 OK (PolicyStatusSubscription)
@enduml
```

@endum1



Figure 9.1.4.11.1-1: Query A1 policy status subscription operation

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer. The target URI shall identify the resource “/policies/subscriptions/{subscriptionId}“. The message content shall be empty. The API Producer shall process the HTTP GET message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP GET response. On success, “200 OK“ shall be returned. The message content shall carry the PolicyStatusSubscription representing the queried policy status subscription. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

9.1.4.11.2 Referenced procedures.

9.1.4.11.2.1 Query A1 policy status subscription procedure

The Query A1 policy status subscription operation illustrated in figure 9.1.4.11.1-1 is based on the Query A1 policy status subscription procedure defined in R1GAP [5].

9.1.4.12 Unsubscribe A1 policy status

9.1.4. 12.1 Operation definition

The API Consumer uses this operation to unsubscribe from notifications on status changes of A1 policies.

The operation to unsubscribe from A1 policy status notifications is based on HTTP DELETE.

```

@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: DELETE .../policies/subscriptions/{subscriptionId}
Producer -->> Consumer : 204 No Content
@enduml
  
```



Figure 9.1.4.12.1-1: Unsubscribe from A1 policy status operation

The service operation is as follows:

1. The API Consumer shall send an HTTP DELETE request to the API Producer. The target URI shall identify the resource “/policies/subscriptions/{subscriptionId}“. The message content shall be empty. The API Producer shall process the request received in the HTTP DELETE message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP DELETE response. On success, “204 No Content“ shall be returned. The message content shall be empty. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

9.1.4.12.2 Referenced procedures.

9.1.4.12.2.1 Unsubscribe A1 policy status procedure

The Unsubscribe A1 policy status operation illustrated in figure 9.1.4.12.1-1 is based on the Unsubscribe A1 policy status procedure defined in R1GAP [5].

9.1.4.13 Notify A1 policy status changes

9.1.4.13.1 Operation definition

The API Producer uses this operation to notify the API Consumer about status changes of an A1 policy.

The operation to notify A1 policy status is based on HTTP POST.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Producer ->> Consumer : POST ../{notificationDestination} (A1PolicyStatusChangeNotification)
Consumer -->> Producer : 204 No Content
@enduml
```




Figure 9.1.4.13.1-1: Notify A1 policy status changes API operation.

The service operation is as follows:

1. The API Producer shall send an HTTP POST request to the API Consumer . The target URI (notificationDestination) identifies the sink for policy status change notifications. The message body shall contain a A1PolicyStatusChangeNotifications.
2. The API Consumer shall return the HTTP POST response with “204 No Content“. The message body shall be empty. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

9.1.4.13.2 Referenced procedures.

9.1.4.13.2.1 Notify A1 policy status procedure

The Notify A1 policy status changes operation illustrated in figure 9.1.4.13.1-1 is based on the Notify A1 policy status changes procedure defined in R1GAP [5].

9.1.5 Resources

9.1.5.1 Overview

This clause defines the resources for the A1 policy management API.

9.1.5.2 Resource: "All A1 policy types"

9.1.5.2.1 Description

The resource All A1 policy types represents all A1 policy types that are available in all Near-RT RIC's over the A1 Interface.

The methods defined in clause 9.1.5.2.3 shall be supported by these resources.

9.1.5.2.2 Resource Definition

Resource URI: {**apiRoot**}/**a1-policy-management** /<**apiVersion**>/**policy-types**

The resource URI variables supported by the resource are defined in Table 9.1.5.2.2-1.

Table 9.1.5.2.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.2.
apiVersion	See clause 9.1.2.

9.1.5.2.3 Resource Standard Methods

9.1.5.2.3.1 GET

This method shall support the URI query parameters specified in table 9.1.5.2.3.1-1, the request data structure specified in the table 9.1.5.2.3.1-2 and the response data structures, and response code specified in the table 9.1.5.2.3.1-3.

Table 9.1.5.2.3.1-1: URI query parameters supported by the GET method on this resource.

Name	Data type	P	Cardinality	Description	Applicability
nearRtRicId	string	O	0..1	The identifier of Near-RT RIC (See NOTE).	
typeName	string	O	0..1	The unique label of the policy type (See NOTE).	

NOTE: If multiple query parameters are provided these shall be combined with AND when evaluating the query.

Table 9.1.5.2.3.1-2: Data structures supported by the GET request body on this resource.

Data Type	P	Cardinality	Description
N/A			There is no object in the message content of the GET request.

Table 9.1.5.2.3.1-3: Data structures supported by the GET response body on this resource.

Data Type	P	Cardinality	Response codes	Description
array(PolicyTypeInfo)	M	0.. N	200 OK	The operation is successful, the policy type information. (See NOTE1 ,NOTE 2 , and NOTE 3).
ProblemDetails	O	0..1	4xx/5xx	The operation has failed, and the message content may contain Problem description details.

NOTE 1: If a Near-RT RIC identifier has been provided as query parameter, the response body shall contain only entries for policy types supported by the related Near-RT RIC.
NOTE 2: If a policy type identifier has been provided as query parameter, the response body shall contain only entries for the related policy type.
NOTE 3: If both a Near-RT RIC identifier and a policy type identifier have been provided as query parameters, the response body shall contain only entries for the related policy type supported by the related Near-RT RIC.

9.1.5.2.4 Resource Custom Operations

None.

9.1.5.3 Resource: "Individual A1 policy type"

9.1.5.3.1 Description

The resource individual A1 policy type represents the A1 policy type that are available in the A1 policy management service.

Only the methods defined in clause 9.1.5.3.3 shall be supported by these resources.

9.1.5.3.2 Resource Definition

Resource URI: **{apiRoot}/a1-policy-management /<apiVersion>/policy-types/{policyTypeId}**

The resource URI variables supported by the resource are defined in Table 9.1.5.3.2-1.

Table 9.1.5.3.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.2.
apiVersion	See clause 9.1.2.
policyTypeId	The policy type identifier as defined in A1TD [24].

9.3.5.3.3 Resource Standard Methods

9.3.5.3.3.1 GET

This method shall support the URI query parameters specified in table 9.1.5.3.3.1-1, and the response data structure and response code specified in the table 9.1.5.3.3.1-2.

Table 9.1.5.3.3.1-1: Data structures supported by the HTTP GET request body on this resource.

Data type	P	Cardinality	Description
N/A			There is no object in the message content of a GET request.

Table 9.1.5.3.3.1-2: Data structures supported by the HTTP GET response body on this resource.

Data type	P	Cardinality	Response codes	Description
PolicyTypeObject	M	1	200 OK	Requested policy type object as defined in A1TD [24].
ProblemDetails	O	0..1	4xx/5xx	Detailed problem description.

9.1.5.3.4 Resource Custom Operations

None.

9.1.5.4 Resource: "All A1 policies"

9.1.5.4.1 Description

The resource All A1 policies represents the A1 policy that are available in the A1 policy management service.

Only the methods defined in clause 9.1.5.4.3 shall be supported by these resources.

9.1.5.4.2 Resource Definition

Resource URI: **{apiRoot}/a1-policy-management /<apiVersion>/policies**

The resource URI variables supported by the resource are defined in Table 9.1.5.4.2-1.

Table 9.1.5.4.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.2.
apiVersion	See clause 9.1.2.

9.1.5.4.3 Resource Standard Methods

9.1.5.4.3.1 GET

This method shall support the URI query parameters specified in table 9.1.5.4.3.1-1, the request data structure specified in the table 9.1.5.4.3.1-2 and the response data structure and response code specified in the table 9.1.5.4.3.1-3.

Table 9.1.5.4.3.1-1: URI query parameters supported by the GET method on this resource.

Name	Data type	P	Cardinality	Description	Applicability
nearRtRicId	string	O	0..1	The identifier of Near-RT RIC (See NOTE).	
policyTypeId	string	O	0..1	The identifier of the policy (See NOTE).	
NOTE: If multiple query parameters are provided these shall be combined with AND when evaluating the query.					

Table 9.1.5.4.3.1-2: Data structures supported by the HTTP GET request body on this resource.

Data type	P	Cardinality	Description
N/A			There is no object in the message content of a GET request

Table 9.1.5.4.3.1-3: Data structures supported by the HTTP GET response body on this resource.

Data type	P	Cardinality	Response codes	Description
array(PolicyInformation)	M	0..N	200 OK	The operation is successful, and the response body carries a list of policy information entries.
ProblemDetails	O	0..1	4xx/5xx	Detailed problem description
NOTE 1: If a Near-RT RIC identifier has been provided as query parameter, the response body shall contain only entries for policies existing in the related Near-RT RIC.				
NOTE 2: If a policy type identifier has been provided as query parameter, the response body shall contain only entries for policies of the related policy type.				
NOTE 3: If both a Near-RT RIC identifier and a policy type identifier have been provided as query parameters, the response body shall contain only entries for policies of the related policy type existing in the related Near-RT RIC.				

9.1.5.4.3.2 POST

This method shall support the request data structures specified in table 9.1.5.4.3.2-1 and the response data structures and response codes specified in table 9.1.5.4.3.2-2 and the HTTP headers specified in table 9.1.5.4.3.2-3.

Table 9.1.5.4.3.2-1: Data structures supported by the HTTP POST request body on this resource.

Data type	P	Cardinality	Description
PolicyObjectInformation	M	1	Information related to the creation of the policy.

Table 9.1.5.4.3.2-2: Data structures supported by the HTTP POST response body on this resource.

Data type	P	Cardinality	Response codes	Description
PolicyObjectInformation	M	1	201 Created	Confirmation of creation of the policy.
ProblemDetails	O	0..1	4xx/5xx	Detailed problem description.

Table 9.1.5.4.3.2-3: Headers supported by the 201 Response Code on this resource.

Name	Data type	P	Cardinality	Description
Location	string	M	1	Contains the URI of the newly created "Individual registered" A1 policy resource, as defined in clause 9.1.5.3, with the policyId in the URI.

9.1.5.4.4 Resource Custom Operations

None.

9.1.5.5 Resource: "Individual A1 policy"

9.1.5.5.1 Description

The resource Individual A1 policy represents an A1 policy created by the A1 policy management service.

Only the methods defined in clause 9.1.5.5.3 shall be supported by these resources.

9.1.5.5.2 Resource Definition

Resource URI: {apiRoot}/a1-policy-management /<apiVersion>/policies/{policyId}

The resource URI variables supported by the resource are defined in Table 9.1.5.5.2-1.

Table 9.1.5.5.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.2.
apiVersion	See clause 9.1.2.
policyId	Policy Identifier of the policy as defined in A1AP [23].

9.1.5.5.3 Resource Standard Methods

9.1.5.5.3.1 PUT

This method shall support the request data structures specified in table 9.1.5.5.3.1-1 and the response data structure and response codes specified in table 9.1.5.5.3.1-2.

Table 9.1.5.5.3.1-1: Data structures supported by the HTTP PUT request body on this resource.

Data type	P	Cardinality	Description
PolicyObject	M	1	Update the Policy.

Table 9.1.5.5.3.1-2: Data structures supported by the HTTP PUT response body on this resource.

Data type	P	Cardinality	Response codes	Description
PolicyObject	M	1	200 OK	Confirmation of updated policy.
ProblemDetails	O	0..1	4xx/5xx	Detailed problem description.

9.1.5.5.3.2 GET

This method shall support the request data structures specified in table 9.1.5.5.3.2-1 and the response data structures and response codes specified in table 9.1.5.5.3.2-2.

Table 9.1.5.5.3.2-1: Data structures supported by the HTTP GET request body on this resource.

Data type	P	Cardinality	Description
N/A		0	There is no object in the message content of a GET request.

Table 9.1.5.5.3.2-2: Data structures supported by the HTTP GET response body on this resource.

Data type	P	Cardinality	Response codes	Description
PolicyObject	M	1	200 OK	Requested policy object.
ProblemDetails	O	0..1	4xx/5xx	Detailed problem description.

9.1.5.5.3.3 DELETE

This method shall support the request data structures specified in table 9.1.5.5.3.3-1 and the response data structures and response codes specified in table 9.1.5.5.3.3-2.

Table 9.1.5.5.3.3-1: Data structures supported by the HTTP DELETE request body on this resource.

Data type	P	Cardinality	Description
N/A			There is no object in the message content of a DELETE request.

Table 9.1.5.5.3.3-2: Data structures supported by the HTTP DELETE response body on this resource.

Data type	P	Cardinality	Response codes	Description
N/A			204 No content	Confirmation of successful deletion.
ProblemDetails	O	0..1	4xx/5xx	Detailed problem description.

9.1.5.5.4 Resource Custom Operations

None.

9.1.5.6 Resource: "Individual A1 policy status"

9.1.5.6.1 Description

The resource Individual A1 policy status represents the status of an A1 policy that is available in the A1 policy management service.

Only the methods defined in clause 9.1.5.6.3 shall be supported by these resources.

9.1.5.6.2 Resource Definition

Resource URI: **{apiRoot}/a1-policy-management /<apiVersion>/policies/{policyId}/status**

The resource URI variables supported by the resource are defined in Table 9.1.5.6.2-1.

Table 9.1.5.6.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.2.
apiVersion	See clause 9.1.2.

9.1.5.6.3 Resource Standard Methods

9.1.5.6.3.1 GET

This method shall support the request data structures specified in table 9.1.5.6.3.1-1 and the response data structures and response codes specified in table 9.1.5.6.3.1-2.

Table 9.1.5.6.3.1-1: Data structures supported by the HTTP GET request body on this resource.

Data type	P	Cardinality	Description
N/A		0	There is no object in the message content of a GET request.

Table 9.1.5.6.3.1-2: Data structures supported by the HTTP GET response body on this resource.

Data type	P	Cardinality	Response codes	Description
PolicyStatusObject	M	1	200 OK	Requested policy status object as defined in A1TD[24], clause 6.4.2.
ProblemDetails	O	0..1	4xx/5xx	Detailed problem description.

9.1.5.6.4 Resource Custom Operations

None.

9.1.5.7 Resource: "All A1 policy status subscriptions"

9.1.5.7.1 Description

The resource represents the subscriptions for A1 policy status notifications.

The methods defined in clause 9.1.5.7.3 shall be supported by this resource.

9.1.5.7.2 Resource Definition

Resource URI: {apiRoot}/a1-policy-management /<apiVersion>/policies/subscriptions

The resource URI variables supported by the resource are defined in table 9.1.5.7.2-1.

Table 9.1.5.7.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.2.
apiVersion	See clause 9.1.2.

9.1.5.7.3 Resource Standard Methods

9.1.5.7.3.1 POST

This method shall support the request data structures specified in table 9.1.5.7.3.1-1 and the response data structures and response codes specified in table 9.1.5.7.3.1-2 and the HTTP headers specified in table 9.1.5.7.3.1-3.

Table 9.1.5.7.3.1-1: Data structures supported by the HTTP POST request body on this resource.

Data type	P	Cardinality	Description
PolicyStatusSubscription	M	1	Information of A1 Policy status subscription information.

Table 9.1.5.7.3.1-2: Data structures supported by the POST response body on this resource.

Data Type	P	Cardinality	Response codes	Description
PolicyStatusSubscription	M	1	201 Created	The operation was successful. The message content of the POST response contains a PolicyStatusSubscriptionInfo representing the created resource.
ProblemDetails	O	0..1	4xx/5xx	The operation was unsuccessful. Detailed problem description may be carried in the response message content.

Table 9.1.5.7.3.1-3: Headers supported by the 201-response code on the resource.

Name	Data type	P	Cardinality	Description
Location	String	M	1	Contains the URI of the newly created "Individual A1 policy status subscription" resource as defined in clause 9.1.5.5.2 with subscriptionId in the URI.

9.1.5.7.4 Resource Custom Operations

None

9.1.5.8 Resource: "Individual A1 policy status subscription"

9.1.5.8.1 Description

The resource represents a subscription for A1 policy status notifications.

The methods defined in clause 9.1.5.8.3 shall be supported by this resource.

9.1.5.8.2 Resource Definition

Resource URI: **{apiRoot}/a1-policy-management /<apiVersion>/policies/subscriptions/{subscriptionId}**

The resource URI variables supported by the resource are defined in Table 9.1.5.8.2-1.

Table 9.1.5.8.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.2.
apiVersion	See clause 9.1.2.
subscriptionId	Identifier of subscription.

9.1.5.8.3 Resource Standard Methods

9.1.5.8.3.1 PUT

This method shall support the request data structures specified in table 9.1.5.8.3.1-1 and the response data structure and response codes specified in table 9.1.5.8.3.1-2.

Table 9.1.5.8.3.1-1: Data structures supported by the HTTP PUT request body on this resource.

Data type	P	Cardinality	Description
PolicyStatusSubscription	M	1	Updated Policy status subscription information.

Table 9.1.5.8.3.1-2: Data structures supported by the HTTP PUT response body on this resource.

Data type	P	Cardinality	Response codes	Description
PolicyStatusSubscription	M	1	200 OK	Confirmation of updated policy status subscription.
ProblemDetails	O	0..1	4xx/5xx	The operation has failed, and the message content may contain Problem description details.

9.1.5.8.3.2 GET

This method shall support the request data structures specified in table 9.1.5.8.3.2-1 and the response data structures and response codes specified in table 9.1.5.8.3.2-2.

Table 9.1.5.8.3.2-1: Data structures supported by the HTTP GET request body on this resource.

Data type	P	Cardinality	Description
N/A		0	There is no object in the message content of a GET request.

Table 9.1.5.8.3.2-2: Data structures supported by the HTTP GET response body on this resource.

Data type	P	Cardinality	Response codes	Description
PolicyStatusSubscription	M	1	200 OK	Requested policy status subscription information associated with the subscriptionId has been queried successfully and the response contains the PolicyStatusSubscriptionInfo as representation of the queried resource.
ProblemDetails	O	0..1	4xx/5xx	The operation has failed, and the message content may contain Problem description details.

9.1.5.8.3.3 DELETE

This method shall support the request data structures specified in table 9.1.5.8.3.3-1 and the response data structures and response codes specified in table 9.1.5.8.3.3-2.

Table 9.1.5.8.3.3-1: Data structures supported by the HTTP DELETE request body on this resource.

Data type	P	Cardinality	Description
N/A			There is no object in the message content of a DELETE request.

Table 9.1.5.8.3.3-2: Data structures supported by the HTTP DELETE response body on this resource.

Data type	P	Cardinality	Response codes	Description
N/A			204 No content	Confirmation of successful deletion.
ProblemDetails	O	0..1	4xx/5xx	The operation has failed, and the message content may contain Problem description details.

9.1.5.8.4 Resource Custom Operations

None.

9.1.6 Custom operation without associated resources

None.

9.1.7 Notifications

9.1.7.1 Resource: Policy status change notifications

9.1.7.1.1 Description

The resource represents the destination for A1 policy status change notifications.

9.1.7.1.2 Resource Definition

The resource URI (notificationDestination) is provided when subscribing to A1 policy status notifications.

9.1.7.1.3 Resource Standard Methods

9.1.7.1.3.1 POST

This method shall support the request data structures specified in table 9.1.7.1.3.1-1 and the response data structure and response codes specified in table 9.1.7.1.3.1-2.

Table 9.1.7.1.3.1-1: Data structures supported by the HTTP POST request body on this resource

Data type	P	Cardinality	Description
A1PolicyStatusChange Notification	M	1	Notify policy status change as specified in clause 9.1.8.1.6.

Table 9.1.7.1.3.1-2: Data structures supported by the HTTP POST response body on this resource

Data type	P	Cardinality	Response codes	Description
N/A			204 No content	Confirmation of received notification.

9.1.8 Data Model

9.1.8.1 Structured data types

9.1.8.1.1 Overview

The following clause defines the structured data types and their attributes to be used by the A1 policy management API.

9.1.8.1.2 Data type: PolicyTypeInfoInformation

The PolicyTypeInfoInformation data type represents a pair of policy type identifier and related Near-RT RIC identifier. It contains the attributes defined in table 9.1.8.1.2-1.

Table 9.1.8.1.2-1: Definition of type PolicyTypeInfoInformation.

Attribute Name	Data type	P	Cardinality	Description
policyTypeId	string	M	1	Policy Type identifier as defined in A1AP [23], clause 6.2.3.1.3.
nearRtRicId	NearRtRicId	M	1	Near-RT RIC identifier.

The data model for the data types transported is defined in A1TD [24].

9.1.8.1.3 Data type: PolicyInformation

The PolicyInformation data type represents a pair of policy identifier and related Near-RT RIC identifier. It contains the attributes defined in table 9.1.8.1.3-1.

Table 9.1.8.1.3-1: Definition of type PolicyInformation.

Attribute Name	Data type	P	Cardinality	Description
policyId	string	M	1	Policy Identifier of a policy as defined in A1AP [23].
nearRtRicId	NearRtRicId	M	1	Near-RT RIC identifier.

9.1.8.4 Data type: PolicyObjectInformation

The PolicyObjectInformation data type represents a policy object, related Near-RT RIC identifier and optional policy type identifier. It contains the attributes defined in table 9.1.8.1.4-1.

Table 9.1.8.1.4-1: Definition of type PolicyObjectInformation

Attribute Name	Data type	P	Cardinality	Description
policyObject	object	M	1	Policy Object is a JSON representation of an A1 policy; the A1 policies are specified in A1TD [24].
nearRtRicId	NearRtRicId	M	1	Near-RT RIC identifier.
policyTypeId	PolicyTypeId	O	0..1	policy type identifier as defined in A1AP [23].

9.1.8.1.5 Data type: PolicyStatusSubscription

The PolicyStatusSubscription data type represents the subscription information of A1 policy status. It contains the attributes defined in table 9.1.8.1.5-1.

Table 9.1.8.1.5-1: Definition of type PolicyStatusSubscription

Attribute Name	Data type	P	Cardinality	Description
subscriptionScope	QueryFilter	C	1	See clause 9.1.8.3.3.1. See NOTE 2, NOTE 4, NOTE 6, NOTE 8, NOTE 10.
notificationDestination	URI	M	1	Call back URI for A1 policy status notifications
policyIdList	array(policyId)	C	1..N	List of identifiers of A1 policies as defined in clause 6.2.6 of A1AP [23]. See NOTE 1 ,NOTE 3 and NOTE 4.
policyTypeIdList	array(policyTypeId)	C	1..N	List of A1 policy type identifiers as defined in clause 9.1.5.4.3.1 See NOTE 1, NOTE 5, NOTE 6, NOTE9 and NOTE 10.
nearRtRicIdList	array(NearRtRicId)	C	1..N	List of Near-RT RIC identifiers as defined in clause 9.1.5.4.3.1. See NOTE 1, NOTE 7, NOTE 8, NOTE9 and NOTE 10.

NOTE 1: It is conditionally optional to include either a policyIdList; or a policyTypeIdList; or a nearRtRicIdList; or a policyTypeIdList and a nearRtRicIdList; or none of the lists.

NOTE 2: If neither policyIdList nor policyTypeIdList nor nearRtRicIdList is provided, then a subscriptionScope shall be provided.

NOTE 3: If a policyIdList is provided, the subscription is for the status of the indicated A1 policies.

NOTE 4 : If a policyIdList is provided then subscriptionScope shall not be provided.

NOTE 5: If a policyTypeIdList is provided, the subscription is for the status of A1 policies of the indicated A1 policy types.

NOTE 6: If both policyTypeIdList and subscriptionScope are provided, then the subscription is for the status of A1 policies of the indicated A1 policy types that fulfill the subscriptionScope.

NOTE 7: If a nearRtRicIdList is provided, the subscription is for the status of A1 policies created in the indicated Near-RT RICs.

NOTE 8: If both nearRtRicIdList and subscriptionScope are provided, then the subscription is for the status of A1 policies created in the indicated Near-RT RICs that fulfill the subscriptionScope.

NOTE 9: If both policyTypeIdList and nearRtRicIdList are provided, then the subscription is for the status of A1 policies of the indicated A1 policy types created in the indicated Near-RT RICs.

NOTE 10: If policyTypeIdList, nearRtRicIdList and subscriptionScope are provided, then the subscription is for the status of A1 policies of the indicated A1 policy types created in the indicated Near-RT RICs that fulfill the subscriptionScope.

9.1.8.1.6 Data type: A1PolicyStatusChangeNotification

Table 9.1.8.1.6-1: Definition of type A1PolicyStatusChangeNotification

Attribute Name	Data type	P	Cardinality	Description
subscriptionId	SubscriptionId	M	1	Identifier of Subscription as specified in clause 9.1.5.5.2.
policyStates	array(SubscriptionStatusObject)	M	1..N	List of policy states to be notified about.

9.1.8.1.7 Data type: SubscriptionStatusObject

Table 9.1.8.1.7-1: Definition of type SubscriptionStatusObject

Attribute Name	Data type	P	Cardinality	Description
policyId	PolicyId	M	1	Policy identifier as specified in clause 6.2.6 of A1AP [23].
policyStatusObject	PolicyStatusObject	M	1..N	Policy status object as specified in clause 6.4.2 of A1TD [24].

9.1.8.2 Simple data types and enumerations

9.1.8.2.1 Introduction

The following clause defines simple data types and enumerations that can be referenced from data structures defined in the previous clauses.

9.1.8.2.2 Simple data types

The resource identifiers defined in clause include policy type identifier and policy identifier based on the simple data types specified in table 9.1.8.2.2-1.

Table 9.1.8.2.1-1: General definition of simple data types

Type Name	Type Definition	Description	Applicability
PolicyTypeId	string	policy type identifier as defined in A1TD [24].	
PolicyId	string	policy identifier of an A1 policy as defined in A1 AP [23].	
NearRtRicId	string	Near RT RIC identifier.	

9.1.8.3.3 Enumerations

9.1.8.3.3.1 Enumeration: QueryFilter

This indicates whether the request is for A1 policies created by the requesting API Consumer, for A1 policies created by other API Consumers, or for all A1 policies created by any API Consumer.

Table 9.1.8.3.3.1 -1: Enumeration type of QueryFilter

Enumerations Value	Description
OWN	indicate the A1 policies created by API Consumer.
OTHERS	indicate the A1 policies created other API Consumers.
ALL	indicate the A1 policies created by any API Consumers.

9.1.8.3 Re-used data types

None.

9.1.8.4 Service-specific registration information

None.

9.1.9 Error Handling

9.1.9.1 General

In addition to the general provisions in clause 5.4.3, the requirements in the following clauses are applicable for the A1 policy management API.

9.1.9.2 Protocol Errors

No specific protocol errors are defined in the present document.

9.1.9.3 Application Errors

The application errors defined for the A1 policy management service are listed in table 9.1.9.3-1.

Table 9.1.9.3-1: Application errors

Application Error	HTTP status code	Description
Unauthorized	401	Used when the API consumer lacks proper authentication credentials or has provided invalid credentials
Forbidden	403	Used when the API Consumer has successfully authenticated the user, but the user is still denied access to the requested resource.
Bad Request	400	Used when the A1 policy management service cannot or will not process a request, e.g., when the validation of PolicyObject towards a policy type schema, or the validation of PolicyStatusObject towards a policy status schema, fails.
Not Found	404	Used when the Near-RT RIC did not find a current representation for the resource representing a policy type or a policy, e.g., for a policy type that is not available or a policy that does not exist.
Method Not Allowed	405	Used when the HTTP method is not supported by the resource defined for the A1 policy management API.
Conflict	409	Used if detecting that a policy requested to be created or updated may be overlapping or conflicting with a policy that exists in the Near-RT RIC.

Application errors should be mapped to the most applicable 4xx/5xx HTTP error status code. If no such status code is applicable, one of the status codes 400 (Bad Request) or 500 (Internal Server Error) should be used.

The HTTP status codes listed in table 9.1.9.3-1 shall be used as defined in clause 5.4.3 for the A1 policy management procedures and clause 9.1.5 for the resources.

Implementations may use additional HTTP error status codes in addition to those listed in table 9.1.9.3-1, as long as they are valid HTTP status codes.

A list of all valid HTTP status codes and their specification documents can be obtained from the HTTP status code registry [21].

In addition, the response body may contain a JSON representation of a “ProblemDetails” data structure in the payload body as defined in clause 9.1.8.2.2. In that case, as defined by IETF RFC 7807 [10], the “Content-Type” HTTP header shall be set to “application/problem+json”.

10. AI/ML workflow services

10.1 AI/ML model registration API

10.1.1 Introduction

This API enables the API Consumer to register, query, update and deregister an AI/ML model based on the AI/ML model registration service defined in R1GAP [5].

10.1.2 API version

For the AI/ML model registration API as specified in the present document, the MAJOR version field shall be 1, the MINOR version field shall be 0 and the PATCH version field shall be 0 (see 3GPP TS 29.501 [1] for a definition of the version fields). Consequently, the <apiVersion> URI path segment shall be set to “v1”.

10.1.3 Resource structure and methods

The request URIs used in HTTP requests from the API Consumer towards the API Producer shall have the resource URI structure as defined in clause 5.2. The <apiName> resource URI variable shall be “ai-ml-model-registration”. The <apiSpecificResourceUriPart> for each resource shall be set as described in clause 10.1.5.

Figure 10.1.3-1 shows the overall resource URI structure defined for the model registration API.




Figure 10.1.3-1: Resource URI structure of the AI/ML model registration API

Table: 10.1.3-1 1 lists the individual resources defined for the API, the applicable HTTP methods, and the associated service operations.

Table 10.1.3-1: Resource and methods overview of the AI/ML model registration API

Resource name	Resource URI	HTTP method	Service Operation
Registered model registrations	.../ model-registrations	POST	Register model information.
Individual registered model registration	.../ model-registrations/{modelRegistrationId}	GET	Query model registration information.
		PUT	Update model registration information.
		DELETE	Deregister model registration information.

10.1.4 Service operations


10.1.4.1 Register model information

10.1.4.1.1 Operation definition

The API Consumer uses this operation to register AI/ML model information.

The operation to register the model information is based on HTTP POST.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer -->> Producer: POST .../model-registrations (ModelRelatedInformation)
Producer -->> Consumer: 201 Created (ModelRelatedInformation)
@enduml
```


Figure 10.1.4.1.1 -1: Register model information operation

The service operation is as follows:

1. The API Consumer shall send an HTTP POST request to the API Producer. The target URI shall identify the resource (.../model-registrations) under which the new registration is requested to be created. The message content shall carry a ModelRelatedInformation structure.
2. The API Producer shall generate the model registration identifier and construct the URI for the created resource. The API Producer shall return the HTTP POST response. On success, "201 Created" shall be returned. The "Location" header shall be present and shall carry the URI of the new registration resource. The message content shall carry a ModelRelatedInformation structure that represents the new resource. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

10.1.4.1.2 Referenced procedures.

10.1.4.1.2.1 Register AI/ML model procedure

The Register model information operation illustrated in figure 10.1.4.1.1-1. is based on the Register AI/ML model procedure defined for the AI/ML workflow services in R1GAP [5].

10.1.4.2 Deregister model information.

10.1.4.2.1 Operation definition

The API Consumer uses this operation to delete the registered model information.

The operation to deregister an AI/ML model information that was previously registered is based on HTTP DELETE.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: DELETE ../model-registrations/{modelRegistrationId}
Producer -->> Consumer: 204 No Content
@enduml
```




Figure 10.1.4.2.1 -1: Deregister model information operation

The service operation is as follows:

1. The API Consumer shall send an HTTP DELETE request to the API Producer. The target URI shall identify the resource to be deleted (`../model-registrations/{modelRegistrationId}`).
2. The API Producer shall return the HTTP DELETE response. On success, "204 No Content" shall be returned and the response message content shall be empty. On failure, the appropriate error code shall be returned, and the message response content may contain additional error information.

10.1.4.2.2 Referenced procedures.

10.1.4.2.2.1 Deregister AI/ML Model procedure.

The Deregister model information operation illustrated in figure 10.1.4.2.1-1 is based on the Deregister AI/ML model procedure defined for the AI/ML workflow services in R1GAP [5].

10.1.4.3 Update model information

10.1.4.3.1 Operation definition

The API Consumer uses this operation to Update model information.

The operation to update the model information is based on HTTP PUT.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: PUT.../model-registrations/{modelRegistrationId} (ModelRelatedInformation)
Producer -->> Consumer: 200 OK (ModelRelatedInformation)
@enduml
```




Figure 10.1.4.3.1 -1: Update model information operation

The service operation is as follows:

1. The API Consumer shall send an HTTP PUT request to the API Producer. The target URI shall identify the resource (.../model-registrations/{modelRegistrationId}). The message content shall carry an updated ModelRelatedInformation structure. The API producer shall process the HTTP PUT message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP PUT response. On success, "200 OK" shall be returned. The message body shall contain updated ModelRelatedInformation structure. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

10.1.4.3.2 Referenced procedures.

10.1.4.3.2.1 Update AI/ML model registration procedure

The Update model information operation illustrated in figure 10.1.4.1.1-1. is based on the Update AI/ML model registration procedure defined for the AI/ML workflow services in R1GAP [5].

10.1.4.4 Query model information

10.1.4.4.1 Operation definition

The API Consumer uses this operation to query model information that it has previously registered.

The operation to query model information is based on HTTP GET.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: GET .../model-registrations/{modelRegistrationId}
Producer -->> Consumer: 200 OK (ModelRelatedInformation)
@enduml
```




Figure 10.1.4.4.1 -1: Query model information operation

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer. The target URI shall identify the resource (.../model-registrations/{modelRegistrationId}). The message content shall be empty. The API producer shall process the HTTP GET message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP GET response. On success, "200 OK" shall be returned. The message content shall carry the queried model related information. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

10.1.4.4.2 Referenced procedures.

10.1.4.4.2.1 Query AI/ML model registration procedure

The Query model information operation illustrated in figure 10.1.4.4.1-1. is based on the Query AI/ML model registration procedure defined for the AI/ML workflow services in R1GAP [5].

10.1.5 Resources

10.1.5.1 Overview

The following clause defines the resources for the AI/ML model registration API.

10.1.5.2 Resource: "Registered model registrations"

10.1.5.2.1 Description

The resource represents the model information of an rApp that it wants to register.

Only the methods defined in clause 10.1.5.2.3 shall be supported by this resource.

10.1.5.2.2 Resource Definition

Resource URI: {apiRoot}/ai-ml-model-registration/<apiVersion>/model-registrations

The resource URI variables supported by the resource is defined in Table 10.1.5.2.2-1.

Table 10.1.5.2.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.2.
apiVersion	See clause 10.1.2.

10.1.5.2.3 Resource Standard Methods

10.1.5.2.3.1 POST

This method shall support the request data structure specified in the table 10.1.5.2.3.1-1 and the response data structure and response code specified in the table 10.1.5.2.3.1-2, and the HTTP headers specified in table 10.1.5.2.3.1-3.

Table 10.1.5.2.3.1-1: Data structures supported by the POST request body on this resource.

Data Type	P	Cardinality	Description
ModelRelatedInformation	M	1	Information related to the model

Table 10.1.5.2.3.1-2: Data structures supported by the POST response body on this resource.

Data Type	P	Cardinality	Response codes	Description
ModelRelatedInformation	M	1	201 Created	The operation was successful, and the message content of the POST response contains a ModelRelatedInformation structure as a representation of the created resource.
ProblemDetails	O	0..1	4xx/5xx	The operation has failed, and the message content may contain Problem description details.

Table 10.1.5.2.3.1-3: Headers supported by the 201 Response Code on this resource.

Name	Data type	P	Cardinality	Description
Location	string	M	1	Contains the URI of the newly created "Individual registered ModelInformation" resource, as defined in clause 10.1.5.3, with the registrationId in the URI.

10.1.5.3 Resource: "Individual registered model registration"

10.1.5.3.1 Description

The resource represents the model information of an rApp that it wants to update, deregister, and query.

Only the methods defined in clause 10.1.5.3.3 shall be supported by this resource.

10.1.5.3.2 Resource Definition

Resource URI: {apiRoot}/ai-ml-model-registration/<apiVersion>/model-registrations/{modelRegistrationId}

The resource URI variables supported by the resource are defined in Table 10.1.5.3.2-1.

Table 10.1.5.3.2-1: Resource URI variables for the resource.

Name	Definition
apiRoot	See clause 5.2.
apiVersion	See clause 10.1.2.
modelRegistrationId	The registration identifier of the model.

10.1.5.3.3 Resource Standard Methods

10.1.5.3.3.1 DELETE

This method shall support the request data structure specified in table 10.1.5.3.3.1-1 and the response data structure and response code specified in 10.1.5.3.3.1-2.

Table 10.1.5.3.3.1-1: Data structure supported by the DELETE request body on this resource.

Data type	P	Cardinality	Description
N/A			A DELETE request has no message content.

Table 10.1.5.3.3.1-2: Data structure supported by the DELETE response body on this resource.

Data type	P	Cardinality	Response codes	Description
N/A			204 No Content	The AI/ML model registration associated with the modelRegistrationId has been deleted successfully. The message content shall be empty.
ProblemDetails	O	0..1	4xx/5xx	The operation has failed, and the message content may contain Problem description details.

10.1.5.3.3.2 PUT

This method shall support the request data structure specified in the table 10.1.5.3.3.2-1 and the response data structure and response code specified in the table 10.1.5.3.3.2-2.

Table 10.1.5.3.3.2-1: Data structures supported by the PUT request body on this resource.

Data Type	P	Cardinality	Description
ModelRelatedInformation	M	1	Updated model related information.

Table 10.1.5.3.3.2-2: Data structures supported by the PUT response body on this resource.

Data Type	P	Cardinality	Response codes	Description
ModelRelatedInformation	M	1	200 OK	The model related information associated with the modelRegistrationId has been updated successfully and the response contain the ModelRelatedInformation as a representation of the updated resource.
ProblemDetails	O	0..1	4xx/5xx	The operation has failed, and the message content may contain Problem description details.

10.1.5.3.3.3 GET

This method shall support the request data structure specified in the table 10.1.5.3.3.3-1 and the response data structure and response code specified in the table 10.1.5.3.3.3-2.

Table 10.1.5.3.3.3-1: Data structures supported by the GET request body on this resource.

Data Type	P	Cardinality	Description
N/A			A GET request has no message content

Table 10.1.5.3.3-2: Data structures supported by the GET response body on this resource.

Data Type	P	Cardinality	Response codes	Description
ModelRelatedInformation	M	1	200 OK	The model related information registration associated with the modelRegistrationId has been queried successfully and the response contain the ModelRelatedInformation as a representation of the query resource.
ProblemDetails	O	0..1	4xx/5xx	The operation has failed, and the message content may contain Problem description details.

10.1.5.3.4 Resource Custom Operations

None.

10.1.6 Custom operation without associated resources.

None.

10.1.7 Notifications

None.

10.1.8 Data Model

10.1.8.1 Structured data types

10.1.8.1.1 Overview

The following clauses define the structured data types and their attributes to be used by the AI/ML model registration API.

10.1.8.1.2 Data type: ModelRelatedInformation

The ModelRelatedInformation data type represents registration information for an AI/ML model . It contains the attributes defined in table 10.1.8.1.2-1.

Table 10.1.8.1.2-1: Definition of type ModelRelatedInformation.

Attribute Name	Data type	P	Cardinality	Description
modelId	ModelId	M	1	Identifier of a model
description	string	M	1	Description of the AIML model
modelInformation	ModelInformation	M	1	Information of the AIML model
modelLocation	URI	O	0..1	Location of the model stored in the runtime catalogue that can be discovered and referred to when using AI/ML workflow services.

10.1.8.1.3 Data type: ModelId

The ModelId data type represents information of AI/ML model . It contains the attributes defined in table 10.1.8.1.3-1.

Table 10.1.8.1.3-1: Definition of type ModelId.

Attribute Name	Data type	P	Cardinality	Description
modelName	String	M	1	Name of the model as specified in R1GAP [1].
modelVersion	String	M	1	Version of the model as specified in R1GAP [1].
artifactVersion	String	O	0..1	Artifact version of AIML model as specified in R1GAP [1].

10.1.8.1.4 Data type: ModelInformation

The Model information data type contains the attributes defined in table 10.1.8.1.4-1.

Table 10.1.8.1.4-1: Definition of type ModelInformation.

Attribute Name	Data type	P	Cardinality	Description
metadata	MetaData	M	1	Metadata of the model.
inputDataType	array(dataTypeId)	M	1..N	Input data type for the model, the structure of dataTypeId is specified in clause 7.1.8.
outputDataType	array(dataTypeId)	M	1..N	Output data type for the model, the structure of dataTypeId is specified in clause 7.1.8.
targetEnvironment	array(TargetEnvironment)	O	0..N	Information on the target environment is required for deployment of an AI/ML model.

10.1.8.1.5 Data type: MetaData

The Metadata data type contains the attributes defined in table 10.1.8.1.5-1.

Table 10.1.8.1.5-1: Definition of type MetaData.

Attribute Name	Data type	P	Cardinality	Description
author	String	M	1	Author of the AIML model.
owner	String	O	0..1	Ownership of the AIML model to regulate how the model can be used in the Run-Time environment.

10.1.8.1.6 TargetEnvironment

The TargetEnvironment data type contains the attributes defined in table 10.1.8.1.6-1.

Table 10.1.8.1.6-1: Definition of type TargetEnvironment

Attribute Name	Data type	P	Cardinality	Description
platformName	String	M	1	Name of the platform.
environmentType	String	M	1	Name of the platform Execution service type, and this is dependent on the platformName.
dependencyList	URI	M	1	Location to the template that has all the list of dependencies platform must provide needs to be installed for the model. (for example, scikit-learn 0.21.3).

10.1.8.2 Simple data types and enumerations

10.1.8.2.1 Enumerations

For this AI/ML model registration API, no enumerations are defined in the present document.

10.1.9 Error Handling

10.1.9.1 General

In addition to the general provisions in clause 5.4.3, the requirements in the following clauses are applicable for the AI/ML model Registration API.

10.1.9.2 Protocol Errors

No specific protocol errors are defined in the present document.

10.1.9.3 Application Errors

No additional application errors defined in the present document.

10.2 AI/ML model discovery API

10.2.1 Introduction

This API enables the API Consumer to discover an AI/ML model based on the AI/ML model discovery service defined in R1GAP [5].

10.2.2 API version

For the AI/ML model discovery API as specified in the present document, the MAJOR version field shall be 1, the MINOR version field shall be 1 and the PATCH version field shall be 0 (see 3GPP TS 29.501 [1] for a definition of the version fields). Consequently, the <apiVersion> URI path segment shall be set to “v1.1”.

10.2.3 Resource structure and methods

The request URIs used in HTTP requests from the API Consumer towards the API Producer shall have the resource URI structure as defined in clause 5.2. The <apiName> resource URI variable shall be “ai-ml-model-discovery”.

Figure 10.2.3-1 shows the overall resource URI structure defined for the AI/ML model discovery API.




Figure 10.2.3-1: Resource URI structure of the AI/ML model discovery API

Table: 10.2.3-1 lists the individual resources defined for the API, the applicable HTTP methods, and the associated service operations.

Table 10.2.3-1: Resource and methods overview of the AI/ML model discovery API

Resource name	Resource URI	HTTP method	Service Operation
ALL registered models	.../models	GET	Discover registered AI/ML models
Individual AI/ML model	/models/{modelId}	GET	Query AI/ML model

10.2.4 Service operations

10.2.4.1 Discover AI/ML models

The API Consumer uses this operation to discover the registered AI/ML models.

The operation to discover the AI/ML models is based on HTTP GET.

```

@startuml
autonumber
Participant "API Consumer" as Consumer
  
```

```

Participant "API Producer" as Producer
Consumer ->> Producer: GET .../models
Producer -->> Consumer: 200 OK (array(ModelRelatedInformation))
@enduml

```




Figure 10.2.4.1-1: Discover models operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer. The target URI shall identify the resource (.../models) and may also contain query parameters to discover the registered model identifiers. The API Producer shall process the request received in the HTTP GET message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP GET response. On success, "200 OK" shall be returned and the message content shall carry an array of ModelRelatedInformation that shall include modelId and corresponding metadata. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

10.2.4.1.2 Referenced procedures.

10.2.4.1.2.1 Discover AI/ML model procedure.

The Discover AI/ML models operation illustrated in figure 10.2.4.1-1 is based on the Discover AI/ML model procedure defined for the AI/ML workflow service in R1GAP [5].

10.2.4.2 Query AI/ML models

The API Consumer uses this operation to query location information about a registered AI/ML model.

The operation to query the AI/ML models is based on HTTP GET.

```

@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: GET /models/{modelId}
Producer -->> Consumer: 200 OK (ModelLocationInfomation)
@enduml

```




Figure 10.2.4.2-1: Query models operation.

- 1) The API Consumer shall send an HTTP GET request to the API Producer. The target URI shall identify the resource "/models/{modelId}", the message content shall carry a modelId. The API Producer shall process the request received in the HTTP GET message and determine if the request sent by the API Consumer is authorized or not.
- 2) The API Producer shall return the HTTP GET response. On success, "200 OK" shall be returned and the message content shall carry a ModelLocationInformation structure. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

10.2.4.2.2 Referenced procedures.

10.2.4.2.2.1 Discover AI/ML model procedure.

The Discover AI/ML models operation illustrated in figure 10.2.4.2-1 is based on the Discover AI/ML model procedure defined for the AI/ML workflow service in R1GAP [5].

10.2.5 Resources

10.2.5.1 Overview

This clause defines the resource for the AI/ML model discovery API.

10.2.5.2 Resource: "All registered models"

10.2.5.2.1 Description

The resource represents all registered AI/ML models in the Non-RT RIC.

The methods defined in clause 10.2.5.2.3 shall be supported by this resource.

10.2.5.2.2 Resource Definition

Resource URI: {apiRoot}/ai-ml-model-discovery/<apiVersion>/models

The resource URI variables supported by the resource is defined in table 10.2.5.2.2-1.

Table 10.2.5.2.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.2.
apiVersion	See clause 10.2.2.

10.2.5.2.3 Resource Standard Methods

10.2.5.2.3.1 GET

This method shall support the URI query parameters specified in table 10.2.5.2.3.1-1, the request data structure specified in the table 10.2.5.2.3.1-2 and the response data structures, and response code specified in the table 10.2.5.2.3.1-3.

Table 10.2.5.2.3.1-1: URI query parameters supported by the GET method on this resource.

Name	Data type	P	Cardinality	Description	Applicability
model-name	string	O	0..1	Name of the model as specified in R1GAP [5] (See NOTE).	
model-version	string	O	0..1	Version of the model as specified in R1GAP [5] (See NOTE).	

NOTE: If multiple query parameters are provided these shall be combined with AND when evaluating the query.

Table 10.2.5.2.3.1-2: Data structures supported by the GET request body on this resource.

Data Type	P	Cardinality	Description
N/A			There is no object in the message content of the GET request.

Table 10.2.5.2.3.1-3: Data structures supported by the HTTP GET response body on this resource.

Data type	P	Cardinality	Response codes	Description
array (ModelRelatedInformation)	O	0..N	200 OK	The message content of the GET response carries an array of model identifiers and metadata of the models.
ProblemDetails	O	0..1	4xx/5xx	Detailed problem description.

10.2.5.3 Resource; “Individual AI/ML model”

10.2.5.3.1 Description

The resource represents the model location.

The methods defined in clause 10.2.5.2.3 shall be supported by this resource.

10.2.5.3.2 Resource Definition

Resource URI: {apiRoot}/ai-ml-model-discovery/<apiVersion>/models/{modelId}

The resource URI variables supported by the resource is defined in table 10.2.5.3.2-1.

Table 10.2.5.3.2-1: Resource URI variable for the resource

Name	Definition
apiRoot	See clause 5.2
apiVersion	See clause 10.2.2

10.2.5.3.3 Resource Standard Methods

10.2.5.3.3.1 GET

This method shall support the request data structures specified in the table 10.2.5.3.3.1-1 and the response data structures and response codes specified in table 10.2.5.3.3.1-2.

Table 10.2.5.3.3.1-1: Data structures supported by the HTTP GET request body on this resource.

Data type	P	Cardinality	Description
modelId	M	1	The identifier of the model.

Table 10.2.5.3.1-2: Data structures supported by the HTTP GET Response Body on this resource.

Data type	P	Cardinality	Response codes	Description
ModelLocationInformation			200 OK	The model location related information associated with the modelId has been got successfully and the response contain the ModelLocationInformation as a representation of the updated resource.
ProblemDetails	O	0..1	4xx/5xx	Detailed problem description

10.2.5.3.4 Resource Custom Methods

None.

10.2.6 Custom operation without associated resources

None.

10.2.7 Notifications

NOTE: no notifications are specified in the current version of the present document.

10.2.8 Data Model

10.2.8.1 Structured data types

10.2.8.1.1 Overview

The following clause defines the structured data types and their attributes to be used by the service API.

10.2.8.1.2 Data type: ModelRelatedInformation

The ModelRelatedInformation data type represents registration information for an AI/ML model . It contains the attributes defined in table 10.2.8.1.2-1.

Table 10.2.8.1.2-1: Definition of type ModelRelatedInformation.

Attribute Name	Data type	P	Cardinality	Description
modelId	ModelId	M	1	Identifier of a model as specified in clause 10.1.8.1.3
metadata	string	M	1	Description of the AIML model that includes the AI/ML model related information and training related information.

10.2.8.1.3 Data type: ModelLocationInformation

The ModelLocationInformation data type represents location information for an AI/ML model . It contains the attributes defined in table 10.2.8.1.3-1.

Table 10.2.8.1.3-1: Definition of type ModelRelatedInformation.

Attribute Name	Data type	P	Cardinality	Description
locationUri	string	M	1	The URI where the AI/ML model artifact can be accessed.
modelId	ModelId	O	0..1	Identifier of a model as specified in clause 10.1.8.1.3.

10.2.8.2 Simple data types and enumerations

10.2.8.2.1 Introduction

The following clause defines simple data types and enumerations that can be referenced from data structures defined in the previous clauses.

10.2.8.2.2 Simple data types

For this service API, no simple data types are defined in the present document.

10.2.8.3.3 Enumerations

For this service API, no enumerations are defined in the present document.

10.2.9 Error Handling

10.2.9.1 General

In addition to the general provisions in clause 5.4.3, the requirements in the following clauses are applicable for the AI/ML model discovery API.

10.2.9.2 Protocol Errors

No specific protocol errors are defined in the present document.

10.2.9.3 Application Errors

No additional application errors defined in the present document.

10.3 AI/ML model training API

10.3.1 Introduction

This API enables the API Consumer to request AI/ML model training, query AI/ML model training job status, and cancel AI/ML model training based on the procedures for “AI/ML model training services” as defined in R1GAP [5]. It also allows the API Producer to notify AI/ML model training job status change based on the procedure for “AI/ML model training services” defined in R1GAP [5].

10.3.2 API version

For the AI/ML model training API as specified in the present document, the MAJOR version field shall be 1, the MINOR version field shall be 0, and the PATCH version field shall be 0 (see 3GPP TS 29.501 [1] for a definition of the version fields). Consequently, the <apiVersion> URI path segment shall be set to “v1”.

The AI/ML model training API is under development and consequently the API version shall include the pre-release version “alpha.1”.

10.3.3 Resource structure and methods

The request URIs used in HTTP requests from the API Consumer towards the API Producer shall have the resource URI structure as defined in clause 5.2. The <apiName> resource URI variable shall be “ai-ml-model-training”.

Figure 10.3.3-1 shows the overall resource URI structure defined for the AI/ML model training API.




Figure 10.3.3-1: Resource URI structure of the AI/ML model training API

Table: 10.3.3-1 lists the individual resources defined for the API, the applicable HTTP methods, and the associated service operations.

Table 10.3.3-1: Resource and methods overview of the AI/ML model training API

Resource name	Resource URI	HTTP method	Service Operation
All AI/ML model training jobs	.../training-jobs	POST	Request AI/ML model training.
Individual AI/ML model training job	.../training-jobs/{trainingJobId}	DELETE	Cancel AI/ML model training job.
Individual AI/ML model training job status	.../training-jobs/{trainingJobId}/status	GET	Query AI/ML model training job status.

10.3.4 Service operations

10.3.4.1 Request AI/ML model training

10.3.4.1.1 Operation definition

The API Consumer uses this operation to request AI/ML model training.

The operation to create AI/ML model training job is based on HTTP POST.

```

@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
  
```

```

Consumer ->> Producer: POST .../training-jobs (TrainingJobInfo)
Producer -->> Consumer: 201 Created (TrainingJobInfo)
@enduml

```




Figure 10.3.4.1.1-1: Request AI/ML model training operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP POST request to the API Producer. The target URI shall identify the resource “/training-jobs“, the message content shall carry a TrainingJobInfo structure which includes information for training. The API Producer shall process the request received in the HTTP POST message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall generate the training job identifier and construct the URI for the created resource. The API Producer shall return the HTTP POST response. On success, “201 Created“ shall be returned. The “Location“ HTTP header shall be present and shall carry the URI for the newly created resource. The message content shall carry a TrainingJobInfo structure represents the new resource. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

10.3.4.1.2 Referenced procedures.

10.3.4.1.2.1 Request AI/ML model training procedure

The request AI/ML model training operation illustrated in figure 10.3.4.1.1-1 is based on the request AI/ML model training procedure defined in R1GAP [5].

10.3.4.2 Cancel AI/ML model training

10.3.4.2.1 Operation definition

The API Consumer uses this operation to cancel AI/ML model training.

The operation to delete AI/ML model training job is based on HTTP DELETE.

```

@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: DELETE .../training-jobs/{trainingJobId}
Producer -->> Consumer: 204 No Content
@enduml

```





Figure 10.3.4.2.1-1: Cancel AI/ML model training operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP DELETE request to the API Producer. The target URI shall identify the training job resource to be deleted as “/training-jobs/{trainingJobId}”, the message content shall be empty. The API Producer shall process the request received in the HTTP DELETE message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP DELETE response. On success, “204 No Content” shall be returned. The message content shall be empty. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

10.3.4.2.2 Referenced procedures.

10.3.4.2.2.1 Cancel AI/ML model training procedure

The cancel AI/ML model training operation illustrated in figure 10.3.4.2.1-1 is based on the cancel AI/ML model training procedure defined in R1GAP [5].

10.3.4.3 Query AI/ML model training job status

10.3.4.3.1 Operation definition

The API Consumer uses this operation to query the AI/ML model training job status.

The operation to query AI/ML model training job status is based on HTTP GET.

```

@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: GET .../training-jobs/{trainingJobId}/status
Producer -->> Consumer: 200 OK (TrainingJobStatus)
@enduml
  
```




Figure 10.3.4.3.1-1: Query AI/ML model training job status operation.

The service operation is as follows:

1. The API Consumer shall send an HTTP GET request to the API Producer. The target URI shall identify the resource “/training-jobs/{trainingJobId}/status“, the message content shall be empty. The API Producer shall process the request received in the HTTP GET message and determine if the request sent by the API Consumer is authorized or not.
2. The API Producer shall return the HTTP GET response. On success, “200 OK“ shall be returned. The message content shall carry a TrainingJobStatus representing the status of the training job, which is identified by the trainingJobId. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

10.3.4.3.2 Referenced procedures.

10.3.4.3.2.1 Query AI/ML model training job status procedure

The query AI/ML model training job status operation illustrated in figure 10.3.4.3.1-1 is based on the query AI/ML model training job status procedure defined in R1GAP [5].

10.3.4.4 Notify AI/ML model training job status change

10.3.4.4.1 Operation definition

The API Producer uses this operation to notify the status change of an AI/ML model training job.

The operation to notify AI/ML model training job status change is based on HTTP POST.

```
@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer <<- Producer: POST {notificationDestination} (TrainingJobStatusChangeNotification)
Consumer -->> Producer: 204 No Content
@enduml
```




Figure 10.3.4.4.1-1: Notify AI/ML model training job status change operation.

The service operation is as follows:

1. The API Producer shall send an HTTP POST request to the API Consumer. The target URI {notificationDestination} shall be the one provided by API Consumer during the creation of the training job, the message content shall carry a TrainingJobStatusChangeNotification which includes the updated training job status. The API Consumer shall process the request received in the HTTP POST message and determine if the request sent by the API Producer is authorized or not.
2. The API Consumer shall return the HTTP POST response. On success, “204 No Content“ shall be returned. The message content shall be empty. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

10.3.4.4.2 Referenced procedures.

10.3.4.4.2.1 Notify AI/ML model training job status change procedure

The notify AI/ML model training job status change operation illustrated in figure 10.3.4.4.1-1 is based on the notify AI/ML model training job status change procedure defined in R1GAP [5].

10.3.5 Resources

10.3.5.1 Overview

This clause defines the resource for the AI/ML model training API.

10.3.5.2 Resource: "All AI/ML model training jobs"

10.3.5.2.1 Description

The resource represents all AI/ML model training jobs created in the AI/ML model training API producer.

The methods defined in clause 10.3.5.2.3 shall be supported by this resource.

10.3.5.2.2 Resource Definition

Resource URI: {apiRoot}/ai-ml-model-training/<apiVersion>/training-jobs

The resource URI variables supported by the resource is defined in table 10.3.5.2.2-1.

Table 10.3.5.2.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.2.
apiVersion	See clause 10.3.2.

10.3.5.2.3 Resource Standard Methods

10.3.5.2.3.1 POST

This method shall support the request data structures specified in the table 10.3.5.2.3.1-1 and the response data structures, and response codes specified in table 10.3.5.2.3.1-2 and the HTTP headers specified in table 10.3.5.2.3.1-3.

Table 10.3.5.2.3.1-1: Data structures supported by the HTTP POST request body on this resource.

Data type	P	Cardinality	Description
TrainingJobInfo	M	1	Information related to the creation of the AI/ML model training job.

Table 10.3.5.2.3.1-2: Data structures supported by the HTTP POST response body on this resource.

Data type	P	Cardinality	Response codes	Description
TrainingJobInfo	M	1	201 Created	Confirmation of creation of the AI/ML model training job.
ProblemDetails	O	0..1	4xx/5xx	Detailed problem description.

Table 10.3.5.2.3.1-3: Headers supported by the 201 Response Code on this resource.

Name	Data type	P	Cardinality	Description
Location	string	M	1	Contains the URI of the newly created individual AI/ML model training job resource, as defined in clause 10.3.5.3, with the trainingJobId in the URI.

10.3.5.2.4 Resource Custom Methods

None.

10.3.5.3 Resource: "Individual AI/ML model training job"

10.3.5.3.1 Description

The resource represents an individual AI/ML model training job created in the AI/ML model training API producer.

The methods defined in clause 10.2.5.3.3 shall be supported by this resource.

10.3.5.3.2 Resource Definition

Resource URI: {apiRoot}/ai-ml-model-training/<apiVersion>/training-jobs/{trainingJobId}

The resource URI variables supported by the resource is defined in table 10.3.5.3.2-1.

Table 10.3.5.3.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.2.
apiVersion	See clause 10.3.2.
trainingJobId	The training job identifier assigned by the Service Producer.

10.3.5.3.3 Resource Standard Methods

10.3.5.3.3.1 DELETE

This method shall support the request data structures specified in the table 10.3.5.3.3.1-1 and the response data structures, and response codes specified in table 10.3.5.3.3.1-2.

Table 10.3.5.3.3.1-1: Data structures supported by the HTTP DELETE request body on this resource.

Data type	P	Cardinality	Description
N/A			There is no object in the message content of a DELETE request.

Table 10.3.5.3.3.1-2: Data structures supported by the HTTP DELETE response body on this resource.

Data type	P	Cardinality	Response codes	Description
N/A			204 No content	Confirmation of successful deletion.
ProblemDetails	O	0..1	4xx/5xx	Detailed problem description.

10.3.5.3.4 Resource Custom Methods

None.

10.3.5.4 Resource: "Individual AI/ML model training job status"

10.3.5.4.1 Description

The resource represents the status of an individual AI/ML model training job created in the Non-RT RIC.

The methods defined in clause 10.3.5.4.3 shall be supported by this resource.

10.3.5.4.2 Resource Definition

Resource URI: **{apiRoot}/ai-ml-model-training/<apiVersion>/training-jobs/{trainingJobId}/status**

The resource URI variables supported by the resource is defined in table 10.3.5.4.2-1.

Table 10.3.5.4.2-1: Resource URI variables for the resource

Name	Definition
apiRoot	See clause 5.2.
apiVersion	See clause 10.3.2.
trainingJobId	The training job identifier assigned by the Service Producer.

10.3.5.4.3 Resource Standard Methods

10.3.5.4.3.1 GET

This method shall support the request data structures specified in the table 10.3.5.4.3.1-1 and the response data structures, and response codes specified in table 10.3.5.4.3.1-2.

Table 10.3.5.4.3.1-1: Data structures supported by the HTTP GET request body on this resource.

Data type	P	Cardinality	Description
N/A			There is no object in the message content of a GET request.

Table 10.3.5.4.3.1-2: Data structures supported by the HTTP GET response body on this resource.

Data type	P	Cardinality	Response codes	Description
TrainingJobStatus	M	1	200 OK	The status of the AI/ML model training job.
ProblemDetails	O	0..1	4xx/5xx	Detailed problem description.

10.3.5.4.4 Resource Custom Methods

None.

10.3.6 Custom operation without associated resources.

None.

10.3.7 Notificationss

10.3.7.1 Notify training job status change.

10.3.7.1.1 Description

The notification informs the receiver about the updated status of an AI/ML model training job.

10.3.7.1.2 Resource Definition

The Resource URI {notificationDestination} is a callback URI provided when creating an AI/ML model training job.

10.3.7.1.3 Resource Standard Methods

10.3.7.1.3.1 POST

This method shall support the request data structures specified in table 10.3.7.1.3.1-1 and the response data structure and response codes specified in table 10.3.7.1.3.1-2.

Table 10.3.7.1.3.1-1: Data structures supported by the HTTP POST request body on this resource.

Data type	P	Cardinality	Description
TrainingJobStatusChangeNotification	M	1	Notify a status changes of an AI/ML model training job.

Table 10.3.7.1.3.1-2: Data structures supported by the HTTP POST response body on this resource.

Data type	P	Cardinality	Response codes	Description
N/A			204 No content	Confirmation of received notification.
ProblemDetails	O	0..1	4xx/5xx	The operation was unsuccessful. Detailed problem description may be carried in the response message content.

10.3.8 Data Model

10.3.8.1 Structured data types

10.3.8.1.1 Overview

The following clauses define the data types and attributes to be used by the AI/ML model training API.

10.3.8.1.2 Data type: TrainingJobInfo

Table 10.3.8.1.2-1: Definition of type TrainingJobInfo

Attribute Name	Data type	P	Cardinality	Description
modelId	ModelId	M	1	The model identifier which contains model name, model version, and artifact version. See clause 10.1.8.1.3-1.
modelLocation	Uri	O	0..1	Location of the AI/ML model.
trainingDataset	Uri	O	0..1	Information for reference to the training dataset.

trainingConfig	Object	O	0..1	trainingConfig provided by the training service producer.
notificationDestination	Uri	O	0..1	Callback URI where the notification should be delivered to.
trainingProducerId	String	O	0..1	Identifier of training producer "apfld" as specified in SME.

10.3.8.2 Simple data types and enumerations

10.3.8.2.1 Overview

The following clauses define simple data types and enumerations that can be referenced from data structure defined in the previous clauses.

10.3.8.2.2 Simple data types

No simple data types are defined in this version of the specification.

10.3.8.2.3 Enumerations

No enumerations are defined in this version of the specification.

10.3.9 Error Handling

10.3.9.1 General

For the AI/ML model training API, HTTP error responses shall be supported as specified in 3GPP TS 29.501 [1]. Protocol errors and application errors specified in 3GPP TS 29.500 [2], table 5.2.7.2-1, shall be supported for an HTTP method if the corresponding HTTP status codes are specified as mandatory for that HTTP method in 3GPP TS 29.500 [2], table 5.2.7.1-1.

In addition, the requirements in the following clauses are applicable for the AI/ML model training API.

10.3.9.2 Protocol Errors

No specific protocol errors are defined in the present document.

10.3.9.3 Application Errors

No additional application errors defined in the present document.

10.4 AI/ML model deployment API

10.4.1 Introduction

This API enables the API Consumer to request the deployment of an AI/ML model based on the AI/ML model deployment request service defined in R1GAP [5].

10.4.2 API version

For the AI/ML model deployment API as specified in the present document, the MAJOR version field shall be 1, the MINOR version field shall be 0 and the PATCH version field shall be 0 (see 3GPP TS 29.501 [1] for a definition of the version fields). Consequently, the <apiVersion> URI path segment shall be set to "v1".

The AI/ML model deployment API is under development and consequently the API version shall include the pre-release version "alpha.1".

10.4.3 Resource structure and methods

The request URIs used in HTTP requests from the API Consumer towards the API Producer shall have the resource URI structure as defined in clause 5.2. The <apiName> resource URI variable shall be "ai-ml-model-deployment". The <apiSpecificResourceUriPart> for each resource shall be set as described in clause 10.4.5.

Figure 10.4.3-1 shows the overall resource URI structure defined for the AI/ML model deployment API.




Figure 10.4.3-1: Resource URI structure of the AI/ML model deployment API

Table: 10.4.3-1 lists the individual resources defined for the API, the applicable HTTP methods, and the associated service operations.

Table 10.4.3-1: Resource and methods overview of the AI/ML model deployment API

Resource name	Resource URI	HTTP method	Service Operation
All AI/ML model deployments	.../model-deployments	POST	Request AI/ML model deployment.
Individual AI/ML deployment status	.../model-deployments/{modelDeploymentId}/status	GET	Query AI/ML model deployment status.

10.4.4 Service operations

10.4.4.1 Request AI/ML model deployment

10.4.4.1.1 Operation definition

The API Consumer uses this operation to request AI/ML model deployment.

The operation to request AI/ML model deployment is based on HTTP POST.

```

@startuml
autonumber
Participant "API Consumer" as Consumer
Participant "API Producer" as Producer
Consumer ->> Producer: POST .../model-deployments (ModelDeploymentInformation)
Producer -->> Consumer: 201 Created (ModelDeploymentInformation)
@enduml
  
```



Figure 10.4.4.1.1-1: Request AI/ML model deployment operation.

The service operation is as follows:

- 1) The API Consumer shall send an HTTP POST request to the API Producer. The target URI shall identify the resource "/modeldeployments", the message content shall carry a ModelDeploymentInformation which includes information for deployment. The API Producer shall process the request received in the HTTP POST message and determine if the request sent by the API Consumer is authorized or not.
- 2) The API Producer shall generate the deployment identifier and construct the URI for the created resource. The API Producer shall return the HTTP POST response. On success, "201 Created" shall be returned. The "Location" header shall be present and shall carry the URI of the new resource. The message content shall carry a ModelDeploymentInformation structure that represents the new resource. On failure, the appropriate error code shall be returned, and the message content may contain additional error information.

10.4.4.1.2 Referenced procedures.

10.4.4.1.2.1 Request AI/ML model deployment procedure

The request AI/ML model deployment operation illustrated in figure 10.4.4.1.1-1 is based on the request AI/ML model deployment procedure defined in R1GAP [5].

10.4.4.2 Notify AI/ML model deployment status change

10.4.4.2.1 Operation definition

The API Producer uses this operation to notify the change of an AI/ML model deployment status.

The operation to notify AI/ML model deployment status change is based on HTTP POST.

```

@startuml
autonumber
participant "API Consumer" as Consumer
participant "API Producer" as Producer
Consumer <- Producer: POST {notificationDestination} (DeploymentStatusChangeNotification)
Consumer -->> Producer: 204 No Content
@enduml
  
```




Figure 10.4.4.2.1-1: Notify AI/ML model deployment status change operation.

The service operation is as follows:

- 1) The API Producer shall send an HTTP POST request to the API Consumer. The target URI {notificationDestination} may be provided by API Consumer during the ai/ml model deployment request, where the message content shall carry a DeploymentStatusChangeNotification which includes the updated AI/ML model deployment status. The API Consumer shall process the request received in the HTTP POST message and determine if the request sent by the API Producer is authorized or not.
- 2) The API Consumer shall return the HTTP POST response. On success, “204 No Content” shall be returned. The message content shall be empty. On failure, the appropriate error code shall be returned, and the response message content may contain additional error information.

10.4.4.2.2 Referenced procedures.

10.4.4.2.2.1 Notify AI/ML model deployment status change procedure

The notify AI/ML model deployment status change operation illustrated in figure 10.4.4.2.1-1 is based on the AI/ML model deployment procedure defined in R1GAP [5].

10.4.5 Resources

10.4.5.1 Overview

This clause defines the resource for the AI/ML model deployment API.

10.4.5.2 Resource: "All AI/ML model deployment"

10.4.5.2.1 Description

The resource represents all AI/ML model deployment in the Non-RT RIC.

The methods defined in clause 10.4.5.2.3 shall be supported by this resource.

10.4.5.3.2 Resource Definition

Resource URI: {apiRoot}/ai-ml-model-deployment/<apiVersion>

The resource URI variables supported by the resource is defined in table 10.4.5.2.2-1.

Table 10.4.5.3.2-1: Resource URI variable for the resource

Name	Definition
apiRoot	See clause 5.2
apiVersion	See clause 10.4.2

10.4.5.2.3 Resource Standard Methods

10.4.5.2.3.1 POST

This method shall support the request data structures specified in the table 10.4.5.2.3.1-1 and the response data structures and response codes specified in table 10.4.5.2.3.1-2.

Table 10.4.5.2.3.1-1: Data structures supported by the HTTP POST Request Body on this resource.

Data type	P	Cardinality	Description
ModelDeploymentInformation	M	1	Information related to the deployment of the AI/ML model

Table 10.4.5.2.3.1-2: Data structures supported by the HTTP POST Response Body on this resource.

Data type	P	Cardinality	Response codes	Description
ModelDeploymentInformation	1	M	201 Created	The operation was successful. The message content of the POST response carries ModelDeploymentInformation.
ProblemDetails	O	0..1	4xx/5xx	Detailed problem description

10.4.5.2.4 Resource Custom Methods

None.

10.4.6 Custom operation without associated resources.

None.

10.4.7 Notifications

10.4.7.1 Notify AI/ML model deployment status change

10.4.7.1.1 Overview

The notification informs the receiver about the AI/ML model deployment status.

10.4.7.1.2 Resource Definition

The Resource URI {notificationDestination} is a callback URI provided when requesting deployment of an AI/ML model.

10.4.7.1.3 Resource Standard Methods

10.4.7.1.3.1 POST

This method shall support the request data structures specified in table 10.4.7.1.3.1-1 and the response data structure and response codes specified in table 10.4.7.1.3.1-2.

Table 10.4.7.1.3.1-1: Data structures supported by the HTTP POST request body on this resource

Data type	P	Cardinality	Description
DeploymentStatusChangeNotification	M	1	Notify a status changes of an AI/ML model deployment status.

Table 10.4.7.1.3.1-2: Data structures supported by the HTTP POST response body on this resource

Data type	P	Cardinality	Response codes	Description
N/A			204 No Content	Confirmation of received notification
ProblemDetails	O	0..1	4xx/5xx	The operation was unsuccessful. Detailed problem description may be carried in the response message content

10.4.8 Data Model

10.4.8.1 Structured data types

10.4.8.1.1 Overview

The following clauses define the structured data types and their attributes to be used by the AI/ML model deployment API.

10.4.8.1.2 Data type: ModelDeploymentInformation

The ModelDeploymentInformation data type represents deployment information for an AI/ML model. It contains the attributes defined in table 10.4.8.1.2-1.

Table 10.4.8.1.2-1: Definition of type ModelDeploymentInformation.

Attribute Name	Data type	P	Cardinality	Description
modelId	ModelId	M	1	Identifier of a model. See clause 10.1.8.1.3
notificationDestination	Uri	O	0..1	Callback URI where the notification would be delivered to, once the deployment status changes.

10.5 Void

Annex A (normative): OpenAPI specifications

A.1 General

A.1.1 Overview

This Annex formally specifies the RESTful R1 service APIs by defining OpenAPI documents in YAML format that comply with the OpenAPI 3.0.3 Specification [3].

The Open API specifications of the RESTful R1 service APIs provided in this annex are versioned as described in clause 5.2.

The OpenAPI's define in this annex has references to the common definitions define in clause A.1.2 of the present document.

A.1.2 Common schemas for general use

A.1.2.1 Introduction

The Open API specified in clause A.1.2.2 provides schemas for general data types and responses for usage across the R1 APIs.

A.1.2.2 Common definitions

```
openapi: 3.0.3
info:
  title: 'R1 Common definitions'
  version: 1.0.1
  description: |
    R1 Common definitions - O-RAN.WG2.R1AP_Common.yaml.

    Copyright 2026 O-RAN ALLIANCE e.V.
    Licensed under the Standards Collaboration
    Copyright License Version 1.0 (the "License");
    you may not use this file except in compliance with the License.
    You may obtain a copy of the License at
    https://www.o-ran.org/sccl license:
    name: SCCL
    url: https://o-ran.org/scclexternalDocs:
  description: 'O-RAN.WG2.R1AP'
  url: 'https://www.o-ran.org/specifications'
paths: {}
components:
  schemas:
    Uri:
      description: 'A string formatted according to IETF RFC 3986 [8].'
      type: string
    ProblemDetails:
      description: 'A problem detail to carry details in an HTTP response according to RFC 7807'
      type: object
      properties:
        type:
          description: 'a URI reference according to IETF RFC 3986 that identifies the problem type'
          type: string
        title:
          description: 'human-readable summary of the problem type'
          type: string
        status:
          description: 'the HTTP status code'
          type: number
        detail:
          description: 'human-readable explanation '
          type: string
        instance:
          description: 'URI reference that identifies the specific occurrence of the problem'
```

```

        type: string
responses:
  '400':
    description: 'Bad Request'
    content:
      application/problem+json:
        schema:
          $ref: '#/components/schemas/ProblemDetails'
  '401':
    description: 'Unauthorized'
    content:
      application/problem+json:
        schema:
          $ref: '#/components/schemas/ProblemDetails'
  '403':
    description: 'Forbidden'
    content:
      application/problem+json:
        schema:
          $ref: '#/components/schemas/ProblemDetails'
  '404':
    description: 'Not Found'
    content:
      application/problem+json:
        schema:
          $ref: '#/components/schemas/ProblemDetails'
  '405':
    description: 'Method Not Allowed'
    content:
      application/problem+json:
        schema:
          $ref: '#/components/schemas/ProblemDetails'
  '406':
    description: 'Not Acceptable'
    content:
      application/problem+json:
        schema:
          $ref: '#/components/schemas/ProblemDetails'
  '409':
    description: 'Conflict'
    content:
      application/problem+json:
        schema:
          $ref: '#/components/schemas/ProblemDetails'
  '411':
    description: 'Length Required'
    content:
      application/problem+json:
        schema:
          $ref: '#/components/schemas/ProblemDetails'
  '413':
    description: 'Payload Too Large'
    content:
      application/problem+json:
        schema:
          $ref: '#/components/schemas/ProblemDetails'
  '414':
    description: 'URI Too Large'
    content:
      application/problem+json:
        schema:
          $ref: '#/components/schemas/ProblemDetails'
  '415':
    description: 'Unsupported Media Type'
    content:
      application/problem+json:
        schema:
          $ref: '#/components/schemas/ProblemDetails'
  '429':
    description: 'Too Many Requests'
    content:

```

```

    application/problem+json:
      schema:
        $ref: '#/components/schemas/ProblemDetails'
  '500':
    description: 'Internal Server Error'
    content:
      application/problem+json:
        schema:
          $ref: '#/components/schemas/ProblemDetails'
  '502':
    description: 'Bad Gateway'
    content:
      application/problem+json:
        schema:
          $ref: '#/components/schemas/ProblemDetails'
  '503':
    description: 'Service Unavailable'
    content:
      application/problem+json:
        schema:
          $ref: '#/components/schemas/ProblemDetails'

```

A.1.2.3 Notification

```

openapi: 3.2.0
info:
  title: 'R1 Common definitions'
  version: 1.0.0
  description: |
    R1 Common definitions - O-RAN.WG2.R1AP_Notification.yaml.
    Copyright 2025 O-RAN ALLIANCE e.V.
    Licensed under the Standards Collaboration
    Copyright License Version 1.0 (the "License");
    you may not use this file except in compliance with the License.
    You may obtain a copy of the License at
    https://www.o-ran.org/scclALLIANCE.
    All rights reserved.
  license:
    name: SCCL
    url: https://o-ran.org/sccl
externalDocs:
  description: 'O-RAN.WG2.R1AP'
  url: 'https://www.o-ran.org/specifications'
paths: {}
components:
  schemas:
    NotificationType:
      type: string
      description: 'A string formatted as concatenation of "org.o-ran.", a string representing the service
name (e.g. "DME"), a dot ".", and an API-specific name for the event type (e.g. "DATA_AVAILABILITY")
defined in the API specification.'
    Notification:
      type: object
      description: 'The general Notification data structure is specified in table B.2.4.5-1, aligned with
the CloudEvents [30].'
      properties:
        id:
          type: string
          description: 'Identifier of the event, unique within the scope identified by the "source"
attribute, as defined in CloudEvents [30].'
          example: '123456789'
        specversion:
          type: string
          description: 'The version of the CloudEvents specification which the event uses, as defined in
CloudEvents [X]. E.g. the spec version is 1.0 aligned with the version of the CloudEvents specification
[X]. (See NOTE).'
          example: '1.0'

```



```

    $ref: '#/components/schemas/NotificationType'
  source:
    type: string
    description: 'The source from which the event from has originated, as defined in CloudEvents
[30]'.
    example: 'https://example.com/data-access/v2/data-jobs/1234567'
  time:
    type: string
    description: 'Timestamp when the event is generated, as defined in CloudEvents [30].'
    example: '2020-01-01T00:00:00Z'
  datacontenttype:
    type: object
    description: 'Content type of the value of the "data" attribute, as defined in CloudEvents
[30]. (See NOTE).'
    example: 'application/json'
  dataschema:
    type: Uri
    description: 'Identifies the schema that data adheres to, as defined in CloudEvents [30].'
    example: 'https://example.com/data'
  data:
    type: object
    additionalProperties: true
    description: 'Application event payload data encoded as declared by the "datacontenttype"
attribute. The structure of this attribute is defined by the API that specifies the notification type.'
  required:
    - id
    - specversion
    - type
    - source

```

A.2 Service management and exposure service

A.2.1 Service registration API

A.2.1.1 Introduction

The Open API for this service is reusing the CAPIF_Publish_Service_API as specified in clause A.2.1.2 with exceptions specified in clause A.2.1.3 below.

A.2.1.2 CAPIF_Publish_Service_API

The Open API for the SME service registration API specified in clause 6.1 reuses the CAPIF_Publish_Service_API as specified in 3GPP TS 29.222 [9], clause A.3.

The API version of the Service registration API as specified in clause 6.1.2 shall use the CAPIF_Publish_Service_API OpenAPI version as specified in Table A.2.1.2-1.

Table A.2.1.2-1

API name	API version	CAPIF OpenAPI version
Service registration API	1.2.0	1.3.0

A.2.1.3 Adaptations and Exceptions

The OpenAPI code below represents the "VersionExtensions" data type which needs to be added to the OpenAPI definitions of the CAPIF_Publish_Service_API defined in 3GPP TS 29.222 [9].

```

openapi: 3.0.3
info:
  title: 'Version_Extensions'

```

```

version: 1.0.0
description: |
  R1 Common definitions - O-RAN.WG2.R1AP_Common.yaml.
  Copyright 2026 O-RAN ALLIANCE e.V.
  Licensed under the Standards Collaboration
  Copyright License Version 1.0 (the "License");
  you may not use this file except in compliance with the License.
  You may obtain a copy of the License at
  https://www.o-ran.org/scclALLIANCE.
  All rights reserved.
license:
  name: SCCL
  url: https://o-ran.org/sccl
externalDocs:
  description: 'O-RAN.WG2.R1AP'
  url: 'https://www.o-ran.org/specifications'

components:
  schemas:
    VersionExtensions:
      description: 'The VersionExtensions data structure specified in table B.3.4.1-1 in R1AP defines O-
RAN extensions to the CAPIF Version data type which allows to signal the versions supported for an
interface endpoint.'
      type: object
      properties:
        fullApiVersions:
          description: 'List of version strings, as defined in R1GAP clause 5.2, to signal the API
versions supported by the API Producer for a particular major API version.'
          type: array
          items:
            type: string
            minItems: 1

```

The OpenAPI code below represents the "ServiceProperties" data type which needs to be added to the OpenAPI definitions of the CAPIF_Publish_Service_API defined in 3GPP TS 29.222 [9].

```

openapi: 3.0.3
info:
  title: 'Service_Properties'
  version: 1.0.0
  description: |
    R1 Common definitions - O-RAN.WG2.R1AP_Common.yaml.
    Copyright 2026 O-RAN ALLIANCE e.V.
    Licensed under the Standards Collaboration
    Copyright License Version 1.0 (the "License");
    you may not use this file except in compliance with the License.
    You may obtain a copy of the License at
    https://www.o-ran.org/scclALLIANCE.
    All rights reserved.
  license:
    name: SCCL
    url: https://o-ran.org/sccl
externalDocs:
  description: 'O-RAN.WG2.R1AP'
  url: 'https://www.o-ran.org/specifications'

components:
  schemas:
    ServiceProperties:
      description: 'Defines a container that can be used by individual service APIs to register and
discover service-specific properties.'
      type: object
      properties:
        serviceCapabilities:
          description: 'Service capabilities. The content of this attribute is service-specific and is
defined per service.'
          type: object

```

Table A.2.1.3-1 below lists exceptions and adaptations related to certain attributes in certain CAPIF data types when re-using the CAPIF_Publish_Service_API in the context of the present document .

Table A.2.1.3-1: Message content exceptions and adaptations when reusing the CAPIF_Publish_Service_API

Data type	Reference	Attributes	Adaptations/Exceptions
ServiceAPIDescription	3GPP TS 29.222 [9], clause A.3	supportedFeatures	Not required to be supported.
		shareableInfo	Not required to be supported.
		serviceAPICategory	Not required to be supported.
		ccfld	Not required to be supported.
		apiSuppFeats	Not required to be supported.
		pubApiPath	Not required to be supported.
		vendorSpecific-o-ran.org	This additional attribute shall be present if service-specific registration information is available for the service API. It shall have the type ServiceProperties as specified in clause B.3.4.2 and defined in annex A.2.1.3.
AefProfile	3GPP TS 29.222 [9], clause A.3	aefId	Shall be set to the value of "rAppId" if an rApp produces the API.
		aefLocation	Not required to be supported.
		domainName	Not required to be supported.
		serviceKpis	Not required to be supported.
		uelpRange	Not required to be supported.
Version	3GPP TS 29.222 [9], clause A.3	vendorSpecific-o-ran.org	This additional attribute shall be supported and shall have the type VersionExtensions as specified in clause B.3.4.1 and defined above.

A.2.2 Service discovery API

A.2.2.1 Introduction

The Open API for this service is reusing the CAPIF_Discover_Service_API in as specified in clause A.2.2.2 with exceptions specified in clause A.2.2.3 below.

A.2.2.2 CAPIF_Discovery_Service_API

The Open API for the SME service discovery API specified in clause 6.2 reuses the CAPIF_Discover_Service_API as specified in 3GPP TS 29.222 [9], clause A.2.

The API version of the Service discovery API as specified in clause 6.2.2 shall use the CAPIF_Discover_Service_API OpenAPI version as specified in Table A.2.2.2-1.

Table A.2.2.2-1

API name	API version	CAPIF OpenAPI version
Service discover API	1.2.0	1.3.0

A.2.2.3 Adaptations and Exceptions

Table A.2.2.3-1 lists exceptions and adaptations related to CAPIF message content when re-using the CAPIF_Discover_Service_API in the context of the present document.

Table A.2.2.3-1 lists exceptions and adaptations related to CAPIF URI query parameters when re-using the CAPIF_Discover_Service_API in the context of the present document.

Table A.2.2.3-1: Message content exceptions and adaptations when reusing the CAPIF_Discover_Service_API

Data type	Reference	Attributes	Exceptions/Adaptations
ServiceAPIDescription	3GPP TS 29.222 [9], clause A.3	supportedFeatures	Not required to be supported.
		shareableInfo	Not required to be supported.
		serviceAPICategory	Not required to be supported.
		ccfld	Not required to be supported.
		apiSuppFeats	Not required to be supported.
		pubApiPath	Not required to be supported.
		vendorSpecific-o-ran.org	This additional attribute shall be present if service-specific registration information is available for the service API. It shall have the type ServiceProperties as specified in clause B.3.4.2 and defined in annex A.2.1.3.
		ue-ip-addr	Not required to be supported.
		service-kpis	Not required to be supported.
AefProfile	3GPP TS 29.222 [9], clause A.3	aefld	Shall be set to the value of "rAppId" if an rApp produces the API. Shall be set to an identifier related to the SMO/Non-RT RIC functions if these produce the API. See note.
		aefLocation	Not required to be supported.
		domainName	Not required to be supported.
Version	3GPP TS 29.222 [9], clause A.3	vendorSpecific-o-ran.org	This additional attribute shall be supported and shall have the type VersionExtensions as specified in clause B.3.4.1 and defined in annex A.2.1.3.
NOTE: It is out of scope of the present document whether each SMO/Non-RT RIC framework function is identifiable by a separate identifier value or whether such decomposition information is hidden from the rApps. However, the SMO/Non-RT RIC framework shall ensure that the identifiers used for rApps as AEFs and the identifiers used for SMO/Non-RT RIC framework functions as AEFs do not collide.			

The Query parameters in the table A.2.2.3-2 below are not required to be supported when the CAPIF_Discover_Service_API is reused.

Table A.2.2.3-2: Query parameters exceptions and adaptations when reusing the CAPIF_Discover_Service_API

Resource	Reference	Exceptions	Comment
/allServiceAPIs	3GPP TS 29.222 [9], clause A.2	api-invoker-id	Shall be set to the value of "rAppId" for an API-consuming rApp.
	3GPP TS 29.222 [9], clause A.2	comm-type	Not required to be supported.
	3GPP TS 29.222 [9], clause A.2	protocol	Not required to be supported.
	3GPP TS 29.222 [9], clause A.2	aef-id	Not required to be supported.
	3GPP TS 29.222 [9], clause A.2	data-format	Not required to be supported.
	3GPP TS 29.222 [9], clause A.2	api-cat	Not required to be supported.
	3GPP TS 29.222 [9], clause A.2	preferred-aef-loc	Not required to be supported.
	3GPP TS 29.222 [9], clause A.2	supported-features	Not required to be supported.
	3GPP TS 29.222 [9], clause A.2	api-supported-features	Not required to be supported.
	3GPP TS 29.222 [9], clause A.2	ue-ip-addr	Not required to be supported.
	3GPP TS 29.222 [9], clause A.2	service-kpis	Not required to be supported.

A.2.3 Service events subscription API

A.2.3.1 Introduction

The Open API for this service is reusing the CAPIF_Events_API as specified in clause A.2.3.2 with exceptions specified in clause A.2.3.3 below.

A.2.3.2 CAPIF_Events_API

The Open API for the SME service events subscription API specified in clause 6.3 reuses the CAPIF_Events_API as specified in 3GPP TS 29.222 [9], clause A.4.

The API version of the SME service events subscription API as specified in clause 6.3.2 shall use the CAPIF_Events_API OpenAPI version as specified in Table A.2.3.2-1

Table A.2.3.2-1

API name	API version	CAPIF OpenAPI version
Service events subscription API	1.2.0	1.3.0

A.2.3.3 Adaptations and Exceptions

Table A.2.3.3-1 lists exceptions and adaptations related to CAPIF message content when re-using the CAPIF_Events_API in the context of the present document.

Table A.2.3.3-1: Message content exceptions and adaptations when reusing the CAPIF_Events_API

Data type	Reference	Attributes	Exceptions/Adaptations
AccessControlPolicyListExt	3GPP TS 29.222 [9], Clause A.4		Not required to be supported.
CAPIFEvent	3GPP TS 29.222 [9], Clause A.4		See clause B.3.5.
CAPIFEventDetail	3GPP TS 29.222 [9], Clause A.4	accCtrlPolList	Not required to be supported.
		invocationLogs	Not required to be supported.
		apiTopoHide	Not required to be supported.
CAPIFEventFilter	3GPP TS 29.222 [9], Clause A.4	apiInvokerIds	Shall be set to the value of "rAppId" for an API-consuming rApp.
		aefIds	Shall be set to the value of "rAppId" if an rApp -produces the API. Shall be set to an identifier related to the SMO/Non-RT RIC framework functions if these produce the API. See table A.2.2.3-1.
		ReportingInformation	Not required to be supported.
EventNotification	3GPP TS 29.222 [9], Clause A.4	invocationLogs	Not required to be supported.
		apiTopoHide	Not required to be supported.
EventSubscription	3GPP TS 29.222 [9], Clause A.4	supportedFeatures	Not required to be supported.
		eventReq	Not required to be supported.
TopologyHiding	3GPP TS 29.222 [9], Clause A.4		Not required to be supported.

A.2.4 Bootstrap API

A.2.4.1 Introduction

The Open API for this service as specified in clause A.2.4.2.

A.2.4.2 Bootstrap API

```

openapi: 3.0.3
info:
  title: 'BootStrap'
  version: 1.0.0
  description: |
    API for BootStrap service.
    R1 Common definitions - O-RAN.WG2.R1AP_Common.yaml.
    Copyright 2026 O-RAN ALLIANCE e.V.
    Licensed under the Standards Collaboration
    Copyright License Version 1.0 (the "License");
    you may not use this file except in compliance with the License.
    You may obtain a copy of the License at
    https://www.o-ran.org/scclALLIANCE.
    All rights reserved.
license:
  name: SCCL
  url: https://o-ran.org/sccl
externalDocs:
  description: 'O-RAN.WG2.R1AP'
  url: 'https://www.o-ran.org/specifications'
servers:
  - url: '{apiRoot}/bootstrap/v1/'
    variables:
      apiRoot:
        description: 'apiRoot as defined in clause 5.3 in O-RAN.WG2.R1AP'
        default: 'https://example.com'
paths:

```

```

'/bootstrap-info':
  get:
    description: 'To discover the entry points into Service management and exposure '
    responses:
      '200':
        description: '.'
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/BootstrapInformation'
      '400':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
      '401':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
      '403':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
      '404':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
      '429':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
      '500':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
      '502':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
      '503':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
    components:
      schemas:
        BootstrapInformation:
          type: object
          properties:
            apiEndpoints:
              type: array
              items:
                $ref: '#/components/schemas/ApiEndpointInformation'
        ApiEndpointInformation:
          type: object
          properties:
            apiName:
              type: string
              description: 'Name of the API ("service-apis" or "published-apis")'
            tokenEndpoint:
              $ref: 'TS29122_CAPIF_publish_Service_API.yaml#/components/schemas/InterfaceDescription'
              description: 'Token endpoint shall be provided if the API requires authorization over OAuth2.0'
              nullable: true
            apiEndPoint:
              $ref: 'TS29122_CAPIF_publish_Service_API.yaml#/components/schemas/InterfaceDescription'
              description: 'End point of the API'
              nullable: true
          required:
            - apiName
            - apiEndPoint

```

A.3 Data management and exposure service

A.3.1 Data registration API

A.3.1.1 Introduction

The Open API for the Data Registration API is specified in clause A.3.1.2.

A.3.1.2 Data registration API

```

openapi: 3.0.3
info:
  title: 'Data registration service'
  version: 2.0.0-alpha.3

```

```

description: |
  API for Data registration service.
  R1 Common definitions - O-RAN.WG2.R1AP_Common.yaml.
  Copyright 2026 O-RAN ALLIANCE e.V.
  Licensed under the Standards Collaboration
  Copyright License Version 1.0 (the "License");
  you may not use this file except in compliance with the License.
  You may obtain a copy of the License at
  https://www.o-ran.org/scclALLIANCE.
  All rights reserved.
license:
  name: SCCL
  url: https://o-ran.org/sccl

externalDocs:
  description: 'O-RAN.WG2.R1AP'
  url: 'https://www.o-ran.org/specifications'
servers:
  - url: '{apiRoot}/data-registration/v2/'
    variables:
      apiRoot:
        description: 'apiRoot as defined in clause 5.3 in O-RAN.WG2.R1AP'
        default: 'https://example.com'

paths:
  '/production-capabilities':
    post:
      description: 'Registers the capabilities of a Data Producer related to a DME type as specified in
clause 7.1.5.2.3.1.'
      tags:
        - Registered DME type production capabilities
      requestBody:
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/DmeTypeRelatedCapabilities'
      responses:
        '201':
          description: 'Success case 201 created'
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/DmeTypeRelatedCapabilities'
          headers:
            Location:
              description: 'URI of the newly created Individual registered DME type production capability
resource'
              required: true
              schema:
                type: string
        '400':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
        '401':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
        '403':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
        '404':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
        '405':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/405'
        '409':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/409'
        '413':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/413'
        '415':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/415'
        '429':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
        '500':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'

```



```

'502':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
'503':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'

'/production-capabilities/{registrationId}':
  parameters:
    - name: registrationId
      in: path
      description: 'The DME type production capabilities registration identifier as defined in clause
7.1.5.3.2'
      required: true
      schema:
        $ref: '#/components/schemas/registrationId'
  put:
    description: 'Updates the DME type production capability associated with the registrationId as
specified in clause 7.1.5.3.2'
    tags:
      - Individual registered DME type production capability
    requestBody:
      required: true
      content:
        application/json:
          schema:
            $ref: '#/components/schemas/DmeTypeRelatedCapabilities'
    responses:
      '200':
        description: 'Success case 200 with updated information'
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/DmeTypeRelatedCapabilities'
      '400':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
      '401':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
      '403':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
      '404':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
      '406':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/406'
      '411':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/411'
      '413':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/413'
      '415':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/415'
      '429':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
      '500':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
      '502':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
      '503':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
  get:
    description: 'Retrieves the registered DME type production capability associated with the
registrationId as specified in clause 7.1.5.3.3.'
    tags:
      - Individual registered DME type production capability
    responses:
      '200':
        description: 'Success case 200 with queried information'
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/DmeTypeRelatedCapabilities'
      '400':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
      '401':

```

```

    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
  '403':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
  '404':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
  '406':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/406'
  '429':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
  '500':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
  '502':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
  '503':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
delete:
  description: 'Deletes the DME type production capability associated with the registrationId as
specified in clause 7.3.1.'
  tags:
    - Individual registered DME type production capability
  responses:
    '204':
      description: 'The registration was deleted'
    '400':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
    '401':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
    '403':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
    '404':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
    '429':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
    '500':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
    '502':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
    '503':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'

components:
  schemas:
    registrationId:
      description: 'The related DME type production capabilities registration identifier'
      type: string
      example: '12345'
    DmeTypeRelatedCapabilities:
      description: 'Represents capabilities of a Data Producer related to providing data instances of a
DME type, as defined in clause 7.1.8.1.2.'
      type: object
      properties:
        dmeTypeDefinition:
          $ref: '#/components/schemas/DmeTypeDefinition'
        constraints:
          description: 'Formulates producer constraints or constraints applicable to the consumption
related to the DME type based on the dataProductionSchema'
          type: object
        dataAccessEndpoint:
          $ref: 'TS29222_CAPIF_Publish_Service_API.yaml#/components/schemas/InterfaceDescription'
        dataDeliveryMode:
          type: array
          items:
            $ref: '#/components/schemas/DataDeliveryMode'
            description: 'Supported modes for data delivery (e.g., one-time data request or continuous data
subscription).'
      required:
        - dmeTypeDefinition
        - dataDeliveryMode
    DmeTypeDefinition:
      description: 'Represents information about a DME type, as defined in clause 7.1.8.1.3.'
      type: object

```

```

properties:
  dmeTypeId:
    $ref: '#/components/schemas/DmeTypeIdStruct'
  metadata:
    $ref: '#/components/schemas/Metadata'
  dataProductionSchema:
    type: object
    description: 'Schema that defines the information necessary to formulate a data request or data
subscription. If this attribute is not present, the schema is assumed to be known from the DME type
definition that is referenced by dmeTypeId.'
  dataDeliverySchemas:
    description: 'List of delivery schemas supported by the producer for the DME type being
registered.'
    type: array
    items:
      $ref: '#/components/schemas/DeliverySchema'
  dataDeliveryMechanisms:
    description: 'Supported data delivery mechanisms as defined in clause B.4.4.2.'
    type: array
    items:
      $ref: '#/components/schemas/DataDeliveryMechanism'
required:
  - dmeTypeId
  - metadata
  - dataDeliverySchemas
  - dataDeliveryMechanisms
DmeTypeIdStruct:
  description: 'Represents the identifier of a DME type, as defined in clause B.4.4.1.'
  type: object
  properties:
    namespace:
      type: string
      description: 'Indicating the entity responsible for the DME type definition.'
      example: 'ORAN'
    name:
      type: string
      description: 'Name of the DME type. The string can be any character except ":" (colon).'
      pattern: '^[^:]{1,}$'
      example: 'RanOamPmData'
    version:
      type: string
      description: 'Version of the DME type. The versioning and allowed characters are according to
SemVer [11]'
      example: '1.0.0'
  required:
    - namespace
    - name
    - version
DeliverySchema:
  description: 'Represents a delivery schema supported by the Data Producer, as defined in clause
7.1.8.1.5.'
  type: object
  properties:
    type:
      $ref: '#/components/schemas/SchemaTypes'
    deliverySchemaId:
      type: string
      description: 'A Data Producer may support one or more delivery schemas and for each supported
schema type a delivery schema identifier is assigned. A Data Consumer uses this attribute while creating a
data job and request to deliver the data using specific schema type which is identified by this
attribute.'
    schema:
      type: string
      description: 'The schema serialized to string. If this attribute is not present, the schema is
assumed to be known from the DME type definition that is referenced by dmeTypeId.'
  required:
    - type
    - deliverySchemaId
DataDeliveryMechanism:
  description: 'Represents the data delivery mechanism supported by a Data Producer, as defined in
clause B.4.4.2.'

```

```

type: object
properties:
  dataDeliveryMethod:
    $ref: '#/components/schemas/DataDeliveryMethod'
  kafkaDeliveryConfiguration:
    $ref: '#/components/schemas/KafkaDeliveryConfiguration'
required:
  - dataDeliveryMethod
oneOf:
  - properties:
      dataDeliveryMethod:
        enum: [STREAMING_KAFKA]
        required: [kafkaDeliveryConfiguration]
      description: 'This attribute shall be present if the deliveryMethod attribute is set to
STREAMING_KAFKA'
    DataDeliveryMethod:
      type: string
      description: 'Enumeration of data delivery methods supported by a Data Producer, as defined in
clause B.4.3.1.'
      enum:
        - PULL_HTTP
        - PUSH_HTTP
        - STREAMING_KAFKA
    Metadata:
      description: 'Metadata that can be used in discovering the DME type'
      type: object
      properties:
        dataCategory:
          description: 'Defines the category of the DME type e.g., PM counters'
          type: array
          items:
            type: string
          minItems: 1
        rat:
          description: 'Defines the radio access technology e.g., 5G'
          type: array
          items:
            type: string
          minItems: 1
      required:
        - dataCategory
    SchemaTypes:
      description: 'Enumeration of schema types supported for data delivery, as defined in clause
7.1.8.2.3.1.'
      type: string
      enum:
        - JSON_SCHEMA
        - XML_SCHEMA
        - PROTOBUF_SCHEMA
        - AVRO_SCHEMA
    KafkaDeliveryConfiguration:
      description: 'These configuration will be applied if STREAMING_KAFKA is selected as delivery method
as defined in clause B.4.4.3'
      type: object
      properties:
        numPartitions:
          description: 'Number of partitions'
          type: integer
        cleanUpPolicy:
          description: 'cleanUpPolicy is based on cleanup.policy defined in the Kafka Documentation [15].'
          type: string
        compressionType:
          description: 'compressionType is based on compression.type defined in the Kafka Documentation
[15].'
          type: string
        retentionBytes:
          description: 'retentionBytes is based on retention.bytes defined in the Kafka Documentation
[15]. This attribute is applicable ONLY when cleanUpPolicy is set to DELETE'
          type: integer
        retentionMs:

```

```

    description: 'retentionMs is based on retention.ms defined in the Kafka Documentation [15]. This
attribute is applicable ONLY when cleanUpPolicy is set to DELETE'
    type: integer
    required:
      - cleanUpPolicy
      - compressionType
  DataDeliveryMode:
    type: string
    description: 'Enumeration of data delivery modes supported by a Data Producer, as defined in clause
7.3.8.2.3.1'
    enum:
      - ONE_TIME #description: 'indicate the data job to be created is for on-time data delivery,
i.e., for data request.'
      - CONTINUOUS #description: 'indicate the data job to be created is for continuous data delivery,
i.e., for data subscription.'
```

A.3.2 Data discovery API

A.3.2.1 Introduction

The Open API for the Data Discovery API is specified in clause A.3.2.2.

A.3.2.2 Data discovery API

```

openapi: 3.0.3
info:
  title: 'Data discovery service'
  version: 2.0.1
  description: |
    API for Data discovery service.
    R1 Common definitions - O-RAN.WG2.R1AP_Common.yaml.
    Copyright 2026 O-RAN ALLIANCE e.V.
    Licensed under the Standards Collaboration
    Copyright License Version 1.0 (the "License");
    you may not use this file except in compliance with the License.
    You may obtain a copy of the License at
    https://www.o-ran.org/scclALLIANCE.
    All rights reserved.
  license:
    name: SCCL
    url: https://o-ran.org/sccl
  externalDocs:
    description: 'O-RAN.WG2.R1AP'
    url: 'https://www.o-ran.org/specifications'
  servers:
    - url: '{apiRoot}/data-discovery/v2/'
      variables:
        apiRoot:
          description: 'apiRoot as defined in clause 5.3 in O-RAN.WG2.R1AP'
          default: 'https://example.com'
  paths:
    /dme-types:
      get:
        description: 'To discover the available DME types'
        parameters:
          - name: identity-namespace
            in: query
            description: 'Identity namespace to match the "namespace" part of the "dmeTypeId" attribute'
            schema:
              type: string
          - name: identity-name
            in: query
            description: 'Identity name to match the "name" part of the "dmeTypeId" attribute.'
            schema:
              type: string
          - name: data-category
            in: query
```

```

    description: 'Set of data category entries, all of which to match entries of the "dataCategory"
attribute.'
    schema:
      type: array
      explode: false
      items:
        type: string
    responses:
      '200':
        description: 'The response body contains the result of the search over the list of registered
APIs.'
        content:
          application/json:
            schema:
              type: array
              items:
                $ref: 'O-
RAN.WG2.R1AP_DataRegistration.yaml#/components/schemas/DmeTypeRelatedCapabilities'
      '400':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
      '401':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
      '403':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
      '404':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
      '406':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/406'
      '414':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/414'
      '429':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
      '500':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
      '502':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
      '503':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
    /dme-types/{dmeTypeId}:
      get:
        description: To obtain information about an individual DME type.
        parameters:
          - name: dmeTypeId
            in: path
            required: true
            schema:
              $ref: '#/components/schemas/dmeTypeId'
        responses:
          '200':
            description: The response body contains information about the DME type.
            content:
              application/json:
                schema:
                  $ref: 'O-
RAN.WG2.R1AP_DataRegistration.yaml#/components/schemas/DmeTypeRelatedCapabilities'
          '400':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
          '401':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
          '403':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
          '404':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
          '406':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/406'
          '414':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/414'
          '429':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
          '500':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'

```

```
'502':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
'503':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
components:
  schemas:
    dmeTypeId:
      type: string
      description: 'The DmeTypeId is constructed based on the three parts separated by ":" (colon)
{dmeTypeId} = {namespace}:{name}:{version}. See O-
RAN.WG2.R1AP_DataRegistration.yaml#/components/schemas/DmeTypeIdStruct for the definition of "namespace",
"name" and "version".'
```

A.3.3 Data access API

A.3.3.1 Introduction

The Open API for the Data access API is specified in clause A.3.3.2.

A.3.3.2 Data access API

```
openapi: 3.2.0
info:
  title: 'Data access service'
  version: 2.0.0-alpha.3
  description: |
    API for Data access service.
    R1 Common definitions - O-RAN.WG2.R1AP_Common.yaml.
    Copyright 2026 O-RAN ALLIANCE e.V.
    Licensed under the Standards Collaboration
    Copyright License Version 1.0 (the "License");
    you may not use this file except in compliance with the License.
    You may obtain a copy of the License at
    https://www.o-ran.org/scclALLIANCE.
    All rights reserved.
  license:
    name: SCCL
    url: https://o-ran.org/sccl
externalDocs:
  description: 'O-RAN.WG2.R1AP'
  url: 'https://www.o-ran.org/specifications'
servers:
  - url: '{apiRoot}/data-access/v2/'
    variables:
      apiRoot:
        description: 'apiRoot as defined in clause 5.3 in O-RAN.WG2.R1AP'
        default: 'https://example.com'
paths:
  '/data-jobs':
    post:
      description: 'To create a data job'
      tags:
        - Create all data jobs
      requestBody:
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/DataJobInfo'
      responses:
        '201':
          description: 'Success case 201 created'
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/DataJobInfo'
          headers:
            Location:
```

```

    description: 'Contains the URI of the newly created resource'
    required: true
    schema:
      type: string
  '400':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
  '401':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
  '403':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
  '404':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
  '405':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/405'
  '409':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/409'
  '413':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/413'
  '415':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/415'
  '429':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
  '500':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
  '502':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
  '503':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
callbacks:
  DataAvailabilityNotification:
    '{$request.body.dataAvailabilityNotificationUri}':
      post:
        description: 'Notification on the availability of requested data, with the "type" attribute
set to "org.o-ran.DME.DATA_AVAILABILITY" and the "data" attribute containing a
"DataAvailabilityNotification" structure defined in clause 7.3.8.1.5.'
        requestBody:
          required: true
          content:
            application/cloudevents+json:
              schema:
                $ref: '# O-RAN.WG2.R1AP_Notification.yaml#/components/Notification'
        responses:
          '204':
            description: 'The notification was delivered'
          '400':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
          '401':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
          '403':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
          '404':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
          '429':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
          '500':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
          '502':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
          '503':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
'/data-jobs/{dataJobId}':
  parameters:
    - name: dataJobId
      in: path
      required: true
      schema:
        $ref: '#/components/schemas/dataJobId'
  get:
    description: 'To get the created data job'
    tags:
      - Individual data job

```



```

responses:
  '200':
    description: 'Success case 200 OK'
    content:
      application/json:
        schema:
          $ref: '#/components/schemas/DataJobInfo'
  '400':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
  '401':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
  '403':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
  '404':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
  '429':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
  '500':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
  '502':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
  '503':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
put:
  description: 'To update the created data job'
  tags:
    - Individual data job
  requestBody:
    required: true
    content:
      application/json:
        schema:
          $ref: '#/components/schemas/DataJobInfo'
  responses:
    '200':
      description: 'The data job was updated'
    '400':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
    '401':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
    '403':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
    '404':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
    '429':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
    '500':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
    '502':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
    '503':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
delete:
  description: 'To delete the created data job'
  tags:
    - Individual data job
  responses:
    '204':
      description: 'The data job was deleted'
    '400':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
    '401':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
    '403':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
    '404':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
    '429':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
    '500':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'

```

```

'502':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
'503':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
'/data-jobs/{dataJobId}/status':
  description: 'To get the status of the created data job'
  tags:
    - Individual data job
  parameters:
    - name: dataJobId
      in: path
      required: true
      schema:
        $ref: '#/components/schemas/dataJobId'
  get:
    description: 'To get the status of the created data job'
    tags:
      - Individual data job
    responses:
      '200':
        description: 'The data job status is returned'
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/DataJobStatus'
      '400':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
      '401':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
      '403':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
      '404':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
      '429':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
      '500':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
      '502':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
      '503':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
  components:
    schemas:
      dataJobId:
        description: 'A successful created data job is identified by dataJobId '
        type: string
      DataJobInfo:
        description: 'Information related to a data job'
        allOf:
          - type: object
            properties:
              dataDeliveryMode:
                $ref: '#/components/schemas/DataDeliveryMode'
              dmeTypeId:
                $ref: '#/components/schemas/DmeTypeIdStruct'
              productionJobDefinition:
                description: 'Job description based on the DME type specific dataProductionSchema'
                type: object
              dataDeliveryMethod:
                $ref: '#/components/schemas/DataDeliveryMethod'
              dataDeliverySchemaId:
                description: 'A delivery schema identifier provided by a Data Producer during the data
registration procedure'
                type: string
                required: [ dataDeliveryMode, dmeTypeId, productionJobDefinition, dataDeliveryMethod,
dataDeliverySchemaId ]
            - type: object
              oneOf:
                - properties:
                    dataDeliveryMethod:
                      type: string

```

```

        enum: [ PULL_HTTP ]
        dataDeliveryMode:
          type: string
          enum: [ ONE_TIME ]
        required:
          - pullDeliveryDetailsHttp
      - properties:
        dataDeliveryMethod:
          type: string
          enum: [ PULL_HTTP ]
        dataDeliveryMode:
          type: string
          enum: [ CONTINUOUS ]
        required:
          - dataAvailabilityNotificationUri
      - properties:
        dataDeliveryMethod:
          type: string
          enum: [STREAMING_KAFKA]
        required:
          - streamingConfigurationKafka
      - properties:
        dataDeliveryMethod:
          type: string
          enum: [ PUSH_HTTP ]
        required:
          - pushDeliveryDetailsHttp
DataDeliveryMode:
  description: 'This indicates whether the data instance is created in a one-time data delivery (data
request) or continuously (data subscription)'
  type: string
  enum:
    - ONE_TIME
    - CONTINUOUS
DataDeliveryMethod:
  description: 'This indicates supported delivery method'
  type: string
  enum: [ PULL_HTTP, PUSH_HTTP, STREAMING_KAFKA ]
PullDeliveryDetailsHttp:
  description: 'The PullDeliveryDetailsHttp data type signals how to pull data using the HTTP
protocol.'
  readOnly: true
  type: object
  properties:
    dataPullUri:
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/schemas/Uri'
    required: [ dataPullUri ]
PushDeliveryDetailsHttp:
  description: 'The PushDeliveryDetailsHttp data type signals how to push data using the HTTP
protocol.'
  type: object
  properties:
    dataPushUri:
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/schemas/Uri'
    required: [ dataPushUri ]
StreamingConfigurationKafka:
  description: 'The StreamingConfigurationKafka data type signals a data streaming configuration for
the Kafka protocol.'
  type: object
  properties:
    topicName:
      description: 'Name of the Kafka topic'
      type: string
    kafkaBootstrapServers:
      description: 'Server configuration'
      type: array
      items:
        $ref: '#/components/schemas/ServerAddressWithPort'
    required: [ topicName, kafkaBootstrapServers ]
ServerAddressWithPort:
  description: 'Server configuration'

```

```

type: object
properties:
  hostname:
    description: 'string identifying a hostname shall be formatted according to clause 2.3.1 as
defined in IETF RFC 1035 [19]'
    type: string
  portAddress:
    description: 'Port address, e.g. 9092'
    type: integer
    minimum: 1
    maximum: 65535
  required: [ hostname, portAddress ]
DataAvailabilityNotification:
  description: 'Availability of the data'
  type: object
  properties:
    dataJobId:
      description: 'data job identifier'
      type: string
    pullDeliveryDetailsHttp:
      $ref: '#/components/schemas/PullDeliveryDetailsHttp'
DataJobStatus:
  description: 'The status of the data job'
  type: string
  $ref: 'TS28623_GenericNrm.yaml#/components/schemas/ProcessMonitor'
DmeTypeIdStruct:
  description: 'Defining the attributes of DME type identifier'
  type: object
  properties:
    namespace:
      type: string
      description: 'Indicating the entity responsible for the DME type definition.'
    name:
      type: string
      description: 'Name of the DME type. The string can be any character except ":" (colon)'
      pattern: '^[^:]{1,}$'
    version:
      type: string
      description: 'Version of the DME type. The versioning and allowed characters are according to
SemVer [11]'
    required: [ namespace, name, version ]

```

A.3.4 HTTP based Push data API

Deliberately, no OpenAPI is specified for this API in the present document.

NOTE: OpenAPI requires the definition of the valid content types for the request message content. However, this API is agnostic with respect to the content type of the data carried in the request message. Within the DME services, the valid content types are defined as part of separate data message schemas which specify the structure of the data to be carried over the API. Because of the requirement to fix the content types that can be carried over the API, defining an OpenAPI would restrict the versatility of the API.

A.3.5 HTTP based Pull data API

Deliberately, no OpenAPI is specified for this API in the present document.

NOTE: OpenAPI requires the definition of the valid content types for the response message content. However, this API is agnostic with respect to the content type of the data carried in the response message. Within the DME services, the valid content types are defined as part of a separate data message schema which specifies the structure of the data to be carried over the API. Because of the requirement to fix the content types that can be carried over the API, defining an OpenAPI would restrict the versatility of the API.

A.3.6 Data offer API

A.3.6.1 Introduction

The Open API for the Data offer API is specified in clause A.3.6.2.

A.3.6.2 Data offer API

```
openapi: 3.0.3
info:
  title: 'Data offer service'
  version: 2.0.0-alpha.1
  description: |
    API for Data offer service.
    R1 Common definitions - O-RAN.WG2.R1AP_Common.yaml.
    Copyright 2026 O-RAN ALLIANCE e.V.
    Licensed under the Standards Collaboration
    Copyright License Version 1.0 (the "License");
    you may not use this file except in compliance with the License.
    You may obtain a copy of the License at
    https://www.o-ran.org/scclALLIANCE.
    All rights reserved.
  license:
    name: SCCL
    url: https://o-ran.org/sccl
externalDocs:
  description: 'O-RAN.WG2.R1AP'
  url: 'https://www.o-ran.org/specifications'
servers:
  - url: '{apiRoot}/data-offer/v1'
    variables:
      apiRoot:
        description: 'apiRoot as defined in clause 5.3 in O-RAN.WG2.R1AP'
        default: 'https://example.com'
      apiConsumerId:
        description: 'Identifier of API Consumer'
        default: ''
paths:
  '/offers':
    post:
      description: 'Allows to create a new data offer'
      tags:
        - All data offers
      requestBody:
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/DataOfferInfo'
      responses:
        '201':
          description: 'Success case 201 created'
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/DataOfferInfo'
          headers:
            Location:
              description: 'Contains the URI of the newly created resource'
              required: true
              schema:
                type: string
        '400':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
        '401':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
        '403':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
```

```

'404':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
'405':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/405'
'409':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/409'
'413':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/413'
'415':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/415'
'429':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
'500':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
'502':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
'503':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
links:
  notifyDataAvailabilityLink:
    operationId: notifyDataOfferDataAvailability
    parameters:
      notificationSink: "$response.body#/dataAvailabilityNotificationUri"
    description: 'The URI referring to the notification target, local to the API Producer.'
    server:
      url: {apiRoot}
      variables:
        apiRoot:
          description: 'target operation to be called against the server defined in
{apiRoot} i.e. notificationSink is local to {apiRoot}'
          default: 'https://example.com'
    callbacks:

    DataOfferTerminationNotification:
      '{$request.body.dataOfferTerminationNotificationUri}':
        post:
          description: 'Notification on termination of data offer by the API producer, with the "type"
attribute set to "org.o-ran.DME.DATA_OFFER_TERMINATION" and the "data" attribute containing a
"DataOfferTerminationNotification" structure defined in clause 7.6.8.1.3.'
          requestBody:
            required: true
            content:
              application/cloudevents+json:
                schema:
                  $ref: '#O-RAN.WG2.R1AP_Notification.yaml#/components/Notification '
          responses:
            '204':
              description: 'The notification was delivered'
            '400':
              $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
            '401':
              $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
            '403':
              $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
            '404':
              $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
            '429':
              $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
            '500':
              $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
            '502':
              $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
            '503':
              $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
'/offers/{dataOfferId}':
  parameters:
    - name: dataOfferId
      in: path
      required: true
      schema:
        type: string

```

```

delete:
  description: 'To delete the data offer'
  tags:
  - Individual data offer
  responses:
    '204':
      description: 'The data offer was deleted.'
    '400':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
    '401':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
    '403':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
    '404':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
    '429':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
    '500':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
    '502':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
    '503':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
  '/{notificationSink}':
    post:
      description: 'Notification on the availability of offered data, with the "type" attribute set to
"org.o-ran.dme.data_offer_data_availability" and the "data" attribute containing a
"DataOfferDataAvailabilityNotification" structure defined in clause 7.6.8.1.4.'
      operationId: notifyDataOfferDataAvailability
      parameters:
        - name: notificationSink
          in: path
          required: true
          schema:
            type: string
      requestBody:
        required: true
        content:
          application/cloudevents+json:
            schema:
              $ref: 'O-RAN.WG2.R1AP_Notification.yaml#/components/Notification'
      responses:
        '204':
          description: 'The notification was delivered'
        '400':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
        '401':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
        '403':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
        '404':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
        '429':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
        '500':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
        '502':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
        '503':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
components:
  schemas:
    DataOfferInfo:
      description: 'Information related to a data offer'
      type: object
      properties:
        dataDeliveryMode:
          $ref: 'O-RAN.WG2.R1AP_DataAccess.yaml#/components/schemas/DataDeliveryMode'
        dmeTypeId:
          $ref: 'O-RAN.WG2.R1AP_DataDiscovery.yaml#/components/schemas/DmeTypeId'
        productionJobDefinition:

```

```

    description: 'Job description based on the DME type specific dataProductionSchema'
    type: object
  dataDeliveryMethods:
    type: array
    items:
      $ref: 'O-RAN.WG2.R1AP_DataAccess.yaml#/components/schemas/DataDeliveryMethod'
  dataDeliverySchemaIds:
    description: 'A delivery schema identifier provided by a Data Producer during the data
registration procedure'
    type: array
    items:
      type: string
  pullDeliveryDetailsHttp:
    $ref: 'O-RAN.WG2.R1AP_DataAccess.yaml#/components/schemas/PullDeliveryDetailsHttp'
  dataAvailabilityNotificationUri:
    $ref: '/components/schemas/DataOfferAvailabilityNotification'
  dataOfferTerminationNotificationUri:
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/schemas/Uri'
  pushDeliveryDetailsHttp:
    $ref: 'O-RAN.WG2.R1AP_DataAccess.yaml#/components/schemas/PushDeliveryDetailsHttp'
  streamingConfigurationKafka:
    $ref: 'O-RAN.WG2.R1AP_DataAccess.yaml#/components/schemas/StreamingConfigurationKafka'
  required: [ "dataDeliveryMode", "dmeTypeId", "productionJobDefinition", " dataDeliveryMethods ",
"dataDeliverySchemaIds", "dataOfferTerminationNotificationUri"]
  DataOfferTerminationNotification:
    description: 'Termination of a data offer by the API producer'
    type: object
    properties:
      dataOfferId:
        description: 'Identifies the deleted data offer'
        type: string
      required: ["dataOfferId"]
  DataOfferDataAvailabilityNotification:
    description: 'Availability of the data'
    type: object
    properties:
      dataOfferId:
        description: 'data offer identifier'
        type: string
      pullDeliveryDetailsHttp:
        $ref: 'O-RAN.WG2.R1AP_DataAccess.yaml#/components/schemas/PullDeliveryDetailsHttp'
      required: ['dataOfferId', 'pullDeliveryDetailsHttp']:
        type: string
      required: ["dataOfferId"]

```

A.4 RAN OAM related services

A.4.1 Configuration management API

A.4.1.1 Introduction

The Open API for this service is reusing the provisioning management service API as specified in clause A.4.1.2 with exceptions specified in clause A.4.1.3 below.

A.4.1.2 Configuration management API

The Open API for the Configuration management API specified in clause 8.1 reuses the Provisioning management service API (TS28532_ProvMnS.yaml) as specified in 3GPP TS 28.532 [20], clause A.1.1.

The API version of the Configuration management API as specified in clause 8.1.2 shall use the Provisioning management service OpenAPI version as specified in Table A.4.1.2-1.

Table A.4.1.2-1

API name	API version	ProvMnS OpenAPI version
Configuration management API	1.0.0	18.5.0

A.4.1.3 Adaptations and Exceptions

Table A.4.1.3-1 lists exceptions and adaptations related to HTTP methods when re-using the TS28532_ProvMnS _API in the context of the present document.

Table A.4.1.3-1: HTTP methods exceptions and adaptations when reusing the TS28532_ProvMnS _API

HTTP Methods	Reference	Attributes	Exceptions/Adaptations
PUT	3GPP TS 28.532 [20], clause A.1.1		HTTP operation not required to be supported in current version.
DELETE	3GPP TS 28.532 [20], clause A.1.1		HTTP operation not required to be supported in current version.

Within the PATCH request message content, the following content types shall be supported.

- application/3gpp-json-patch+json (3GPPTS 32.158 [29]).

A.4.2 Fault management API

A.4.2.1 Introduction

The Open API for this service is reusing the provisioning management service API as specified in clause A.4.2.2 with exceptions specified in clause A.4.2.3 below.

A.4.2.2 Fault management API

The Open API for the fault management API specified in clause 8.1 reuses the Provisioning management service API (TS28111_FaultNrm.yaml) as specified in 3GPP TS 28.111 [26], clause A.1.3.

The API version of the fault management API as specified in clause 8.2.2 shall use the FaultNRM service OpenAPI version as specified in Table A.4.2.2-1.

Table A.4.2.2-1

API name	API version	FaultNrm OpenAPI
Fault management API	1.0.0	18.1.0

A.4.2.3 Adaptations and Exceptions

NOTE: The adaptations and exceptions are not specified in present version of the document.

A.4.3 Configuration schema information API

A.4.3.1 Introduction

The Open API for the Configuration schema information API is specified in clause A.4.3.2.

A.4.3.2 Configuration schema information API

```

openapi: 3.0.3
info:
  title: 'Configuration Schema information API'
  version: 1.0.1
  description: This API enables the API Consumer to retrieve configuration schema information based on the
    procedure defined in R1GAP [5].
    R1 Common definitions - O-RAN.WG2.R1AP_Common.yaml.
    Copyright 2026 O-RAN ALLIANCE e.V.
    Licensed under the Standards Collaboration
    Copyright License Version 1.0 (the "License");
    you may not use this file except in compliance with the License.
    You may obtain a copy of the License at
    https://www.o-ran.org/scclALLIANCE.
    All rights reserved.
  license:
    name: SCCL
    url: https://o-ran.org/sccl

  apiVersion:
    description: See clause 8.3.2 (Version of the API, e.g., v1)
    default: v1
  externalDocs:
    description: 'O-RAN.WG2.R1AP'
    url: 'https://www.o-ran.org/specifications'
  servers:
    - url: '{apiRoot}/ran-oam-cm-schema-info/v1'
      variables:
        apiRoot:
          description: 'apiRoot as defined in clause 10.3 in O-RAN.WG2.R1AP'
          default: 'https://example.com'
  paths:
    '/schemas':
      get:
        summary: Get all schema information
        description: 'Retrieves configuration schema information'
        responses:
          '200':
            description: 'The results with the schema information'
            content:
              application/json:
                schema:
                  type: array
                  items:
                    $ref: '#/components/schemas/Schema'
          '400':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
          '401':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
          '403':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
          '404':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
          '405':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/405'
          '409':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/409'
          '413':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/413'
          '415':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/415'
          '429':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
          '500':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
          '502':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
          '503':
            $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'

```

```

'/schemas/{schemaId}':
  get:
    summary: Get individual schema information
    parameters:
      - name: schemaId
        in: path
        required: true
        description: Where schemaId = "name" (for latest revision or if revision is not available) or
"name@revision" for a specific revision.
    schema:
      type: string
    responses:
      '200':
        description: The results with the schema information matching the request.
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/Schema'
      '400':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
      '401':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
      '403':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
      '404':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
      '405':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/405'
      '409':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/409'
      '413':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/413'
      '415':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/415'
      '429':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
      '500':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
      '502':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
      '503':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
    components:
      schemas:
        Schema:
          type: object
          required:
            - name
            - location
            - type
          properties:
            name:
              type: string
              description: The unique name of the schema.
            revision:
              type: string
              description: The unique revision of the schema (required for YANG).
            location:
              type: string
              format: uri
              description: Location of where to find the schema content.
            type:
              $ref: '#/components/schemas/SchemaType'
              description: This data type is designed to provide extensibility. As specified in clause
8.3.8.2.3.1, Only YANG is supported in the present version of the present document.
            namespace:
              type: string
              description: The namespace of the schema, (See NOTE 1, clause 8.3.8.2.3.1, only applicable if
type is YANG).
            features:
              type: array

```

```

        items:
          type: string
          description: List of supported features (See NOTE 1, clause 8.3.8.2.3.1, only applicable if type
is YANG).
        deviations:
          type: array
          items:
            type: string
            description: List of schema deviation(s) (See NOTE 1, clause 8.3.8.2.3.1, only applicable if type
is YANG).
        SchemaType:
          type: string
          enum:
            - YANG
          description: Enumeration of schema types.

```

A.5 A1 related service

A.5.1 A1 policy management API

A.5.1.1 Introduction

The Open API for the A1 policy management API is specified in clause A.5.1.2.

A.5.1.2 A1 policy management API

```

openapi: 3.0.3
info:
  title: 'A1 policy management API'
  version: 1.0.1
  description: |
    API for A1 policy management service.
    R1 Common definitions - O-RAN.WG2.R1AP_Common.yaml.
    Copyright 2026 O-RAN ALLIANCE e.V.
    Licensed under the Standards Collaboration
    Copyright License Version 1.0 (the "License");
    you may not use this file except in compliance with the License.
    You may obtain a copy of the License at
    https://www.o-ran.org/scclALLIANCE.
    All rights reserved.
  license:
    name: SCCL
    url: https://o-ran.org/sccl

externalDocs:
  description: 'O-RAN.WG2.R1AP'
  url: 'https://www.o-ran.org/specifications'
servers:
  - url: '{apiRoot}/a1-policy-management/v1'
    variables:
      apiRoot:
        description: 'apiRoot as defined in clause 5.3 in O-RAN.WG2.R1AP'
        default: 'https://example.com'
paths:
  '/policy-types':
    get:
      description: 'To query A1 policy type identifier'
      tags:
        - All A1 policy types
      parameters:
        - name: nearRtRicId
          in: query
          description: 'The identifier of Near-RT RIC'
          schema:
            type: string
        - name: typeName

```

```

    in: query
    description: 'The unique label of the policy type'
    schema:
      type: string
  responses:
    '200':
      description: 'Success case 200 with queried information'
      content:
        application/json:
          schema:
            type: array
            items:
              $ref: '#/components/schemas/PolicyTypeInfo'
    '400':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
    '401':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
    '403':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
    '404':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
    '406':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/406'
    '429':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
    '500':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
    '502':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
    '503':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
  '/policy-types/{policyTypeId}':
    parameters:
      - name: policyTypeId
        in: path
        required: true
        schema:
          $ref: '#/components/schemas/policyTypeId'
    get:
      description: 'To query A1 policy type'
      tags:
        - Individual A1 policy type
      responses:
        '200':
          description: 'Success case 200 with queried information'
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/PolicyTypeObject'
        '400':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
        '401':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
        '403':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
        '404':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
        '406':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/406'
        '429':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
        '500':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
        '502':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
        '503':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
  '/policies':
    get:
      description: 'To query A1 policy type'
      tags:

```

```

- All A1 policies
parameters:
  - name: nearRtRicId
    in: query
    description: 'The identifier of Near-RT RIC'
    schema:
      type: string
  - name: policyTypeId
    in: query
    description: 'The identifier of the policy'
    schema:
      type: string
responses:
  '200':
    description: 'Success case 200 with queried information'
    content:
      application/json:
        schema:
          type: array
          items:
            $ref: '#/components/schemas/PolicyInformation'
  '400':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
  '401':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
  '403':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
  '404':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
  '406':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/406'
  '429':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
  '500':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
  '502':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
  '503':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
post:
  description: 'To create A1 policies'
  tags:
    - All A1 policies
  requestBody:
    required: true
    content:
      application/json:
        schema:
          $ref: '#/components/schemas/PolicyObjectInformation'
  responses:
    '201':
      description: 'Success case 201 created'
      content:
        application/json:
          schema:
            $ref: '#/components/schemas/PolicyObjectInformation'
      headers:
        Location:
          description: 'Contains the URI of the newly created resource'
          required: true
          schema:
            type: string
    '400':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
    '401':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
    '403':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
    '404':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
    '405':

```

```

    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/405'
  '409':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/409'
  '413':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/413'
  '415':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/415'
  '429':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
  '500':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
  '502':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
  '503':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
'/policies/{policyId}':
  parameters:
    - name: policyId
      in: path
      required: true
      schema:
        $ref: '#/components/schemas/policyId'
  put:
    description: 'To update a created policy'
    tags:
      - Individual A1 policy
    requestBody:
      required: true
      content:
        application/json:
          schema:
            "$ref": "#/components/schemas/PolicyObject"
    responses:
      200:
        description: 'The policy was updated'
        content:
          application/json:
            schema:
              "$ref": "#/components/schemas/PolicyObject"
  '400':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
  '401':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
  '403':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
  '404':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
  '406':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/406'
  '411':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/411'
  '413':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/413'
  '415':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/415'
  '429':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
  '500':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
  '502':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
  '503':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
  get:
    description: 'To query created A1 policy'
    tags:
      - Individual A1 policy
    responses:
      '200':
        description: 'Success case 200 with queried information'
        content:

```

```

    application/json:
      schema:
        $ref: '#/components/schemas/PolicyObject'
    '400':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
    '401':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
    '403':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
    '404':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
    '406':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/406'
    '429':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
    '500':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
    '502':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
    '503':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
  delete:
    description: 'To delete the created A1 policy'
    tags:
      - Individual A1 policy
    responses:
      '204':
        description: 'The created A1 policy was deleted'
      '400':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
      '401':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
      '403':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
      '404':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
      '406':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/406'
      '429':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
      '500':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
      '502':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
      '503':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
  '/policies/subscriptions':
    post:
      summary: Create a new A1 policy status subscription
      description: This operation creates a new subscription for receiving A1 policy status notifications.
      tags:
        - A1 policy status subscription
      requestBody:
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/PolicyStatusSubscription'
      responses:
        '201':
          description: 'Success case 201 created'
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/PolicyStatusSubscription'
          headers:
            Location:
              description: 'Contains the URI of the newly created resource'
              required: true
              schema:
                type: string

```



```

'400':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
'401':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
'403':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
'404':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
'406':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/406'
'429':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
'500':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
'502':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
'503':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
'/policies/subscriptions/{subscriptionId}':
  parameters:
    - name: subscriptionId
      in: path
      required: true
      schema:
        $ref: '#/components/schemas/subscriptionId'
  get:
    summary: Get details of an AI policy status subscription
    description: This operation retrieves information about a specific subscription.
    tags:
      - AI policy status subscription
    responses:
      '200':
        description: OK
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/PolicyStatusSubscription'
      '400':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
      '401':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
      '403':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
      '404':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
      '406':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/406'
      '429':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
      '500':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
      '502':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
      '503':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
  put:
    description: 'This operation modifies an existing subscription.'
    tags:
      - AI policy status subscription
    requestBody:
      required: true
      content:
        application/json:
          schema:
            "$ref": "#/components/schemas/PolicyStatusSubscription"
    responses:
      200:
        description: 'The policy was updated'
        content:
          application/json:
            schema:

```

```

    "$ref": "#/components/schemas/PolicyObject"
  '400':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
  '401':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
  '403':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
  '404':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
  '406':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/406'
  '411':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/411'
  '413':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/413'
  '415':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/415'
  '429':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
  '500':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
  '502':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
  '503':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'

delete:
  summary: Delete an A1 policy status subscription
  description: This operation removes a subscription.
  tags:
  - A1 policy status subscription
  responses:
    '204':
      description: No Content
components:
  schemas:
    policyTypeId:
      description: 'Policy Type identifier as defined in A1AP [23], clause 6.2.3.1.3'
      type: string
    policyId:
      description: 'Policy Identifier of a policy'
      type: string
    NearRtRicId:
      description: 'Near-RT RIC identifier'
      type: string
    subscriptionId:
      description: 'subscription identity of the policy'
      type: string
    PolicyObject:
      description: 'Policy Object is a JSON representation of an A1 policy; the A1 policies are specified in
A1TD [24]'
      type: object
    PolicyTypeObject:
      description: 'policy type object as defined in A1TD'
      type: object
    PolicyTypeInfo:
      description: 'Available policy types and for each policy type identifier the Near-RT RIC identifiers
of those Near-RT RICs that support the related A1 policy type'
      type: object
      properties:
        policyTypeId:
          description: 'Identity of the policy type'
          type: string
        nearRtRicId:
          $ref: '#/components/schemas/NearRtRicId'
          required: ["policyTypeId", "nearRtRicId"]
    PolicyInformation:
      description: 'Near-RT RIC identifiers where A1 policies exist and for each Near-RT RIC identifier the
policy identifiers of those policies that exist in that Near-RT RIC'
      type: object
      properties:

```

```

policyId:
  description:
    $ref: '#/components/schemas/policyId'

nearRtRicId:
  $ref: '#/components/schemas/NearRtRicId'
required: ["policyId","nearRtRicId"]
PolicyObjectInformation:
  description: 'Information related to the creation of the policy'
  type: object
  properties:
    policyObject:
      description: 'Policy Object is a JSON representation of an AI policy; the AI policies are
specified in AlTD [24]'
      type: object
      nearRtRicId:
        $ref: '#/components/schemas/NearRtRicId'
      policyTypeId:
        $ref: "#/components/schemas/policyTypeId"
      required: ["policyObject","nearRtRicId"]
    PolicyStatusSubscription:
      description: 'PolicyStatusSubscription data type represents the subscription information of AI
policy status'
      type: object
      properties:
        subscriptionScope:
          $ref: '#/components/schemas/QueryFilter'
        notificationDestination:
          type: URI
          description: URI for policy status notifications
        policyIdList:
          type: array
          items:
            $ref: '#/components/schemas/policyId'
        policyTypeIdList:
          type: array
          items:
            $ref: '#/components/schemas/ policyTypeId'
        nearRtRicIdList:
          type: array
          items:
            $ref: '#/components/schemas/ nearRtRicId'
    QueryFilter:
      type: string
      enum:
        - OWN #'indicate the AI policies created by API Consumer '
        - OTHERS #'indicate the AI policies created other API Consumers'
        - ALL #'indicate the AI policies created by any API Consumers'

```

A.6 AI/ML workflow service

A.6.1 AI/ML model registration API

A.6.1.1 Introduction

The Open API for the AI/ML model registration API is specified in clause A.6.1.2.

A.6.1.2 AI/ML model registration API

```

openapi: 3.0.3
info:
  title: 'AI/ML Model registration API '
  version: 1.0.1
  description: API for registering an AI/ML model|
    API for AI/ML Model registration service.

```

```

R1 Common definitions - O-RAN.WG2.R1AP_Common.yaml.
Copyright 2026 O-RAN ALLIANCE e.V.
Licensed under the Standards Collaboration
Copyright License Version 1.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at
https://www.o-ran.org/scclALLIANCE.
All rights reserved.
license:
  name: SCCL
  url: https://o-ran.org/sccl

externalDocs:
  description: 'O-RAN.WG2.R1AP'
  url: 'https://www.o-ran.org/specifications'
servers:
  - url: '{apiRoot}/ai-ml-model-registration/{apiVersion}'
paths:
  '/model-registrations':
    post:
      description: 'Register a new AI/ML model'
      tags:
        - Registered AI/ML Model registration details
      requestBody:
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/ModelRelatedInformation'
      responses:
        '201':
          description: 'Success case 201 created'
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/ModelRelatedInformation'
          headers:
            Location:
              description: 'Contains the URI of the newly created resource'
              required: true
              schema:
                type: string
        '400':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
        '401':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
        '403':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
        '404':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
        '405':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/405'
        '409':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/409'
        '413':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/413'
        '415':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/415'
        '429':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
        '500':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
        '502':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
        '503':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'

  '/model-registrations/{modelRegistrationId}':
    get:
      summary: Get details of a registered AI/ML model
      parameters:

```

```

- in: path
  name: modelRegistrationId
  required: true
  schema:
    type: string
responses:
  '200':
    description: AI/ML model details retrieved successfully
    content:
      application/json:
        schema:
          $ref: '#/components/schemas/ModelRelatedInformation'
  '400':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
  '401':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
  '403':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
  '404':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
  '405':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/405'
  '409':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/409'
  '413':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/413'
  '415':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/415'
  '429':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
  '500':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
  '502':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
  '503':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
put:
  summary: Update information of a registered AI/ML model
  parameters:
    - in: path
      name: modelRegistrationId
      required: true
      schema:
        type: string
  requestBody:
    required: true
    content:
      application/json:
        schema:
          $ref: '#/components/schemas/ModelRelatedInformation'
  responses:
    '200':
      description: AI/ML model information updated successfully
      content:
        application/json:
          schema:
            $ref: '#/components/schemas/ModelRelatedInformation'
    '400':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
    '401':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
    '403':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
    '404':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
    '405':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/405'
    '409':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/409'
    '413':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/413'

```

```

    '415':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/415'
    '429':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
    '500':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
    '502':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
    '503':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'

delete:
  summary: Deregister an AI/ML model
  parameters:
    - in: path
      name: modelRegistrationId
      required: true
      schema:
        type: string
  responses:
    '204':
      description: AI/ML model deregistered successfully
    '400':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
    '401':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
    '403':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
    '404':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
    '429':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
    '500':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
    '502':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
    '503':
      $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'

components:
  schemas:
    ModelRelatedInformation:
      type: object
      properties:
        modelId:
          $ref: '#/components/schemas/ModelId'
        description:
          type: string
        modelInformation:
          $ref: '#/components/schemas/ModelInformation'
        modelLocation:
          type: string
          format: uri
      required:
        - modelId
        - description
        - modelInformation
    ModelId:
      type: object
      description: 'Identifier of a model'
      properties:
        modelName:
          type: string
          description: 'name of AI/ML model as specified in R1GAP'
        modelVersion:
          type: string
          description: 'version of AI/ML model as specified in R1GAP'
        artifactVersion:
          type: string
          format: uri
          description: 'artifact version of AI/ML model as specified in R1GAP'
      required:

```

```

- modelName
- modelVersion
ModelInformation:
  type: object
  properties:
    metadata:
      description: 'Meta data of AI/ML Model'
      $ref: '#/components/schemas/MetaData'
    inputDataType:
      type: array
      description: 'Input data type for the model, the structure of dataTypeId is specified in clause
7.1.8'
      items:
        $ref: 'O-RAN.WG2.R1AP_DataRegistration.yaml#/components/schemas/DataTypeId' # DataTypeId is
specified (clause 7.1.8)
    outputDataType:
      type: array
      description: 'Output data type for the model, the structure of dataTypeId is specified in
(clause 7.1.8)'
      items:
        $ref: 'O-RAN.WG2.R1AP_DataRegistration.yaml#/components/schemas/DataTypeId' # DataTypeId is
specified (clause 7.1.8)
    targetEnvironment:
      type: array
      description: 'Information on the target environment is required for deployment of an AI/ML
model'
      items:
        $ref: '#/components/schemas/TargetEnvironment'
  required:
    - metadata
    - inputDataType
    - outputDataType
MetaData:
  type: object
  properties:
    author:
      type: string
      description: 'Author of an AI/ML model'
    owner:
      type: string
  required:
    - author
TargetEnvironment:
  type: object
  properties:
    platformName:
      type: string
      description: 'Name of the platform'
    environmentType:
      type: string
      description: 'Name of the platform execution service type, and this is dependent on the
platformName'
    dependencyList:
      type: string
      format: uri
      description: 'Location to the template that has all the list of dependencies platform must
provide needs to be installed for the model. (for example, scikit-learn 0.21.3)'
  required:
    - platformName
    - environmentType
    - dependencyList

```

A.6.2 AI/ML model discovery API

A.6.2.1 Introduction

The Open API for the AI/ML model discovery API is specified in clause A.6.2.2.

A.6.2.2 AI/ML model discovery API

```

openapi: 3.0.0
info:
  title: AI/ML Model Discovery API
  version: 1.1.1 # Placeholder: actual version to be defined in clause 10.2.2.
  description: |
    R1 Common definitions - O-RAN.WG2.R1AP_Common.yaml.
    Copyright 2026 O-RAN ALLIANCE e.V.
    Licensed under the Standards Collaboration
    Copyright License Version 1.0 (the "License");
    you may not use this file except in compliance with the License.
    You may obtain a copy of the License at
    https://www.o-ran.org/scclALLIANCE.
    All rights reserved.
  license:
    name: SCCL
    url: https://o-ran.org/sccl

servers:
  - url: '{apiRoot}/ai-ml-model-discovery/{apiVersion}'
    description: Base URL for the AI/ML Model Discovery API.
    variables:
      apiRoot:
        description: The root path of the API, as defined in clause 5.2 of the specification.
        default: https://example.com/api # Example placeholder for apiRoot
      apiVersion:
        description: The version of the API, as defined in clause 10.2.2 of the specification.
        default: v1.1 # Example placeholder for apiVersion

paths:
  /models:
    get:
      summary: Retrieve all registered AI/ML models
      description: |
        This resource represents all registered AI/ML models in the Non-RT RIC.
        This GET method supports filtering by `model-name` and `model-version`
        query parameters. If multiple query parameters are provided, these
        shall be combined with an AND logical operation when evaluating the query.
      operationId: getAllRegisteredModels
      parameters:
        - name: model-name
          in: query
          description: Name of the model as specified in R1GAP[5].
          required: false
          schema:
            type: string
        - name: model-version
          in: query
          description: Version of the model as specified in R1GAP[5].
          required: false
          schema:
            type: string
      responses:
        '200':
          description: |
            The message content of the GET response carries an array of model
            identifiers and metadata of the models.
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: '#/components/schemas/ModelRelatedInformation'
        '400':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
        '401':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
        '403':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
        '404':

```



```

    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
  '406':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/406'
  '414':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/414'
  '429':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
  '500':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
  '502':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
  '503':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'

```

/models/{modelId}:

get:

summary: Retrieve an individual AI/ML model's location

description: |

This resource represents the model location for a specific AI/ML model, identified by its unique `modelId`.

operationId: getIndividualModelLocation

parameters:

```

- name: modelId
  in: path
  description: The unique identifier of the AI/ML model.
  required: true
  schema:
    $ref: '#/components/schemas/ModelId'

```

responses:

```

  '200':
    description: |
      The model location related information associated with the `modelId`
      has been successfully retrieved. The response contains the
      `ModelLocationInformation` as a representation of the resource.
    content:
      application/json:
        schema:
          $ref: '#/components/schemas/ModelLocationInformation'
  '400':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
  '401':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
  '403':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
  '404':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
  '406':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/406'
  '414':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/414'
  '429':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
  '500':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
  '502':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
  '503':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'

```

components:

schemas:

ModelRelatedInformation:

type: object

description: 'The ModelRelatedInformation data type represents registration information for an AI/ML model'

required:

```

- modelId
- metadata

```

properties:

```

    modelId:
      $ref: 'O-RAN.WG2.R1AP_AI/ML_model_registrtaion_API.yaml/components/schemas/ModelId'
      description: "Identifier of a model as specified in clause 10.1.8.1.3"
    metadata:
      type: string
      description: "Description of the AIML model that includes the AI/ML model related information
and training related information"
    ModelLocationInformation:
      type: object
      description: |
        Represents the location and related information for an individual AI/ML model.
      required:
        - locationUri
      properties:
        locationUri:
          type: string
          format: uri
          description: The URI where the AI/ML model artifact can be accessed or downloaded.
          example: "https://model-repo.example.com/models/123e4567-e89b-12d3-a456-426614174000/v1.0"
        modelId: # Including modelId here for context, though not strictly required by the prompt's schema
definition
      $ref: 'O-RAN.WG2.R1AP_AI/ML_model_registrtaion_API.yaml/components/schemas/ModelId'
      description: "Identifier of a model as specified in clause 10.1.8.1.3"

```

A.6.3 AI/ML model training API

A.6.3.1 Introduction

The Open API for the AI/ML model API is specified in clause A.6.3.2.

A.6.3.2 AI/ML model training API

```

openapi: 3.0.3
info:
  title: 'AI/ML Model Training API'
  version: 1.0.0-alpha.2
  description: |
    R1 Common definitions - O-RAN.WG2.R1AP_Common.yaml.
    Copyright 2026 O-RAN ALLIANCE e.V.
    Licensed under the Standards Collaboration
    Copyright License Version 1.0 (the "License");
    you may not use this file except in compliance with the License.
    You may obtain a copy of the License at
    https://www.o-ran.org/scclALLIANCE.
    All rights reserved.
  license:
    name: SCCL
    url: https://o-ran.org/sccl
  externalDocs:
    description: 'O-RAN.WG2.R1AP'
    url: 'https://www.o-ran.org/specifications'
  servers:
    - url: '{apiRoot}/ai-ml-model-training/v1'
      variables:
        apiRoot:
          description: 'apiRoot as defined in clause 10.3 in O-RAN.WG2.R1AP'
          default: 'https://example.com'
  paths:
    '/training-jobs':
      post:
        summary: Create a new AI/ML model training job
        tags:
          - Creation of AI/ML model training job
        requestBody:
          required: true

```

```

content:
  application/json:
    schema:
      $ref: "#/components/schemas/TrainingJobDescription"
responses:
  '201':
    description: 'Success case 201 created'
    content:
      application/json:
        schema:
          $ref: '#/components/schemas/TrainingJobInfo'
    headers:
      Location:
        description: 'Contains the URI of the newly created resource'
        required: true
        schema:
          type: string
  '400':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
  '401':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
  '403':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
  '404':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
  '405':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/405'
  '409':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/409'
  '413':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/413'
  '415':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/415'
  '429':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
  '500':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
  '502':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
  '503':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'

'/training-jobs/{trainingJobId}':
  delete:
    summary: 'Delete an AI/ML model training job'
    tags:
      - Delete AI/ML model training job
    responses:
      '204':
        description: 'The AI/ML model training job was AI/ML deleted'
      '400':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
      '401':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
      '403':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
      '404':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
      '406':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/406'
      '429':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
      '500':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
      '502':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
      '503':
        $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
  '/training-jobs/{trainingJobId}/status':
    get:
      summary: Get the status of an AI/ML model training job

```

```

tags:
  - Status of AI/ML model training job
parameters:
  - in: path
    name: trainingJobId
    required: true
    schema:
      type: string
responses:
  '200':
    description: 'Training job status retrieved successfully'
    content:
      application/json:
        schema:
          type: array
          items:
            $ref: '#/components/schemas/TrainingJobStatus'
  '400':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
  '401':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
  '403':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
  '404':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
  '406':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/406'
  '429':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/429'
  '500':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
  '502':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/502'
  '503':
    $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/503'
components:
  schemas:
    TrainingJobDescription:
      type: object
      properties:
        modelId:
          $ref: "#O-RAN.WG2.R1AP_ai_ml_model_registration.yaml/components/schemas/modelId"
          description: "The model identifier which contains model name, model version, and artifact
version see clause 10.1.8.1.3-1 in R1AP."
        modelLocation:
          type: string
          format: uri
          description: "Location of the AI/ML model."
        trainingDataset:
          type: string
          format: uri
          description: "Information for reference to the training dataset."
        validationDataset:
          type: string
          format: uri
          description: "Information for reference to the validation dataset."
        trainingConfig:
          type: object
          description: "Configuration of AI/ML model training based on training service producer specific
trainingConfigSchema."
        notificationDestination:
          type: string
          format: uri
          description: "Callback URI where the notification should be delivered to."
        consumerRAppId:
          type: string
          description: "rAppId of the training service consumer rApp."
        producerRAppId:
          type: string
          description: "rAppId of the training service producer rApp."
      required:

```

- modelId

A.6.4 AI/ML model deployment API

A.6.4.1 Introduction

The Open API for the AI/ML model deployment API is specified in clause A.6.4.2.

A.6.4.2 AI/ML model deployment API

```
openapi: 3.0.3
info:
  title: 'AI/ML Model Deployment API'
  version: 1.0.0-alpha.1
  description: |
    R1 Common definitions - O-RAN.WG2.R1AP_Common.yaml.
    Copyright 2026 O-RAN ALLIANCE e.V.
    Licensed under the Standards Collaboration
    Copyright License Version 1.0 (the "License");
    you may not use this file except in compliance with the License.
    You may obtain a copy of the License at
    https://www.o-ran.org/scclALLIANCE.
    All rights reserved.
license:
  name: SCCL
  url: https://o-ran.org/sccl
externalDocs:
  description: 'O-RAN.WG2.R1AP'
  url: 'https://www.o-ran.org/specifications'
servers:
  - url: '{apiRoot}/ai-ml-model-deployment/v1'
    variables:
      apiRoot:
        description: 'apiRoot as defined in clause 5.2 in O-RAN.WG2.R1AP'
        default: 'https://example.com'
paths:
  '/model-deployments':
    post:
      summary: Request AI/ML model deployment
      tags:
        - Request AI/ML model deployment
      requestBody:
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/ModelDeploymentInformation'
      responses:
        '201':
          description: 'AI/ML model deployment created successfully'
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/ModelDeploymentInformation'
          headers:
            Location:
              description: 'URI of the created deployment resource'
              required: true
              schema:
                type: string
        '400':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/400'
        '401':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/401'
        '403':
          $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/403'
        '404':
```

```
$ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/404'
'500':
  $ref: 'O-RAN.WG2.R1AP_Common.yaml#/components/responses/500'
```

```
components:
  schemas:
    ModelDeploymentInformation:
      type: object
      properties:
        modelId:
          $ref: '#/components/schemas/ModelId'
          description: 'Unique identifier for the AI/ML model.'
        deploymentLocation:
          type: string
          format: uri
          description: 'URI for the deployment location.'
        deploymentConfig:
          type: object
          description: 'Configuration parameters for AI/ML model deployment.'
      required:
        - modelId
        - deploymentLocation

    DeploymentStatus:
      type: object
      properties:
        deploymentId:
          type: string
          description: 'Identifier for the AI/ML model deployment.'
        status:
          type: string
          description: 'Current status of the deployment.'
        details:
          type: string
          description: 'Additional details about the deployment status.'
```

Annex B (normative): Common data types for R1 service APIs

B.1 Introduction

In the subsequent clauses, common data types for the following areas are defined:

- Generic usage,
- Service management and exposure,
- Data management and exposure,
- RAN OAM.

B.2 Common data types for Generic Usage

B.2.1 Introduction

This clause defines common data types for generic usage.

B.2.2 Simple data types

Table B.2.2-1: Simple data types for generic use

Type name	Type Definition	Description
Uri	string	A string formatted according to IETF RFC 3986 [8].
NotificationType	string	A string formatted as concatenation of "org.o-ran.", a string representing the service name (e.g. "DME"), a dot ".", and an API-specific name for the event type (e.g. "DATA_AVAILABILITY") defined in the API specification.

B.2.3 Enumeration

B.2.3.1 Void

B.2.4 Structured data types

B.2.4.1 Data type: ProblemDetails

The ProblemDetails structure is specified in table B.2.4.1-1. It is based on IETF RFC 7807 [10] and shall comply with the provisions defined there.

Table B.2.4.1-1: Definition of type ProblemDetails

Attribute name	Data type	P	Cardinality	Description
type	string	O	0..1	URI reference according to IETF RFC 3986 [8] that identifies the problem type.
title	string	O	0..1	Human-readable summary of the problem type.
status	number	O	0..1	The HTTP status code.
detail	string	O	0..1	Human-readable explanation.
instance	string	O	0..1	URI reference that identifies the specific occurrence of the problem.

B.2.4.2 Void

B.2.4.3 Void

B.2.4.4 Void

B.2.4.5 Data type: Notification

The general Notification data structure is specified in table B.2.4.5-1, aligned with the CloudEvents specification [30].

Table B.2.4.5-1: Definition of type Notification

Attribute name	Data type	P	Cardinality	Description
id	string	M	1	Unique identifier of the event, unique within the scope identified by the “source” attribute, as defined in CloudEvents [30].
specversion	string	M	1	The version of the CloudEvents specification which the event uses, as defined in CloudEvents [X]. E.g. the spec version is 1.0 aligned with the version of the CloudEvents specification [30]. (See NOTE).
type	NotificationType	M	1	See table B.2.2.
source	string	M	1	The source from which the event from has originated, as defined in CloudEvents [30].
dataschema	Uri	O	0..1	Identifies the schema that data adheres to, as defined in CloudEvents [30]. (See NOTE).
datacontenttype	object	O	0..1	Content type of the value of the “data” attribute, as defined in CloudEvents [30]. (See NOTE).
data	string	O	0..1	Application event payload data encoded as declared by the “datacontenttype” attribute. The structure of this attribute is defined by the API that specifies the notification type.
time	string	O	0..1	Timestamp when the event is generated, as defined in CloudEvents [30].
NOTE : The naming convention is aligned with that of CloudEvents, hence deviating from the “lowerCamel” convention used commonly in the R1 service APIs.				

B.2.5 Re-used data types

Re-used data types are not defined in the present document.

B.3 Common data types for Service management and exposure

B.3.1 Introduction

This clause defines common data types for usage in the service management and exposure APIs.

Clause B.3.5 references and profiles data types defined in external specifications and defines restrictions on and adaptations of these data type for their usage within the context of the service management and exposure APIs.

B.3.2 Simple data types

None.

B.3.3 Enumerations

None.

B.3.4 Structured data types

B.3.4.1 Data type: VersionExtensions

The VersionExtensions data structure specified in table B.3.4.1-1 defines extensions to the CAPIF "Version" data type which allows to signal the versions supported for an interface endpoint.

Table B.3.4.1-1: Definition of type VersionExtensions

Attribute name	Data type	P	Cardinality	Description
fullApiVersions	array(string)	M	1..N	List of version strings, as defined in clause 5.2, to signal the API versions supported by the API Producer for a particular major API version.

B.3.4.2 Data type: ServiceProperties

The ServiceProperties data structure specified in table B.3.4.2-1 defines a container to be used to register and discover service-specific properties of individual service APIs.

Table B.3.4.2-1: Definition of type ServiceProperties

Attribute name	Data type	P	Cardinality	Description
serviceCapabilities	object	M	0..1	Service capabilities. The content of this attribute is service-specific and is defined per service.

B.3.5 Re-used data types

Table B.3.5-1 references data types that are reused from external documents by the service management and exposure APIs and defines restrictions on and adaptations of these data type for their usage within the context of the service management and exposure APIs.

NOTE: All externally-defined data types that are directly used in request or response message content of the service management and exposure APIs (such as ServiceAPIDescription) are listed below. In addition, those externally-defined data types are listed that are descendants of a directly used data type and for which restrictions and adaptations are defined in the present document. Other external descendant data types are not listed, as they are referenced directly in the external specification.

Table B.3.5-1: Re-used data types

Data type	Reference	Comments	Applicability
ServiceAPIDescription	3GPP TS 29.222 [9], clause 8.2.4.2.2	The following attributes are not applicable in the context of the R1 SME services and therefore need not be supported: "supportedFeatures", "shareableInfo", "serviceAPICategory", "ccfld", "apiSuppFeats", "pubApiPath"	
InterfaceDescription	3GPP TS 29.222 [9], clause 8.2.4.2.3	The CAPIF feature "ExtendedIntfDesc" shall be supported .	
AefProfile	3GPP TS 29.222 [9], clause 8.2.4.2.4	The AEF profile holds information related to the discoverable APIs produced by a single API Producer. In case the API Producer is an rApp, the "aefld" attribute shall contain the value of the rAppID. The following attributes are not applicable in the context of the R1 SME services and need therefore not be supported: "aefLocation", "domainName", "serviceKpis", and "uelpRange".	
Version	3GPP TS 29.222 [9], clause 8.2.4.2.5	The following additional attribute shall be supported: "vendorSpecific-o-ran.org" of type VersionsList as specified in clause B.3.4.1, to signal the full API versions supported	
CAPIFEvent	3GPP TS 29.222 [9], clause 8.3.4.3.3	The enumeration values "SERVICE_API_AVAILABLE", "SERVICE_API_UNAVAILABLE" and "SERVICE_API_UPDATE" shall be supported. The remaining enumeration values are not applicable in the context of the R1 SME services and therefore need not be supported.	

B.4 Common data types for Data Management and Exposure

B.4.1 Introduction

This clause defines common data types for DME usage.

B.4.2 Simple data types

Table B.4.2-1: Simple data types

Type Name	Type Definition	Description
DmeTypeld	string	A DME type Id is constructed based on the three parts separated by ":" (colon) {dataTypeld} = {namespace}:{name}:{version} See clause B.4.4.1 for the definition of "namespace", "name" and "version".

B.4.3 Enumerations

B.4.3.1 Enumeration: DataDeliveryMethod

Table B.4.3.1-1: Enumeration: DataDeliveryMethod

Enumeration value	Description
STREAMING_KAFKA	Kafka based streaming delivery mechanism as defined in R1TP [7], clause 6.
PULL_HTTP	HTTP based pull delivery mechanism as defined in clause 7.5.
PUSH_HTTP	HTTP based push delivery mechanism as defined in clause 7.4.

B.4.4 Structured data types

B.4.4.1 Data type: DmeTypeIdStruct

The DmeTypeIdStruct data type contains the attributes defined in table B.4.4.1-1.

Table B.4.4.1-1: Definition of type DmeTypeIdStruct

Attribute Name	Data type	P	Cardinality	Description
namespace	string	M	1	Indicating the entity responsible for the DME type definition.
name	string	M	1	Name of the DME type. The string shall not contain the colon ":" character.
version	string	M	1	Version of the DME type. The versioning and allowed characters are according to SemVer [11].

B.4.4.2 Data type: DataDeliveryMechanism

The DataDeliveryMechanism data type contains the attributes defined in table B.4.4.2-1.

Table B.4.4.2-1: Definition of type DataDeliveryMechanism

Attribute Name	Data type	P	Cardinality	Description
dataDeliveryMethod	DataDeliveryMethod	M	1	Delivery method supported by a Data Producer. See clause B.4.3.1.
kafkaDeliveryConfiguration	KafkaDeliveryConfiguration	C	0..1	See clause B.4.4.3 (NOTE).
NOTE: This attribute shall be presented if the "deliveryMethod" attribute is set to STREAMING_KAFKA.				

B.4.4.3 Data type: KafkaDeliveryConfiguration

The KafkaDeliveryConfiguration data type contains the attributes defined in table B.4.4.3-1.

Table B.4.4.3-1: Definition of type KafkaDeliveryConfiguration

Attribute Name	Data type	P	Cardinality	Description
numPartitions	integer	O	0..1	Number of partitions.
cleanUpPolicy	string	M	1	cleanUpPolicy is based on cleanup.policy defined in the Kafka Documentation [15].
compressionType	string	M	1	compressionType is based on compression.type defined in the Kafka Documentation [15] .
retentionBytes	integer	C	0..1	retentionBytes is based on retention.bytes defined in the Kafka Documentation [15].
retentionMs	integer	C	0..1	retentionMs is based on retention.ms defined in the Kafka Documentation [15].
NOTE: Presence condition "C" this attribute may be included when cleanUpPolicy is set to DELETE.				

B.4.5 Re-used data types

Re-used data types are not defined in the present document.

B.5 Common data types for RAN OAM related services

B.5.1 Introduction

This clause defines common data types for usage in the RAN OAM related service APIs.

Clause B.5.5 references and profiles data types defined in external specifications and defines restrictions on and adaptations of these data type for their usage within the context of the RAN OAM related APIs.

B.5.2 Simple data types

None.

B.5.3 Enumerations

None.

B.5.4 Structured data types

None.

B.5.5 Re-used data types

Table B.5.5-1 references data types that are reused from external documents by the RAN OAM related service APIs and defines restrictions on and adaptations of these data type for their usage within the context of the RAN OAM related APIs.

NOTE: All externally defined data types that are directly used in request or response message content of the RAN OAM related service APIs are listed below. In addition, those externally defined data types are listed that are descendant of a directly used data type and for which restrictions and adaptations are defined in the present document. Other external ancestor data types are not listed, as they are referenced directly in the external specification.

Table B.5.5-1: Re-used data types

Data type	Reference	Comments	Applicability
Resource	3GPP TS 28.532 [20], clause 12.1.1.4.1a.1	All the attributes are supported.	
Scope	3GPP TS 28.532 [20], clause 12.1.1.4.1a.2	All the attributes are supported.	
PatchItem	3GPP TS 28.532 [20]ss, clause 12.1.1.4.1a.9	All the attributes are supported.	

Annex (informative): Bibliography

ETSI GS NFV-SOL 015v1.2.1: “ Protocols and Data Models; Specification of Patterns and Conventions for RESTful NFV-MANO APIs“, December 2020.

Annex (informative): Change history

Date	Revision	Description
2025.11.24	10.00	updates to Open APIs to include the SCCL license, updates to data availability notifications for Data access API and for Data offer API and updated the configuration schema API to release version.
2025.07.07	09.00	Published with updating the Configuration management API, Data registration API, configuration schema API and AI/ML model discovery API, Void the clause of AI/ML model retrieve API, and adopting the specifications to TS template version04.
2025.03.14	08.00	Published with updating the Bootstrap API, RAN OAM CM API's, RAN OAM FM API's, Adding Configuration schema information API, AI/ML Model deployment API, AI/ML model retrieve API, Updates to AI/ML model registration API, AI/ML model discovery API and AI/ML model training API.
2024.11.21	07.00	Published with migration of all API's from Release 17 to Release 18 of 3GPP, Updated the A1 Policy management API and Model discovery API and moved the same to release version, Updated the Data registration API, Data access API and Data offer API by removing the consumerId from the uri structure.
2024.07.18	06.00	Published with addition of Bootstrap API in SME, AI/ML model registration, AI/ML model discovery, AI/ML model training API in AI/ML workflow service, Updated A1 policy management API, Uplifted all the DME, AI/ML,A1 policy management APIs in compliance with 29.501 URI Structure, and generalized the DME API to support further enhancements. Updated the naming of data type to DME type.
2024.03.18	05.00	Published with addition of A1 policy management API , RAN OAM CM and FM API , updates to data registration API and removing alpha indicator for data registration API.
2023.11.20	04.00	Published as version 04.00 with addition of Service events subscription API, data access API, Configuration management API and removed alpha indicator for data registration API , data discovery API , service events subscription API and data access API.
2023.07.29	03.00	Published version 03.00
2023.03.24	02.00	Published version 02.00
2022.11.19	01.00	Published version 01.00