WanderLog — Final ER Diagram

Chen notation · cardinalities read across the relationship (e.g. 1 user — N posts) · 0..1 = optional

Entity
Relationship
Attribute (underlined = key)

MODERATORS
user_id
moderator_since
0..1
REVIEWS
IS_A
0..1
1
CREATES
1
N
USERS
user_id
username
email
password_hash
display_name
bio
account_status
created_at
updated_at
followed_at
follower
following
FOLLOWS
M
N
POSTS
post_id
title
content
location
created_at
updated_at
LIKES_POST
N
M
liked_at
1
HAS_COMMENT
N
1
ABOUT_POST
N
exactly one
1
WRITES_COMMENT
N
M
LIKES_COMMENT
N
liked_at
COMMENTS
comment_id
created_at
content
updated_at
1
ABOUT_COMMENT
N
REPORTS
N
report_id
reason
status
created_at
N
1
WRITES_REPLY
N
1
REPLIES_TO
N
1
ABOUT_REPLY
N
REPLIES
reply_id
content
created_at
updated_at
SUBMITS

Design notes

- Likes are M:N → junction tables post_likes / comment_likes (user_id, post_id | comment_id, liked_at), composite PK.
- FOLLOWS is a self-referencing M:N; CHECK follower ≠ following.
- MODERATORS is a subtype of USERS (user_id is PK and FK).
- Each report targets exactly one of post / comment / reply (3 nullable FKs + CHECK exactly one is NOT NULL).
- REVIEWS is optional per report: reviewed_by is NULL until a moderator picks it up.
- username and email are UNIQUE.
- Only posts and comments can be liked (replies cannot).
- liked_at is stored on the like relationships (post_likes / comment_likes).