

TUGAS PERORANGAN/INDIVIDU

LAPORAN JOBSHEET MINGGU 7

REDUX

Disusun Sebagai:

MATA KULIAH: PEMROGRAMAN BERBASIS FRAMEWORK

Oleh:

Moh. Khoirul Arifin/1741720051

TI-3B



PROGRAM STUDI D-IV TEKNIK INFORMATIKA

JURUSAN TEKNOLOGI INFORMASI

POLITEKNIK NEGERI MALANG

2020

1. Install Redux

```
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents
": "win32", "arch": "x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@1.2.11 (node_modules\w
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents
s": "win32", "arch": "x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@1.2.11 (node_modules\w
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents
s": "win32", "arch": "x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@1.2.11 (node_modules\j
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents
s": "win32", "arch": "x64"})

+ redux@4.0.5
added 2 packages from 1 contributor and audited 919180 packages in 63.15s

found 302 moderate severity vulnerabilities
run `npm audit fix` to fix them, or `npm audit` for details
```

2. Install React-Redux

```
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@1.2.11 (node_modules\w
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents
s": "win32", "arch": "x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@1.2.11 (node_modules\w
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents
s": "win32", "arch": "x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@1.2.11 (node_modules\j
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents
s": "win32", "arch": "x64"})

+ react-redux@7.2.0
added 2 packages from 2 contributors and audited 919176 packages in 78.096s
52 packages are looking for funding
run `npm fund` for details

found 302 moderate severity vulnerabilities
run `npm audit fix` to fix them, or `npm audit` for details
```

3. Membuat Folder action



a. Membuat File actionCreator.js

```
import { ADD_TODO, REMOVE_TODO, TOGGLE_TODO,
SET_VISIBILITY_FILTER } from './actionTypes'
```

```

let TodoId = 2

export const addTodo = text => ({
  type: ADD_TODO,
  id: TodoId++,
  text
})

export const deleteTodo = (id) => ({
  type: REMOVE_TODO,
  id: id
})

export const toggleTodo = (id) => ({
  type: TOGGLE_TODO,
  id: id
})

export const setVisibilityFilter = filter => ({
  type: SET_VISIBILITY_FILTER,
  filter
})

```


b. Membuat File actionTypes.js

```

export const ADD_TODO = 'ADD_TODO'
export const TOGGLE_TODO = 'TOGGLE_TODO'
export const REMOVE_TODO = 'REMOVE_TODO'
export const SHOW_ALL = 'SHOW_ALL'
export const SHOW_COMPLETED = 'SHOW_COMPLETED'
export const SHOW_ACTIVE = 'SHOW_ACTIVE'
export const SET_VISIBILITY_FILTER = 'SET_VISIBILITY_FILTER'

```

4. Membuat Folder containers



a. Membuat File createTodo.js

```

import React, {Component} from 'react'
import {connect} from 'react-redux'
import {addTodo} from '../action/actionCreator'
import {bindActionCreators} from 'redux'

class createTodo extends Component {
  constructor(props) {
    super(props)
    this.state = {
      todotext: '',
    }
    this.onChangeTodoText = this.onChangeTodoText.bind(this)
  }
  onChangeTodoText(e) {

```

```

        this.setState({
          todotext: e.target.value
        })
      }
      render() {
        return (
          <div className="form-group row">
            <div className="col-xl-5 col-lg-6 col-md-8 col-sm-10 mx-auto text-center form p-4">
              <input onChange={this.onChangeTodoText} value={this.state.todotext} type="text" className="form-control" id="inputEmail3" style={{textAlign: "center"}} placeholder="add todo here"/>
              <button type="button" onClick={() => this.setState({ todotext: '' })} style={{marginTop: "25px", marginRight: "15px"}} className="btn btn-danger">
                Cancel
              </button>
              <button type="button" onClick={() => {this.props.addToDo(this.state.todotext); this.setState({ todotext: '' })}} style={{marginTop: "25px"}} className="btn btn-success">
                Add Todo
              </button>
            </div>
          </div>
        );
      }
    }

    const mapDispatchToProps = (dispatch) => {
      return bindActionCreators({
        addToDo
      }, dispatch)
    }

    export default connect(null, mapDispatchToProps)(createTodo)

```

b. Membuat File table.js

```

import React, { Component } from "react";
import { connect } from "react-redux";
import {
  deleteTodo,
  toggleTodo,
  setVisibilityFilter
} from "../action/actionCreator";
import { SHOW_ALL, SHOW_COMPLETED, SHOW_ACTIVE } from "../action/actionsTypes";
import { bindActionCreators } from "redux";

class Table extends Component {
  render() {
    return (
      <div className="col-lg-10 offset-lg-1 col-md-10 col-sm-12 col-xs-12">
        <nav style={{ marginTop: "60px" }}>
          <ol className="breadcrumb">
            <li>

```

```

        className={"breadcrumb-
item "+ (this.props.visibilityFilter === SHOW_ALL ? 'active' : ''
) }
        onClick={() => this.props.setVisibilityFi
lter(SHOW_ALL)}
    >
        All
    </li>
    <li
        className={"breadcrumb-
item "+ (this.props.visibilityFilter === SHOW_COMPLETED ? 'active
' : '') }
        onClick={() => this.props.setVisibilityFi
lter(SHOW_COMPLETED)}
    >
        Completed
    </li>
    <li
        className={"breadcrumb-
item "+ (this.props.visibilityFilter === SHOW_ACTIVE ? 'active' :
'') }
        onClick={() => this.props.setVisibilityFi
lter(SHOW_ACTIVE)}
    >
        Active
    </li>
</ol>
</nav>
{this.props.todos.length !== 0 ? (
    <table
        style={{ marginTop: "60px" }}
        className="table table-hover table-dark"
    >
        <thead>
            <tr>
                <th scope="col">Todos</th>
                <th scope="col">Actions</th>
            </tr>
        </thead>
        <tbody>
            {this.props.todos.map(todo => (
                <tr key={todo.id}>
                    <td
                        style={{
                            textDecoration: todo.completed ?
"line-through" : "none" }}
                    >
                        {todo.text} {todo.completed =
== true ? "(completed)" : ""}
                    </td>
                    <td>
                        <span
                            className="fas fa-minus-
circle"
                            onClick={() => this.props.del
eteTodo(todo.id)}
                        >
                            style={{
                                color: "white",
                                fontSize: "20pt",
                                marginRight: "20px"
                            }}

```

```

        />
        <span
          className="fas fa-check-
circle"
          onClick={() => this.props.tog
          style={{ color: "white", font
Size: "20pt" }}
        />
      </td>
    </tr>
  )}
</tbody>
</table>
):(
  <div
    style={{ marginTop: "50px" }}
    className="col-lg-10 col-md-10 col-xs-12 col-
sm-12 offset-lg-1"
  >
    <div className="alert alert-
danger" role="alert">
      Todo List is empty or Filter results
      show no results
    </div>
  </div>
  )}{" "}
</div>
);
}
}

const getVisibleTodos = (todos, filter) => {
  switch (filter) {
    case SHOW_ALL:
      return todos;
    case SHOW_COMPLETED:
      return todos.filter(t => t.completed);
    case SHOW_ACTIVE:
      return todos.filter(t => !t.completed);
    default:
      throw new Error("Unknown filter: " + filter);
  }
};

const mapStateToProps = state => {
  return {
    todos: getVisibleTodos(state.todos, state.visibilityFilde
r),
    visibilityFilter: state.visibilityFilter
  };
};


const mapDispatchToProps = dispatch => {
  return bindActionCreators({
    deleteTodo,
    toggleTodo,
    setVisibilityFilter
  },
  dispatch
);

```

```
};

export default connect(mapStateToProps, mapDispatchToProps)(Table);
```

5. Membuat Folder reducers



a. Membuat File filterReducer.js

```
import {
  SHOW_ALL,
  SET_VISIBILITY_FILTER
} from '../action/actionsTypes';

const visibilityFilter = (state = SHOW_ALL, action) => {
  switch (action.type) {
    case SET_VISIBILITY_FILTER:
      return action.filter;
    default:
      return state;
  }
};

export default visibilityFilter;
```

b. Membuat File todoReducer.js

```
import {
  ADD_TODO,
  REMOVE_TODO,
  TOGGLE_TODO
} from '../action/actionsTypes'

const INITIAL_DATA = []

const TodoReducer = (state=INITIAL_DATA, action) => {
  switch (action.type){
    case ADD_TODO:
      return [
        ...state,{
          id: action.id,
          text: action.text,
          completed: false
        }
      ]
    default:
      return state;
  }
};

export default TodoReducer;
```

```

    }
  ]
  case TOGGLE_TODO:
    return state.map(todo => (todo.id === action.id) ? {
      ...todo,
      completed: !todo.completed
    }
    : todo
  )
  case REMOVE_TODO:
    const numIndex = parseInt(action.id)
    return state.filter(todo => todo.id !== numIndex);
  default:
    return state
  }
}

export default TodoReducer

```

c. Membuat File mainReducer.js

```

import { combineReducers } from 'redux'
import todos from './todoReducer'
import visibilityFilter from './filterReducer'

export default combineReducers({
  todos,
  visibilityFilter
})

```

6. Instalasi Font Awesome untuk menampilkan simbol complited dan delete

```

npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@1.2.11 (node_modules\watchpack\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@1.2.11: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@1.2.11 (node_modules\jest-haste-map\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@1.2.11: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})

+ @fortawesome/fontawesome-free@5.12.1
added 1 package from 6 contributors and audited 919263 packages in 92.027s

54 packages are looking for funding
  run `npm fund` for details

found 302 moderate severity vulnerabilities
  run `npm audit fix` to fix them, or `npm audit` for details
PS G:\Kuliah\Semester6\PemrogramanBerbasisFramework\mohkhoirularifin-minggu7\praktikum>

```

Saya menginstall ini agar icon remove dan centang bisa muncul pada tabel bagian action.

7. Mengubah index.js

```

import React from 'react';
import ReactDOM from 'react-dom';
import { Provider } from 'react-redux'
import { createStore, applyMiddleware, compose } from 'redux'
import MainReducer from './reducers/mainReducer'
import App from './App';
import Table from './containers/table'
import CreateTodo from './containers/createTodo'
import 'bootstrap/dist/css/bootstrap.min.css'
import '@fortawesome/fontawesome-free/css/all.min.css';

// import registerServiceWorker from './registerServiceWorker';

```



```
import * as serviceWorker from './serviceWorker';

const store = compose(window.devToolsExtension ? window.devToolsExtension() : f =>
f)(createStore)(MainReducer)


ReactDOM.render(<Provider store={store}>
  <CreateTodo/>
  <Table/>
</Provider>
, document.getElementById('root'));
// registerServiceWorker();
serviceWorker.unregister();
```

Di bagian index saya sedikit merubahnya agar bisa menampilkan CreateTodo, dan Table.


Saya juga menambahkan import untuk bootstrap dan import untuk icon centang dan remove yang ada pada action.

8. Output


a. Tampilan Awal




b. Tampilan Setelah Diisi




c. Tampilan Jika dicentang




d. Tampilan jika dihapus



e. Tampilan All



f. Tampilan Completed



g. Tampilan Active

