SWC_ADC_IF

Version v1.0 7/19/2023 11:55:00 PM

Table of Contents

Data Structure Index	2
File Index	3
Data Structure Documentation	4
ACSR_type	4
ADC_type	5
ADCSRA_type	7
ADMUX_type	9
LBTY_tuniPort16	11
LBTY_tuniPort8	13
SENSOR_tstrConfig	15
SFIOR_type	16
File Documentation	18
ADCIF_cfg.c	18
ADCIF_cfg.h	19
ADCIF_int.h	21
ADCIF_prg.c	24
ADCIF_priv.h	26
main.c	
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/main.c	
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/ADC_cfg.c	
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/ADC_cfg.h	
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/ADC_cfg.h	33
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/ADC_int.h	
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/ADC_int.h	
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/ADC_prg.c	
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/ADC_priv.h	
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/ADC_priv.h	
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_BSW/LBIT_int.h	
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_BSW/LBIT_int.h	
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_BSW/LBTY_int.h	
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_BSW/LBTY_int.h	
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_BSW/LCTY_int.h	
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_BSW/LCTY_int.h	
Index Error! Bookmark no	ot defined.

Data Structure Index

Data Structures

Here are	the data	structures	with	brief	descri	ntions:
Ticic aic	uic autu	buactares	** 1 (11	OTICI	accert	outons.

ACSR_type (: Type define of Union bit field of "Analog Comparator Control and Status")4				
ADC_type (: Analog to Digital Converter Registers					
)	5				
ADCSRA_type (: Type define of Union bit field of "ADC Control and Status Reg A")	7				
ADMUX type (: Type define of Union bit field of "ADC Multiplexer Selection Reg")					
LBTY tuniPort16	11				
LBTY tuniPort8	13				
SENSOR_tstrConfig					
SFIOR_type (: Type define of Union bit field of "Special Function I/O Register")	16				

File Index

File List

Here is a list of all files with brief descriptions:

ADCIF_cfg.c	18
ADCIF_cfg.h	19
ADCIF_int.h	21
ADCIF_prg.c	
ADCIF_priv.h	
main.c	
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/ADC_cfg.c	
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/ADC_cfg.h	31
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/ADC_int.h	35
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/ADC_prg.c	49
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/ADC_priv.h	57
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/main.c	29
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_BSW/LBIT_int.h	
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC BSW/LBTY int.h	67
H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_BSW/LCTY_int.h	

Data Structure Documentation

ACSR_type Union Reference

: Type define of Union bit field of "Analog Comparator Control and Status" #include <ADC priv.h>

Collaboration diagram for ACSR_type:



Data Fields

- <u>u8</u> <u>u Reg</u>
- struct {
- <u>IO</u> <u>u8</u>: 7
- <u>IO u8 m_ACD</u>: 1
- } <u>sBits</u>

Detailed Description

: Type define of Union bit field of "Analog Comparator Control and Status"

Type: Union **Unit**: None

Field Documentation

```
lO u8 m_ACD
```

Analog Comparator Disable

struct { ... } sBits

__<u>IO u8</u>

Reversed

u8 u_Reg

Byte

The documentation for this union was generated from the following file:


H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/ADC_priv.h

ADC_type Struct Reference

: Analog to Digital Converter Registers

#include <ADC priv.h>

Collaboration diagram for ADC_type:



Data Fields

- <u>I u16 m_ADC</u>: 10
- <u>I u16</u>: 6
- <u>IO ADCSRA_type m_ADCSRA</u>
- <u>IO ADMUX_type m_ADMUX</u>
- <u>IO ACSR type m ACSR</u>

Detailed Description

: Analog to Digital Converter Registers

Type : Struct Unit : None

Field Documentation

<u>IO</u> <u>ACSR_type</u> m_ACSR

Analog Comparator Control and Status

__I <u>u16</u> m_ADC

ADC Read Data

IO ADCSRA type m_ADCSRA

ADC Control and Status Reg A

__IO ADMUX_type m_ADMUX

ADC Multiplexer Selection Reg

__l <u>u16</u>

Reversed

The documentation for this struct was generated from the following file:

• H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/<u>ADC_priv.h</u>

ADCSRA_type Union Reference

: Type define of Union bit field of "ADC Control and Status Reg A" #include <ADC_priv.h>

Collaboration diagram for ADCSRA_type:



Data Fields

- <u>u8 u_Reg</u>
- struct {
- <u>IO u8 m_ADPS</u>: 3
- <u>IO u8 m ADIE</u>: 1
- <u>IO u8 m ADIF</u>: 1
- <u>IO u8 m_ADATE</u>: 1
- <u>IO u8 m ADSC</u>: 1
- <u>IO u8 m_ADEN</u>: 1
- } <u>sBits</u>

Detailed Description

: Type define of Union bit field of "ADC Control and Status Reg A"

Type: Union Unit: None

Field Documentation

__<u>IO</u> u8 m_ADATE

ADC Auto Trigger Enable

__IO u8 m_ADEN

ADC Enable

__IO u8 m_ADIE

ADC Interrupt Enable

__IO u8 m_ADIF

ADC Interrupt Flag

```
__lO u8 m_ADPS
ADC Prescaler Select Bits
__lO u8 m_ADSC
ADC Start Conversion
struct { ... } sBits
u8 u_Reg
```

Byte

The documentation for this union was generated from the following file:

• H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/<u>ADC_priv.h</u>

ADMUX_type Union Reference

: Type define of Union bit field of "ADC Multiplexer Selection Reg" #include <ADC_priv.h>

Collaboration diagram for ADMUX_type:



Data Fields

- <u>u8</u> <u>u_Reg</u>
- struct {
- <u>IO u8 m_MUX</u>: 5
- <u>IO u8 m ADLAR</u>: 1
- <u>IO u8 m REFS</u>: 2
- } <u>sBits</u>

Detailed Description

: Type define of Union bit field of "ADC Multiplexer Selection Reg"

Type: Union Unit: None

Field Documentation

```
___IO u8 m_ADLAR
ADC Left Adjust Result
___IO u8 m_MUX
Analog Channel and Gain Selection Bits
```

__<u>IO</u> <u>u8</u> m_REFS

Reference Selection Bits

struct { ... } sBits

u8 u_Reg


Byte

The documentation for this union was generated from the following file:

• H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/ADC_priv.h

LBTY_tuniPort16 Union Reference

#include <LBTY_int.h>
Collaboration diagram for LBTY_tuniPort16:



Data Fields

- struct {
- <u>u8 m_u8b0</u>:1
- <u>u8 m u8b1</u>:1
- <u>u8 m_u8b2</u>:1
- <u>u8</u> <u>m</u> <u>u8b3</u>:1
- <u>u8 m u8b4</u>:1
- u8 m_u8b5:1
- <u>u8 m u8b6</u>:1
- <u>u8 m_u8b7</u>:1
- <u>u8 m u8b8</u>:1
- <u>u8 m_u8b9</u>:1
- <u>u8 m_u8b10</u>:1
- <u>u8 m u8b11</u>:1
- <u>u8 m_u8b12</u>:1
- <u>u8 m u8b13</u>:1
- <u>u8 m_u8b14</u>:1
- <u>u8 m_u8b15</u>:1
- } <u>sBits</u>
- struct {
- <u>u8 m_u8low</u>
- <u>u8 m_u8high</u>
- } <u>sBytes</u>
- <u>u16 u u16Word</u>

Field Documentation


```
u8 m_u8b0
u8 m_u8b1
u8 m_u8b10
u8 m_u8b11
u8 m_u8b12
u8 m_u8b13
u8 m_u8b14
u8 m_u8b15
u8 m_u8b2
u8 m_u8b3
u8 m_u8b4
<u>u8</u> m_u8b5
u8 m_u8b6
u8 m_u8b7
u8 m_u8b8
u8 m_u8b9
u8 m_u8high
u8 m_u8low
struct { ... } sBits
struct { ... } sBytes
<u>u16</u> u_u16Word
```

The documentation for this union was generated from the following file:

• H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_BSW/<u>LBTY int.h</u>

LBTY_tuniPort8 Union Reference

#include <LBTY_int.h> Collaboration diagram for LBTY_tuniPort8:



Data Fields

- struct {
- <u>u8 m_u8b0</u>:1
- <u>u8 m u8b1</u>:1
- <u>u8 m_u8b2</u>:1
- <u>u8 m u8b3</u>:1
- <u>u8 m_u8b4</u>:1
- <u>u8 m_u8b5</u>:1
- <u>u8</u> <u>m</u> <u>u8b6</u>:1
- u8 m_u8b7:1
- } sBits
- u8 u_u8Byte

Detailed Description

Union Byte bit by bit

Field Documentation

```
      u8 m_u8b0

      u8 m_u8b1

      u8 m_u8b2

      u8 m_u8b3

      u8 m_u8b4

      u8 m_u8b5

      u8 m_u8b6

      u8 m_u8b7

      struct {...} sBits


      u8 u_u8Byte
```

The documentation for this union was generated from the following file:

• H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_BSW/<u>LBTY_int.h</u>

SENSOR_tstrConfig Struct Reference

#include <ADCIF_int.h>
Collaboration diagram for SENSOR_tstrConfig:



Data Fields

- ADC_tenuChannel m_Channel
- s32 m_MaxValue
- <u>s32</u> <u>m MinValue</u>
- <u>u8</u> <u>m_Unit</u>

Field Documentation

ADC_tenuChannel m_Channel

s32 m_MaxValue

s32 m_MinValue

u8 m_Unit

The documentation for this struct was generated from the following file:

ADCIF_int.h

SFIOR_type Union Reference

: Type define of Union bit field of "Special Function I/O Register" #include <ADC_priv.h>

Collaboration diagram for SFIOR_type:



Data Fields

- u8 u_Reg
- struct {
- <u>IO u8</u>: 3
- <u>IO u8 m ACME</u>: 1
- <u>IO u8 m ADTS</u>: 3
- } sBits

Detailed Description

: Type define of Union bit field of "Special Function I/O Register"

Type: Union Unit: None

Field Documentation

```
__IO u8 m_ACME
    Analog Comparator Multiplexer Enable
__<u>IO</u> u8 m_ADTS
    ADC Auto Trigger Source
struct { ... } sBits
<u>IO u8</u>
   Reversed
```

u8 u_Reg

Byte


The documentation for this union was generated from the following file:

• H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/ADC_priv.h

File Documentation

ADCIF_cfg.c File Reference

```
#include "LBTY_int.h"
#include "ADC_int.h"
#include "ADCIF_int.h"
Include dependency graph for ADCIF_cfg.c:
```



Variables

- const <u>SENSOR_tstrConfig_katstrSensorConfig_GLB</u> []
- const <u>u8 SENSOR NUM</u> = sizeof(<u>katstrSensorConfig GLB</u>)/sizeof(<u>SENSOR tstrConfig</u>)

Variable Documentation

const **SENSOR** tstrConfig katstrSensorConfig_GLB[]

```
Initial value:= {

{}
}
```

const <u>u8</u> SENSOR_NUM = sizeof(<u>katstrSensorConfig_GLB</u>)/sizeof(<u>SENSOR_tstrConfig</u>)

ADCIF_cfg.h File Reference

This graph shows which files directly or indirectly include this file:



Variables

- const <u>SENSOR_tstrConfig_katstrSensorConfig_GLB</u> []
- const <u>u8</u> <u>SENSOR NUM</u>

Variable Documentation

const <u>SENSOR_tstrConfig</u> katstrSensorConfig_GLB[][extern]


const u8 SENSOR_NUM[extern]

ADCIF_cfg.h

```
Go to the documentation of this file.1 /*
*****************
3 /* ***********
4 /* File Name : ADCIF_cfg.h
11
12 #ifndef ADCIF_CFG_H_
13 #define ADCIF CFG H
14
18
22
26 extern const SENSOR tstrConfig katstrSensorConfig GLB[];
27 extern const u8 SENSOR NUM;
31
34 /* ***
35
36
37 #endif /* ADCIF CFG H */
```

ADCIF_int.h File Reference

This graph shows which files directly or indirectly include this file:



Data Structures

struct SENSOR_tstrConfigFunctions


- void SENSOR_vidInit (void)
- <u>LBTY tenuErrorStatus</u> <u>SENSOR u8GetData</u> (<u>f32</u> *paf32Read)
- LBTY_tenuErrorStatus SENSOR_u8GetChannel (u8 u8Num, f32 *pf32Read)

Function Documentation

<u>LBTY_tenuErrorStatus</u> SENSOR_u8GetChannel (<u>u8</u> u8Num, <u>f32</u> * pf32Read)

```
68
69
        LBTY tenuErrorStatus u8RetErrorState = LBTY OK;
70
       u16 u16AdcReadValue = LBTY u8ZERO;
71 const SENSOR tstrConfig* pstrSensor = (const SENSOR tstrConfig*)&katstrSensorConfig GLB[u8Num];
72
       u8RetErrorState = ADC u8ReadChannel (pstrSensor->m Channel, &u16AdcReadValue);
73
        if (u8RetErrorState == LBTY OK) {
74
            *pf32Read = (f32)(ADC f32GetVoltage()
                      * (pstrSensor->m MaxValue - pstrSensor->m MinValue) /
(f32) ADC V REF) + pstrSensor->m MinValue;
76
77
        return u8RetErrorState;
```

Here is the call graph for this function:



Here is the caller graph for this function:

```
SENSOR_u8GetData SENSOR_u8GetChannel
```

<u>LBTY_tenuErrorStatus</u> SENSOR_u8GetData (<u>f32</u> * paf32Read)

```
55

56

LBTY tenuErrorStatus u8RetErrorState = LBTY OK;

57

for(u8 i = SENSOR NUM ; i-- && (u8RetErrorState == LBTY OK) ; ) {

58

u8RetErrorState = SENSOR u8GetChannel (i, paf32Read + i);


59
}

60

return u8RetErrorState;


61 }
```

Here is the call graph for this function:



void SENSOR_vidInit (void)

```
46
47
48 }
         ADC vidInit();
```




ADCIF_int.h

```
Go to the documentation of this file.1 /*
3 /* ***********
4 /* File Name : ADCIF_int.h
11
12 #ifndef ADCIF_INT_H_
13 #define ADCIF INT H
14
18
19 typedef struct{
 ADC tenuChannel
         m Channel;
20
21
          m MaxValue;
  s32
22 <u>s32</u>
          m MinValue;
23
  u8
          m Unit;
24 } SENSOR tstrConfig;
25
26
27 /* ***************** MACRO/DEFINE SECTION **************** */
28 /*
29
30 /* *****
31
33
34 /* ****
37
39
41
42 /* ******************
43 /* Description : Initialization of the Sensors
44 /* Input : void
45 /* Return : void
                                */
46 /* ************
47 extern void SENSOR vidInit (void);
48
49 /* ******************
50 /* Description : Get Sensors Read
51 /* Input/Output: paf32Read
52 /* Poturn
54 extern <u>LBTY tenuErrorStatus</u> <u>SENSOR u8GetData</u>(\underline{\text{f32}}* paf32Read);
55
56 /* ****************
61 extern LBTY tenuErrorStatus SENSOR u8GetChannel(u8 u8Num, f32* pf32Read);
62
```

ADCIF_prg.c File Reference

```
#include "LBTY_int.h"
#include "ADC_int.h"
#include "ADC_cfg.h"
#include "ADCIF_int.h"
#include "ADCIF_cfg.h"
#include "ADCIF_priv.h"
Include dependency graph for ADCIF_prg.c:
```



Functions


- void <u>SENSOR vidInit</u> (void)
- <u>LBTY tenuErrorStatus SENSOR u8GetData (f32</u> *paf32Read)
- <u>LBTY_tenuErrorStatus_SENSOR_u8GetChannel_(u8_u8Num, f32_*pf32Read)</u>

Function Documentation

<u>LBTY_tenuErrorStatus</u> SENSOR_u8GetChannel (<u>u8</u> u8Num, <u>f32</u> * pf32Read)

```
68
69
         LBTY tenuErrorStatus u8RetErrorState = LBTY OK;
u16 u16AdcReadValue = LBTY u8ZERO;
70
         const SENSOR tstrConfig* pstrSensor = (const
SENSOR tstrConfig*) & katstrSensorConfig GLB [u8Num];
72 u8RetErrorState = ADC u8ReadChannel (pstrSens
         u8RetErrorState = ADC u8ReadChannel (pstrSensor->m Channel, &u16AdcReadValue);
73
         if (u8RetErrorState == LBTY OK) {
74
              *pf32Read = (\underline{f32}) (\overline{ADC} \underline{f32}GetVoltage()
75
                         * (pstrSensor->m MaxValue - pstrSensor->m MinValue) /
(f32)ADC V REF) + pstrSensor->m MinValue;
77
         return u8RetErrorState;
78 }
```

Here is the call graph for this function:



Here is the caller graph for this function:


```
SENSOR_u8GetData SENSOR_u8GetChannel
```

LBTY_tenuErrorStatus SENSOR_u8GetData (f32 * paf32Read)

```
55 {
56    LBTY tenuErrorStatus u8RetErrorState = LBTY OK;
57    for(u8 i = SENSOR NUM ; i-- && (u8RetErrorState == LBTY OK) ; ) {
58    u8RetErrorState = SENSOR u8GetChannel(i, paf32Read + i);
```




Here is the call graph for this function:



void SENSOR_vidInit (void)


```
46
47 ADC vidInit();
48 }
```

Here is the call graph for this function:



ADCIF_priv.h File Reference

This graph shows which files directly or indirectly include this file:



ADCIF_priv.h


```
Go to the documentation of this file.1 /*
*************************************
3 /* ************
4 /* File Name : ADCIF_priv.h
11
12 #ifndef ADCIF_PRIV_H_
13 #define ADCIF_PRIV_H_
14
18
22
26
27 /* ***
 28 /* ************************* VARIABLE SECTION ********************************
29 /* *****************************
30
33 /*
34
35
```

main.c File Reference

H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/main.c File Reference

H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/ADC_cfg.c File Reference

```
#include "LBTY_int.h"
#include "ADC_int.h"
#include "ADC_cfg.h"
Include dependency graph for ADC_cfg.c:
```



Variables


• const <u>u8</u> <u>kau8ActiveChannel_LGB</u> []

Variable Documentation

const <u>u8</u> kau8ActiveChannel_LGB[]

H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/ADC_cfg.h File Reference

This graph shows which files directly or indirectly include this file:



Macros

- #define <u>ADC_CH0</u> <u>ADC0</u>
- #define <u>ADC CH1</u> <u>ADC1</u>
- #define <u>ADC_CH2</u> <u>ADC2</u>
- #define <u>ADC CH3</u> <u>ADC3</u>
- #define <u>ADC_CH4</u> <u>ADC4</u>
- #define <u>ADC_CH5</u> <u>ADC5</u>
- #define <u>ADC CH6</u> <u>ADC6</u>
- #define <u>ADC_CH7</u> <u>ADC7</u>
- #define <u>ADC ADJUSTMENT</u> <u>LBTY RESET</u>
- #define <u>ADC_TRIG_SRC_ADC_Free_Running_Mode</u>
- #define <u>ADC_INIT_STATE</u> <u>LBTY_SET</u>
- #define ADC AUTO TRIG LBTY RESET
- #define <u>ADC_IRQ_STATE</u> <u>LBTY_RESET</u>
- #define <u>ADC PRESCALER</u> <u>ADC Division Factor 2</u>
- #define <u>ADC V REF</u> 5u
- #define <u>ADC_READ_DELAY</u> 26u

Variables

• const <u>u8</u> <u>kau8ActiveChannel_LGB</u> []

Macro Definition Documentation

```
#define ADC_ADJUSTMENT LBTY_RESET
#define ADC_AUTO_TRIG LBTY RESET
#define ADC_CH0 ADC0
#define ADC_CH1 ADC1
#define ADC_CH2 ADC2
#define ADC_CH3 ADC3
#define ADC_CH4 ADC4
#define ADC_CH5 ADC5
#define ADC_CH6 ADC6
#define ADC_CH7 ADC7
#define ADC_INIT_STATE LBTY_SET
   ADC Control State
#define ADC_IRQ_STATE LBTY_RESET
#define ADC_PRESCALER <u>ADC_Division_Factor_2</u>
#define ADC_READ_DELAY 26u
#define ADC_TRIG_SRC <u>ADC_Free_Running_Mode</u>
   SFIOR
#define ADC_V_REF 5u
#define ADC_V_REF_SRC ADC_AVCC
   ADC MUX
```

Variable Documentation


const u8 kau8ActiveChannel_LGB[][extern]

ADC_cfg.h

```
Go to the documentation of this file.1 /*
*******************
2 /* ************************* FILE DEFINITION SECTION ************************
3 /* ***********
4 /* File Name : ADC_cfg.h
11
12 #ifndef ADC_CFG_H_
13 #define ADC CFG H
14
16 /* *********************** TYPE DEF/STRUCT/ENUM SECTION ****************** */
18
22
23 #if defined(AMIT KIT)
24
                     ADC0
25 #define ADC_CH0
26 #define ADC_CH1
27 #define ADC_CH2
                      ADC1
28 #define ADC_CH3
                      ADC3
29
30 #elif defined(ETA32 KIT)
31
32 #define ADC CH0
33 #define ADC CH1
                      ADC1
34
35 #elif defined(ETA32 MINI KIT)
36
37 #define ADC CHO
                      ADC0
38
39 #else
40
41 #define ADC CHO
                      ADC0
42 #define ADC CH1
                      ADC1
43 #define ADC CH2
                      ADC2
44 #define ADC_CH3
                      ADC3
ADC4
45 #define ADC CH4
46 #define ADC_CH5
47 #define ADC_CH6
                      ADC5
                      ADC6
48 #define ADC_CH7
                      ADC7
49
50 #endif
51
52 #define ADC ADJUSTMENT
                      LBTY RESET
53
                      ADC Free Running Mode
55 #define ADC TRIG SRC
56
58 #define ADC_INIT_STATE
59 #define ADC_AUTO_TRIG
60 #define ADC_IRQ_STATE
61 #define ADC_PRESCALER
                     LBTY SET
                      LBTY RESET
                      LBTY RESET
                      ADC Division Factor 2
62
64 #define ADC_V_REF_SRC
65 #define ADC_V_REF
66
67 #define ADC READ DELAY
                      2611
68
69 /* *******************************
70 /* ************************ CONST SECTION ***********************************
71 /*
72
73 extern const u8 kau8ActiveChannel LGB[];
```

H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/ADC_int.h File Reference

This graph shows which files directly or indirectly include this file:



Enumerations

- enum <u>ADC tenuPrescalerSelection</u> { <u>ADC Division Factor 2 DEF</u> = (u8)0u,
 <u>ADC Division Factor 2</u>, <u>ADC Division Factor 4</u>, <u>ADC Division Factor 8</u>,
 <u>ADC Division Factor 16</u>, <u>ADC Division Factor 32</u>, <u>ADC Division Factor 64</u>,
 <u>ADC Division Factor 128</u> }
- enum <u>ADC tenuTriggerSource</u> { <u>ADC Free Running Mode</u> = (u8)0u,
 <u>ADC Analog Comparator</u>, <u>ADC External INTO</u>, <u>ADC TMRO Compare MatchA</u>,
 <u>ADC TMRO Overflew</u>, <u>ADC TMR1 Compare MatchB</u>, <u>ADC TMR1 Overflew</u>,
 <u>ADC TMR1 Capture Event</u> }
- enum <u>ADC_tenuRefSelection</u> { <u>ADC_AREF</u> = (u8)0u, <u>ADC_AVCC</u>, <u>RESERVED</u>, <u>ADC_INTERNAL_Vref</u> }

Functions

- void ADC vidInit (void)
- <u>LBTY tenuErrorStatus ADC u8CofigChannel (ADC tenuChannel u8Channel)</u>
- void ADC_vidCalibrate (void)
- void <u>ADC vidEnable</u> (void)
- void ADC vidDisable (void)
- void <u>ADC_vidAutoTriggerEnable</u> (void)
- void <u>ADC vidAutoTriggerDisable</u> (void)
- LBTY_tenuErrorStatus_ADC_u8SetAutoTriggerSource_(ADC_tenuTriggerSource_u8Source)
- <u>LBTY tenuErrorStatus</u> <u>ADC u8SetPrescaler</u> (<u>ADC tenuPrescalerSelection</u> u8Prescaler)
- <u>LBTY_tenuErrorStatus_ADC_u8SetV_REF (ADC_tenuRefSelection_u8Vref)</u>
- LBTY_tenuErrorStatus ADC_u8SetChannel (ADC_tenuChannel u8Channel)
- void <u>ADC vidStartConversion</u> (void)
- void <u>ADC_vidWaitConversion</u> (void)
- u16 ADC u16GetData (void)
- f32 ADC_f32GetVoltage (void)
- <u>LBTY_tenuErrorStatus_ADC_u8StartRead_(ADC_tenuChannel_u8Channel)</u>
- <u>LBTY tenuErrorStatus</u> <u>ADC u8ReadChannel</u> (<u>ADC tenuChannel</u> u8Channel, <u>u16</u>
 *pu16ADC Value)
- <u>LBTY tenuErrorStatus ADC u8ReadConvValue</u> (u8 u8Channel, u16 *pu16ADC_Value)

- $\bullet \quad \underline{LBTY_tenuErrorStatus} \ \underline{ADC_u16RefreshADC} \ (void)$
- <u>LBTY tenuErrorStatus ADC u16GetAll (u16 pu16ADC_Value[])</u>
- void <u>ADC vidEnableINT</u> (void)
- void <u>ADC vidDisableINT</u> (void)
- void <u>ADC_vidClrFlagINT</u> (void)
- void <u>ADC vidSetCallBack</u> (void(*pvidCallBack)(void))

Enumeration Type Documentation

enum ADC_tenuChannel

Enumerator:

Litaliciator.	
ADC0	Analog Channels
ADC1	
ADC2	
ADC3	
ADC4	
ADC5	
ADC6	
ADC7	
ADC0_ADC0_10	Analog Amplifier
X	7 maiog 7 mpmer
ADC1_ADC0_10	
X	
ADC0_ADC0_200	
X	
ADC1_ADC0_200	
X	
ADC2_ADC2_10	
X	
ADC3_ADC2_10	
X	
ADC2_ADC2_200	
X	
ADC3_ADC2_200	
X	
ADC0_ADC1_1X	Analog Comparator with ADC1
ADC1_ADC1_1X	
ADC2_ADC1_1X	
ADC3_ADC1_1X	
ADC4_ADC1_1X	
ADC5_ADC1_1X	
ADC6_ADC1_1X	
ADC7_ADC1_1X	
ADC0_ADC2_1X	Analog Comparator with ADC1
ADC1_ADC2_1X	
ADC2_ADC2_1X	
ADC3_ADC2_1X	
ADC4_ADC2_1X	
ADC5_ADC2_1X	
	

```
VBG_1V22
                         Constant Voltage
                 GND
   ADC_ChannelMu
19
21
         \underline{ADC0} = (\underline{u8}) 0u,
22
         ADC1,
23
         ADC2,
24
         ADC3,
25
        ADC4,
26
         ADC5,
27
         ADC6,
        ADC7,
ADC0 ADC0 10X,
28
30
        ADC1 ADC0 10X,
31
32
        ADCO ADCO 200X,
33
        ADC1 ADC0 200X,
        ADC2 ADC2 10X,
ADC3 ADC2 10X,
34
35
36
       ADC2 ADC2 200X,
        ADC3 ADC2 200X,
ADC0 ADC1 1X,
37
39
        ADC1 ADC1 1X,
ADC2 ADC1 1X,
40
41
42
        ADC3 ADC1 1X,
        ADC4 ADC1 1X,
ADC5 ADC1 1X,
43
44
45
        ADC6 ADC1 1X,
46
        ADC7 ADC1 1X,
48
        ADCO ADC2 1X,
        ADC1 ADC2 1X,
ADC2 ADC2 1X,
49
50
51
        ADC3_ADC2_1X,
        ADC4 ADC2 1X,
ADC5 ADC2 1X,
52
53
         VBG 1V22,
55
56
         GND,
57
        ADC ChannelMux
58 }ADC tenuChannel;
                               // ADC Channel Selection
```

enum <u>ADC_tenuPrescalerSelection</u>

Enumerator:

```
ADC_Division_Fa
         ctor_2_DEF
  ADC_Division_Fa
              ctor_2
  ADC_Division_Fa
              ctor_4
  ADC_Division_Fa
              ctor_8
  ADC_Division_Fa
             ctor_16
  ADC_Division_Fa
             ctor_32
  ADC_Division_Fa
             ctor_64
  ADC_Division_Fa
           ctor_128
61
        ADC Division Factor 2 DEF = (u8) Ou,
        ADC Division Factor 2,
ADC Division Factor 4,
62
63
64
        ADC Division Factor 8,
       ADC Division Factor 16, ADC Division Factor 32,
65
66
```

```
67 ADC Division Factor 64,
68 ADC Division Factor 128
69 }ADC tenuPrescalerSelection; // ADC Prescaler Selections
```

enum <u>ADC_tenuRefSelection</u>

Enumerator:

ADC_AREF	Internal Vref turned off
ADC_AVCC	external capacitor at AREF pin
RESERVED	
ADC_INTERNAL	2.56v with external capacitor at AREF pin
_Vref	
82 {	
82 { 83 <u>ADC AREF</u> =	
82 { 83 <u>ADC AREF</u> = 84 <u>ADC AVCC</u> ,	(<u>u8</u>) 0u,

enum <u>ADC_tenuTriggerSource</u>

Enumerator:

```
ADC_Free_Runni
          ng_Mode
   ADC_Analog_Co
          mparator
  ADC_External_IN
  ADC_TMR0_Com
      pare_MatchA
  ADC_TMR0_Ove
              rflew
  ADC_TMR1_Com
      pare_MatchB
  ADC_TMR1_Ove
              rflew
  ADC_TMR1_Capt
         ure_Event
71
       ADC Free Running Mode = (u8) 0u,
72
       ADC Analog Comparator,
ADC External INTO,
73
74
75
       ADC TMR0 Compare MatchA,
       ADC TMR0 Overflew,
       ADC TMR1 Compare MatchB,
       ADC TMR1 Overflew,
ADC TMR1 Capture Event
78
79
80 }ADC tenuTriggerSource;
                                 // ADC Auto Trigger Source
```

Function Documentation

f32 ADC_f32GetVoltage (void)

```
292 {
293    return (<u>f32</u>) <u>ADC u16GetData</u>() * <u>f32V REF</u> / <u>ADC MAX</u>;
294 }
```

Here is the call graph for this function:



Here is the caller graph for this function:

```
SENSOR_u8GetData SENSOR_u8GetChannel ADC_f32GetVoltage
```

<u>LBTY_tenuErrorStatus</u> ADC_u16GetAll (<u>u16</u> *pu16ADC_Value*[])


Clear complete flag by writing logic one

```
396
397
        LBTY tenuErrorStatus u8RetErrorState = LBTY OK;
398
399
        if(u8ConvDone GLB == LBTY SET){
400
             S ADC->m ADCSRA.sBits.m ADIE = LBTY RESET;
             S ADC->m ADCSRA.sBits.m ADIF = LBTY SET;
401
             for(u8 i = 0 ; i<ADC Num ; i++) {
402
403
                 pu16ADC_Value[i] = au8ChannelValue LGB[i];
404
405
        }else{
406
            u8RetErrorState = <a href="LBTY">LBTY IN PROGRESS;</a>;
407
408
        return u8RetErrorState;
409 }
```

u16 ADC_u16GetData (void)

```
283 {
284 return (<u>u16</u>) <u>S ADC</u>->m_ADC;
285 }
```

Here is the caller graph for this function:



<u>LBTY_tenuErrorStatus</u> ADC_u16RefreshADC (void)

Clear complete flag by writing logic one

```
377
378
        LBTY tenuErrorStatus u8RetErrorState = LBTY OK;
379
380
        if (u8ConvDone GLB == LBTY SET) {
381
            u8ConvDone GLB = LBTY RESET;
382
            S ADC->m ADCSRA.sBits.m ADIE
            S ADC->m ADCSRA.sBits.m ADIF = LBTY SET;
383
384
            u8RetErrorState = ADC u8StartRead(*kau8ActiveChannel LGB);
385
        }else{
386
            u8RetErrorState = LBTY IN PROGRESS;
387
388
        return u8RetErrorState;
389 }
```

Here is the call graph for this function:



LBTY tenuErrorStatus ADC u8CofigChannel (ADC tenuChannel u8Channel)

```
110
111 LBTY_tenuErrorStatus u8RetErrorState = LBTY_OK;
112
113 if(IS_CHANNEL(u8Channel)){
```

```
114 u8RetErrorState = GPIO_u8SetPinDirection(ADC PORT, u8Channel, PIN_INPUT);
115 }else{
116 u8RetErrorState = LBTY NOK;
117 }
118 return u8RetErrorState;
119 }
```

Here is the caller graph for this function:



<u>LBTY_tenuErrorStatus</u> ADC_u8ReadChannel (<u>ADC_tenuChannel</u> u8Channel, <u>u16</u> * pu16ADC_Value)

```
323
324
        LBTY_tenuErrorStatus u8RetErrorState = LBTY_OK;
325
326
        if(pu16ADC Value == LBTY NULL) {
327
            u8RetErrorState = LBTY NULL POINTER;
        }else{
328
            if((u8)u8Channel < ADC ChannelMux){</pre>
329
330
                S ADC->m ADMUX.sBits.m MUX = u8Channel;
331
            }else{
332
                u8RetErrorState = LBTY NOK;
333
            }
334
335
            S ADC->m ADCSRA.sBits.m ADSC = LBTY SET;
336
            while(<u>S_ADC</u>->m_ADCSRA.sBits.m_ADSC);
337
338
339
            //vidMyDelay ms(ADC READ DELAY);
340
            //while(!S_ADC->m_ADCSRA.sBits.m_ADIF);
341
S ADC->m ADCSRA.sBits.m ADIF = LBTY RESET;
342
343
            *pu16ADC Value = (u16)S ADC->m ADC;
344
        return u8RetErrorState;
345
346 }
```

Here is the caller graph for this function:

```
SENSOR_u8GetData SENSOR_u8GetChannel ADC_u8ReadChannel
```

<u>LBTY_tenuErrorStatus</u> ADC_u8ReadConvValue (<u>u8</u> *u8Channel*, <u>u16</u> * *pu16ADC_Value*)

```
354
355
        LBTY tenuErrorStatus u8RetErrorState = LBTY OK;
356
357
        if(pu16ADC Value == LBTY NULL) {
358
             u8RetErrorState = LBTY NULL POINTER;
359
        }else{
360
             for (u8 i = 0 ; i < ADC Num ; i++) {
361
                 if (u8Channel == kau8ActiveChannel LGB[i]) {
                      *pu16ADC_Value = au8ChannelValue LGB[i];
362
363
                      break:
364
                 }else{
365
                      u8RetErrorState = <a href="LBTY_NOK">LBTY_NOK</a>;
366
367
368
369
         return u8RetErrorState;
370 }
```

<u>LBTY_tenuErrorStatus</u> ADC_u8SetAutoTriggerSource (<u>ADC_tenuTriggerSource</u> *u8Source*)

```
182
             case ADC Analog Comparator:
             case ADC External INT0:
case ADC TMR0 Compare MatchA:
183
184
185
             case ADC TMR0 Overflew:
             case ADC TMR1 Compare MatchB:
case ADC TMR1 Overflew:
186
187
              case ADC TMR1 Capture Event:
188
189
                   S SFIOR->sBits.m ADTS = u8Source;
190
                  break;
191
              default:
192
                  u8RetErrorState = <u>LBTY_NOK</u>;
193
194
195
         return u8RetErrorState;
196 }
```

LBTY_tenuErrorStatus ADC_u8SetChannel (ADC_tenuChannel u8Channel)

```
249
        LBTY tenuErrorStatus u8RetErrorState = LBTY OK;
250
251
        if((u8)u8Channel < ADC ChannelMux) {
252
            S ADC->m ADMUX.sBits.m MUX = u8Channel;
253
        }else{
254
            u8RetErrorState = LBTY NOK;
255
256
257
        return u8RetErrorState;
258 }
```

Here is the caller graph for this function:



<u>LBTY_tenuErrorStatus</u> ADC_u8SetPrescaler (<u>ADC_tenuPrescalerSelection</u> u8Prescaler)

```
203
204
        LBTY tenuErrorStatus u8RetErrorState = LBTY OK;
205
         switch (u8Prescaler) {
206
         case ADC Division Factor 2 DEF:
207
             case ADC Division Factor 2:
            case ADC Division Factor 4:
208
            case ADC Division Factor 8:
case ADC Division Factor 16:
209
210
211
             case ADC Division Factor 32:
             case ADC Division Factor 64: case ADC Division Factor 128:
212
213
214
                 S ADC->m ADCSRA.sBits.m ADPS = u8Prescaler;
215
                  break;
216
             default:
217
                 u8RetErrorState = LBTY NOK;
218
219
220
         return u8RetErrorState;
221 }
```

LBTY tenuErrorStatus ADC u8SetV REF (ADC tenuRefSelection u8Vref)

```
229
        LBTY tenuErrorStatus u8RetErrorState = LBTY OK;
230
        switch(u8Vref){
231
           case ADC AREF:
232
            case ADC AVCC:
233
                    INTERNAL Vref:
            case ADC
234
               S ADC->m ADMUX.sBits.m REFS = u8Vref;
235
               break;
236
            default:
237
               u8RetErrorState = LBTY NOK;
238
239
240
        return u8RetErrorState;
241 }
```

LBTY_tenuErrorStatus ADC_u8StartRead (ADC_tenuChannel u8Channel)

```
304
         LBTY tenuErrorStatus u8RetErrorState = LBTY OK;
305
306
        if((u8)u8Channel < ADC ChannelMux) {</pre>
             S ADC->m_ADMUX.sBits.m_MUX = u8Channel;
307
308
         }else{
309
             u8RetErrorState = <u>LBTY NOK</u>;
310
311
312
        S ADC->m_ADCSRA.sBits.m_ADSC = LBTY SET;
313
314
         return u8RetErrorState;
315 }
```

Here is the caller graph for this function:




void ADC_vidAutoTriggerDisable (void)

void ADC_vidAutoTriggerEnable (void)

void ADC_vidCalibrate (void)

Here is the call graph for this function:



Here is the caller graph for this function:



void ADC_vidCIrFlagINT (void)

Clear complete flag by writing logic one

void ADC vidDisable (void)

```
151 (
```

```
152 <u>S ADC</u>->m_ADCSRA.sBits.m_ADEN = <u>LBTY RESET</u>;
153 }
```

void ADC_vidDisableINT (void)

void ADC_vidEnable (void)


void ADC_vidEnableINT (void)

void ADC_vidInit (void)

Clear complete flag by writing logic one

```
76
77
        for(u8 i = ADC Num; i--; ){
78
            ADC_u8CofigChannel(kau8ActiveChannel_LGB[i]);
79
80
81
       S SFIOR->sBits.m ADTS = ADC TRIG SRC;
82
       S ADC->m ADCSRA.sBits.m ADEN = LBTY SET;
S ADC->m ADCSRA.sBits.m ADSC = LBTY RESET;
83
84
       S ADC->m ADCSRA.sBits.m ADATE = ADC AUTO TRIG;
85
        S ADC->m ADCSRA.sBits.m ADIE = ADC IRQ STATE;
86
                                         = LBTY SET;
87
        S ADC->m ADCSRA.sBits.m ADIF
        S ADC->m ADCSRA.sBits.m ADPS = ADC PRESCALER;
88
89
       ADC vidSetCallBack(vid AdcSyncRead);
90
91
       S ADC->m_ADMUX.sBits.m_REFS = ADC V REF SRC;
S ADC->m_ADMUX.sBits.m_ADLAR = ADC ADJUSTMENT;
92
93
       S ADC->m ADMUX.sBits.m MUX
94
95
       // first conversion will take 25 ADC clock cycles instead of the normal 13.
96
        S_ADC->m_ADCSRA.sBits.m_ADSC = LBTY_SET;
97
       while(<u>S_ADC</u>->m_ADCSRA.sBits.m_ADSC);
98
99
       ADC vidCalibrate();
100
101
         S_ADC->m_ADCSRA.sBits.m_ADEN = ADC_INIT_STATE;
102
103 }
```

Here is the call graph for this function:



Here is the caller graph for this function:



void ADC_vidSetCallBack (void(*)(void) pvidCallBack)

Here is the caller graph for this function:



void ADC_vidStartConversion (void)

Here is the caller graph for this function:



void ADC_vidWaitConversion (void)

```
274 {
275 while(<u>S_ADC</u>->m_ADCSRA.sBits.m_ADSC);
276 }
```

Here is the caller graph for this function:



ADC_int.h

```
Go to the documentation of this file.1 /*
3 /* **********
4 /* File Name : ADC_int.h
11
12 #ifndef ADC_INT_H_
13 #define ADC INT H
14
18
19 typedef enum{
   \frac{ADC0}{ADC1} = (\underline{u8}) 0u,
21
22
23
    ADC2,
24
     ADC3,
     ADC4,
25
26
    ADC5,
     ADC6,
27
28
    ADC7,
    ADC0 ADC0 10X,
ADC1 ADC0 10X,
30
31
32
    ADCO ADCO 200X,
    ADC1 ADC0 200X,
ADC2 ADC2 10X,
33
34
    ADC3 ADC2 10X,
ADC2 ADC2 200X,
35
36
37
    ADC3 ADC2 200X,
39
    ADC0 ADC1 1X,
40
     ADC1 ADC1 1X,
    ADC2 ADC1 1X,
ADC3 ADC1 1X,
41
42
    ADC4 ADC1 1X,
43
44
    ADC5 ADC1 1X,
4.5
     ADC6 ADC1 1X,
46
    ADC7 ADC1 1X,
    ADC0 ADC2 1X,
ADC1 ADC2 1X,
48
49
    ADC2 ADC2 1X,
ADC3 ADC2 1X,
50
51
52
    ADC4 ADC2 1X,
     ADC5 ADC2 1X,
VBG_1V22,
53
55
56
    GND,
57
     ADC ChannelMux
58 }ADC tenuChannel;
                 // ADC Channel Selection
59
60 typedef enum{
61
   ADC Division Factor 2 DEF = (u8)0u,
     ADC Division Factor 2,
ADC Division Factor 4,
62
63
    ADC Division Factor 8,
ADC Division Factor 16,
64
65
66
    ADC Division Factor 32,
    ADC Division Factor 64,
ADC Division Factor 128
67
68
                       // ADC Prescaler Selections
69 }ADC tenuPrescalerSelection;
70
71 typedef enum{
   ADC Free Running Mode = (u8) Ou,
ADC Analog Comparator,
72
73
74
     ADC External INTO,
    ADC TMR0 Compare MatchA,
ADC TMR0 Overflew,
75
76
77
    ADC_TMR1_Compare_MatchB,
```

```
78 ADC TMR1 Overflew,
79 ADC TMR1 Capture Event
                   // ADC Auto Trigger Source
80 }ADC tenuTriggerSource;
81
82 typedef enum{
   \underline{ADC}\underline{AREF} = (\underline{u8}) 0u,
8.3
    ADC AVCC,
84
85
    RESERVED,
    ADC INTERNAL Vref
86
87 }ADC tenuRefSelection;
                   // ADC Voltage Reference Selections
88
              ***********
89 /* ***
91 /* ******
92
93 /*
96
97 /*
99 /* ****
100
101 /*
104
105 /* ******************
106 /* Description : Initialization of the ADC 107 /* Input : void 108 /* Return : void
108 /* Return
110 extern void ADC vidInit(void);
111
113 /* Description : Configuration of the Channel
114 /* Input : u8Channel
115 /* Return : LBTY_tenuErrorStatus
117 extern LBTY tenuErrorStatus ADC u8CofigChannel(ADC tenuChannel u8Channel);
118
119 /* *********
120 /* Description : Calibrate ADC Voltage
121 /* Input : void
122 /* Return : void
              void
123 /* ****************
124 extern void <a href="ADC vidCalibrate">ADC vidCalibrate</a> (void);
125
127 /* Description : Enable ADC to be ready for conversion
128 /* Input : void
129 /* Return : void
131 extern void ADC vidEnable(void);
132
134 /* Description : Disable ADC to be wont make further conversions 135 /* Input : void 136 /* Return : void
136 /* Return
137 /* ***************
138 extern void ADC vidDisable(void);
139
140 /* *********
141 /* Description : Enable ADC Auto Trigger
142 /* Input : void
143 /* Return : void
               void
145 extern void ADC_vidAutoTriggerEnable(void);
146
148 /* Description : Disable ADC Auto Trigger
149 /* Input : void
150 /* Return
               void
152 extern void ADC vidAutoTriggerDisable(void);
153
```

```
155 /* Description : Set Auto Trigger Source
156 /* Input : u8Source
157 /* Return : LBTY_tenuErrorStatus
158 /* *************************
159 extern LBTY tenuErrorStatus ADC u8SetAutoTriggerSource(ADC tenuTriggerSource
u8Source):
160
161 /*
/* Description : Set ADC Prescaler
163 /* Input : u8Prescaler
164 /* Return : LBTY tenuErrorStatus
166 extern LBTY tenuErrorStatus ADC u8SetPrescaler(ADC tenuPrescalerSelection
u8Prescaler);
167
168 /* *******
169 /* Description : Set V_Ref
170 /* Input : u8Vref
171 /* Return : LBTY tenuErrorStatus
173 extern <u>LBTY tenuErrorStatus</u> <u>ADC u8SetV REF(ADC tenuRefSelection</u> u8Vref);
174
176 /* Description : Set Channel
177 /* Input : u8Channel
178 /* Return : LBTY tenuErr
178 /* Return
                 LBTY tenuErrorStatus
180 extern LBTY tenuErrorStatus ADC u8SetChannel(ADC tenuChannel u8Channel);
181
183 /* Description : Start conversion

184 /* Input : void


185 /* Return : void
185 /* Return
186 /* *************
187 extern void ADC vidStartConversion(void);
190 /* Description : wait conversion done
191 /* Input : void
192 /* Return : void
194 extern void ADC vidWaitConversion(void);
195
197 /* Description : Get ADC Read
198 /* Input : void
199 /* Return : u16
201 extern u16 ADC u16GetData(void);
202
203 /* ***************
208 extern f32 ADC f32GetVoltage(void);
209
210 /* ****************************
211 /* Description : start ADC Read of the channel
212 /* Input : u8Channel
213 /* Return : LBTY tenuErrorStatus
215 extern <u>LBTY tenuErrorStatus</u> <u>ADC u8StartRead(ADC tenuChannel u8Channel)</u>;
216
217 /* *************************
223 extern LBTY tenuErrorStatus ADC u8ReadChannel(ADC tenuChannel u8Channel, u16*
pu16ADC Value);
224
226 /* Description : Get the ADC Read from Conversion Array 227 /* Input : u8Channel
228 /* Input/Output: pu16ADC Value
```

```
229 /* Return : LBTY tenuErrorStatus
231 extern LBTY tenuErrorStatus ADC u8ReadConvValue(u8 u8Channel, u16* pu16ADC Value);
232
234 /* Description : Start the ADC Interrupt Conversion 235 /* Input : void 236 /* Return : LBTY_tenuErrorStatus
238 extern LBTY tenuErrorStatus ADC u16RefreshADC(void);
239
240 /* ****************************
241 /* Description : Get the ADC Interrupt Conversion
242 /* Input : pul6ADC_Value
243 /* Return : LBTY_tenuErrorStatus
244 /* ********
245 extern <a href="LBTY">LBTY</a> tenuErrorStatus <a href="ADC">ADC</a> u16GetAll (u16</a> pu16ADC Value[]);
246
247
248
250 /* Description : Enable ADC Interrupt
251 /* Input : void
252 /* Return : void
254 extern void ADC vidEnableINT(void);
255
256 /* *********************************
257 /* Description : Disable ADC Interrupt
258 /* Input : void
259 /* Return : void
260 /* ****************************
261 extern void ADC vidDisableINT(void);
264 /* Description : Clear ADC interrupt Flag
265 /* Input : void 266 /* Return : void
              void
268 extern void ADC vidClrFlagINT(void);
269
272 /* Input : void
273 /* Return
              void
275 extern void ADC vidSetCallBack(void (*pvidCallBack)(void));
276
277
```

H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/ADC_prg.c File Reference

```
#include "LBTY_int.h"
#include "LBIT_int.h"
#include "LCTY_int.h"
#include "INTP.h"
#include "GPIO_int.h"
#include "ADC_int.h"
#include "ADC_cfg.h"
#include "ADC_priv.h"
```

Include dependency graph for ADC_prg.c:



Functions

- static void vid AdcSyncRead (void)
- void <u>ADC_vidInit</u> (void)
- <u>LBTY tenuErrorStatus ADC u8CofigChannel (ADC tenuChannel u8Channel)</u>
- void ADC vidCalibrate (void)
- void <u>ADC_vidEnable</u> (void)
- void ADC vidDisable (void)
- void ADC vidAutoTriggerEnable (void)
- void <u>ADC vidAutoTriggerDisable</u> (void)
- LBTY tenuErrorStatus ADC u8SetAutoTriggerSource (ADC tenuTriggerSource u8Source)
- <u>LBTY_tenuErrorStatus_ADC_u8SetPrescaler (ADC_tenuPrescalerSelection_u8Prescaler)</u>
- LBTY tenuErrorStatus ADC u8SetV REF (ADC tenuRefSelection u8Vref)
- LBTY_tenuErrorStatus_ADC_u8SetChannel (ADC_tenuChannel u8Channel)
- void ADC vidStartConversion (void)
- void ADC_vidWaitConversion (void)
- u16 ADC u16GetData (void)
- <u>f32 ADC f32GetVoltage</u> (void)
- <u>LBTY_tenuErrorStatus_ADC_u8StartRead_(ADC_tenuChannel_u8Channel)</u>
- <u>LBTY tenuErrorStatus ADC u8ReadChannel</u> (<u>ADC tenuChannel</u> u8Channel, <u>u16</u> *pu16ADC_Value)
- <u>LBTY_tenuErrorStatus_ADC_u8ReadConvValue_(u8_u8Channel, u16_*pu16ADC_Value)</u>
- <u>LBTY tenuErrorStatus ADC u16RefreshADC</u> (void)
- <u>LBTY_tenuErrorStatus_ADC_u16GetAll_(u16_pu16ADC_Value[])</u>
- void <u>ADC vidEnableINT</u> (void)
- void ADC_vidDisableINT (void)
- void ADC_vidClrFlagINT (void)
- void <u>ADC_vidSetCallBack</u> (void(*pvidCallBack)(void))
- <u>ISR</u> (ADC_vect)

Variables

- static <u>u8 au8ChannelValue LGB [ADC Num]</u>
- static <u>u8 u8ConvDone_GLB</u> = <u>LBTY_SET</u>
- static <u>f32 f32V REF</u> = <u>ADC V REF</u>
- static void(* pvidFunctionCallBack)(void)

Function Documentation

f32 ADC_f32GetVoltage (void)

```
292 {
293    return (<u>f32</u>) <u>ADC_u16GetData</u>() * <u>f32V_REF</u> / <u>ADC_MAX</u>;
294 }
```

Here is the call graph for this function:



Here is the caller graph for this function:

```
SENSOR_u8GetData SENSOR_u8GetChannel ADC_f32GetVoltage
```

<u>LBTY_tenuErrorStatus</u> ADC_u16GetAll (<u>u16</u> *pu16ADC_Value*[])


Clear complete flag by writing logic one

```
396
397
        LBTY tenuErrorStatus u8RetErrorState = LBTY OK;
398
399
        if(u8ConvDone GLB == LBTY SET) {
            S ADC->m ADCSRA.sBits.m ADIE = LBTY RESET;
400
            S ADC->m ADCSRA.sBits.m ADIF = LBTY SET;
401
402
            for(u8 i = 0 ; i < ADC Num ; i++) {
403
                pu16ADC Value[i] = au8ChannelValue LGB[i];
404
405
        }else{
406
            u8RetErrorState = LBTY IN PROGRESS;
407
408
        return u8RetErrorState;
409 }
```

u16 ADC_u16GetData (void)

```
283 {
284 return (<u>u16</u>) <u>S ADC</u>->m_ADC;
285 }
```

Here is the caller graph for this function:



LBTY_tenuErrorStatus ADC_u16RefreshADC (void)

Clear complete flag by writing logic one

```
377

378

LBTY tenuErrorStatus u8RetErrorState = LBTY OK;

379

380

if (u8ConvDone GLB == LBTY SET) {

381

u8ConvDone GLB = LBTY RESET;

382

SADC->m ADCSRA.sBits.m ADIE = LBTY SET;

383

SADC->m ADCSRA.sBits.m ADIF = LBTY SET;

384

u8RetErrorState = ADC u8StartRead (*kau8ActiveChannel LGB);

385

}else{
```

```
386     u8RetErrorState = LBTY IN PROGRESS;
387   }
388   return u8RetErrorState;
389 }
```

Here is the call graph for this function:



Here is the caller graph for this function:



LBTY_tenuErrorStatus ADC_u8CofigChannel (ADC_tenuChannel u8Channel)

```
111
        LBTY tenuErrorStatus u8RetErrorState = LBTY OK;
112
113
        if(IS CHANNEL(u8Channel)) {
             u8RetErrorState = GPIO u8SetPinDirection(ADC PORT, u8Channel,
114
PIN_INPUT);
115
        }else{
            u8RetErrorState = \underline{LB}TY NOK;
116
117
118
        return u8RetErrorState;
119 }
```

Here is the caller graph for this function:



<u>LBTY tenuErrorStatus</u> ADC_u8ReadChannel (<u>ADC tenuChannel</u> u8Channel, <u>u16</u> * pu16ADC_Value)

```
323
324
        LBTY tenuErrorStatus u8RetErrorState = LBTY OK;
325
326
        if(pu16ADC_Value == LBTY_NULL) {
327
            u8RetErrorState = LBTY NULL POINTER;
328
        }else{
329
            if((u8)u8Channel < ADC ChannelMux){</pre>
                S ADC->m_ADMUX.sBits.m_MUX = u8Channel;
330
331
            }else{
332
                u8RetErrorState = LBTY NOK;
333
334
335
            S ADC->m ADCSRA.sBits.m ADSC = LBTY SET;
336
337
            while (S ADC->m ADCSRA.sBits.m ADSC);
338
339
            //vidMyDelay ms(ADC READ DELAY);
340
            //while(!S ADC->m ADCSRA.sBits.m ADIF);
341
S ADC->m ADCSRA.sBits.m ADIF = LBTY RESET;
342
343
            *pu16ADC Value = (u16)S ADC->m ADC;
344
345
        return u8RetErrorState;
346 }
```

Here is the caller graph for this function:

```
SENSOR_u8GetData SENSOR_u8GetChannel ADC_u8ReadChannel
```

<u>LBTY_tenuErrorStatus</u> ADC_u8ReadConvValue (<u>u8</u> *u8Channel*, <u>u16</u> * *pu16ADC_Value*)

```
if(u8Channel == kau8ActiveChannel LGB[i]){
361
362
                      *pu16ADC_Value = <u>au8ChannelValue LGB</u>[i];
363
                     break;
364
                 }else{
365
                     u8RetErrorState = LBTY NOK;
366
367
368
        return u8RetErrorState;
369
370 }
```

<u>LBTY_tenuErrorStatus</u> ADC_u8SetAutoTriggerSource (<u>ADC_tenuTriggerSource</u> *u8Source*)

```
178
179
        LBTY tenuErrorStatus u8RetErrorState = LBTY OK;
180
        switch(u8Source){
181
             case ADC Free Running Mode:
            case ADC Analog Comparator:
182
            case ADC External INT0:
case ADC TMR0 Compare MatchA:
183
184
185
            case ADC TMR0 Overflew:
            case ADC TMR1 Compare MatchB:
case ADC TMR1 Overflew:
186
187
188
             case ADC TMR1 Capture Event:
             S SFIOR->sBits.m ADTS = u8Source;
189
190
                break;
191
             default:
192
                 u8RetErrorState = LBTY NOK;
193
        }
194
195
        return u8RetErrorState;
196 }
```

LBTY tenuErrorStatus ADC_u8SetChannel (ADC_tenuChannel u8Channel)

Here is the caller graph for this function:



<u>LBTY_tenuErrorStatus</u> ADC_u8SetPrescaler (<u>ADC_tenuPrescalerSelection</u> *u8Prescaler*)

```
203
204
        LBTY_tenuErrorStatus u8RetErrorState = LBTY OK;
205
        switch(u8Prescaler){
206
           case ADC Division Factor 2 DEF:
207
            case ADC Division Factor 2:
           case ADC Division Factor 4:
208
209
            case ADC Division Factor 8:
            case ADC Division Factor
210
211
            case ADC Division Factor 32:
            case ADC Division Factor 64
case ADC Division Factor 128:
212
213
                S ADC->m ADCSRA.sBits.m ADPS = u8Prescaler;
214
215
                break;
216
            default:
217
                u8RetErrorState = LBTY NOK;
218
219
220
        return u8RetErrorState;
221 }
```

<u>LBTY_tenuErrorStatus</u> ADC_u8SetV_REF (<u>ADC_tenuRefSelection</u> u8Vref)

```
229
        LBTY tenuErrorStatus u8RetErrorState = LBTY OK;
230
        switch(u8Vref){
            case ADC AREF: case ADC AVCC:
231
232
            case ADC INTERNAL Vref:
233
234
                S ADC->m_ADMUX.sBits.m_REFS = u8Vref;
                break;
235
236
            default:
237
                u8RetErrorState = LBTY NOK;
238
        }
239
240
        return u8RetErrorState;
241 }
```

LBTY_tenuErrorStatus ADC_u8StartRead (ADC_tenuChannel u8Channel)

```
304
        LBTY tenuErrorStatus u8RetErrorState = LBTY OK;
305
306
        if((u8)u8Channel < ADC ChannelMux) {
307
            S ADC->m ADMUX.sBits.m MUX = u8Channel;
308
        }else{
            u8RetErrorState = LBTY NOK;
309
310
311
312
        S ADC->m ADCSRA.sBits.m_ADSC = <u>LBTY SET</u>;
313
314
        return u8RetErrorState;
315 }
```

Here is the caller graph for this function:




void ADC_vidAutoTriggerDisable (void)

void ADC_vidAutoTriggerEnable (void)

void ADC_vidCalibrate (void)

Here is the call graph for this function:



Here is the caller graph for this function:



void ADC_vidCIrFlagINT (void)

Clear complete flag by writing logic one

void ADC vidDisable (void)

void ADC_vidDisableINT (void)

void ADC_vidEnable (void)


void ADC_vidEnableINT (void)

void ADC_vidInit (void)

Clear complete flag by writing logic one

```
75
76
77
        for (u8 i = ADC Num; i--; ){
78
             ADC u8CofigChannel(kau8ActiveChannel LGB[i]);
79
80
        S SFIOR->sBits.m_ADTS = ADC TRIG SRC;
81
82
        S ADC->m ADCSRA.sBits.m_ADEN = LBTY SET;
S ADC->m ADCSRA.sBits.m_ADSC = LBTY RESET;
83
84
85
        S ADC->m ADCSRA.sBits.m ADATE = ADC AUTO TRIG;
        S ADC->m ADCSRA.sBits.m ADIE = ADC IRQ S
S ADC->m ADCSRA.sBits.m ADIF = LBTY SET;
86
87
88
        S ADC->m_ADCSRA.sBits.m_ADPS = ADC PRESCALER;
89
        ADC vidSetCallBack (vid AdcSyncRead);
90
        S ADC->m_ADMUX.sBits.m_REFS = ADC V REF SRC;
S ADC->m_ADMUX.sBits.m_ADLAR = ADC ADJUSTMENT;
91
92
93
        S ADC->m ADMUX.sBits.m MUX = ADC0;
94
95
        // first conversion will take 25 ADC clock cycles instead of the normal 13.
96
        S ADC->m ADCSRA.sBits.m ADSC = LBTY SET;
        while (S ADC->m_ADCSRA.sBits.m_ADSC);
97
98
99
        ADC vidCalibrate();
100
101
         S ADC->m_ADCSRA.sBits.m_ADEN = ADC INIT STATE;
102
```

Here is the call graph for this function:



void ADC_vidSetCallBack (void(*)(void) pvidCallBack)

Here is the caller graph for this function:



void ADC_vidStartConversion (void)

Here is the caller graph for this function:



void ADC_vidWaitConversion (void)

```
274 {
275 while(<u>S_ADC</u>->m_ADCSRA.sBits.m_ADSC);
276 }
```

Here is the caller graph for this function:



ISR (ADC_vect)

static void vid_AdcSyncRead (void)[static]

```
51
52
        static u8 u8Channel = LBTY u8ZERO;
53
54
        if (u8Channel < ADC Num) {
55
56
            \underline{u8ConvDone\ GLB} = \underline{LBTY\ RESET};
58
             au8ChannelValue LGB[u8Channel++] = (u16)S ADC->m ADC;
59
60
            while(ADC u8StartRead(u8Channel));
61
62
        }else{
```


Variable Documentation

```
u8 au8ChannelValue_LGB[ADC_Num][static]
f32 f32V_REF = ADC_V_REF[static]
void(* pvidFunctionCallBack) (void) (void )[static]
```

u8 u8ConvDone_GLB = LBTY_SET[static]

H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_ADC/ADC_priv.h File Reference

This graph shows which files directly or indirectly include this file:



Data Structures

union <u>ADCSRA_type</u>: Type define of Union bit field of "ADC Control and Status Reg A" union <u>ADMUX_type</u>: Type define of Union bit field of "ADC Multiplexer Selection Reg" union <u>ACSR_type</u>: Type define of Union bit field of "Analog Comparator Control and Status" struct <u>ADC_type</u>: Analog to Digital Converter Registers

union SFIOR type: Type define of Union bit field of "Special Function I/O Register"

Macros

- #define <u>IS_CHANNEL</u>(channel) ((channel >= <u>ADC0</u>) && (channel <= <u>ADC7</u>))
- #define <u>ADC_PORT_</u> A
- #define <u>ADC_MAX</u> 1023u
- #define <u>ADC_VBG_1V22</u> 1.22f
- #define <u>S ADC</u> ((<u>ADC type</u>* const)0x24U)
- #define <u>ADCL</u> (*(volatile <u>u8</u>* const)0x24U)
- #define <u>ADCH</u> (*(volatile <u>u8</u>* const)0x25U)
- #define \underline{ADCSRA} (*(volatile $\underline{u8}$ * const)0x26U)
- #define \underline{ADMUX} (*(volatile $\underline{u8}$ * const)0x27U)
- #define <u>ACSR</u> (*(volatile <u>u8</u>* const)0x28U)
 #define <u>S_SFIOR</u> ((<u>SFIOR_type</u>* const)0x50U)
- #define SFIOR (*(volatile u8* const)0x50U)

Enumerations

enum <u>ADC_tenuPinNum</u> { <u>ADC_Num</u> }
 : Type define of ADC Pin Number enum

Macro Definition Documentation

```
#define ACSR (*(volatile u8* const)0x28U)

#define ADC_MAX 1023u

#define ADC_PORT A

#define ADC_VBG_1V22 1.22f

#define ADCH (*(volatile u8* const)0x25U)

#define ADCL (*(volatile u8* const)0x24U)

#define ADCSRA (*(volatile u8* const)0x26U)

#define ADMUX (*(volatile u8* const)0x27U)

#define IS_CHANNEL( channel) ((channel >= ADC0) && (channel <= ADC7))

#define S_ADC ((ADC_type* const)0x24U)

Analog Digital Converter

#define S_SFIOR ((SFIOR_type* const)0x50U)

Special Function I/O Register

#define SFIOR (*(volatile u8* const)0x50U)
```

Enumeration Type Documentation

enum ADC tenuPinNum

: Type define of ADC Pin Number enum

Type: Union **Unit**: None

Enumerator:


ADC_priv.h

```
Go to the documentation of this file.1 /*
*************
3 /* **********
4 /* File Name : ADC_priv.h
11
12 #ifndef ADC_PRIV_H_
13 #define ADC PRIV H
14
18
21 typedef enum {
22 #ifdef ADC_CH0
23 ADC_0 = (u8)0u
23
24 #endif
25 #ifdef ADC CH1
      , ADC_1
26
27 #endif
28 #ifdef ADC CH2
, ADC_2
30 #endif
31 #ifdef ADC CH3
      , ADC_3
32
33 #endif
34 #ifdef ADC CH4
, ADC_4
37 #ifdef ADC CH5
, ADC_5
40 #ifdef ADC CH6
, ADC_6
43 #ifdef ADC CH7
      , ADC_7
44
45 #endif
46
  , ADC Num
47 }ADC tenuPinNum;
48
50
53 typedef union{
  u8 u_Reg;
struct {
54
55
   IO U8 m ADPS: 3;
IO U8 m ADIE: 1;
IO U8 m ADIF: 1;
IO U8 m ADATE: 1;
IO U8 m ADATE: 1;
IO U8 m ADSC: 1;
IO U8 m ADEN: 1.
56
57
58
59
60 IC
61 IC
62 }sBits;
60
       IO u8 m ADEN : 1;
63 }ADCSRA type;
64
65 /***********
66
69 typedef union{
  u8 u Reg;
70
71
    struct {
   _____<u>IO u8 m MUX</u> : 5;
72
    <u>IO u8 m ADLAR: 1;</u>
<u>IO u8 m REFS: 2;</u>
73
74 <u>10</u>
75 }sBits;
76 }ADMUX type;
```

```
82 typedef union{
83 <u>u8 u Reg;</u>
84 struct {
85 <u>IO</u> <u>u8</u>
86 <u>IO</u> <u>u8</u>
87 }sBits;
      <u>IO u8 m ACD</u> : 1;
88 }ACSR type;
89
91
94 typedef struct{
95 #if ADC_ADJUSTMENT
96 <u>I</u> <u>u16</u>
           m_ADC : 10;
97
      <u>u</u>16
99 <u>I u16</u> <u>m ADC</u> : 10;
100 <u>I u16</u> : 6;
101 #endif
105 }ADC type;
106
108
111 typedef union{
112 <u>u8 u Reg;</u>
113 struct {
    struct {
114
   ___<u>IO</u> <u>u8</u>
      <u>IO</u> <u>u8</u> <u>m ACME</u> : 1;
115
    : 1;
116
117 <u>IC</u>
118 }sBits;
       IO <u>u8</u> <u>m AD</u>TS : 3;
119 } SFIOR type;
120
121 /* ******************************
124
125 #define IS CHANNEL(channel)
                  ((channel >= ADC0) && (channel <= ADC7))
126
127 #define ADC PORT
129 #define ADC MAX
                   1023u
130 #define ADC_VBG_1V22
                   1.22f
131
133 #define S ADC
               ((ADC type* const)0x24U)
               (*(volatile u8* const)0x24U)
(*(volatile u8* const)0x25U)
134 #define ADCL
135 #define ADCH
               (*(volatile u8* const)0x26U)
136 #define ADCSRA
137 #define ADMUX
               (*(volatile u8* const)0x27U)
               (*(volatile u8* const)0x28U)
138 #define ACSR
139
141 #define S_SFIOR ((SFIOR_type* const)0x50U)
142 #define SFIOR
               (*(volatile u8* const)0x50U)
143
151
154 /* ****************************
155
156
```

H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_BSW/LBIT_int.h File Reference

This graph shows which files directly or indirectly include this file:



Macros

- #define _BV(bit) (1u<<(bit))
- #define <u>SET_BIT(REG</u>, bit) ((REG) |= (1u<<(bit)))
- #define $\underline{\text{CLR_BIT}}(\text{REG}, \text{ bit}) ((\text{REG}) \&= \sim (1u << (\text{bit})))$
- #define TOG BIT(REG, bit) ((REG) ^= (1u<<(bit)))
- #define $\underline{SET}\underline{BYTE}(REG, bit)$ ((REG) |= (0xFFu << (bit)))
- #define $\underline{\text{CLR}}\underline{\text{BYTE}}(\text{REG}, \text{ bit})$ ((REG) &= \sim (0xFFu<<(bit)))
- #define TOG BYTE(REG, bit) ((REG) ^= (0xFFu<<(bit)))
- #define $\underline{SET_MASK}(REG, MASK)$ ((REG) |= (MASK))
- #define <u>CLR_MASK(REG, MASK)</u> ((REG) &= ~(MASK))
- #define TOG MASK(REG, MASK) ((REG) ^= (MASK))
- #define GET_MASK(REG, MASK) ((REG) & (MASK))
- #define <u>SET_REG(REG)</u> ((REG) = \sim (0u))
- #define $\underline{CLR}\underline{REG}(REG)$ ((REG) = (0u))
- #define $\overline{\text{TOG REG}}(\text{REG})$ ((REG) $^= \sim (0\text{u})$)
- #define GET_BIT(REG, bit) (((REG)>>(bit)) & 0x01u)
- #define GET NIB(REG, bit) (((REG)>>(bit)) & 0x0Fu)
- #define GET BYTE(REG, bit) (((REG)>>(bit)) & 0xFFu)
- #define <u>ASSIGN_BIT</u>(REG, bit, value) $((REG) = ((REG) \& \sim (0x01u << (bit))) | (((value) \& 0x01u) << (bit)))$
- #define <u>ASSIGN_NIB</u>(REG, bit, value) $((REG) = ((REG) \& \sim (0x0Fu << (bit))) | (((value) \& 0x0Fu) << (bit)))$
- #define <u>ASSIGN BYTE</u>(REG, bit, value) $((REG) = ((REG) \& \sim (0xFFu << (bit))))$ (((value) & 0xFFu) << (bit)))
- #define <u>CON_u8Bits</u>(b7, b6, b5, b4, b3, b2, b1, b0)

(0b##b7##b6##b5##b4##b3##b2##b1##b0)

• #define <u>CON u16Bits</u>(b15, b14, b13, b12, b11, b10, b9, b8, b7, b6, b5, b4, b3, b2, b1, b0)

(0b##b15##b14##b13##b12##b11##b10##b9##b8##b7##b6##b5##b4##b3##b2##b1##b0)

Macro Definition Documentation

```
#define BV(bit) (1u<<(bit))
#define ASSIGN_BIT( REG, bit, value) ((REG) = ((REG) & \sim(0x01u<<(bit)))
                                                                            I
(((value) & 0x01u)<<(bit)))
#define ASSIGN BYTE( REG, bit, value) ((REG) = ((REG) & ~(0xFfu<<(bit)))
                                                                            Τ
(((value) & 0xFFu)<<(bit)))
#define ASSIGN_NIB( REG, bit, value) ((REG) = ((REG) & \sim(0x0Fu<<(bit)))
                                                                            I
(((value) & 0x0Fu)<<(bit)))
#define CLR_BIT( REG, bit) ((REG) &= ~(1u<<(bit)))
#define CLR_BYTE( REG, bit) ((REG) &= ~(0xFFu<<(bit)))
#define CLR_MASK( REG, MASK) ((REG) &= ~(MASK))
#define CLR_REG( REG) ((REG) = (0u))
#define CON_u16Bits( b15, b14, b13, b12, b11, b10, b9, b8, b7, b6, b5,
b4, b3, b2, b1, b0)
       (0b##b15##b14##b13##b12##b11##b10##b9##b8##b7##b6##b5##b4##b3##b2##
b1##b0)
#define CON_u8Bits( b7, b6, b5, b4, b3, b2, b1, b0)
      (0b##b7##b6##b5##b4##b3##b2##b1##b0)
#define GET_BIT( REG, bit) (((REG)>>(bit)) & 0x01u)
#define GET_BYTE( REG, bit) (((REG)>>(bit)) & 0xFFu)
#define GET_MASK( REG, MASK) ((REG) & (MASK))
#define GET_NIB( REG, bit) (((REG)>>(bit)) & 0x0Fu)
#define SET_BIT( REG, bit) ((REG) |= (1u<<(bit)))
   Bitwise Operation
```

```
#define SET_BYTE( REG, bit) ((REG) |= (0xFFu<<(bit)))

#define SET_MASK( REG, MASK) ((REG) |= (MASK))

#define SET_REG( REG) ((REG) = ~(0u))

#define TOG_BIT( REG, bit) ((REG) ^= (1u<<(bit)))

#define TOG_BYTE( REG, bit) ((REG) ^= (0xFFu<<(bit)))

#define TOG_MASK( REG, MASK) ((REG) ^= (MASK))


#define TOG_REG( REG) ((REG) ^= ~(0u))
```

LBIT_int.h


```
Go to the documentation of this file.1 /*
3 /* **********
4 /* File Name : LBIT_int.h
5 /* Author : MAAM
6 /* Version : v01
7 /* date : Mar 24, 2023
8 \ /* \ description : Bitwise Library
9 /* *********
11 /* ***********
12
13 #ifndef LBIT INT H
14 #define LBIT INT H
15
17 /* ***************** TYPE DEF/STRUCT/ENUM SECTION **************** */
19
23
24 #define _BV(bit)
                                              (1u<<(bit))
25
27 #define SET BIT(REG, bit)
                                           ((REG) \mid = (1u << (bit)))
28 #define CLR BIT(REG, bit)
                                           ((REG) &= ~(1u<<(bit)))
29 #define TOG_BIT(REG, bit)
                                           ((REG) ^= (1u<<(bit)))
30
                                          ((REG) |= (0xFFu<<(bit)))
((REG) &= ~(0xFFu<<(bit)))
31 #define SET_BYTE(REG, bit)
32 #define CLR BYTE (REG, bit)
33 #define TOG BYTE (REG, bit)
                                           ((REG) ^= (0xFFu<<(bit)))
34
                                           ((REG) |= (MASK))
35 #define SET MASK (REG, MASK)
36 #define CLR MASK (REG, MASK)
                                           ((REG) &= ~(MASK))
37 #define TOG_MASK(REG, MASK)
38 #define GET MASK(REG, MASK)
                                           ((REG) ^= (MASK))
((REG) & (MASK))
39
                                           ((REG) = \sim (0u))
((REG) = (0u))
40 #define SET_REG(REG)
41 #define CLR REG(REG)
42 #define TOG REG(REG)
                                           ((REG) ^= \sim (Ou))
43
44 #define GET BIT(REG, bit)
                                           (((REG)>>(bit)) & 0x01u)
45 #define GET NIB(REG, bit)
                                           (((REG)>>(bit)) & 0x0Fu)
46 #define GET BYTE (REG, bit)
                                           (((REG)>>(bit)) & 0xFFu)
47
48 #define ASSIGN BIT (REG, bit, value)
                                          ((REG) = ((REG) \& \sim (0x01u << (bit)))
| (((value) \& 0x01u) << (bit)))
49 #define ASSIGN NIB(REG, bit, value)
                                          ((REG) = ((REG) \& \sim (0x0Fu << (bit)))
| (((value) & 0x0Fu)<<(bit)))
50 #define ASSIGN_BYTE(REG, bit, value)
                                          ((REG) = ((REG) & \sim (0xFFu << (bit)))
| (((value) & 0xFFu) << (bit)))
51
52 /*
53 #define ASSIGN BIT(REG, bit, value)
                                           do {
54
                                            REG &= \sim (0 \times 01 u << bit);
55
                                            REG \mid= ((value & 0x01u)<<bit);
56
                                           }while(0)
57 */
58
       bits together in an u8 register
59 /*
60 #define CON_u8Bits(b7, b6, b5, b4, b3, b2, b1, b0)
61
(0b##b7##b6##b5##b4##b3##b2##b1##b0)
            bits together in an u16 register
64 #define CON u16Bits(b15, b14, b13, b12, b11, b10, b9, b8, b7, b6, b5, b4, b3, b2, b1,
b0) \
```

H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_BSW/LBTY_int.h File Reference

#include <stdint.h>
Include dependency graph for LBTY_int.h:



This graph shows which files directly or indirectly include this file:



Data Structures

union <u>LBTY tuniPort8union LBTY tuniPort16</u>

Macros

- #define <u>IO</u> volatile
- #define O volatile
- #define I volatile const
- #define <u>LBTY_u8vidNOP()</u>
- #define <u>LBTY NULL</u> ((void *) 0U)
- #define <u>LBTY_u8ZERO</u> ((<u>u8</u>)0x00U)
- #define <u>LBTY u8MAX</u> ((<u>u8</u>)0xFFU)
- #define <u>LBTY s8MAX</u> ((<u>s8</u>)0x7F)
- #define <u>LBTY_s8MIN</u> ((<u>s8</u>)0x80)
- #define <u>LBTY u16ZERO</u> ((<u>u16</u>)0x0000U)
- #define <u>LBTY_u16MAX</u> ((<u>u16</u>)0xFFFFU)
- #define <u>LBTY s16MAX</u> ((<u>u16</u>)0x7FFF)
- #define <u>LBTY s16MIN</u> ((<u>u16</u>)0x8000)
- #define <u>LBTY_u32ZERO</u> ((<u>u32</u>)0x0000000UL)
- #define <u>LBTY_u32MAX</u> ((<u>u32</u>)0xFFFFFFFUL)
- #define LBTY_s32MAX ((u32)0x7FFFFFFL)
- #define LBTY s32MIN ((u32)0x80000000L)
- #define <u>LBTY_u64ZERO</u> ((<u>u64</u>)0x000000000000000ULL)
- #define LBTY_u64MAX ((u64)0xFFFFFFFFFFFFFFFULL)
- #define LBTY_s64MAX ((u64)0x7FFFFFFFFFFFFFLL)
- #define <u>LBTY_s64MIN</u> ((<u>u64</u>)0x8000000000000000LL)

Typedefs

- typedef uint8_t <u>u8</u>
- typedef uint16_t <u>u16</u>
- typedef uint32_t <u>u32</u>
- typedef uint64_t <u>u64</u>
- typedef int8_t <u>s8</u>
- typedef int16_t <u>s16</u>
- typedef int32_t <u>s32</u>
- typedef int64_t <u>s64</u>
- typedef float <u>f32</u>
- typedef double <u>f64</u>
- typedef <u>u8</u> * <u>pu8</u>
- typedef <u>u16</u> * <u>pu16</u>
- typedef <u>u32</u> * <u>pu32</u>
- typedef <u>u64</u> * <u>pu64</u>
- typedef $\underline{s8} * \underline{ps8}$
- typedef <u>\$16</u> * <u>p\$16</u>
- typedef $\frac{1}{832} * \frac{1}{9832}$
- typedef <u>s52</u> <u>ps52</u>
 typedef <u>s64</u> * <u>ps64</u>

Enumerations

- enum <u>LBTY_tenuFlagStatus</u> { <u>LBTY_RESET</u> = 0, <u>LBTY_SET</u> = !LBTY_RESET }
- enum LBTY tenuBoolean { LBTY TRUE = 0x55, LBTY FALSE = 0xAA }
- enum <u>LBTY_tenuErrorStatus</u> { <u>LBTY_OK</u> = (u16)0, <u>LBTY_NOK</u>, <u>LBTY_NULL_POINTER</u>, <u>LBTY_INDEX_OUT_OF_RANGE</u>, <u>LBTY_NO_MASTER_CHANNEL</u>, <u>LBTY_READ_ERROR</u>, <u>LBTY_WRITE_ERROR</u>, <u>LBTY_UNDEFINED_ERROR</u>, <u>LBTY_IN_PROGRESS</u> }

Macro Definition Documentation

```
#define I volatile const
#define __IO volatile
#define O volatile
#define LBTY_NULL ((void *) 0U)
#define LBTY_s16MAX ((u16)0x7FFF)
#define LBTY_s16MIN ((u16)0x8000)
#define LBTY_s32MAX ((u32)0x7FFFFFFL)
#define LBTY_s32MIN ((<u>u32</u>)0x80000000L)
#define LBTY_s64MAX ((u64)0x7FFFFFFFFFFFLL)
#define LBTY s64MIN ((u64)0x800000000000000LL)
#define LBTY_s8MAX ((s8)0x7F)
#define LBTY_s8MIN ((s8)0x80)
#define LBTY_u16MAX ((u16)0xFFFFU)
#define LBTY_u16ZERO ((<u>u16</u>)0x0000U)
#define LBTY_u32MAX ((u32)0xFFFFFFFUL)
#define LBTY_u32ZERO ((<u>u32</u>)0x0000000UL)
#define LBTY_u64MAX ((u64)0xFFFFFFFFFFFFFULL)
#define LBTY_u64ZERO ((<u>u64</u>)0x00000000000000ULL)
#define LBTY_u8MAX ((u8)0xFFU)
#define LBTY_u8vidNOP()
#define LBTY_u8ZERO ((u8)0x00U)
   Data Types Limitation
```

Typedef Documentation

typedef float f32

Standard Real Decimal number

```
typedef double f64
typedef s16* ps16
typedef s32* ps32
typedef <u>s64</u>* <u>ps64</u>
typedef s8* ps8
   Standard Pointer to Signed Byte/Word/Long_Word
typedef u16* pu16
typedef u32* pu32
typedef u64* pu64
typedef u8* pu8
   Standard Pointer to Unsigned Byte/Word/Long_Word
typedef int16_t s16
typedef int32_t s32
typedef int64_t s64
typedef int8_t s8
   Standard Signed Byte/Word/Long_Word
typedef uint16_t u16
typedef uint32_t u32
typedef uint64_t u64
typedef uint8_t u8
   Data Types New Definitions Standard Unsigned Byte/Word/Long_Word
```

Enumeration Type Documentation

enum <u>LBTY_tenuBoolean</u>

Boolean type

Enumerator:

```
LBTY_TRUE

LBTY_FALSE

96 {
97  LBTY TRUE = 0x55,
98  LBTY FALSE = 0xAA
99 } LBTY tenuBoolean;
```

enum <u>LBTY_tenuErrorStatus</u>

Error Return type

Enumerator:

```
LBTY_OK
       LBTY_NOK
  LBTY_NULL_PO
            INTER
  LBTY_INDEX_O
   UT_OF_RANGE
   LBTY_NO_MAS
   TER_CHANNEL
  LBTY_READ_ER
              ROR
  LBTY_WRITE_E
             RROR
  LBTY_UNDEFIN
       ED_ERROR
  LBTY_IN_PROG
             RESS
102
103 LBTY OK = (u16)0,
104 LBTY NOK,
105 LBTY NULL POINTER,
106 LBTY INDEX OUT OF RANGE,
107 LBTY NO MASTER CHANNEL,
107 LBTY NO MASTER CHANNEL,
108 LBTY READ ERROR,
      LBTY WRITE ERROR,
LBTY UNDEFINED ERROR,
109
110
111 LBTY IN PROGRESS
                                /* Error is not available, wait for availability */
112 } LBTY tenuErrorStatus;
```

enum <u>LBTY_tenuFlagStatus</u>

Flag Status type

Enumerator:

```
LBTY_RESET

LBTY_SET

90 {
91    LBTY RESET = 0,
92    LBTY SET = !LBTY RESET
93 } LBTY_tenuflagStatus;
```

LBTY int.h

```
Go to the documentation of this file.1 /*
3 /* ***********
4 /* File Name : LBTY_int.h
5 /* Author : MAAM
6 /* Version : v01
7 /* date : Mar 23, 2023
8 /* description : Basic Library
9 /* **********
11 /* ************
12
13 #ifndef _LBTY_INT_H_
14 #define _LBTY_INT_H_
15
16 #include <stdint.h>
17
21
               <u>u8</u>;
<u>u16</u>;
<u>u32</u>;
<u>u64</u>;
24 typedef uint8 t
25 typedef uint1\overline{6} t
26 typedef uint32 t
27 typedef uint64_t
28
               <u>sb</u>
<u>s16;</u>
<u>s32;</u>
<u>s64</u>
30 typedef int8 t
31 typedef int16_t
32 typedef int32 t
33 typedef int64_t
34
36 typedef float
37 typedef double
                 <u>f64</u>;
38
40 typedef u8*
              pu16;
pu32;
pu64;
41 typedef u16*
42 typedef \overline{u32}*
43 typedef <u>u64</u>*
44
46 typedef s8*
                ps8 ;
47 typedef <u>s16</u>*
              <u>ps16;</u>
<u>ps32;</u>
<u>ps64</u>;
48 typedef \frac{1}{832}*
49 typedef <u>s64</u>*
50
54
60
61 #define LBTY u8vidNOP()
62 #define LBTY NULL
                    ((void *) OU)
63
65 #define LBTY_u8ZERO ((u8)0x00U)
66 #define LBTY_u8MAX ((u8)0xFFU)
67 #define LBTY_s8MAX ((s8)0x7F)
68 #define LBTY_s8MIN ((s8)0x80)
69
70 #define LBTY_u16ZERO ((u16)0x0000U)
71 #define LBTY_u16MAX ((u16)0xFFFFU)
72 #define LBTY_s16MAX ((u16)0x7FFF)
73 #define LBTY_s16MIN ((u16)0x8000)
74
75 #define LBTY_u32ZERO ((u32)0x00000000UL)
76 #define LBTY_u32MAX ((u32)0xFFFFFFFFUL)
77 #define LBTY_s32MAX ((u32)0x7FFFFFFFFL)
77 #define LBTY_s32MAX
78 #define LBTY_s32MIN
                     ((u32)0x7FFFFFFFL)
                  ((u32)0x7FFFFFFFL)
((u32)0x80000000L)
79
```

```
80 #define LBTY u64ZERO ((u64)0x000000000000000ULL)
81 #define LBTY_u64MAX ((u64)0xFFFFFFFFFFFFFFFLLL)

82 #define LBTY_s64MAX ((u64)0x7FFFFFFFFFFFFLL)

83 #define LBTY_s64MIN ((u64)0x8000000000000000LL)
84
87 /* ***************
88
90 typedef enum {
    LBTY RESET = 0,
LBTY SET = !LBTY RESET
91
92
93 } LBTY tenuFlagStatus;
94
96 typedef enum {
97 LBTY TRUE = 0x55,
98 \overline{LBTY FALSE} = 0xAA
99 } LBTY_tenuBoolean;
100
102 typedef enum {
     \underline{LBTY OK} = (\underline{u16}) 0,
103
104 <u>LBTY NOK</u>,
105 LBTY NULL POINTER,
106 LBTY INDEX OUT OF RANGE,
107 LBTY NO MASTER CHANNEL,
108 LBTY READ ERROR,
109 LBTY WRITE ERROR,
110 LBTY UNDEFINED ERROR,
111 LBTY IN PROGRESS
                              /* Error is not available, wait for availability */
112 } LBTY tenuErrorStatus;
113
116 /* ****************
117
119 typedef union {
120 struct {
                       // LSB
      <u>u8</u> <u>m u8b0</u> :1;
121
      <u>u8</u> <u>m u8b1</u> :1;
<u>u8</u> <u>m u8b2</u> :1;
122
123
124
       <u>u8</u> <u>m u8b3</u> :1;
<u>u8</u> <u>m u8b4</u> :1;
125
126
       u8 m u8b5 :1;


    u8
    m
    u8b6
    :1;

    u8
    m
    u8b7
    :1;

127
128
                          // MSB
129 } sBits;
130 <u>u8 u u8Byte</u>;
131 } LBTY tuniPort8;
132
133 typedef union {
134 struct {
    <u>u8</u> <u>m</u> u8b0
       <u>u8</u> <u>m u8b0</u> :1;
u8 <u>m u8b1</u> :1;
135
                           // LSB
136
                  :1;
      u8 m u8b2
u8 m u8b3
137
138
                   :1;
139 <u>u8 m u8b4</u> :1;
       <u>u8</u> <u>m u8b5</u>
<u>u8</u> <u>m u8b6</u>
140
                   :1;
                  :1;
141
142
       <u>u8</u> <u>m u8b7</u>
                  :1;
143
        u8 m u8b8
                   :1;
144
       u8 m u8b9 :1;
      <u>u8</u> m<u>u8b10</u> :1;
145
        u8 m u8b11 :1;
146
<u>u8</u> <u>m u8b15</u> :1;
                          // MSB
150
151 } sBits;
152 struct {
    u8 m u8low;
u8 m u8high;
153
154
155 } sBytes;
156
      u16 u u16Word;
157 } LBTY tuniPort16;
158
159 /* **************************
```

H:/0/Workspaces/MCU Drivers/ATmega32/MCAL/SWC_BSW/LCTY_int.h File Reference

This graph shows which files directly or indirectly include this file:



Macros

- #define <u>LCTY_PROGMEM</u> __attribute__((__progmem__))
- #define <u>LCTY_PURE</u> __attribute__((__pure__))
- #define <u>LCTY_INLINE</u> __attribute__((always_inline)) static inline
- #define <u>LCTY INTERRUPT</u> __attribute__((interrupt))
- #define CTY_PACKED __attribute__((__packed__))
- #define LCTY_CONST __attribute__((__const__))
- #define <u>LCTY_DPAGE</u> __attribute__((dp))
- #define <u>LCTY_NODPAGE</u> __attribute__((nodp))
- #define <u>LCTY_SECTION</u>(section) __attribute__((section(# section)))
- #define <u>LCTY_ASM</u>(cmd) __asm__ _volatile__ (# cmd ::)

Macro Definition Documentation

```
#define CTY_PACKED __attribute__((__packed__))

#define LCTY_ASM( cmd) __asm____volatile__ ( # cmd ::)

#define LCTY_CONST __attribute__((__const__))

#define LCTY_DPAGE __attribute__((dp))

#define LCTY_INLINE __attribute__((always_inline)) static inline

#define LCTY_INTERRUPT __attribute__((interrupt))

#define LCTY_NODPAGE __attribute__((nodp))

#define LCTY_PROGMEM __attribute__((__progmem__))

#define LCTY_PURE __attribute__((_pure__))

#define LCTY_SECTION( section) __attribute__((section( # section)))
```

LCTY_int.h

```
Go to the documentation of this file.1 /*
3 /* ***********
4 /* File Name : LCTY_int.h
5 /* Author : MAAM
6 /* Version : v00
7 /* date : Apr 26, 2023
8 /* description : Compiler Library
9 /* ***********
11 /* ************
12
13 #ifndef LCTY INT H
14 #define LCTY INT H
15
17 /* **************** TYPE DEF/STRUCT/ENUM SECTION **************** */
19
21 /* ****************** MACRO/DEFINE SECTION **********************************
23
24 /* prog memory attribute */
25 #define LCTY PROGMEM
                    attribute (( progmem ))
26
27 /* pure attribute */
28 #define LCTY PURE
                    __attribute__((__pure__))
29
30 /* Abstraction for inlining */
31 //#define LCTY_INLINE
                    static inline
32 #define LCTY INLINE
                    __attribute__((always_inline)) static inline
33
34 /* define function as interrupt handler */
                    __attribute__((interrupt))
35 #define LCTY INTERRUPT
36
37 /* Memory packed to pass Memory padding */
38 #define CTY PACKED
                   __attribute__((__packed ))
39
40 /* Const attribute */
41 #define LCTY CONST
                    __attribute__((__const__))
42
43 /* place variable in direct page */
44 #define LCTY_DPAGE
                     attribute ((dp))
45
46 /* do not place variable in direct page */
47 #define LCTY_NODPAGE __attribute__((nodp))
48
49 /* Sections */
50 #define LCTY SECTION(section)
                   attribute ((section( # section)))
51
52 /* Abstraction for assembly command */
53 # define LCTY_ASM(cmd) __asm___volatile__ ( # cmd ::)
54
55 /* *****************
58
62
66
67
68 #endif /* LCTY INT H */
```