

✓ APPROVED · VITAL

Start here.

The single source of truth for Clink's interface — a mobile-first, bilingual (AR/EN), light+dark system for all five roles: patient, doctor, secretary, owner, admin. Everything is built from documented tokens and patterns, so screens stay consistent and fast to ship.

- Mobile-first
- Light + Dark
- عربي RTL + EN LTR
- Token-based
- WCAG AA

The system — 4 documents

Read top to bottom the first time. Each opens in its own page with the same theme & language toggles.

01

Foundations
Color, typography, iconography, spacing, radius, elevation, breakpoints, the component library, motion & accessibility — plus the copy-paste token block.
[Open](#) →

02

Patterns & States
The product layer: messages & the Arabic catalog, appointment status system, verification states, the medication-safety banner, per-actor warnings, loading, and system/error pages.
[Open](#) →

03

Applied screens · Vital
The system in use — Home, Guest, Patient, Doctor & Secretary, each in desktop + mobile. Reference layouts for how tokens & components compose.
[Open](#) →

04

Interactive demo
A working shell — switch account type, language and theme live, and run the clickable booking flow. Shows the switchers & state transitions in motion.
[Open](#) →

For developers

The system is CSS-variable driven, so it maps cleanly onto your Tailwind + light/dark stack.

Token → Tailwind

```
// globals.css — copy from Foundations
:root { --color-primary:#0F54E0; --bg:#F6F8FA; ... }
[data-theme="dark"] { --color-primary:#4F8DFF; ... }

// tailwind.config.js
darkMode: ['selector', '[data-theme="dark"]'],
theme: { extend: { colors: {
  primary: 'var(--color-primary)',
  bg: 'var(--bg)', panel: 'var(--panel)',
}}}

```

Non-negotiable conventions

✓ **Arabic-first copy** — pull user-facing text from the message catalog (Patterns 01); never hardcode strings.

✓ **RTL-safe** — logical properties only (inset-inline-start, ms/me). Test with the ع toggle.

✓ **Theme via token** — color only through vars; dark is [data-theme="dark"], never a hardcoded hex.

✓ **≥44px** touch targets on mobile; Lucide-style icons, 1.8px stroke, `currentColor`.

✓ **Status & feedback** — reuse the fixed status colors + toast variants (Patterns 01–02); don't invent new ones.

Adding or changing anything — the order

1 Add/confirm the token in Foundations

→

2 Build the component from tokens

→

3 Document its states in Patterns

→

4 Show it in an applied screen

 **Open build task**

The offline / no-connection state is designed & spec'd (Patterns 07) but needs client wiring (connection listener + optional service worker). Everything else — 400/403/404/500, all statuses, all messages — already exists in the codebase.