Experiment 19

Logistic Regression for a given data set

```
import numpy as np
import pandas as pd
df=pd.read_csv('Social_Network_Ads.csv')
df
```

✓ 0.0s

	User ID	Gender	Age	EstimatedSalary	Purchased
0	15624510	Male	19	19000	0
1	15810944	Male	35	20000	0
2	15668575	Female	26	43000	0
3	15603246	Female	27	57000	0
4	15804002	Male	19	76000	0
...	...	...	...	...	...
395	15691863	Female	46	41000	1
396	15706071	Male	51	23000	1
397	15654296	Female	50	20000	1
398	15755018	Male	36	33000	0
399	15594041	Female	49	36000	1

400 rows × 5 columns

```
df.head()
```

✓ 0.0s

	User ID	Gender	Age	EstimatedSalary	Purchased
0	15624510	Male	19	19000	0
1	15810944	Male	35	20000	0
2	15668575	Female	26	43000	0
3	15603246	Female	27	57000	0
4	15804002	Male	19	76000	0

```
features=df.iloc[:,[2,3]].values
label=df.iloc[:,4].values
features
```

✓ 0.0s

```
array([[    19,  19000],
       [    35,  20000],
       [    26,  43000],
       [    27,  57000],
       [    19,  76000],
       [    27,  58000],
       [    27,  84000],
       [    32, 150000],
       [    25,  33000],
       [    35,  65000],
       [    26,  80000],
       [    26,  52000],
       [    20,  86000],
       [    32,  18000],
       [    18,  82000],
       [    29,  80000],
       [    47,  25000],
       [    45,  26000],
       [    46,  28000],
```

```
label
```

✓ 0.0s

```
array([0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 1, 1, 1, 1, 1, 1,
       1, 1, 1, 1, 1, 1, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0,
       0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0,
       0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 0, 1, 1, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 1, 0, 1, 0, 1, 0, 1, 0, 1, 1, 0, 0, 0, 1, 0, 0, 0, 1,
       0, 1, 1, 1, 0, 0, 1, 1, 0, 1, 1, 0, 1, 1, 0, 1, 0, 0, 0, 1, 1, 0,
       1, 1, 0, 1, 0, 1, 0, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 1, 0, 1, 1, 0,
       1, 1, 0, 0, 1, 0, 0, 1, 1, 1, 1, 1, 0, 1, 1, 1, 1, 0, 1, 1, 0, 1,
       0, 1, 0, 1, 1, 1, 1, 0, 0, 0, 1, 1, 0, 1, 1, 1, 1, 1, 0, 0, 0, 1,
       1, 0, 0, 1, 0, 1, 0, 1, 1, 0, 1, 0, 1, 1, 0, 1, 1, 0, 0, 0, 1, 1,
       0, 1, 0, 0, 1, 0, 1, 0, 0, 1, 1, 0, 0, 1, 1, 0, 1, 1, 0, 0, 1, 0,
       1, 0, 1, 1, 1, 0, 1, 0, 1, 1, 1, 0, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1,
       0, 1, 0, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 0, 1,
       1, 1, 0, 1])
```

```
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LogisticRegression
```

✓ 0.4s

```
for i in range(1,401):
  x_train,x_test,y_train,y_test=train_test_split(features,label,test_size=0.2,random_st
    ate=i)
  model=LogisticRegression()
  model.fit(x_train,y_train)
  train_score=model.score(x_train,y_train)
  test_score=model.score(x_test,y_test)
  if test_score>train_score:
    print("Test {} Train{} Random State {}".format(test_score,train_score,i))
```

✓ 4.8s

```
Test 0.9 Train0.840625 Random State 4
Test 0.8625 Train0.85 Random State 5
Test 0.8625 Train0.859375 Random State 6
Test 0.8875 Train0.8375 Random State 7
Test 0.8625 Train0.8375 Random State 9
Test 0.9 Train0.840625 Random State 10
Test 0.8625 Train0.85625 Random State 14
Test 0.85 Train0.84375 Random State 15
Test 0.8625 Train0.85625 Random State 16
Test 0.875 Train0.834375 Random State 18
Test 0.85 Train0.84375 Random State 19
Test 0.875 Train0.84375 Random State 20
Test 0.8625 Train0.834375 Random State 21
Test 0.875 Train0.840625 Random State 22
Test 0.875 Train0.840625 Random State 24
Test 0.85 Train0.834375 Random State 26
Test 0.85 Train0.840625 Random State 27
Test 0.8625 Train0.834375 Random State 30
Test 0.8625 Train0.85625 Random State 31
```

```
x_train,x_test,y_train,y_test=train_test_split(features,label,test_size=0.2,random_stat
    e=286)
finalModel=LogisticRegression()
finalModel.fit(x_train,y_train)
```

✓ 0.0s

```
LogisticRegression()
```

```
print(finalModel.score(x_train,y_train))
print(finalModel.score(x_test,y_test))
```

✓ 0.0s

```
0.834375
0.9125
```

```
from sklearn.metrics import classification_report
print(classification_report(label,finalModel.predict(features)))
```

✓ 0.0s

```
              precision    recall  f1-score   support

           0       0.85      0.93      0.89       257
           1       0.84      0.71      0.77       143

    accuracy                           0.85       400
   macro avg       0.85      0.82      0.83       400
weighted avg       0.85      0.85      0.85       400
```