```
1 0.000000
                                                                TCP
                                                                        62
                     192.168.1.102
                                           128.119.245.12
                                                                               1161→80 [SYN]
Seq=0 Win=16384 Len=0 MSS=1460 SACK_PERM=1
Frame 1: 62 bytes on wire (496 bits), 62 bytes captured (496 bits)
    Encapsulation type: Ethernet (1)
   Arrival Time: Aug 21, 2004 09:44:20.570381000 EDT
    [Time shift for this packet: 0.00000000 seconds]
   Epoch Time: 1093095860.570381000 seconds
    [Time delta from previous captured frame: 0.000000000 seconds]
    [Time delta from previous displayed frame: 0.000000000 seconds]
    [Time since reference or first frame: 0.000000000 seconds]
   Frame Number: 1
   Frame Length: 62 bytes (496 bits)
   Capture Length: 62 bytes (496 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:tcp]
    [Coloring Rule Name: HTTP]
    [Coloring Rule String: http://tcp.port == 80 || http2]
Ethernet II, Src: Actionte_8a:70:1a (00:20:e0:8a:70:1a), Dst: LinksysG_da:af:73 (00:06:25:da:af:
73)
   Destination: LinksysG da:af:73 (00:06:25:da:af:73)
       Address: LinksysG_da:af:73 (00:06:25:da:af:73)
       .... ..0. .... (factory default)
       .... = IG bit: Individual address (unicast)
   Source: Actionte 8a:70:1a (00:20:e0:8a:70:1a)
       Address: Actionte_8a:70:1a (00:20:e0:8a:70:1a)
       .... ..0. .... = LG bit: Globally unique address (factory default)
       .... = IG bit: Individual address (unicast)
   Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.102, Dst: 128.119.245.12
   0100 \dots = Version: 4
    \dots 0101 = Header Length: 20 bytes (5)
   Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
       0000 00.. = Differentiated Services Codepoint: Default (0)
       .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
   Total Length: 48
   Identification: 0x1e1d (7709)
   Flags: 0x02 (Don't Fragment)
       0... = Reserved bit: Not set
       .1.. = Don't fragment: Set
       ..0. .... = More fragments: Not set
   Fragment offset: 0
   Time to live: 128
   Protocol: TCP (6)
   Header checksum: 0xa518 [validation disabled]
    [Header checksum status: Unverified]
   Source: 192.168.1.102
   Destination: 128.119.245.12
    [Source GeoIP: Unknown]
    [Destination GeoIP: Unknown]
Transmission Control Protocol, Src Port: 1161, Dst Port: 80, Seq: 0, Len: 0
   Source Port: 1161
   Destination Port: 80
    [Stream index: 0]
    [TCP Segment Len: 0]
   Sequence number: 0
                        (relative sequence number)
   Acknowledgment number: 0
   Header Length: 28 bytes
   Flags: 0x002 (SYN)
       000. .... = Reserved: Not set
       ...0 .... = Nonce: Not set
       .... 0... = Congestion Window Reduced (CWR): Not set
```

```
.... .0.. .... = ECN-Echo: Not set
        .... ..0. .... = Urgent: Not set
        .... = Acknowledgment: Not set
        .... 0... = Push: Not set
        .... .... .0.. = Reset: Not set
        .... .... ..1. = Syn: Set
            [Expert Info (Chat/Sequence): Connection establish request (SYN): server port 80]
                [Connection establish request (SYN): server port 80]
                [Severity level: Chat]
               [Group: Sequence]
        \dots \dots 0 = Fin: Not set
        [TCP Flags: ······S·]
   Window size value: 16384
    [Calculated window size: 16384]
   Checksum: 0xf6e9 [unverified]
    [Checksum Status: Unverified]
   Urgent pointer: 0
   Options: (8 bytes), Maximum segment size, No-Operation (NOP), No-Operation (NOP), SACK
permitted
       Maximum segment size: 1460 bytes
           Kind: Maximum Segment Size (2)
           Length: 4
           MSS Value: 1460
       No-Operation (NOP)
           Type: 1
               0... = Copy on fragmentation: No
               .00. .... = Class: Control (0)
               \dots0 0001 = Number: No-Operation (NOP) (1)
       No-Operation (NOP)
           Type: 1
               0... = Copy on fragmentation: No
               .00. .... = Class: Control (0)
               \dots0 0001 = Number: No-Operation (NOP) (1)
       TCP SACK Permitted Option: True
           Kind: SACK Permitted (4)
```

Length: 2