Beyond Visual Agreement: Supplementary Material

Anonymous CVPR submission

1. Scope and Reading Guide

This supplement consolidates the complete protocols and result tables behind the main paper. The first part gives controlled mechanics, observability, additional observations, dynamic drops and all six coupled-scene families. The second part gives public SoftVT and real PhysTwin adapters, every fresh episode and every real transfer pair, including unsuccessful compatibility gates. The final part records a later conditional-flow diagnostic that was not promoted to replace the established predictors.

All studies retain their original cohorts and metric definitions. They are not combined into a single benchmark average or attributed to one shared implementation. Geometry and correspondences are supplied; material/force identifiability and causal raw-video reconstruction are not established. No prior prediction is changed by manuscript consolidation. Manuscript figures are generated from saved measurements; schematic method illustrations are labeled as such.

Implementation contract. Controlled six-family mechanics uses a frozen bulk decoder and quadratic supplied fixtures. The separate static inverse study uses both bulk and nonlinear attachment decoders. Real captured objects use tetrahedral equilibrium with the frozen bulk family and quadratic attachments. SoftVT uses analytic mechanics and a split pose/contact correction. These distinctions are essential when assigning a gain to a component.

2. Adapter contracts and active physical laws

The experiments share a decomposition into material, tool-relative and world-dependent terms. They do not share every law, state discretization or inference procedure. Table 1 summarizes the four implementations. In particular, the nonlinear learned attachment law is used in the static descriptor-refinement experiment, not in the headline six-family coupled benchmark or the real-object adapter.

Six-family material and attachment laws. The pretrained bulk decoder is extended by an independently fitted positive volumetric multiplier. With $B_\theta(s)$ denoting its original positive volumetric coefficient,

$$W_{\theta,\beta}(F,s) = W_\theta(F;s,0,-1)+(e^\beta-1)B_\theta(s)(J-\log J-1). \quad (1)$$

The fitted field is

$$s_b(X) = s_0 + \mathbf{1}_{b=2}\Delta s + c\tanh\big(8(X_1 - r)\big). \quad (2)$$

There are four parameters (s_0, β, c, r), with Δs added for the second body. The nonlinear descriptor coordinates are fixed at $(h, f) = (0, -1)$. The same spatial parameterization is enabled in every family; the family name does not supply the hidden material heterogeneity. No decoder weights are updated during these fits.

For this benchmark, fixture energy is quadratic:

$$\Pi_b = \frac{1}{2}\alpha_b(t)K_b \int_{\Gamma_b} w_b(X)\|x(X) - T_b(X,t)\|^2\, dA_0,$$
$$\int_{\Gamma_b} w_b\, dA_0 = 1. \quad (3)$$

The prescribed release gate α_b scales the assembled fixture matrix. K_b has units N/m; footprint normalization prevents it from becoming a per-node stiffness that changes with mesh density. The force and actuator work use derivatives of the same quadratic energy. The tested actuator paths translate their fixtures; general rotating fixtures are not evaluated in this six-family protocol. The older nonlinear attachment decoder is not called by this rollout.

World contact uses a gap function and a conservative penalty. For the parabolic bowl, the normalized implicit gap is an approximation to geometric signed distance, rather than an exact Euclidean distance. The scene does not implement friction, continuous collision detection or general rotating rigid-body collision. A finite-mass sphere translates under equal-and-opposite contact forces. Two deformable bodies retain separate material and state variables. These capabilities do not imply discovery of contact topology from images.

Real-object units and regularization. The real adapter normalizes coordinates by the initial bounding-box extent and divides the pretrained bulk energy by its 12,000 Pa reference energy scale. It replaces the analytic bulk contribution

Table 1. **Which components are active?** All rows use supplied reference geometry and correspondences. A frozen constitutive decoder is a material prior; it is not a frozen scene-specific parameter estimate.

Study	Bulk and fitted descriptors	Attachments and environment	State evolution
Six-family simulation	Frozen scalar energy; scale, volumetric multiplier, spatial contrast and transition; second-body scale when present	Supplied quadratic Gaussian/taper fixtures; explicit conservative normal penalties; known density and collision geometry	Structured Q2 hexahedra, consistent mass, velocity Verlet; coupled soft bodies and translating rigid sphere
Real PhysTwin	Frozen scalar energy; six material-field coefficients, two global nonlinear descriptors and volumetric adjustment	Quadratic prescribed-tool penalties; supplied footprints/activity, fitted strengths and effective gravity/floor parameters	Filtered tetrahedral equilibrium; implicit differentiation and bounded scene fitting
SoftVTBench	Analytic Neo-Hookean shape anchor and prefix-fitted corrections	Tool-relative slip/release; known static environment	Equilibrium anchor plus separate rigid pose/contact rollout; impulses do not deform the anchor
Static observation refinement	Frozen bulk and nonlinear attachment energies; 15 continuous material/interface descriptors	Inferred attachment strengths, nonlinearities and Gaussian footprint locations/widths; known families, geometry, density and gravity	Structured Q2 equilibrium with implicit sensitivities; separate reset commands

while retaining the external adapter's quadratic tool attachments, gravity and floor terms. Its six Gaussian material features are distinct from the synthetic $tanh$ field. The two global nonlinear descriptors and an independent volumetric adjustment are optimized with the spatial field; network weights remain frozen. Geometry filtering reduces tetrahedra bridging empty parts of the reconstructed cloud, but does not certify a watertight physical interior.

The inherited external energy includes a weak numerical reference-position penalty $\frac{1}{2}\epsilon\sum_i \|x_i - X_i\|^2$ with $\epsilon = 10^{-5}$ in normalized units. This regularization must not be interpreted as an inferred physical fixture. Effective gravity/material and attachment/material ratios are fitted; absolute real elastic moduli are not established by this normalized position-only inverse problem. The first observed configuration is treated as an effective rest shape, so unknown prestress remains a source of model error.

Static nonlinear attachments and the scale argument. The separate static refinement study uses the learned nonlinear attachment potential detailed below, with the quadratic spring recovered at zero nonlinearity. Its unknowns include boundary footprint centers and widths; that result cannot be reassigned to the known-boundary six-family study. The exact common-scale ambiguity concerns an idealized energy in which *all* stiffness-bearing terms are co-scaled and independent body loading is absent. It does not assert exact scale invariance for an external implementation with an unscaled numerical reference pin or fixed contact stiffness. Known gravitational or inertial scale information can break the stated symmetry without guaranteeing global identifiability.

Controlled Mechanics and Physical Evaluation

3. Controlled-study map

The controlled evidence comprises three earlier settings: (i) static composition with oracle physical descriptors, (ii) static inference of 15 continuous unknown descriptors and acquisition of an additional position observation, and (iii) dynamic calibration followed by larger-drop prediction against a native PhysTwin adaptation. A fourth study extends dynamic prediction to six coupled-scene families with unknown materials and known boundaries; its protocol is specified in Sec. 11. Results from these settings are not interchangeable. In particular, the dynamic experiment does not evaluate the static active policy or its uncertainty model.

The central representation is a reusable, conditional *energy law*. A small shared network maps physical descriptors to coefficients of invariant energy functions. A conventional mechanics solver combines this bulk law with attachment and contact potentials. Scene-specific inference estimates descriptors while the shared network weights remain frozen. Gaussian appearance is attached to material coordinates and transported by the resulting deformation. The system does not learn a direct image-to-force map, reconstruct unknown topology, or learn friction from video.

Units and metric conventions. Coordinates and tool translations are in metres; rotation vectors are in radians; force is in newtons; torque is in newton-metres. Bulk energy density is in pascals, total energy in joules, attachment stiffness in N/m, and normal-contact stiffness density in N/m^3. Static tables report *coordinate* RMSE. Dynamic benchmark




Figure 1. **Static learned-law composition.** This schematic depicts the bulk energy decoder; the separate nonlinear attachment decoder is specified in the text. The six-family and real-object adapters instead use quadratic attachments. Frozen constitutive weights are distinct from fitted scene descriptors and transported appearance.

tables report *point-vector* RMS, which is $\sqrt{3}$ times coordinate RMS for identical samples and weights. Numerical qualification thresholds remain in their originally declared coordinate convention.

What is shared. The bulk network is frozen across controlled objects and mechanical compositions. The bilateral-interface network is additionally active in the static composition and descriptor-refinement studies; the six-family dynamic study uses supplied quadratic fixtures. Reference geometry, material-coordinate fields, prescribed tool poses, gravity, and collision geometry enter the solver explicitly. Gravity is an external body load, rather than an output of the interface network. The dynamic drop study uses the shared bulk law and analytic normal contact; bilateral learned interfaces are evaluated in the static composition study, not covertly inserted into a free-body drop.

What is conventional. Invariant hyperelasticity, finite elements, sparse Newton solves, penalty contact, consistent mass, Verlet integration, implicit differentiation, and affine covariance transport are established ingredients. Our implementation combines them with shared conditional laws and auditable descriptor inference. We do not claim a new finite-element formulation, proof of polyconvexity, a general collision engine, or calibrated uncertainty.

4. Conditional bulk energy

Let X be a material coordinate, $x(X) = X + u(X)$ the deformation, $F = \partial x/\partial X$, $J = \det F > 0$, and $C = F^\top F$. Define

$$I_1 = \operatorname{tr} C, \qquad I_2 = \tfrac{1}{2}[(\operatorname{tr} C)^2 - \operatorname{tr}(C^2)], \tag{4}$$

$$q_1 = J^{-2/3} I_1 - 3, \qquad q_2 = J^{-4/3} I_2 - 3, \tag{5}$$

$$v(J) = J - \log J - 1. \tag{6}$$

The shared bulk energy is

$$W_\theta(F; s, h, c) = e^s E_0 \, a_\theta(h, c)^\top b(F), \qquad E_0 = 12000\,\text{Pa}, \tag{7}$$

with

$$b = [q_1/2, q_2/2, v, q_1^2, q_1^3, \phi_1(q_1), \phi_2(q_1)]^\top, \tag{8}$$

$$a_\theta = \operatorname{softplus}(\operatorname{MLP}_\theta(h, c)) + 10^{-8}, \tag{9}$$

$$\phi_i(q) = \operatorname{softplus}(\alpha_i q) - \log 2 - \alpha_i q/2, \tag{10}$$

$$\alpha_i = \operatorname{softplus}(\rho_i) + 10^{-4}. \tag{11}$$

The coefficient decoder has two inputs, one 16-unit SiLU hidden layer, and seven outputs. Including the two slopes, it contains 169 parameters. The descriptor s is a log common stiffness scale; h controls nonlinear material shape; $c = -1$ and $+1$ designate the two teacher families. The scale enters only as e^s, not through the decoder. Spatial heterogeneity is represented through a material-coordinate descriptor field, rather than a separate network per object.

Objectivity and isotropy follow from the invariants. The reference energy and stress vanish at $F = I$. Stress $P = \partial W/\partial F$ and tangent $\partial P/\partial F$ are evaluated by automatic differentiation. Positive coefficients and reference normalization do not imply global convexity in F, uniqueness of equilibrium, or unconditional stability. The implementation rejects nonpositive determinants and applies additional sampled determinant guards during solves.

5. Constitutive pretraining and interface laws

5.1. Bulk teachers and training

The two analytic teacher families share small-strain moduli but differ at finite strain. With $a = \operatorname{sigmoid}(h)$, $\mu = 4000e^s$ Pa, $K = 20000e^s$ Pa, and $f = .15 + .6a$,

$$W_{\text{MR}} = \frac{\mu}{2}[(1-f)q_1 + f q_2] + Kv, \tag{12}$$

$$W_{\text{Y}} = \mu\left[\tfrac{1}{2}q_1 + (.08 + .3a)q_1^2 + (.01 + .08a)q_1^3\right] + Kv. \tag{13}$$

These laws should not be confused with the separate stable-Neo-Hookean engine-control experiments.

Bulk pretraining uses 18 descriptor combinations: three scales $s \in \{-.5, 0, .5\}$, three shapes $h \in \{-1, 0, 1\}$, and both families. There are 4096 training strain coupons and 512 validation coupons. Deformation gradients are upper triangular with log diagonal entries sampled in $[-.2, .2]$ and upper off-diagonal entries in $[-.4, .4]$. This supplies positive determinants. The objective is

$$\mathcal{L}_W = \operatorname{MSE}(P_\theta/12000, P_*/12000) + .1\operatorname{MSE}(W_\theta/12000, W_*/12000). \tag{14}$$

Training uses float64, batch size 256, 6000 fixed Adam steps, initial learning rate .003, and cosine decay. The final iterate is frozen before generating constitutive test coupons. No scene trajectories, reserved-object targets, or rendered future images are used to train this law. The tested interpolation descriptors use scales $\pm.25$ and shapes $\pm.5$; a harder strain test extends the log-diagonal/shear ranges to $.35/.7$.

5.2. Nonlinear attachments in the static studies

The following learned law is used for static composition and descriptor refinement. For a tool with reference origin c_b, translation t_b, and rotation R_b, define

$$\delta_b(X) = x(X) - \{c_b + t_b + R_b(X - c_b)\}. \tag{15}$$

The attachment is a bilateral compliant potential, not a unilateral collision constraint. Let $r = \|\delta\|^2/\ell^2$, with $\ell = .002$m. Its learned law is

$$\psi_\theta(\delta; K, \chi, f) = \tfrac{1}{2}K\ell^2 \left[r + 2\chi \sum_{j=1}^{7} a_j(\chi, f)\phi_j(r) \right]. \tag{16}$$

The bases comprise r^2 and six functions

$$\phi_j(r) = \mathrm{softplus}(b_j + \alpha_j r) - \mathrm{softplus}(b_j) - \sigma(b_j)\alpha_j r. \tag{17}$$

A two-input, 16-unit Tanh, seven-output decoder produces positive coefficients; six slopes and six offsets are also learned. There are 179 parameters. The outer stiffness factor is K, in N/m. At $\chi = 0$ the interface is exactly quadratic. Tractions and tangents are derivatives of this scalar potential.

The analytic interface teachers use

$$\psi_* = \tfrac{1}{2}K\ell^2\{r + 2\chi[(1-f)r^2 + f(r - \log(1+r))]\}, \tag{18}$$

where $f = 0$ is polynomial and $f = 1$ is saturating in its nonlinear correction. The final wide-range checkpoint warm-starts the earlier small-slip model. Its 16384 coupons comprise equal numbers with radii up to 3ℓ and 16ℓ, and strengths $.1, .3, .5, .7, .9$. Training uses 6000 fixed Adam steps, batch 512, initial learning rate .003, final rate .0003, and gradient clipping at 1. Force and energy residuals are normalized by $K\ell + \|t_*\|$ and $K\ell^2 + |\psi_*|$, respectively, with energy weight .05. A failed wide-range random initialization remains recorded; it is not substituted into the final method.

5.3. Spatial interface fields

Attachment weights are reference-area weights multiplied by a Gaussian footprint and a smooth boundary taper, then normalized to sum to one. On normalized face coordinates $q = (q_y, q_z)$, the footprint is proportional to

$$\prod_{d=y,z} 4q_d(1-q_d) \exp\left[-\tfrac{1}{2} \sum_{d=y,z} \left(\frac{q_d - c_d}{w_d} \right)^2 \right]. \tag{19}$$

Centers c_d and log-widths $\log w_d$ are fitted in the static inverse study and supplied in the six-family dynamic study. Normalization makes K a total attachment stiffness rather than a mesh-dependent per-node constant. The weights are differentiable with respect to the centers and widths. Reactions and torques use the same integrated potential and current contact/attachment locations.

Scale ambiguity. For zero independent body load and fixed prescribed tool poses, multiplying all bulk and interface stiffnesses by $\alpha > 0$ gives $\Pi_\alpha(u) = \alpha\Pi(u)$. Consequently the stationary and minimizing sets are unchanged, while reaction forces and tangents scale by α. Position-only data cannot determine this common scale. This is a statement about a specified load model, not global identifiability. Known gravity or known-mass timed dynamics can break the symmetry. A contact term must also be co-scaled for this identity; fixed numerical contact compliance otherwise provides a relative scale.

6. Forward solver, contact and motion

6.1. Controlled Q2 discretization

In these controlled studies, the displacement field is interpolated with tensor-product quadratic hexahedral basis functions. Each element has 27 nodes, and the structured layout is $(4n, n, n)$ elements. Thus $n = 2, 3, 4, 6, 8$ correspond to 425,1225,2673,8281,18785 nodes, respectively. The parameter n is not the total number of elements per direction. Geometry maps support variations of length, width, depth, taper and arch; arbitrary topology is not inferred.

The discrete potential is

$$\Pi(u) = \sum_q w_q W_\theta(F_q, z_q) + \sum_b \sum_{q \in b} \bar{w}_q \psi_\theta(\delta_q, z_b) + \Pi_c(u) - f_g^\top u. \tag{20}$$

Reference-volume and reference-area quadrature are explicit. Static equilibria use sparse Newton iterations with a checked linear residual, descent check and Armijo backtracking. Tangents are energy derivatives. Determinants are checked at quadrature locations and element check points, including nodal locations; these sampled checks are not a global continuous-element positivity certificate. Continuation within a prescribed action improves equilibrium initialization without treating a sequence of unrelated probes as a physical dynamic trajectory.

6.2. Unilateral normal contact

For a known plane or sphere signed distance $g(x)$,

$$\Pi_c = \frac{1}{2}k_c \int_{\Gamma_0} \min(g(x), 0)^2 \, dA_0. \tag{21}$$

The surface points follow the current Q2 deformation, while the integration measure is reference area. The stiffness k_c

has units N/m^3. Contact forces and rigid-body reactions are derived from this potential and evaluated at matching positions, including the torque lever arm. The sphere-contact Hessian need not be positive semidefinite because of surface curvature. Penalty contact allows penetration; we report penetration and numerical sensitivity rather than claim exact nonpenetration. Neither friction nor adhesion is included in this controlled penalty-contact model; the separate SoftVT pose/contact adapter uses a Coulomb impulse cap.

The earlier static contact-transfer diagnostic combined both analytic teacher families and the frozen learned laws with this contact potential. Its 16 fine states yielded four passing family/method numerical qualification sets. This is evidence of composition for known descriptors and known collision geometry, not unknown-contact inference or general contact robustness. Tiny-patch sampling failures and earlier resolution failures remain in the development record.

6.3. Controlled dynamic integration

The controlled dynamic sequences use a consistent mass matrix,

$$M_{ab} = \int_{\Omega_0} \rho N_a N_b \, dV_0, \qquad M\ddot{u} = -\nabla_u \Pi(u), \quad (22)$$

and velocity Verlet: a half velocity update, position update, force recomputation, and second half velocity update. The mass matrix is factorized once. The controlled free-body scenes remove attachments exactly and have no weak reference anchor. This statement does not apply to the separately regularized external tetrahedral adapter. Gravity is a known body force. All dynamic videos sample actual integration states rather than interpolating static equilibria.

A separate finite-mass spherical striker stores center, velocity, angular velocity, mass, and spherical inertia. Its normal reaction is the opposite of that on the soft body. The current implementation is not a general rigid-scene collision engine: spherical orientation is immaterial to isotropic normal geometry, and not every rigid–rigid contact pair is supported. Momentum diagnostics use Mv, and angular momentum uses $\sum_a x_a \times (Mv)_a$.

The zero-damping drop benchmark is separate from the exploratory viscous tests. The latter use objective Kelvin–Voigt stress

$$D = \mathrm{sym}(\nabla_X v F^{-1}), \quad (23)$$

$$\sigma_v = 2\eta \,\mathrm{dev}\, D + \zeta \,\mathrm{tr}(D) I, \qquad P_v = J\sigma_v F^{-\top}, \quad (24)$$

with $\eta = 20$, $\zeta = 40$ Pa s and a velocity-dependent explicit-midpoint integrator. Its dissipated power is nonnegative:

$$\dot{D}_{\mathrm{diss}} = \int_{\Omega_0} J[2\eta \| \,\mathrm{dev}\, D\|^2 + \zeta(\mathrm{tr}\, D)^2] dV_0. \quad (25)$$

Both the material and integrator differ from the conservative control, so this is not an isolated causal damping ablation.

6.4. Earlier drop-study appearance transport

In the earlier four-world drop comparison, a canonical Gaussian is bound to a material coordinate q with offset $r = \mu_0 - X(q)$. At time t,

$$\mu_t = X(q) + u_t(q) + F_t(q) r, \qquad \Sigma_t = F_t(q) \Sigma_0 F_t(q)^\top. \quad (26)$$

The covariance is refactorized into scale and rotation for rendering. The shared initial appearance checkpoint and opacity filter are used for both methods. Opacity and spherical-harmonic coefficients remain frozen; the returned polar material rotation is not applied to the SH coefficients. Native PhysTwin uses its author transport routine with $K = 16$ neighbors, including its own scale/rotation behavior. Consequently image comparisons include both motion and transport differences. Initial canonical geometry is known, not recovered with COLMAP.

7. Inference and static transfer evidence

7.1. Fifteen continuous unknowns

The static unknown-physics experiment estimates bulk log-scale, shape and heterogeneity amplitude; left/right log-stiffness and nonlinear strength; four support-center coordinates; and four support log-widths. Geometry, material family, interface family, heterogeneity-pattern category, gravity and density are known. Therefore "15 unknown descriptors" does not mean unknown categorical discovery.

For observations y at prescribed poses, the objective combines noise-normalized position residuals and a Gaussian descriptor prior. Implicit derivatives satisfy

$$H \frac{\partial u}{\partial z} = -\frac{\partial R}{\partial z}, \qquad H = \frac{\partial R}{\partial u}. \quad (27)$$

Each parameter direction uses the same equilibrium factorization. Wrench derivatives, when used diagnostically, include both direct parameter dependence and the displacement derivative. The bounded trust-region reflective least-squares optimizer uses Jacobian scaling, a neutral initialization, at most 40 evaluations and 900s per fit. Numerical equilibrium, linear-system and tangent checks precede acceptance of derivatives. The unknown-action study uses position observations only; reaction forces are held predictions, not additional fitting observations.

7.2. Oracle composition and geometry

The withheld-composition cohort contains six objects. The geometry cohort contains six draws on two unseen geometry parameterizations of the same mapped-cuboid topology, with familiar categorical compositions; these are not six independently new geometry families. Predictions use $n = 4$, references $n = 8$, and 343 material queries. Coordinate RMSE is computed per command, then averaged over four

Method	Composition	New geometry
Matched analytic	.01642	.01590
Neo-Hookean control	.02953	.02982
Shared learned laws	.01811	.01835
Custom direct, stable 6k	3.65036	3.75043
Custom direct, stable 30k	3.08880	3.29332

Table 2. Static oracle-descriptor transfer: displacement coordinate RMSE in mm. Each column contains six objects and four held commands per object. These are not results of unknown-descriptor inference.

Shared fitted policy	Pos. mm	Force N	Cov.%
Initial observations	.33949	.09605	97.01
Fixed stretch	.08022	.02921	33.01
Target-task variance	.08022	.02921	33.01
Fixed right bend	.21633	.04278	–
Fixed opposed twist	.08347	.02851	–
Seeded random	.09732	.03429	–

Table 3. Six fresh objects, two held commands per object. Position and force use coordinate RMSE. Cov. is nominal 90% marginal position coverage for the primary local uncertainty approximation. Dashes denote values not tabulated here, not missing prediction attempts.

commands and equally over objects. The shared model is close to matched analytic mechanics in this setting (Table 2). Reference resolution was assessed in development; no per-reserved-object continuum certificate is implied.

The direct comparator is a custom DeepSets network, not a published MeshGraphNet implementation. It uses three 128-unit SiLU layers for each node/global encoder, mean and max node pooling, a displacement decoder with three 128-unit SiLU hidden layers and a linear output queried at material points, and a separate 12-output wrench head. Inputs include matched physical descriptors and frozen-law numerical fingerprints. Training uses 54 scenes with six actions each (324 records), and four validation scenes (24 records), with 125 input material nodes and 343 output queries. Its fixed 6k/30k training runs are retained.

The original direct normalization produced severe extrapolation from exactly zero training-feature columns. A separately declared stable-input control replaced only these zero-column scales by public physical units, leaving weights, targets, and nonconstant normalization unchanged. This control was motivated by training/public-input diagnosis, not selecting the best held prediction. The original results remain archived. A directory-only IO recovery later produced the stable-control artifacts after primary results had been visible; this operational history is disclosed rather than presenting a pristine single run.

7.3. Additional observation and uncertainty

The experiment observes 26 positions with 50μm coordinate noise and predicts two held command responses, using $n = 2$ inference and $n = 4$ references. It fits 48 unique models, of which 41 report optimizer success and seven retain incomplete-optimization forecasts. All 12 selected stretch refits converge. There are 144 complete scored rows across two model types, six policies, six objects and two commands.

The target-task variance policy chooses stretch on all six objects. Thus the improvement after one additional observation is real, but does not demonstrate adaptive superiority over a well-chosen fixed probe. The policy knows the target commands. Point accuracy improves while primary 90% coverage falls sharply. Adding a separately frozen, validation-derived forward-discrepancy mean-square term expands intervals and raises coverage, but this is a supplementary predictive diagnostic: it does not refit likelihoods, change the policy or prove calibration. Model discrepancy at oracle descriptors need not cover inference bias.

8. Fresh dynamic cohort and native comparison

8.1. Data and frozen fitting recipe

Four fresh synthetic worlds use the known $0.12 \times 0.06 \times 0.06$m block and 0.27kg mass. Two worlds per analytic material family are shuffled into opaque identifiers. Private scale and shape are continuously sampled; contact stiffness is sampled log-uniformly between 2×10^7 and 8×10^7 N/m^3. Calibration is a 10mm-clearance drop for 0.20s. Forecasts are 40mm and 80mm drops for 0.30s, with gravity 9.8m/s^2, zero initial velocity and no friction. The reference and our model have no physical damping; native PhysTwin fits drag and dashpot parameters. This tests load-magnitude extrapolation, not new interaction types or geometry.

Both methods receive the same 21 calibration frames at 100Hz, 98 masked surface tracks and known initial geometry/mass. These are oracle 3D tracks with visibility, not tracks reconstructed from raw RGB. Known interior geometry supplies 27 additional initial points for the native particle graph. Private family, material parameters and forecast trajectories are inaccessible to fitting. Forecasts contain 31 saved frames. All predictions are committed before scoring against future targets.

Our dynamic fitting variables are $\xi = (s, h, \log k_c)$ and a binary family candidate. Bounds are $s \in [-1, 1]$, $h \in [-2, 2]$, $k_c \in [10^7, 1.6 \times 10^8]$. The position objective is

$$L(\xi) = \frac{1}{3|\Omega|} \sum_{(t,i)\in\Omega,\ t>0} \|x_\xi(X_i, t) - y_{ti}\|^2. \qquad (28)$$

The 54-candidate catalog spans three scales, three shapes, three contact stiffnesses and two families. Only verified forward trajectories are reused; visibility-weighted losses are

World	Drop	World RMS		Shape RMS	
	mm	Ours	Native	Ours	Native
0	40	.9434	8.8154	.8581	2.4369
0	80	1.1800	19.4244	1.0652	2.8790
1	40	1.1501	8.5297	1.1296	3.2741
1	80	1.4850	17.7201	1.4616	3.7512
2	40	.9680	8.8291	.8928	2.3549
2	80	1.1510	19.3087	1.1050	2.9182
3	40	.8195	Failed	.7987	Failed
3	80	1.0098	Failed	.9623	Failed
Paired six only		1.1462	13.7712	1.0854	2.9357

Table 4. Every fresh forecast attempt. Errors are point-vector RMS in mm, with fixed surface weights; shape removes one proper rigid transformation per frame. Native coverage is6/8, ours8/8. The paired row excludes both methods' world3 scores and is conditional on three completed native fits.

recomputed separately for each world. Each family receives a 24-evaluation Powell stage at $n = 2$, followed by 32 evaluations at $n = 3$. The selected prediction uses the lowest-loss saved finite $n = 3$ candidate across both families, not necessarily the optimizer's final iterate. The inference timestep is 50μs. One of 16 optimization stages reports convergence; the other 15 are budget-limited. Nevertheless all eight selected forecasts complete. Completion is not reported as parameter convergence or parameter correctness.

8.2. Native implementation and controls

The native PhysTwin adaptation retains its spring-mass graph, optimizer and prediction routines. Development calibration selected the globally fixed 125-particle extended recipe: at most 100 CMA generations with the author implementation's early stopping, and 1000 epochs. A 729-particle capacity control was also evaluated in development using the same observed tracks and extra known initial geometry. No per-test-world recipe selection is performed. The native model has a different mechanical representation, discretization, contact parameterization and numerical dissipation; it does not receive our analytic teacher law.

The initial native orchestration failed because the child environment did not explicitly satisfy its GPU0 guard. No optimization from that failed attempt was treated as a valid result. An independently reviewed operational recovery used separate output directories and explicit environment settings, preserving the original failures, model recipe and frozen public inputs. The recovery completes three world fits and six forecasts. World 3 remains unavailable; it is not replaced by a new world or assigned an invented error.

The result is a controlled synthetic comparison to an adapted native method, not an official PhysTwin benchmark score or a broad SOTA claim. Analytic reference generation is closer to our model class than to a spring network. That advantage is part of the experimental design and limits generalization of the ranking. The native representation's scale and energy dissipation cannot be inferred from our continuum parameters alone.

World	Comparison	World	Shape	Pass
0	Calib. $n4/n6$	.2235	.1813	No
0	80mm $n4/n6$	.6162	.4198	No
1	Calib. $n4/n6$	.2028	.1897	No
1	80mm $n4/n6$	.7275	.4958	No
0	80mm $n4$ time	.00987	.00985	Yes
0	80mm $n6$ time	.02032	.02004	Yes
1	80mm $n4$ time	.01876	.01755	Yes
1	80mm $n6$ time	.02613	.02547	Yes

Table 5. All eight fixed-subset sensitivity comparisons, coordinate RMS in mm. Time compares 25 to 12.5μs. Common $6 \times 17 \times 17$ face samples and all saved frames are used. The world/shape thresholds are 0.300/0.150mm; all four spatial comparisons fail and all four temporal comparisons pass.

World	Reference	World RMS		Shape RMS	
		Ours	Native	Ours	Native
0	$n4$	1.180	19.424	1.065	2.879
0	$n6$	1.690	18.779	1.059	2.858
0	$n6$, half step	1.697	18.771	1.059	2.857
1	$n4$	1.485	17.720	1.462	3.751
1	$n6$	1.660	17.005	1.444	3.658
1	$n6$, half step	1.659	17.011	1.446	3.659

Table 6. Explicitly post-hoc secondary robustness check on the two already fixed 80mm cases. Frozen predictions are unchanged. Point-vector RMS in mm. The ranking persists, but the spatial reference failure is not thereby repaired.

9. Reference sensitivity, rendering and failures

9.1. Finite-resolution reference assessment

All 20 declared reference jobs complete and pass their individual trajectory checks. The primary generator is $n = 4$, $\Delta t = 25\mu$s. The fixed subset consists of one world from each family (worlds 0 and1), each with $n = 6$ calibration and 80mm forecast companions and half-step80mm runs at both resolutions. These are finite-resolution analytic references, not continuum ground truth.

The sampling norm in this qualification is a uniform face-sample coordinate norm, not an exact mass integral and not the 98-point benchmark weighting. Failure is retained rather than selecting an earlier passing mesh pair or relaxing thresholds. The initial sensitivity writer encountered a NumPy scalar JSON-serialization error; an additive scalar-conversion wrapper produced the report without changing any metric or selected record.

9.2. Appearance and image metrics

The same initial Gaussian appearance is fitted and frozen for both methods; no future images optimize physical predictions or appearance. The image pipeline seals all 2480 declared image slots before reference scoring: 2170 images are scored, and 310 native slots are missing and explicitly retained as failures. On the three paired completed worlds, held-image foreground-union PSNR is 18.734dB versus 12.842dB, foreground-union SSIM is .7473 versus .5770, silhouette IoU is .9562 versus .7950, and jointly visible depth RMSE is 5.478 versus 14.557mm (ours versus native). These are conditional three-world means, not an all-four paired estimate. Shared appearance reduces one source of confounding; different physical trajectories and different transport routines still contribute jointly.

9.3. Development failures and qualified scope

The abrupt 20% compressed release remains spatially unqualified even after its bounded refinement ladder. More aggressive conservative releases and drops can encounter determinant guards; their available prefixes and termination reasons are retained. Energy conservation alone does not guarantee element validity. No artificial restitution or relaxed determinant threshold was introduced to make a failed drop look successful.

A separate smooth position-controlled compression/hold/unload reaches approximately 22.7% actual end-face closure under 30% commanded tool-separation change. Its $n3/n4$ world-coordinate discrepancy is 53.2μm and the declared joint checks pass. A smaller conservative drop passes its $n6/n8$ development checks, whereas that result is not inherited by the fresh material cohort. The viscous 40mm drop and a separate viscous striker pass their timestep pair checks but remain without spatial qualification. The displayed conservative 80g striker is a single-step-size demonstration, without that temporal qualification. Static learned-contact composition has its own qualified sets. These distinct statuses must not be merged into one universal "physics validated" label.

10. Reproducibility, evidence and media

10.1. Source and artifact map

The implementation separates bulk pretraining, interface pretraining, forward mechanics, descriptor inference, and rendering. The following filenames identify the source entry points; they are not additional experimental variants.

- Bulk invariants and basis: `materials.py`; exact common-scale wrapper: `scale_separated_material.py`; final pretraining: `train_scale_separated_material.py`.
- Bilateral law: `interfaces.py`; final wide-range training: `train_interface_range_warm.py`; Q2 assembly and differentiable footprints: `mechanics.py`.
- Normal contact: `contact_mechanics.py`; dynamics: `dynamics.py`; separate viscous variant: `viscous.py`.
- Static inference: `joint_inference.py` and `gauss_newton_inference.py`; fresh dynamic inference: `cohort_shared_fit.py` and `matched_material_fit.py`.
- Gaussian material transport: `gaussian_transport.py`; appearance adaptation: `cohort_appearance_transport.py`; native-author rendering bridge: `matched_gaussian_states.py`.

The first group resides in the compositional neural-mechanics source package; the dynamic experiment and cohort orchestration reside in the compositional-dynamics source package. Earlier frozen sources and reports are preserved rather than overwritten by recovery implementations.

10.2. Evidence records

Static oracle transfer is summarized in `oracle-recovered-plus-stable-io-comparison.json`. Its completed analytic/learned oracle artifact recovery passes 3822 independent checks, and the stable-input direct control passes 3570. These checks verify recorded artifacts and calculations, not a new theoretical correctness guarantee.

The unknown-parameter experiment is summarized in `unknown-action-reaction-paper-summary.json`, with separate action and reaction audits (931 and 1734 checks). The small conditional posterior studies and their recovery histories are distinct from the 15D local uncertainty approximation. Numerical consistency of a small reference posterior does not certify the larger inferred posterior or the dynamic benchmark.

Fresh dynamic scoring is recorded in `fresh-cohort-geometry-recovery-results.json`. Its independent audit checks 2686 identities, arrays and calculations. Reference sensitivity and post-hoc ranking checks are in `fresh-cohort-reference-sensitivity.json` and `fresh-cohort-reference-robustness-posthoc.json`, with 359 and 171 independent checks, respectively. Image results and conditional paired summaries are in `fresh-cohort-appearance-results.json` and `fresh-cohort-appearance-paired-summary.json`.

Sealing and recovery. The cohort protocol and source freeze precede private-world generation. Public calibration export binds world identity, protocol identity, observation arrays and metadata. Predictor processes receive public calibration and known forecast setups, not private material labels or future target arrays. Forecast commits include completion or failure and artifact digests. Geometry scoring waits for all original and recovery prediction slots; im-

age scoring additionally waits for prediction-image commitments. Failures remain in cohort denominators. The native environment recovery, direct-baseline IO recovery and scalar serialization wrapper are operational amendments with separate records; none selects a better prediction using held targets.

Budget and precision. Constitutive derivatives and the Q2 mechanics path use float64. Resource limits terminate jobs with explicit incomplete records; optimizer iteration limits and trajectory completion are reported separately. A runtime success flag is not a convergence certificate. Shared law checkpoints are fixed during object fitting. Reproducing the full numerical evidence requires the pinned sources, checkpoints, canonical geometry, protocol files and local raw trajectory artifacts; the manuscript alone does not replace these inputs.

10.3. Video inventory and interpretation

The archived four-world dynamic comparison contains the following eight files

```
world-0-forecast-40mm-held0.mp4
world-0-forecast-80mm-held0.mp4
world-1-forecast-40mm-held0.mp4
world-1-forecast-80mm-held0.mp4
world-2-forecast-40mm-held0.mp4
world-2-forecast-80mm-held0.mp4
world-3-forecast-40mm-held0.mp4
world-3-forecast-80mm-held0.mp4
```

They use synchronized physical times and a fixed held camera. The filename world identifier is opaque and does not encode material labels. Failed native slots are explicitly indicated rather than filled with an apparently successful synthetic motion. These eight forecast clips and the four development clips below constitute the earlier twelve-clip media set; the six-family clips form a separate set described later. Reference and prediction clips display the finite-resolution benchmark, not captured real-world footage.

The four additional development clips are

```
position-compression-development.mp4
finite-striker-development.mp4
drop-bounce-settle-development.mp4
development-orbit-actual-ours-native-v2.mp4
```

These development clips are not additional held-cohort successes. Dynamic compression, drop and striker clips use sampled integrated states. No static-contact orbit clip is part of that earlier twelve-clip set. Slow playback changes presentation time, not the simulated physical timestep. Visual appeal, image fidelity and mechanical accuracy are reported separately.

10.4. Interpretation of the earlier controlled studies

The oracle study supports composition of reusable learned laws when physical descriptors are supplied. The unknown-descriptor study shows improved point predictions after an informative additional position observation, while exposing overconfident uncertainty and no advantage over its best fixed probe. The fresh dynamic study supports a conditional improvement over one native adaptation on synthetic load-magnitude extrapolation, with incomplete native coverage and unresolved spatial-reference sensitivity. These controlled findings do not themselves establish real-world transfer; the separate real-capture pilot below addresses that question on two compatible pairs. They also do not establish raw-video physical inference, unknown interaction discovery, general frictional dynamics or superior active probing.

10.5. Earlier drop-cohort appearance illustration

Figure 3 illustrates the earlier four-world drop study; the six-family experiment below uses a separate held cohort.

11. Six-family coupled-scene benchmark

11.1. Coupled-scene prediction protocol

We separate the material of an object from the interaction applied to it. A world w specifies fixed object geometry, density, and a hidden material field m_w. An interaction a specifies the initial state, prescribed fixture positions and release schedule, gravity, and collision geometry. For each world, a short calibration interaction provides point observations $\mathcal{D}_w = \{(t_i, X_j, x_{ij})\}$ up to a fixed cutoff. A method fits its material representation to this prefix, seals the fitted parameters, and predicts two different interactions without refitting. The same hidden material is retained across calibration and both queries.

The protocol contains six scene families: moving and released compliant clamps; pushing around a curved obstacle; gravity drops into a curved container, including an obstacle; a translating finite-mass rigid striker; two deformable objects in collision or stacking; and spatially heterogeneous material. Query changes include fixture location, displacement amplitude, impact velocity, drop height and orientation, and contact configuration. The frozen census is four independently sampled material worlds per family and two queries per world. Object shape and density are fixed in this study; transfer is across material and interaction, rather than unseen object geometry. The protocol, implementation inventory, model checkpoints, and development decision were fixed before generating the held worlds. Young's modulus is sampled log-uniformly from 8 to $18\,\mathrm{kPa}$ and Poisson's ratio uniformly from 0.25 to 0.40. Two-body scenes use independent material draws. Heterogeneous worlds additionally sample a log-contrast corresponding to




Figure 2. **All eight earlier drop forecasts.** Top: world and rigid-aligned shape errors for both forecast heights in each world. Bottom: held-view image metrics by world. Crosses mark unavailable native predictions in world 3; they are not zero-valued measurements. Shared appearance initialization makes the image comparison a test of predicted motion plus Gaussian transport.




Figure 3. **Earlier four-world drop cohort: reference versus predicted appearance.** First declared world, 80 mm forecast, first held camera. The same crop is computed across all methods and all 31 frames; RGB values are unchanged. Columns show 0, 0.13, 0.18 and 0.30 s. This selection is a fixed case illustration, not an aggregate result. Some objects intersect the lower edge of the original saved camera viewport: reference/ours at 0.13 s and native at 0.18/0.30 s. No pixels are extrapolated.

factors between two and three and a transition coordinate between 0.35 and 0.65. These draws remain fixed across each world's three interactions.

All methods receive the same calibration tracks, rest geometry, density, and public boundary parameters. Tracks cover a fixed two-face material-point subset and are sampled every 2 ms. This controlled track-input study does not measure image tracking errors or camera-dependent occlusion. Materials are unknown, while fixture compliance and collision geometry are known. Consequently, this experiment evaluates prediction conditional on supplied boundaries; it is not an evaluation of unknown-boundary recovery.

11.2. Shared neural material with spatial descriptors

The pretrained energy decoder is kept fixed. We infer a small spatial material descriptor from the calibration prefix. For material coordinate $X \in [0,1]^3$, the scale field is

$$s_b(X) = s_0 + \mathbf{1}_{b=2}\Delta s + c\tanh(8(X_1 - r)), \qquad (29)$$

where b indexes the deformable body. The same field parameterization is available in every family; the heterogeneous-scene label does not switch on a privileged material model. A second body receives an additional scale offset, while the spatial profile and compressibility parameter are shared. The other two pretrained descriptor coordinates are fixed at their values $(0, -1)$ in this experiment.

We extend the frozen decoder with an independent positive multiplier on its volumetric contribution. Writing W_θ for the pretrained energy, $J = \det F$, and $B_\theta(s)$ for its existing positive volumetric coefficient, the extension is

$$W_{\theta,\beta}(F,s) = W_\theta(F,s) + (e^\beta - 1)B_\theta(s)(J - \log J - 1). \qquad (30)$$

Thus $\beta = 0$ recovers the previous model exactly. The descriptor parameters are fitted by bounded derivative-free optimization of the observed point-position loss. No network weights are updated on a held world. Additional calibration stages, when selected in development, initialize from the preceding sealed best fit to the identical observation prefix. This changes the optimization budget without reading the future query. The frozen schedule permits 64 objective evaluations followed by up to 128 additional evaluations, initialized from the best calibration fit. The analytic control receives the identical schedule. The best calibration loss determines the parameters used for both queries; no query-specific parameter selection is performed. Reaching an evaluation limit is reported separately from optimizer convergence.

Predicted motion follows the coupled mechanics rollout with explicit collision geometry and compliant fixtures. The current scene model includes conservative penalty contact, separation, and translation of the rigid sphere; it does not model general rotating rigid shapes, friction, or continuous collision detection. These limits define the evaluated scene capabilities rather than being hidden in an aggregate score.

11.3. Adapted mechanics baselines

We compare with PhysTwin [2], Spring-Gaus [4], and UniPhy [3], using pinned author implementations. PhysTwin uses the author Warp spring-force kernel and native forecast integration, with per-edge stiffness fitted to the common track prefix. Spring-Gaus uses the author internal forces and integration, a scalar stiffness initialization search, and subsequent per-edge fitting. Both use known object masses and explicit common scene-boundary adapters. PhysTwin uses fixed zero dashpot and drag damping in this adapter. These are mechanics comparisons with disclosed interfaces, not reproductions of the complete author image-reconstruction pipelines. Both native spring adapters use 40 Adam iterations with learning rate 0.03 and a four-hour fitting limit. Spring-Gaus first searches a scalar stiffness initialization. Single-clamp development controls at 160 iterations improved calibration but increased vector forecast error for both adapters; these controls and their shape errors are retained alongside the selected budgets. This observation does not establish that 40 iterations is optimal for every scene. Actual successful iterations and numerical failures are reported rather than assumed from requested budgets.

UniPhy uses the released pretrained constitutive networks and native MPM, with a fitted material latent and explicit bowl/obstacle hooks. Its current adapter supports the drop family only. Its native separating-velocity projection differs from the conservative penalty contact of the reference and the other adapters; its results therefore measure this adapted system's capability, not a matched-contact-law material-inference error. Any adjoint adaptation and its derivative checks are reported separately. Unsupported configurations are retained as unsupported, rather than being counted as failures or wins. An analytic Neo-Hookean control uses the same spatial fitting parameterization but has the advantage of knowing the reference constitutive family. UniPhy uses eight fixed-seed latent-centroid initializations followed by eight AdamW iterations at learning rate 3×10^{-5}. Its derivative qualification remains coordinate-sensitive, which limits attribution of any adapted-system failure to the original method.

11.4. Physical and visual evaluation

We report full-query point-position RMS and per-object rigid-aligned shape RMS separately. Additional physical diagnostics include sampled contact penetration and first-contact time, net nongravitational body impulse, and signed tetrahedron-volume ratios on the same material grid for all methods. The impulse is computed from saved velocity and known mass after subtracting gravity; it does not resolve in-

dividual contact forces. Sampled orientation and gap checks are diagnostics, not proofs of global injectivity or continuous nonintersection.

For a controlled image comparison, every method and the reference use the same frozen Gaussian appearance, the same motion-transport map, and fixed withheld cameras. We report PSNR, SSIM, LPIPS, and silhouette IoU, averaging noninitial query frames for the primary scores and retaining all-frame values separately. This separates motion-induced image error from independent appearance optimization. The rendering is object-only and does not test environmental occlusion or native end-to-end reconstruction quality. Image agreement and physical agreement are evaluated separately; neither is inferred from the other.

Numerical reference uncertainty is assessed through spatial refinement, with dense sampled orientation checks. A completed reference trajectory is not automatically treated as spatially converged. Fitting, rollout, reference and infrastructure failures remain separately visible in the complete planned census. We average the two queries within each world, then compute paired method differences and bootstrap intervals by resampling worlds, not frames. Error comparisons conditional on successful paired worlds are accompanied by their completion and coverage counts. References use Q2 meshes with $(4n, n, n)$ cells, $n = 4$, Lobatto-4 quadrature, and a $25\,\mu$s time step. Both queries of the preselected first world in every family are repeated at $n = 6$. These twelve comparisons quantify resolution sensitivity on those worlds; they are not rigorous error bounds or a population-wide convergence certificate. Our material model and the analytic control use $n = 1$ with $50\,\mu$s steps. Native spring adapters use $25\,\mu$s steps and UniPhy uses $50\,\mu$s steps.

11.5. Held physical prediction results

Ours, the analytic control, Spring-Gaus and PhysTwin each complete all 48 held queries. Table 7 summarizes full-query motion errors, including the shared initial frame, and rigid-aligned shape errors. The paired mean motion-error difference across 24 independent worlds is -8.83 mm against PhysTwin (world-bootstrap 95% interval $[-12.18, -5.83]$) and -9.30 mm against Spring-Gaus ($[-12.40, -6.50]$). Our difference from the analytic control is $+0.13$ mm ($[-0.01, 0.27]$); this does not establish an advantage over the matched analytic family. The analytic control knows the reference constitutive family but fits its unknown material parameters from the same observed prefix.

Our mean motion error is lower than both native adaptations in each of the six families. Against the analytic control, our descriptive mean is lower for clamps/release, curved pushing, two-body interaction and heterogeneous material, and higher for drops and rigid impacts. These per-family results have four independent worlds each and should not be interpreted as universal rankings.

Table 7. Six-family held physical prediction. Motion and rigid-aligned shape RMS are in mm. Folds counts queries with any nonpositive sampled material-grid tetrahedron volume; this is a common diagnostic, not a continuous-injectivity certificate. All rows complete 48/48 queries.

Method	Motion	Shape	Folds
Ours	1.97	1.25	0
Analytic control	1.84	1.16	0
PhysTwin adaptation	10.80	5.94	33
Spring-Gaus adaptation	11.27	6.00	37

The mean net nongravitational impulse error is 0.0098 N s for ours, 0.0086 for the analytic control, 0.0500 for PhysTwin and 0.0572 for Spring-Gaus. This metric compares momentum changes after subtracting gravity; it does not identify individual contact forces. The common sampled contact diagnostic records 44 body–collider or body–body event identities per fully covered method. Ours and the analytic control have no missed or extra contacts. Spring-Gaus has two extra contacts and PhysTwin four, all in the two-body family; neither has a missed contact. Mean absolute errors in maximum sampled penetration are 2.85, 2.27, 4.37 and 4.14 mm for ours, analytic, PhysTwin and Spring-Gaus, respectively. These gaps are sampled and use the declared normalized implicit bowl geometry; they are not exact overlap distances.

UniPhy's single completed query has motion error 18.41 mm and shape error 15.69 mm. Seven supported queries fail numerically and 40 are unsupported; no complete paired world exists for a comparative claim. Eleven of twelve prospective $n = 4$ versus $n = 6$ reference comparisons complete. The refined stacking query reaches its declared time limit; its unfinished trajectory is not scored. Noninitial motion differences range from 0.027 to 0.931 mm, with the largest values in container drops. These are resolution and contact-sampling sensitivities, not error bounds. A post-hoc audit of unchanged predictions against the refined references retains five fully paired worlds: mean motion-error differences for ours minus PhysTwin and Spring-Gaus are -7.20 and -7.87 mm, respectively (compared with -7.30 and -7.95 mm against the primary references on the same subset). The analytic-control difference is $+0.20$ mm. This subset audit does not establish population-wide convergence. All primary query reference trajectories pass their declared sampled Jacobian guard, with minimum dense sampled determinant 0.272; this does not establish spatial convergence.

11.6. Held common-appearance results

Table 8 reports all 48 queries for each fully covered method. All methods transport the same Gaussian appearance us-

Table 8. Six-family held common-appearance evaluation. Foreground-union PSNR and SSIM and image LPIPS use noninitial frames. Means average the same 48 queries per row. Higher PSNR/SSIM and lower LPIPS are better.

Method	PSNR	SSIM	LPIPS
Ours	35.61	0.877	0.0101
Analytic control	36.02	0.887	0.0093
PhysTwin adaptation	25.68	0.731	0.0404
Spring-Gaus adaptation	25.88	0.721	0.0425

Table 9. Foreground PSNR by scene family (dB; eight queries each). Averages describe the frozen held cohort, not population guarantees.

Family	Ours	Analytic	Spring	PhysTwin
Clamps/release	28.78	28.96	19.91	20.06
Curved pushing	30.63	30.20	24.21	21.86
Container drop	45.37	45.83	27.78	27.82
Rigid impact	40.70	42.73	36.94	35.72
Two soft bodies	40.93	41.16	27.16	27.50
Heterogeneous	27.26	27.23	19.30	21.14

ing the same rendering pipeline; this isolates image differences induced by predicted motion and is not a comparison of native end-to-end reconstruction systems. Across 24 independent worlds, the paired foreground PSNR difference (ours minus baseline) is $+9.93$ dB against PhysTwin (world-bootstrap 95% interval $[8.24, 11.76]$) and $+9.73$ dB against Spring-Gaus ($[7.93, 11.67]$). The analytic control is slightly better: our difference is -0.41 dB ($[-0.77, -0.08]$). LPIPS differences favor ours over the two native adaptations, while favoring the analytic control over ours. These comparisons are specific to the declared adapters, observation prefixes and fitting budgets.

UniPhy completes one of eight supported drop queries; seven fail with a native CFL error. The other 40 slots are unsupported by this adapter. Because no UniPhy world completes both queries, no paired-world image comparison is reported. Its one completed query has foreground PSNR 12.24 dB; this isolated descriptive value is not comparable to the 48-query averages above.

Physical errors are reported separately in Section 11.5; reference-resolution sensitivity is reported there with its incomplete stacking case. Image fidelity alone does not establish mechanical accuracy.

11.7. Held comparison media

The six-family media set contains twelve clips: the first predefined world (world00) in every family, with both held interactions. This selection does not depend on prediction errors. Each clip shows six panels: the simulation reference, ours, the analytic control, Spring-Gaus, PhysTwin and UniPhy. Unsupported and failed slots are labeled explicitly. Complete predictions use synchronized saved physical times, the same orbiting camera and common axis limits; deformation is not amplified. Playback is 24 frames per second for states sampled every 2 ms, corresponding to approximately $20.8\times$ slow motion. These checkerboard surface visualizations expose geometry and interaction differences; they are separate from the common-Gaussian image evaluation in Tables 8 and 9. The local media filenames follow `held-{family}-world00-query{0,1}.mp4`. The accompanying audit records source trajectory hashes, movie hashes, frame counts and successful full-stream decoding for all twelve clips.




Figure 4. **Physical prediction across six interaction families.** Each panel shows the first world, query 0, final frame; error colors share a 0–20 mm scale. Dots use all eight queries per family; percentages report mean-error reduction versus PhysTwin. The footer reports all 48 queries. Ours has lower mean error than both native spring adaptations in every family; the analytic control remains competitive. The supplement shows every comparator and the earlier drop cohort.

12. Spatial error maps across all six scene families




Figure 5. **Where the predictions differ from the reference.** Every family uses its first predefined world, query 0 and final frame, without outcome-based selection. The numbers are point-vector RMS for that frame, not full-trajectory averages. All prediction surfaces use one 0–20 mm point-error scale; triangle colors average vertex errors and larger values saturate. Camera and spatial bounds are shared within each row; deformation is not amplified. Reference surfaces use a solid body color. This geometry diagnostic is separate from Gaussian image-quality evaluation. UniPhy is unsupported in five families and fails on this selected drop query; it has no completed surface to plot here.

External Datasets and Real Interactions

13. Reading the Evidence

This part records all per-sequence real-data results, all five declared transfer pairs, and all 40 fresh SoftVT episodes. It distinguishes the benchmark adapters used in the main paper from older exploratory variants. No prediction is refitted, selected per future outcome, or modified for this manuscript. The historical SoftVT illustration selected the largest improvement; the new main-paper teaser instead uses fixed declared simulation cases. Benchmark means retain every episode.

This external-dataset section studies two implementations of the material/interaction separation. The controlled simulator is specified in the preceding part. SoftVT's release model uses an analytic mechanics anchor with empirical correction. PhysTwin's current external adapter uses a frozen neural constitutive energy. There is no claim that the SoftVT gain was obtained with the neural decoder, nor that one shared checkpoint was trained across these datasets. The recent video-query reconstruction prototype is outside this work.

14. Implementation Details

14.1. Initial geometry and material field

The arbitrary-cloud FEM normalizes coordinates by the maximum initial bounding-box extent. A Delaunay tetrahedralization supplies elements; a support-distance filter removes elements bridging empty regions in nonconvex objects. The filter probes element centers and six edge midpoints, retaining probes within 0.045 normalized units of the initial support cloud. Elements with nearly zero reference determinant are excluded.

Six material kernels are selected from initial nodes by farthest-point sampling. Gaussian kernel values at element centers are normalized and volume-centered. The learned spatial scale is a linear combination of these features. Material coefficients are fitted within declared bounds. This compact field is an effective representation of the reconstructed object, not a measurement of six independently identified physical materials.

The analytic model uses Poisson ratio 0.35. The real neural adapter uses the pretrained scalar energy and a separate bounded volumetric adjustment,

$$\widetilde{W} = W_\theta + (e^\beta - 1)e^s c_v(h, f)(J - \log J - 1), \quad (31)$$

where c_v is the positive volumetric coefficient in the normalized pretrained law. The adjustment is zero at $\beta = 0$. Decoder weights are never optimized on the real evaluation sequence.

14.2. Pose and residual corrections

The inherited SoftVT pipeline distinguishes rigid pose correction from a nonrigid empirical residual. A Kabsch alignment fits the discrepancy between the mechanics anchor and the permitted observed prefix. This discrepancy is expressed in the moving controller frame and transported to subsequent attached configurations.

For the residual candidate, a normalized feature vector combines controller-relative translation and rotated gravity. Ridge regression predicts local observed-point residuals from these features. Each marker's predicted residual magnitude is capped at twice its largest prefix residual, with a small positive floor. Inverse-distance interpolation over up to six initial observed neighbors transfers residuals to mechanical nodes. A finite rigid-alignment projection removes the rigid component before applying the nonrigid correction.

The historical selector compares no correction, pose correction and residual correction with strengths 0.25, 0.5 and 1.0. Its chronological validation uses the first 70% of the available observation prefix for a separately fitted mechanics prediction and the remaining prefix for selection. Recalibration of the shortened input recomputes grasp geometry, so later validation observations do not define the fitted subprefix's attachment transform. The selected configuration is then refitted to the full permitted prefix. These corrections are empirical prediction devices, not inferred forces or constitutive laws.

The slip-aware experiment uses the frozen original mechanics/contact anchor, not a hindsight combination of whichever historical selector won a test sequence. Its eight-frame gravity-projected relative velocity and overlap threshold are fixed before the fresh 40-episode evaluation.

14.3. Reduced contact rollout

After release, node positions define a rigid body's instantaneous point distribution. The integrator updates translation and orientation under gravity and sequential static-surface impulses using ten substeps. The friction coefficient is 0.5 and restitution is zero. A position projection removes residual vertical penetration. Elastic shape and collision impulses are not jointly optimized. Consequently a successful placement prediction does not demonstrate accurate compression, friction coefficients or contact stress.

14.4. Real-data solver settings and recovery

The corrected real-data recipe uses 240 nodes, 18 prefix fitting frames and at most 50 parameter-optimization iterations, with a 1,800-second fitting budget and a 3,600-second total run budget. The ordinary equilibrium solve

allows 80 iterations. One single-lift-zebra neural rollout frame exhausted that allowance; a recorded recovery retried the unchanged warm-start state and parameters with 320 iterations. It converged in 102 iterations with residual 1.36×10^{-11} and minimum element determinant 0.714. No parameters were refitted for that recovery.

15. Metrics and Aggregation

For a frame containing N nodes, coordinate RMSE is

$$E_{\text{coord}}(t) = \sqrt{\frac{1}{3N} \sum_{i=1}^{N} \|\hat{x}_i(t) - x_i(t)\|^2}. \tag{32}$$

SoftVT reports the mean of these frame errors, then averages episodes equally. It is not the same quantity as a pooled RMS over all frames. Rigid-aligned shape error applies one best-fitting proper rigid transform per frame before scoring.

Real manual-track error averages pointwise Euclidean distances over finite annotations in each frame and then averages frames and sequences equally. Displacement error uses $\hat{x}_i(t) - \hat{x}_i(0)$ and $x_i(t) - x_i(0)$. Pair-distance-change error averages

$$\left| \left(\|\hat{x}_i^t - \hat{x}_j^t\| - \|\hat{x}_i^0 - \hat{x}_j^0\| \right) - \left(\|x_i^t - x_j^t\| - \|x_i^0 - x_j^0\| \right) \right| \tag{33}$$

over unordered annotated pairs. All three errors are geometric. Missing annotations are excluded; missing predictions are failures, not zero errors. Real transfer scores every noninitial target frame; sequence continuation uses the released test suffix.

Image metrics. A fixed crop comes from the reference foreground mask plus eight pixels of padding. Background treatment is common to all methods, and predicted spill within the crop remains penalized. PSNR uses RGB mean squared error, SSIM uses the common crop, and LPIPS uses a frozen perceptual network. Three noninitial times and three cameras produce nine images per sequence and 72 per method. Frame zero is excluded from the reported means. No image metric is reported for arbitrary unrecorded cameras because no reference RGB exists there.

16. Real-Data Protocol and Historical Results

Ordinary continuation. The eight-sequence table retains sloth, zebra and dinosaur sequences without choosing a subset where the new adapter wins. The released PhysTwin forecast is the comparator, not a retrained model with an artificially restricted fitting budget. Our 240-node neural and analytic adapters use the same external geometry recipe and prefix input contract. Differences in the physical forecasts include discretization, fitting budget and dynamics. Our image evaluation applies a common appearance transport to those forecasts; it is not a comparison of separately optimized native rendering pipelines.

Frozen transfer. The compatibility test is fixed before target-motion scoring: symmetric median initial registration distance must be below 3% of the source bounding-box diagonal, and the 95th percentile below 8%. Sloth lift-to-push and zebra one-hand-to-two-hand lift pass. The three other pairs remain in the diagnostic table, rather than being silently dropped. Identity follows the release's object names; independent confirmation of material identity and rest-state compatibility is not available.

The native frozen adaptation preserves source object springs, reconstructs target controller connections geometrically and assigns the median source controller stiffness to the new connections. Our adapter uses the registered source material field and median source attachment strength. Neither fits target motion after initialization. Initial manual-track matching is common across methods and can itself contribute an offset; this motivates reporting displacement and pair-distance-change metrics alongside absolute tracking.

Preserving the earlier best benchmark results. The development archive contains an earlier selected PhysTwin predictor with mean manual error 33.019 mm, stronger than subsequent 41.277 mm attachment-width and 43.104 mm Gaussian-residual variants. A guarded ridge-switch extension gave 37.044 mm and was not promoted. These values are retained below as historical results, not relabeled as outputs of the current neural model.

The old adapter used different masks, geometry and correction rules. In the current corrected export, a position at time t uses incoming transition validity from $t-1$, rather than the outgoing transition from t to $t+1$. We do not compare historical scores as though only one architectural component changed. The primary manuscript uses the corrected-mask neural and analytic records and gives the historical best its own provenance.

Table 10. All eight corrected-mask real sequence continuations. Mean manual-track distance in mm, lower is better. Each method completes all eight sequences. These historically exposed sequences are an exploratory benchmark, not a sealed new-object test.

Sequence	Ours, neural	Analytic	Position ridge	Released PhysTwin
single_lift_sloth	38.17	37.57	47.61	24.93
single_lift_dinosor	47.08	52.79	17.80	16.63
single_push_sloth	62.13	60.90	36.62	21.12
double_lift_sloth	34.11	34.99	29.32	28.13
double_stretch_sloth	16.01	15.17	7.89	9.75
single_lift_zebra	62.13	69.15	46.61	24.30
double_lift_zebra	34.43	32.07	25.64	31.20
double_stretch_zebra	18.04	21.66	20.84	13.08
Equal-sequence mean	39.01	40.54	29.04	21.14

Table 11. All five declared real transfer pairs, including failed initial-geometry gates. Values are full noninitial interaction tracking errors in mm. Only the two passing pairs enter the primary transfer mean.

Source	Target	Gate	Ours	Analytic	Frozen native	Persistence
single_lift_sloth	double_lift_sloth	Fail	21.50	21.71	58.97	57.77
single_lift_sloth	double_stretch_sloth	Fail	31.87	33.07	42.36	38.37
single_lift_sloth	single_push_sloth	Pass	42.78	42.73	58.23	112.55
single_lift_zebra	double_lift_zebra	Pass	35.54	39.06	31.02	45.68
single_lift_zebra	double_stretch_zebra	Fail	39.76	43.54	39.50	46.24
Two passing pairs			39.16	40.90	44.63	79.11
All five, diagnostic only			34.29	36.02	46.02	60.12

Table 12. Historical PhysTwin configurations on eight exposed sequences. Old input/export and selection protocols; these are not a matched ablation against the corrected-mask table above.

Archived configuration	Track error (mm)
Prior selected predictor	33.019
Guarded ridge-switch extension	37.044
Attachment-width primary	41.277
Always-on Gaussian residual	43.104
Original mechanics/contact anchor	43.426

17. All Fresh SoftVT Episodes

Episode	Original mechanics/contact (mm)	Ours with slip (mm)	Improvement (mm)
object-soft-task1-demo40	16.031	15.868	+0.163
spatial-soft-task1-demo40	12.417	10.148	+2.269
object-soft-task2-demo40	12.967	12.864	+0.103
spatial-soft-task2-demo40	54.241	52.756	+1.485
object-soft-task1-demo41	16.559	16.134	+0.425
spatial-soft-task1-demo41	12.579	10.170	+2.409
object-soft-task2-demo41	13.308	13.458	-0.150
spatial-soft-task2-demo41	22.623	17.402	+5.221
object-soft-task1-demo42	16.702	16.484	+0.218
spatial-soft-task1-demo42	11.770	10.384	+1.386
object-soft-task2-demo42	13.329	13.130	+0.199
spatial-soft-task2-demo42	34.385	33.711	+0.674
object-soft-task1-demo43	16.283	15.996	+0.287
spatial-soft-task1-demo43	11.082	10.194	+0.887
object-soft-task2-demo43	13.246	13.149	+0.098
spatial-soft-task2-demo43	19.793	16.415	+3.378
object-soft-task1-demo44	15.649	15.465	+0.185
spatial-soft-task1-demo44	12.240	10.044	+2.196
object-soft-task2-demo44	12.697	12.903	-0.206
spatial-soft-task2-demo44	56.061	54.759	+1.302
object-soft-task1-demo45	17.165	16.795	+0.371
spatial-soft-task1-demo45	12.437	9.369	+3.068
object-soft-task2-demo45	13.637	13.606	+0.031
spatial-soft-task2-demo45	18.151	15.140	+3.011
object-soft-task1-demo46	15.687	14.907	+0.781
spatial-soft-task1-demo46	11.847	10.493	+1.354
object-soft-task2-demo46	11.753	11.662	+0.091
spatial-soft-task2-demo46	16.481	13.610	+2.871
object-soft-task1-demo47	17.194	16.797	+0.398
spatial-soft-task1-demo47	12.460	10.403	+2.057
object-soft-task2-demo47	12.976	12.926	+0.049
spatial-soft-task2-demo47	58.251	57.654	+0.597
object-soft-task1-demo48	34.294	35.380	-1.086
spatial-soft-task1-demo48	13.020	10.851	+2.169
object-soft-task2-demo48	12.922	13.154	-0.232
spatial-soft-task2-demo48	21.727	20.391	+1.336
object-soft-task1-demo49	15.707	15.351	+0.356
spatial-soft-task1-demo49	12.651	10.698	+1.953
object-soft-task2-demo49	13.140	13.122	+0.018
spatial-soft-task2-demo49	21.828	20.851	+0.977
Equal-episode mean	18.932	17.865	+1.067

All 40 episodes and all 1,998 forecast frames are complete. Positive improvement favors ours. The four losses remain in the mean. Episode IDs 40–49 are drawn from two tasks in each of the object-soft and spatial-soft suites. These are repeated-asset episodes, not 40 distinct objects. The reported bootstrap resamples paired episodes and therefore describes this episode cohort, not unseen-object uncertainty.

18. Regression Preservation and Supporting Studies

SoftVT regression inventory. The full inventory contains 220 cases across development, historical and prospective cohorts. The robust predictor completes all 220 trajectories. The numerical fallback is triggered only by a non-finite original nodal trajectory, repairing object-soft-task2-demo31. All 179 previously finite Phase A predictions remain bitwise identical. The earlier 40 confirmation episodes include an original trajectory with missing frames; their available-frame baseline mean must not be treated as a complete paired forecast score. The main paper instead uses the later fresh 40-episode cohort where both methods have complete coverage.

19. Figure Provenance and Reproduction

Figures are generated programmatically from saved data and metrics. The historical SoftVT illustration uses spatial-soft-task2-demo41, the largest improvement among the 40 fresh episodes; it is not the new main-paper teaser. Its timestamp is 75% through the forecast suffix. Surface triangles come from the initial node convex hull solely for visualization, and the saved node positions are unchanged. The reference and predictions share world limits and camera. No deformation amplification or separate per-method alignment is applied.

The real image panel uses the first declared continuation sequence, single-lift sloth, at final frame 84 in camera 2. Any newly assembled panels retain their own selection records in the figure manifest. The new main-paper panel uses one common reference-mask crop; the archived panel displayed full images. Its appearance assets and transport policy are shared across methods. The method diagram is a schematic of coordinate roles, not generated experimental evidence. Scatter plots and bars include complete declared cohorts.

The editable source package includes precomputed vector PDF figures, so it can compile without raw datasets. Figure regeneration requires the original benchmark assets and saved predictions. A provenance manifest records the exact evaluation sources, hashes and selection rules. The original benchmark records remain unchanged. The paper build performs table checks and verifies numerical summaries without launching fitting or simulation jobs.

Claim boundaries. The work does not claim overall state-of-the-art performance on either dataset's native task, learned camera estimation, image-only material recovery, force accuracy from real captures, calibrated uncertainty, or superiority of uncertainty-guided probing. The external evidence provides a complete prospective episode test, a corrected real continuation benchmark and a limited cross-interaction transfer pilot, complementing the controlled mechanics results above. These are the claims supported by the reported artifacts.

20. Later Conditional-Flow Diagnostics

The following expansion is a separate experiment rather than a replacement for the main-paper predictors. Spatial Gaussian-boundary models use a 128-accepted-bank/256-attempt budget, 5,000 training steps and 32 posterior draws, with matched flow and mixture models and nearest-bank controls. The observation budget and geometry differ from the earlier external studies. These scores must not be substituted into their tables.

Prospective SoftVT cohort. Twelve declared cases use two suites, tasks 0–2 and episodes 50–51. Eleven physics pipelines complete; object-soft/task 1/demo 50 fails bank admission under its fixed budget. Standalone persistence, velocity and rigid/contact controls complete all twelve. On the common eleven, flow-contact coordinate/shape errors are 19.245/1.743 mm versus 19.054/1.199 mm for rigid/contact and 19.512/2.122 mm for nearest-bank contact. Flow improves retrieval slightly, not the stronger rigid control. Of 352 flow draws, 342 produce valid trajectories and ten fail; failure counts remain visible.

Eight real plush cases. All eight physics cases complete under the separate compact-geometry protocol. Flow-contact coordinate/shape errors are 37.242/19.790 mm, rigid/contact 39.776/24.635 mm, nearest-contact 37.024/18.932 mm and nearest-raw 30.794/18.932 mm. These forecast-observable scores are not the manual-track metric used by the main corrected-mask real table. Stretching improves aligned shape relative to rigid motion by roughly 25% and 46%, but nearest retrieval remains better. Four of 256 flow draws fail.

Calibration. Nominal 90% marginal coordinate intervals cover 7.02% on SoftVT and 9.15% on PhysTwin for flow-contact, conditional on successful physics cases and surviving draws. The contact/pose operation does not preserve a calibrated posterior. Coverage therefore cannot justify uncertainty-guided intervention. The earlier static additional-observation study has a related warning: improved point estimates coexist with poorer interval coverage.

Separate RGB-D bridge. A different conditional flow predicts a restricted global 25-dimensional physical code and four-way boundary/force categories from five RGB-D observations. It is not the spatial Gaussian field. Training/validation use 152/44 episodes; 76 previously exposed

Isaac episodes provide retrospective recorded-motion evaluation. Five methods complete 380 method-case predictions before target scoring. Position error is 0.754 mm for flow, 0.736 for matched mixture density, 0.694 for an archived 25D predictor, 0.730 for a chart model and 0.717 for ridge. An explicitly retrospective static control yields 0.732 mm and all five models lose to static on mean aligned-shape error. These small-motion, zero-gravity episodes do not establish accurate impact physics.

Bounded follow-up and adoption. A fixed best/final checkpoint comparison on 44 recorded validation cases produces 176 forecasts. Selecting the final flow checkpoint improves coordinate error by only 0.46% while worsening shape and parameter coverage; no new test rerun or global replacement follows. A known-parameter roundtrip uses two training-bank worlds, not new generalization tests, and retains seven failed rollouts. A no-contact elastic-continuation prototype remains qualified only on its small refinement fixture. The prior best predictors and main-paper results are preserved.

Dataset coverage. Fourteen additional PhysTwin cloth/rope/composite sequences are unsupported by the present volumetric adapter. PokeFlex recordings are not available under approved access, and Deform360 evaluation is deferred. Inventory is not execution; neither dataset is claimed as a completed benchmark here.

21. Artifact and Review Checklist

The source package includes self-contained PDF figures, all manuscript sources and the official unmodified style. Evidence manifests record the local numerical sources and their hashes without bundling raw captures, checkpoints or large trajectories. Scripts regenerate plots from those artifacts. Different metric definitions, observation budgets, known boundaries, failures and retrospective analyses remain explicit.

No submission identifier or author identity is fabricated. The manuscript and supplement require author approval and registration before submission. Anonymous review PDFs contain no identifying repository link or external content needed to understand the results. Additional media illustrate saved trajectories and are not additional independent trials.

22. Additional Visual Comparisons

The main paper highlights selected successful public-dataset predictions. The following figures retain aggregate context and a real continuation case where the native model is stronger. The public-dataset zooms use identical recorded images or unaltered simulation nodes, matched crops and explicit error annotations; no image synthesis or geometric exaggeration is used. The selected real landmark improves from 206.1 to 31.6 mm; the selected SoftVT material point improves from 18.5 to 13.6 mm. They are local illustrations, not aggregate benchmark scores.




Figure 6. **Physical and image agreement under explicit protocols.** Left: method means over the same 48 controlled queries, with fixed appearance and transport, expose motion-induced image error; this is numerical-reference agreement, not measured real-world material accuracy. Right: released PhysTwin wins the eight real continuations, while our frozen adapter has a lower mean on the two qualified changed interactions. These are different tasks and metric definitions; no cross-panel average is formed.




Figure 7. **A real continuation failure.** First declared sloth-lift sequence, final frame, camera 2; identical reference-derived crop. Both predictions use the same initial Gaussian appearance. PhysTwin follows the captured object more closely here, consistent with its advantage on the complete continuation cohort.

23. Dense Rendering with a Learned Mechanics Constraint

The coarse equilibrium adapter below loses image detail despite converged solves. We therefore test a distinct integration: retain PIDG's dense Gaussian appearance and temporal deformation map, and attach our frozen material decoder and inferred Gaussian interaction field as a soft training constraint. This experiment measures reconstruction compatibility, not the accuracy of a new-action forward rollout.

Image-connected mechanics. At 384 deterministic opacity-ranked support points, a 12-neighbor reference graph estimates the local deformation gradient by ridge-regularized least squares. Differentiating the shared material energy gives internal forces; central differences of the shared deformation map at fixed material support coordinates give velocity and acceleration. Sixteen spatial Gaussian kernels carry temporally interpolated vector loads and compliant targets, with positive stiffness and damping; each has 16 time knots. The nondimensional interaction is

$$f_i^{\mathrm{ext}}(t) = g + \sum_{k=1}^{16} \omega_k(y_i)\big[a_k(t) + \mathrm{softplus}(s_k)(c_k(t) - y_i) - \mathrm{softplus}(d_k)v_i\big],$$
$$\omega_k(y) = \frac{\exp(-\|y-\mu_k\|^2/(2\sigma^2))}{1+\sum_j \exp(-\|y-\mu_j\|^2/(2\sigma^2))}. \tag{34}$$

Here $\sigma = 0.65$ in reconstruction-normalized coordinates; fixed centers μ_k are sampled from the reference support. The body-load vector g, temporal loads a_k, targets c_k, stiffness/damping parameters and bounded scene material descriptors are optimized jointly with dense deformation and appearance, while the learned material decoder remains frozen. A fixed acceleration scale s_a from the initial reconstruction defines nondimensional units. The added loss includes $\mathrm{Huber}(\ddot{y}_i/s_a - f_i^{\mathrm{int}} - f_i^{\mathrm{ext}})$, with orientation, energy and parameter penalties. The support coordinates remain fixed while canonical Gaussian centers can be refined. Thus the mechanics term constrains the deformation network shared with rendering, but inference still queries the learned temporal map rather than integrating a contact solver.

Matched protocol. The three released scenes use 101/11/38 fitting/validation/test images for Balls Reaction and 135/15/50 for each of Rubber Duck and Motion Kuro. Each scene has a 50,000-step native base and four independent 5,000-step refinements from that same base: native PIDG and mechanics weights $10^{-5}, 10^{-4}, 10^{-3}$. Capacity, image order, optimizer restart and schedules are shared; refinement does not densify. Native velocity/stress networks are reinitialized in every refinement because upstream checkpoints omit them. Balls Reaction and Motion Kuro use fitting-only optical flow; Rubber Duck follows its released no-flow configuration. Supplied camera poses and released per-image depth are retained. All training uses 320×180 images. The largest validation foreground PSNR selects the positive-weight hybrid; checkpoint hashes are sealed before test evaluation. Balls Reaction was previously exposed in development; the other two test splits were first evaluated in this campaign. The published PIDG paper uses a different setup, so its table values are not mixed with these matched reproductions.

Table 13. **Three PIDG scenes: matched native / dense-hybrid scores.** Each cell lists PIDG first, then our hybrid. PSNR is higher-is-better; LPIPS is lower-is-better. Larger output widths use the same 320-width trained checkpoints. Foreground PSNR guards against black-background dominance. These are 138 held images from one dataset, not 138 independent physical trials.

Scene	Width	PSNR (dB)	Foreground (dB)	LPIPS
Balls Reaction	320	49.54 / 49.51	39.61 / 39.59	0.0004 / 0.0004
Balls Reaction	640	34.48 / 34.49	25.28 / 25.29	0.0086 / 0.0086
Balls Reaction	1600	31.64 / 31.66	22.41 / 22.43	0.0323 / 0.0323
Rubber Duck	320	41.82 / 41.59	32.60 / 32.36	0.0042 / 0.0044
Rubber Duck	640	33.20 / 33.17	25.50 / 25.47	0.0186 / 0.0189
Rubber Duck	1600	30.91 / 30.91	23.56 / 23.55	0.0320 / 0.0322
Motion Kuro	320	39.92 / 39.79	30.57 / 30.46	0.0075 / 0.0078
Motion Kuro	640	32.01 / 32.02	21.82 / 21.82	0.0342 / 0.0345
Motion Kuro	1600	29.59 / 29.60	19.28 / 19.29	0.0606 / 0.0606

Outcome and checks. 3 of three scenes meet the predeclared rendering-parity criterion at the training resolution: at most 0.5 dB loss in both full-image and foreground PSNR and at most 0.005 LPIPS increase. This tolerance is a practical criterion,

not a statistical equivalence test. All candidate validation scores and all test images are retained. The baseline repeat on Balls Reaction agrees with the earlier reproduction within 0.003 dB. Before optimization, adding the mechanical module preserves every pixel on all 112 fitting/validation images of Balls Reaction. Energy-gradient and internal-force conservation tests pass. Ridge regularization introduces a small discrete rotation bias (maximum tested rigid-rotation energy is 0.93% of the tested 5% stretch energy), so exact discrete objectivity is not claimed.




Figure 8. **Dense appearance retained across three scenes.** The middle declared test frame of each scene, rendered at width 640; identical reference-foreground crops, camera and error scale. Labels give full-frame PSNR. These examples illustrate visual agreement rather than new-action prediction.

Interpretation. This hybrid removes the large rendering penalty of the coarse adapter. It does not establish superior physical identification: material descriptors can approach their bounds, momentum residuals remain nonzero, and numerical neighborhood inversions are diagnostics rather than ground-truth physical errors. The scene field does not explicitly separate disconnected objects or enforce unilateral contact. Unknown mass, spatial scale and normalized frame time prevent interpreting fitted loads as calibrated SI forces. Recorded-camera reconstruction also does not quantify unobserved-camera accuracy. The following equilibrium study remains a separate diagnostic of hard mechanical coupling; its solved-state guarantees must not be transferred to this soft-constrained hybrid.

24. RGB Identification with Solver-Driven Gaussians

This qualification closes a different connection from the soft-constrained PIDG hybrid: rendered Gaussian motion is generated by integrated mechanics. We infer physical coefficients from an observed RGB prefix, freeze them, and forecast changed controls and contact without a temporal deformation network or future-frame fitting. The experiment supplies initial volume, appearance, density, cameras and floor geometry; it does not establish automatic volumetric reconstruction from arbitrary video.

Representation and observation model. A $120 \times 60 \times 60$ mm block has 225 nodes and 768 tetrahedra. Its 10,059 retained appearance Gaussians bind to containing tetrahedra. For reference center μ_i^0, shape weights N_{ia} and nodal displacement u_a, transport is

$$\mu_i(t) = \mu_i^0 + \sum_a N_{ia} u_a(t), \quad F_i = I + \sum_a u_a \otimes \nabla N_{ia}, \quad \Sigma_i(t) = F_i \Sigma_i^0 F_i^\top. \tag{35}$$

Polar rotation transports spherical-harmonic viewing directions into the material frame. Displacement-form transport preserves the initial render exactly. Surface splats outside the supplied block (36.79% of retained centers) use explicit affine extension; their centers are not interpreted as occupied material. Appearance remains fixed throughout this qualification.

Mechanics and Gaussian boundary coefficients. The frozen learned invariant-energy decoder supplies stress, with one fitted positive material scale and a fixed material-family descriptor. Eight candidate Gaussian attachment patches lie on the two end faces. Their nonnegative stiffness coefficients, one moving Gaussian target stiffness, and a mass-proportional damping rate are fitted with the material scale (11 coefficients). Gaussian integrals use lumped-volume quadrature, and floor contact uses surface-area quadrature. Gravity, density $625\,\mathrm{kg/m^3}$, prescribed target paths, and release times are supplied. The moving target is a compliant distributed interaction, not a unilateral rigid poker. Symplectic Euler integrates the dynamics at 0.1 ms for forecasting. Floor and reciprocal two-body contact use finite penalties; this experiment includes neither friction nor continuous collision detection.

Calibration and controls. An independent analytic Mooney–Rivlin model generates the numerical reference. Only images from the first 0.14 s in two cameras are available for fitting; two other cameras are withheld. The 144 prefix images include reserved calibration validation images. No material, force, interior-position or future-image labels enter the successful RGB fit. A generic 54-proposal bank spans material scale, either support face, total attachment stiffness and target stiffness. Fitting-image RGB scores initialize 80 differentiable rollout updates; reserved foreground PSNR selects the checkpoint. The matched analytic control replaces the frozen learned law with neo-Hookean energy and receives the same bank and refinement budgets. Calibration is iterative; subsequent prediction uses frozen coefficients and forward integration only.

A separate diagnostic first reconstructs nodal motion from images and then solves linear inverse dynamics. Despite good image fits, its unobserved interior accelerations are unsuitable for force identification, and the resulting calibration scores are approximately 20 dB. The proposal-bank initialization avoids this failure. Reserved foreground PSNR reaches 52.01 dB for solver-driven learned mechanics and 48.77 dB for the analytic control. Fixed-appearance temporal-network adaptations reach 37.07 dB (released PIDG deformation/TV architecture) and 38.13 dB (dense soft constraint). These adaptations do not reproduce PIDG's complete momentum/flow training recipe; their scores are not substitutes for the public-scene comparison above.

Frozen forecasts. All six cases complete. Five single-object cases cover continuation, lateral target motion, earlier release, an added calibrated force, and a 35 mm higher drop. A sixth case releases two independently moving deformable instances with the inferred material reused for the second body. Metrics use times after 0.14 s; image scores average equally sampled times and two withheld cameras. Foreground-union PSNR includes pixels occupied by either reference or prediction, penalizing misplaced geometry. Single-object mean position RMS is 0.691 mm versus 2.174 mm for the analytic control. The two-body contact implementation conserves reciprocal contact force to numerical precision; sampled maximum pair penetration is 0.664 mm for ours, distinct from trajectory error.

Table 14. **Complete controlled forecast results.** Each cell is ours / analytic. Position and rigid-aligned shape RMS are lower-is-better; novel-view union-foreground PSNR is higher-is-better. Six scenarios share one block geometry/material, so they are not independent dataset samples.

Scenario	Position (mm)	Shape (mm)	Novel PSNR (dB)
Continuation	0.413 / 1.739	0.141 / 0.457	36.18 / 23.54
Side poke	1.857 / 3.305	0.363 / 0.557	30.03 / 21.06
Early release	0.331 / 2.154	0.215 / 0.589	36.34 / 23.87
Force pulse	0.452 / 1.998	0.158 / 0.466	35.38 / 23.01
Higher drop	0.402 / 1.675	0.126 / 0.379	35.84 / 23.37
Two objects	1.417 / 2.236	0.574 / 1.398	26.67 / 21.14




Figure 9. **Mechanics drives appearance under changed actions and two-object contact.** Saved predictions at the declared 0.24 s frame, from a withheld camera; each row uses one shared reference-derived crop. Labels report complete forecast-interval motion error, not single-frame error. No per-method alignment or deformation exaggeration is applied. The floor participates in physics but is omitted from the body-only renderer.

An observable action resolves an invisible scale. If density is unknown, multiplying mass, material energy, attachment stiffness, position-controlled target stiffness and contact penalty by the same factor leaves gravity/position-driven trajectories unchanged. We construct two hypotheses at factors one and two. Their calibration and lateral-target trajectories agree to numerical precision; a withheld-camera RGB comparison is exactly identical. A new view therefore cannot resolve this particular ambiguity. Before reading probe targets, prediction disagreement selects a calibrated force pulse over the position-controlled alternative. One RGB observation at $0.08\,\mathrm{s}$ in camera 0 selects the closer hypothesis. On a separate reversed-force action, position error falls from $1.120\,\mathrm{mm}$ for the equal-prior mean to $0.448\,\mathrm{mm}$ for the selected hypothesis; the other hypothesis gives $2.341\,\mathrm{mm}$. This is a constructed two-hypothesis observability test, not a calibrated posterior or a general active-policy superiority claim.




Figure 10. **Physical prediction, rendering and information are tested separately.** Left and center: all six forecast scenarios. Right: a force probe resolves a mass/stiffness ambiguity that camera changes cannot resolve; evaluation uses a different force from the selected probe.

Numerical qualification and limits. Identity/affine transport, internal-force conservation, energy derivatives and gradients through integration pass component tests. A full rasterizer-to-material gradient check agrees with finite differences within 5.5% at the smallest tested perturbation; larger perturbations differ by up to 20%, reflecting the sensitivity of this piecewise rendering check. Reference refinement from $8 \times 4 \times 4$ to $16 \times 8 \times 8$ cells changes position by about $1.3\,\mathrm{mm}$; refinement to $32 \times 16 \times 16$ reduces the change to $0.76/0.61\,\mathrm{mm}$ for continuation/higher drop. Halving the reference time step changes these trajectories by only $0.014/0.016\,\mathrm{mm}$. Small submillimeter differences therefore should not be interpreted as mesh-independent physical truth. The reference and predictors share a discretization family, and the learned law has a compatible invariant basis; this is a controlled coupling test rather than broad constitutive discovery. General RGB-only geometry/mass inference, unknown control histories, heterogeneous second objects, and calibrated uncertainty remain outside this qualification. Earlier public-data and six-family physical studies remain separate evidence.

25. Earlier Coarse Equilibrium Adapter on PIDG

This earlier diagnostic separates appearance initialization from hard mechanical coupling; it is distinct from the dense soft-constrained hybrid above. It uses the public synthetic *Balls Reaction* scene of PIDG [1]. It is an equilibrium reconstruction adapter, not the transient coupled-contact experiment in the main paper. It does not establish material identification from RGB, causal prediction of a new action, or quantitative accuracy at unrecorded cameras.

Observed inputs and physical hypotheses. We retain the declared 101 fitting, 11 validation and 38 test images, with supplied camera poses and a common frame-index clock. A fitting-only PIDG reconstruction initializes the radius/depth gauge. Connected color regions in the fitting images supply object-position and apparent-shape observations. Six separately represented, approximately spherical objects are an explicit initialization prior. Each object has 13 mechanical nodes, 20 tetrahedra and six localized Gaussian attachment footprints. The attachment targets are inferred position controls, not observed real grippers. The shared learned material decoder is frozen. Material descriptors are inherited from the initial image/mechanics fit and held fixed during the appearance-transfer refinement. Gravity is negligible under the unidentified physical scale, and this adapter does not solve coupled inter-object collisions.

Connected inference and rendering. For physical parameters η and inferred boundary targets b, equilibrium satisfies $r(x;\eta,b)=0$. Differentiating an image loss L uses

$$H^\top\lambda=\frac{\partial L}{\partial x},\qquad \frac{dL}{d(\eta,b)}=-\lambda^\top\frac{\partial r}{\partial(\eta,b)},\quad H=\frac{\partial r}{\partial x}. \tag{36}$$

The renderer therefore updates a solved physical state rather than an unconstrained deformation MLP. All 228 held-image object equilibria converge with residual below 9.73×10^{-8}; the minimum tetrahedral Jacobian is 0.868. These numerical checks do not establish correct contact or material identification. Gaussian centers use fixed material-coordinate bindings, covariance follows $\Sigma_t=F_t\Sigma_0F_t^\top$, and view directions are pulled into the material rotation frame for spherical-harmonic radiance. The boundary adjoint agrees with finite differences, and the binding passes affine-position and covariance tests. The earlier sparse-appearance adapter used 4,608 newly initialized Gaussians and achieved only 25.59 dB test PSNR at 320×180 despite converged mechanical states. This motivates retaining fitted appearance instead of conflating its initialization error with a constitutive-model comparison.

Appearance-preserving reference binding. We transfer all 50,524 fitted Gaussian centers, full covariances, opacities and spherical-harmonic coefficients from the matched local PIDG reconstruction at the first fitting frame. At the renderer-conversion stage, RGB RMSE against the original render is 1.55×10^{-8} and both renders have 56.33 dB PSNR on that fitting image. This is a conversion check, not a test-set result. The covariance calculation matches the released rasterizer's unnormalized-quaternion convention; silently normalizing those quaternions changes the image. Material bindings use the physical state at that reference frame, including explicitly disclosed affine extrapolation outside the coarse tetrahedral mesh. Fitted appearance does not supply ground-truth hidden geometry.

Selection and interpretation. Appearance refinement and boundary refinement use only fitting RGB. Temporal controls include global pose/scale and six independently translated Gaussian boundary patches per object; joint fitting is followed by appearance-only refinement with mechanics fixed. Checkpoint selection uses validation foreground PSNR. A validation-only radiance ablation favors material-frame over world-frame directions. All candidate runs are retained. A checkpoint audit found that appearance-only regularization had changed controls behind cached geometry. Restoring the exact controls used to build that cache recovers identical live validation scores; the corrected optimizer freezes those controls explicitly. The invalid evaluation is retained in the artifact audit and excluded from the reported table. Canonical Gaussian offsets and covariance-scale corrections are bounded. PIDG is used for appearance initialization, so this is a reconstruction-assisted comparison rather than an independently initialized competitor. This released test split has also been evaluated in earlier development; it is not a newly collected confirmatory cohort. All methods are trained at 320×180; rendering at a larger resolution is not retraining at that resolution. The original paper's 33.31 dB Balls Reaction score is reported under a different training setup and is not substituted for our matched baseline.

Measured reconstruction results. Table 15 reports all 38 test images. Transferring appearance and refining boundary targets improves the connected model, while the unconstrained PIDG reconstruction remains stronger on recorded cameras. Larger output images use the same 320×180 training. These are held-image reconstruction scores, not forecasts of a new force.

Table 15. **PIDG Balls Reaction, matched image split.** Full-image / foreground PSNR (dB; higher is better), SSIM (higher) and AlexNet LPIPS (lower). The transferred model uses PIDG appearance initialization.

Output width	Method	PSNR	FG PSNR	SSIM	LPIPS
320	PIDG	49.54	39.62	0.9987	0.0004
320	Ours: coarse appearance	25.59	19.81	0.9210	0.0827
320	Ours: transferred appearance	31.43	22.89	0.9710	0.0245
640	PIDG	34.48	25.28	0.9845	0.0086
640	Ours: coarse appearance	25.50	19.28	0.9242	0.0823
640	Ours: transferred appearance	29.86	20.83	0.9549	0.0442
1600	PIDG	31.64	22.41	0.9712	0.0323
1600	Ours: coarse appearance	25.40	19.01	0.9335	0.0896
1600	Ours: transferred appearance	28.68	19.35	0.9473	0.0662




Figure 11. **Image loss reaches the physical state.** Boundary controls update solved equilibrium through an implicit adjoint. Appearance-only refinement then holds the selected mechanics fixed; query-time images use mechanics-transported Gaussians.




Figure 12. **Aggregate recorded-camera reconstruction at width 640.** Foreground scores prevent the black background from dominating interpretation. Native PIDG remains ahead; the transferred mechanical renderer improves on its previous coarse initialization.




Figure 13. **Appearance refinement and camera sweep.** The middle declared test time is fixed in advance. Top: identical reference-derived crop and per-frame full-image PSNR. Bottom: fixed camera offsets, with no reference RGB at nonzero angles. The spherical geometry prior contributes to coherence; these views do not prove hidden-surface accuracy or material identification.

References

[1] Haoqin Hong, Ding Fan, Fubin Dou, Zhi-Li Zhou, Haoran Sun, Congcong Zhu, and Jingrun Chen. Physics-informed deformable gaussian splatting: Towards unified constitutive laws for time-evolving material field. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pages 4725–4733, 2026. 28

[2] Hanxiao Jiang, Hao-Yu Hsu, Kaifeng Zhang, Hsin-Ni Yu, Shenlong Wang, and Yunzhu Li. PhysTwin: Physics-informed reconstruction and simulation of deformable objects from videos. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2025. 11

[3] Himangi Mittal, Peiye Zhuang, Hsin-Ying Lee, and Shubham Tulsiani. UniPhy: Learning a unified constitutive model for inverse physics simulation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2025. 11

[4] Licheng Zhong, Hong-Xing Yu, Jiajun Wu, and Yunzhu Li. Reconstruction and simulation of elastic objects with spring-mass 3D gaussians. In *European Conference on Computer Vision*, 2024. 11