

Butt Joint Adhesive 3341



With high adhesive strength, transparent drying, specifically for the TL Decorative Moldings

Field of application

For permanent gluing of butt joints, specifically for mounting Decorative Moldings TL 3040.

Properties

- Ensures perfect joints between the TL Decorative Moldings (TuneLight)
- Very high adhesive strength
- Permanent connection of joint areas
- Dries transparent
- Solvent-free

Material description

Color shade	milky-transparent
Density	approx. 1.15 g/cm ³
Packaging	310 ml cartridge (approx. 525 g per cartridge)

Use

Substrate preparation	The substrate must be dry, clean, and free from separating agents or other intermediate layers affecting adhesion.
Application	Butt Joint Adhesive 3341 must be used when gluing Decorative Moldings TL 3040 in butt joints. Apply an adequate but controlled amount of Butt Joint Adhesive 3341 with the caulking gun, only onto the butt joints and miter cuts of the TL Decorative Moldings so that the profile joints are completely moistened after pressure has been applied. Any emerging glue can, as required, be removed immediately using Quick-acting Brush Cleaner 111. Fill all connection and miter joints with the Decorative Molding Adhesive 3041, as required, and smooth it with a spatula. Follow the instructions in the "Decorative Moldings 3040" Data Sheet.

Use	
Open time (+20°C, 65 % r. h.)	Approx. 30 minutes. Perform remedial work on the butt joints in this period.
Consumption	Approx. 8–10 ml/joint (corresponds to approx. 30–40 joints per cartridge). The quantity of adhesive used depends on the decorative molding format. Determine the exact consumption by means of a test application on the object to be coated.
Application temperature	Do not apply if air or object temperature is below +10 °C.
Tool cleaning	Immediately after use, with Quick-acting Brush Cleaner 111.
Drying (+20°C, 65% relative humidity)	
	The adhesive solidifies on pressed connections as quickly as approx. 3 hours following application. After approx. 12 hours it is completely dry. The drying time depends on the layer thickness. Allow longer drying times at lower temperatures and/or higher air humidity.
Storage	
	Cool and frost-free. Reseal opened containers tightly.
Declaration	
Product code	Not assigned Comply with the specifications in the current Safety Data Sheet.
Notes	
Further information	Read and follow the instructions in the Data Sheets of the products to be used.
Remark	
	<p>This Data Sheet is based on extensive development work and years of practical experience. The translation corresponds to the current German version, in compliance with the German laws, regulations, standards and guidelines. Its content does not constitute a contractual legal relationship. The user/buyer is not released from the responsibility of checking our products to ensure they are suitable for the intended application. In addition, our general terms of business apply.</p> <p>When a new version of this Data Sheet with updated information is published, the previous version no longer applies. The current version is available on our website.</p> <p>Brillux Weseler Straße 401 48163 Münster GERMANY Phone +49 251 7188-0 Fax +49 251 7188-105 info@brillux.de www.brillux.com</p>