

Floortec Thixofix 837

Special thixotropic agent, easy to mix and stir in,
for increased stability



Field of application

As an additive in Floortec epoxy and polyurethane resin coatings, to control flow characteristics. Increases the stability of the coatings, for use on vertical surfaces in the balcony coating system.

Properties

- Ready to use
- In powder form
- Easy to stir in
- Non-coagulating
- Resistant to aging, weather and light
- Easy to apply

Material description

Color shade	White
Base material	Highly dispersed silicic acid
Density	Approx. 0.60 g/cm ³ , at 20°C
Packaging	5 l

Use	
Mixing ratio	Approx. 0.5-1.0 liter (30–60 g) of Floortec Thixofix 837 per 1 liter of coating material. The quantity to be added varies according to the area of application and depends on the material used and the stipulated field of application. Stir and mix in thoroughly.
Compatibility	Only mix with the specified materials in the appropriate mixing ratio.
Mixing	First mix the respective balcony coating in accordance with the application instructions. Mix Floortec Thixofix 837 in the required amount into the homogenously mixed mass intensively. Quickly apply the mixed coating in a uniform layer thickness using a brush or roller.
Consumption	Approx. 0.5-1.0 liter (30–60 g) per 1 liter of coating material. Determine exact consumption by means of a test application on the object to be coated.
Tool cleaning	Clean with Special Synthetic Resin Thinner 915 or Quick-acting Brush Cleaner 111 immediately after use.

Storage	
	Store in a cool, dry, and frost-free place. Can be stored for 24 months in the unopened container. Reseal opened containers tightly.

Declaration	
Product code	Not assigned. Comply with the specifications in the current Safety Data Sheet.

Notes	
Carefully pour in the material	Carefully pour in the coating material in an area with no wind. The material is very light and is scattered rapidly by the wind.
Reduces application time	The addition of Floortec Thixofix 837 reduces the open time.
Further information	Follow the instructions in the data sheets of the products used.

Remark	
	<p>This Data Sheet is based on extensive development work and years of practical experience. The translation corresponds to the current German version, in compliance with the German laws, regulations, standards and guidelines. Its content does not constitute a contractual legal relationship. The user/buyer is not released from the responsibility of checking our products to ensure they are suitable for the intended application. In addition, our general terms of business apply.</p> <p>When a new version of this Data Sheet with updated information is published, the previous version no longer applies. The current version is available on our website.</p> <p>Brillux Weseler Straße 401 48163 Münster GERMANY Phone +49 251 7188-0 Fax +49 251 7188-105 info@brillux.de www.brillux.com</p>