# **Data Sheet**

# 2K-Durapur Hardener 7770

Brillux

2K-Durapur
Härter 7770

3K-Durapur Hardener 7770

16 br. K. Obrapur-Landan

15 Tot Computed Obrapur points

special PUR hardener for 2K-Durapur 7740 and 2K-Durapur 7741

## Field of application

To be mixed with 2K-Durapur 7740 and 2K-Durapur 7741.

# **Properties**

Special system hardener. The container sizes reflect the mixing ratio.

### **Material description**

Color shade Colorless

Base material Aliphatic polyisocyanate

Flash point > +61°C

Density Approx. 1.09–1.13 g/cm<sup>3</sup>

Packaging 125 ml of hardener for 625 ml of base material

400 ml of hardener for 2.0 l of base material 1.5 l of hardener for 7.5 l of base material

(Base enamel and hardener are supplied separately)

## Use

Mixing Before adding the hardener, thoroughly stir until even. Mix the base

component and hardener in the specified mixing ratio shortly before application. Ensure that the hardener container is completely emptied without residue. Follow the instructions in 2K-Durapur 7740 and 2K-

Durapur 7741 data sheets.

**Compatibility** Can only be mixed with materials specified in this data sheet.

**Application temperature** Do not apply at temperatures below +5°C or above a max. of +25°C air,

substrate and material temperature. Take the dew point temperature into consideration. Do not apply unless the temperature is at least 3°C

above the dew point.



Use

Tool cleaning Clean tools with water and wetting agent immediately after use.

Storage

Store in a cool, dry and frost-free place. Reseal opened containers tightly. Turn opened containers upside down (risk of thickening).

Declaration

Product code PU50

Comply with the specifications in the current safety data sheet.

**Notes** 

**Further information** Follow the instructions on the data sheets of the products used.

Remark

This data sheet is based on extensive development work and years of practical experience. The translation corresponds to the current German version, in compliance with the German laws, regulations, standards and guidelines. Its content does not constitute a contractual legal relationship. The user/buyer is not released from the responsibility of checking our products to ensure they are suitable for the intended application. In addition, our general terms of business apply.

When a new version of this data sheet with updated information is published, the previous version no longer applies. The current version is available on our website.

Brillux Weseler Straße 401 48163 Münster GERMANY Phone +49 251 7188-0 Fax +49 251 7188-105 info@brillux.de www.brillux.com

