according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Fondosil 1903 **Revision date :** 09.08.2021

Revision date : 09.08.2021 **Version (Revision) :** 2.0.1 (2.0.0) **Print date :** 09.08.2021

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Fondosil 1903

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Products Category [PC]

PC9 - Coatings and paints, fillers, putties, thinners

Uses advised against

There are no information about relevant identified uses of the product according to the Regulation (EC) No. 1907/2006 (REACH-Regulation), which are advised against. For using the product observe the information in the Technical data sheet of the product.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Brillux GmbH & Co KG www.brillux.de

Street: Weseler Straße 401

Postal code/city: D - 48163 Münster

Telephone: +49 (0)251-7188-0 **Telefax:** +49 (0)251-7188-280 **Information contact:**

Electronic mail address of the well-informed person for safety data sheets:sdb@brillux.de

1.4 Emergency telephone number

Outside the business hours (9 a.m. to 5 p.m.):

(Giftinformationszentrum-Nord, Göttingen, consultation in german or english language)

Telephone: +49 (0)551-19240.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Eye Irrit. 2; H319 - Serious eye damage/eye irritation: Category 2; Causes serious eye irritation. Skin Irrit. 2; H315 - Skin corrosion/irritation: Category 2; Causes skin irritation.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Exclamation mark (GHS07)

Signal word

Warning

Hazard statements

H315 Causes skin irritation. H319 Causes serious eye irritation.

Precautionary statements

P102 Keep out of reach of children.

Page: 1 / 11

according to Regulation (EC) No. 1907/2006 (REACH)



Fondosil 1903 Trade name:

09.08.2021 **Revision date:** Version (Revision): 2.0.1 (2.0.0)

Print date: 09.08.2021

> P280 Wear protective gloves/protective clothing/eye protection/face protection.

P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P501 Dispose of contents/container to approved disposal company or local collection.

2.3 Other hazards

Adverse environmental effects

The product does not contain any substances, which fulfil the criteria for PBT or vPvB in accordance with the Annex XIII of the Regulation (EC) No 1907/2006 (REACH-Regulation).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description

Silicate paint;

Composition:

Potassium water glass, styrene-acrylic-copolymer dispersion, water and addditives.

Hazardous ingredients

 $SILICID \ ACID, \ POTASSIUM \ SALT, \ MVZ > 3,2 \ ; \ REACH \ No. : 01-2119456888-17 \ ; \ EC \ No. : 215-199-1; \ CAS \ No. : 1312-76-1 \ ACID, \ POTASSIUM \ SALT, \ MVZ > 3,2 \ ; \ REACH \ No. : 01-2119456888-17 \ ; \ EC \ No. : 215-199-1; \ CAS \ No. : 1312-76-1 \ ACID, \ POTASSIUM \ SALT, \ MVZ > 3,2 \ ; \ REACH \ No. : 01-2119456888-17 \ ; \ EC \ No. : 215-199-1; \ CAS \ No. : 1312-76-1 \ ACID, \ POTASSIUM \ SALT, \ MVZ > 3,2 \ ; \ REACH \ No. : 01-2119456888-17 \ ; \ EC \ No. : 215-199-1; \ CAS \ No. : 1312-76-1 \ ACID, \ No$

≥ 5 - < 10 % Weight fraction:

Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 Classification 1272/2008 [CLP]:

POTASSIUM METHYL SILICONATE; REACH No.: 01-2119517439-34; EC No.: 250-807-9; CAS No.: 31795-24-1

Weight fraction: ≥ 1 - < 3 %

Classification 1272/2008 [CLP]: Skin Corr. 1A; H314 Eye Dam. 1; H318

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Immediately remove all contaminated clothing. If unconscious no administration by mouth, storage in recovery position and seek medical advice. If medical advice is needed, have product container or label at hand.

Following inhalation

When symptoms persists, take the casualty into the fresh air and keep warm. Irregular breathing/no breathing: artificial respiration.

In case of skin contact

Take off immediately all contaminated clothes. Wash away with soap and water and rinse. Do NOT use solvents or thinners. If skin irritation continues, consult a doctor.

After eye contact

Remove contact lenses, keep eyelids open. Rinse open eye immediately with plenty of running water. Seek medical adivce if complaint continues.

After ingestion

Drink water in small draught. Keep at rest. Do not induce vomiting. When swallowed immediately consult and show packing or label to physician.

4.2 Most important symptoms and effects, both acute and delayed

Potential symptoms: Skin and eye iriitation are possible.

4.3 Indication of any immediate medical attention and special treatment needed

Page: 2 / 11

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Fondosil 1903

Revision date : 09.08.2021 **Version (Revision) :** 2.0.1 (2.0.0)

Print date : 09.08.2021

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

This product is not flammable. In case of a fire extingnish surroundings as indicated.

Unsuitable extinguishing media

None known.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters

When extinguishing fires, use breathing apparatus with an independent source of air.

5.4 Additional information

Cool endangered containers with water in case of fire. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Refer to protective measures listed in sections 7 and 8. The product produced in combination with water slippery surfaces.

6.2 Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations. Holding polluted washing water back and disposing of duly.

6.3 Methods and material for containment and cleaning up

For cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Remove residue by rinsing thoroughly with water. Thoroughly clean contaminated objects and floors and observe environmental regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

You find information about the safety equipment of persons in the section 8,

information about the refuse disposal in section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

No special measures necessary in the case of regulation storage and handling. Ensure a good ventilation in room and working area. For personal protection see Section 8. Read label before use.

Measures to prevent fire

This product is not flammable. Cool endangered containers with water.

Advices on general occupational hygiene

While working do not eat , drink or smoke. Wash hands and face before breaks and after work and take a shower if necessary. Immediately remove all contaminated clothing.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Page: 3 / 11

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Fondosil 1903

Revision date : 09.08.2021 **Version (Revision) :** 2.0.1 (2.0.0)

Print date : 09.08.2021

Keep container tightly in a dry, cool and good ventilated place. Do not store the product in lounge room. Keep only in the original container. Protect against frost. Keep out of the reach of children.

Hints on joint storage

Store away from foodstuffs. **Storage class (TRGS 510):** 12

Further information on storage conditions

Keep container tightly sealed. Store at 5°-35°C. Containers should be kept dry and sealed.

7.3 Specific end use(s)

For using the product observe the information in the Technical data sheet of the product.

Industrial sector specific solutions

GISCODE: Product code in accordance with GISBAU (hazardous materials information system of the German professional associations of the building and construction industry) for colours and varnishes (GISCODE): BSW60

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

DNEL-/PNEC-values

DNEL/DMEL

Limit value type : DNEL/DMEL (Consumer) (SILICID ACID, POTASSIUM SALT, MVZ > 3,2 ; CAS No. :

1312-76-1)

Exposure route: Dermal
Exposure frequency: Long-term
Limit value: 0,74 mg/kg

Limit value type: DNEL/DMEL (Consumer) (SILICID ACID, POTASSIUM SALT, MVZ > 3,2; CAS No. :

1312-76-1)

Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 1,38 mg/m³

1312-76-1)

Exposure route: Oral
Exposure frequency: Long-term
Limit value: 0,74 mg/kg

Limit value type: DNEL/DMEL (Worker) (SILICID ACID, POTASSIUM SALT, MVZ > 3,2; CAS No.: 1312-

76-1)

Exposure route: Dermal
Exposure frequency: Long-term
Limit value: 1,49 mg/kg

Limit value type : DNEL/DMEL (Worker) (SILICID ACID, POTASSIUM SALT, MVZ > 3,2 ; CAS No. : 1312-

76-1)

Exposure route: Inhalation
Exposure frequency: Long-term
Limit value: 5,61 mg/m³

Limit value type: DNEL Consumer (systemic) (POTASSIUM METHYL SILICONATE ; CAS No. : 31795-24-1

.

Exposure route:

Cral
Exposure frequency:

Limit value:

O,42 mg/kg
Safety factor:

1 D

Limit value type: DNEL Consumer (systemic) (POTASSIUM METHYL SILICONATE ; CAS No. : 31795-24-1

)

Exposure route: Dermal
Exposure frequency: Short-term
Limit value: 4 mg/kg
Safety factor: 1 D

Page: 4 / 11

(EN/D)

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Fondosil 1903

Revision date: 09.08.2021 **Version (Revision):** 2.0.1 (2.0.0)

Print date : 09.08.2021

Limit value type : DNEL Consumer (systemic) (POTASSIUM METHYL SILICONATE ; CAS No. : 31795-24-1

)

Exposure route: Dermal
Exposure frequency: Long-term
Limit value: 4 mg/kg
Safety factor: 1 D

Limit value type : DNEL Consumer (systemic) (POTASSIUM METHYL SILICONATE ; CAS No. : 31795-24-1

)

 $\begin{array}{ll} \mbox{Exposure route:} & \mbox{Inhalation} \\ \mbox{Exposure frequency:} & \mbox{Short-term} \\ \mbox{Limit value:} & \mbox{10 mg/m}^3 \\ \end{array}$

Limit value type: DNEL Consumer (systemic) (POTASSIUM METHYL SILICONATE ; CAS No. : 31795-24-1

)

Exposure route: Inhalation
Exposure frequency: Long-term
Limit value: 10 mg/m³

Limit value type: DNEL worker (systemic) (POTASSIUM METHYL SILICONATE ; CAS No. : 31795-24-1)

Exposure route: Dermal
Exposure frequency: Short-term
Limit value: 6,6 mg/kg
Safety factor: 1 D

Limit value type : DNEL worker (systemic) (POTASSIUM METHYL SILICONATE ; CAS No. : 31795-24-1)

Exposure route: Dermal
Exposure frequency: Long-term
Limit value: 6,6 mg/kg
Safety factor: 1 D

Limit value type: DNEL worker (systemic) (POTASSIUM METHYL SILICONATE ; CAS No. : 31795-24-1)

Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 47 mg/m³

Limit value type: DNEL worker (systemic) (POTASSIUM METHYL SILICONATE ; CAS No. : 31795-24-1)

Exposure route: Inhalation
Exposure frequency: Long-term
Limit value: 47 mg/m³

PNEC

Limit value type : PNEC (Aquatic, freshwater) (SILICID ACID, POTASSIUM SALT, MVZ > 3,2 ; CAS No. :

1312-76-1)

Exposure route : Water (Including sewage plant)

Limit value : 7,5 mg/l

Limit value type : PNEC (Aquatic, freshwater) (POTASSIUM METHYL SILICONATE ; CAS No. : 31795-24-1

)

Limit value : 4,2 mg/l

Limit value type : PNEC (Aquatic, intermittent release) (POTASSIUM METHYL SILICONATE ; CAS No. :

31795-24-1)

Limit value : 42 mg/l

Limit value type: PNEC (Aquatic, marine water) (POTASSIUM METHYL SILICONATE ; CAS No. : 31795-

24-1)

Limit value: 0,42 mg/l

Limit value type: PNEC (Sediment, freshwater) (POTASSIUM METHYL SILICONATE; CAS No.: 31795-24-

1)

Limit value : 3,3 mg/kg

Limit value type : PNEC (Sediment, marine water) (POTASSIUM METHYL SILICONATE ; CAS No. : 31795-

24-1)

Limit value : 0,33 mg/kg

Limit value type : PNEC soil (POTASSIUM METHYL SILICONATE ; CAS No. : 31795-24-1)

Limit value : 0,54 mg/kg

Limit value type: PNEC (Secondary poisoning) (POTASSIUM METHYL SILICONATE ; CAS No. : 31795-24-

1)

Page: 5 / 11

(EN/D)

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Fondosil 1903

Revision date: 09.08.2021 **Version (Revision):** 2.0.1 (2.0.0)

Print date : 09.08.2021

Limit value : 3,3 mg/kg

Limit value type : PNEC (Sewage treatment plant) (POTASSIUM METHYL SILICONATE ; CAS No. : 31795-

24-1)

Limit value : 10 mg/l

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Observe data available of section 7.

Personal protection equipment

Eye/face protection

Use safety glasses.

Skin protection

Hand protection

At use as agreed a protective gloves from nitrile rubber, tested according to EN 374, with a material thickness 0.38 mm has to be used. Notes of the manufacturer have to be taken into account. Penetration time of the glove material: > 8 h.

By longer or repeated contact the penetration times can be considerably shorter. The protective gloves should replaced after the first wear out or a damage of the gloves. Gloves of cotton should be used under the gloves of polychloropren or nitrile rubber. After washing hands replace lost skin fat by fat containing skin creams.

Body protection

Using protective clothing.

Respiratory protection

Breathing protection equipment is not necessary by brush or roll application of the Product in good ventilated rooms. A respiratory protection (combination filter A2-P3) is required by inadequate ventilation. Do not inhale the vapour.

General information

Avoid contact with eyes and skin. Immediately remove all contaminated clothing. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Ensure a good ventilation in room and working area. Do not breathe vapour.

Environmental exposure controls

The product should not reach waters and the ground. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state: Liquid.

Colour: conformable to product designation.

Odour

Characteristic.

Safety characteristics

Initial boiling point and boiling (1013 hPa) not applicable range: Flash point : not applicable Auto-ignition temperature : not applicable Vapour pressure : (50°C) not determined Density: (20°C) 1,08 - 1,12 g/cm³ approx. Solvent separation test: not applicable (20°C) pH: approx. 10,5 - 11,4

Flow time: (20 °C) not determined DIN-cup 4 mm

VOC-value: max. 1 g/l

9.2 Other information

Page: 6 / 11

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Fondosil 1903

Revision date : 09.08.2021 **Version (Revision) :** 2.0.1 (2.0.0)

Print date : 09.08.2021

Other physical and chemical data have not been determined.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangers connected by a possible reactivity of the product are known to proper handling and storage.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

No dangerous reactions are known if stored and handled the product correctly.

10.4 Conditions to avoid

Keep away from frost, heat and direct sunlight.

10.5 Incompatible materials

No dangerous reaction known. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

No dangerous decomposition product are known if stored and handled correctly. When exposed to high temperatures or in case of fire hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen, may produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute toxicity:

- Acute oral toxicity: No data available;
- Acute dermal toxicity: No data available;
- Acute inhalation toxicity: No data available.

Acute oral toxicity

Parameter: ATEmix calculated

Exposure route : Oral
Effective dose : not relevant

Parameter: LD50 (POTASSIUM METHYL SILICONATE ; CAS No. : 31795-24-1)

Exposure route : Oral Species : Rat

Effective dose: > 2000 mg/kg

Acute dermal toxicity

Parameter: ATEmix calculated

Exposure route : Dermal

Effective dose : not relevant

Acute inhalation toxicity

Parameter: ATEmix calculated
Exposure route: Inhalation (vapour)
Effective dose: not relevant

Corrosion

Irritation:

- Skin contact: Skin irritation.
- Eye contact: Causes serious eye irritation.

Respiratory or skin sensitisation

A sensitizing effect by the product is not known.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The product is not classified as human germ cell mutagenic, carcinogenic or human reproductive toxic (CMR effects).

Page: 7 / 11

according to Regulation (EC) No. 1907/2006 (REACH)

09.08.2021



Fondosil 1903 Trade name:

09.08.2021 **Revision date:** Version (Revision): 2.0.1 (2.0.0)

STOT-single exposure

No risk expected.

Print date:

STOT-repeated exposure

No risk expected.

Aspiration hazard

No risk expected.

11.4 Other adverse effects

Other observations

This product is unlikely to harm health, given normal and proper handling and hygenic precautions.

11.5 Additional information

The product is classified in toxicological terms on the basis of the results of the calculation procedure outlined within the Regulation (EC) No 1272/2008 (CLP-Regualtion), listed in sections 2 and 3.

At proper dealing and use as agreed the product does not cause any effects bad for health after our experiences and the information submitted to us.

SECTION 12: Ecological information

12.1 Toxicity

Acute or chronic damages to water organisms by the product in the aquatic environment are not expecting.

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter: LC50 (SILICID ACID, POTASSIUM SALT, MVZ > 3,2; CAS No.: 1312-76-1)

Species: Leuciscus idus (golden orfe)

Effective dose: > 146 mg/l 48 h Exposure time: Acute (short-term) toxicity to crustacea

EC50 (SILICID ACID, POTASSIUM SALT, MVZ > 3,2; CAS No.: 1312-76-1) Parameter:

Species: Daphnia magna (Big water flea)

Effective dose: > 146 mg/l Exposure time: 24 h

Acute (short-term) toxicity to aquatic algae and cyanobacteria

EC50 (POTASSIUM METHYL SILICONATE ; CAS No.: 31795-24-1) Parameter:

Species: Daphnia magna (Big water flea)

Effective dose: > 100 mg/lExposure time: 48 h

EC50 (POTASSIUM METHYL SILICONATE ; CAS No.: 31795-24-1) Parameter:

Species: Pseudokirchneriella subcapitata

Effective dose: > 120 mg/lExposure time: 72 h

12.2 Persistence and degradability

These are not data avaible about the potential of the product concerning his persistency and degradability.

12.3 Bioaccumulative potential

These are not data availble about the bio accumulation potential of the product.

No information about the individual components is available either.

12.4 Mobility in soil

These are not datas availble about the potential of the product concerning his mobility in the ground.

A penetrating into soil, waters and sewage system should be prevented.

12.5 Results of PBT and vPvB assessment

This product does not contain any relevant substances which were classified as a PBT or vPvB-substance.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

Page: 8 / 11

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Fondosil 1903

Revision date: 09.08.2021 **Version (Revision):** 2.0.1 (2.0.0)

Print date : 09.08.2021

Avoid exposing into ground, waterways and drainage.

The classification of the product is based on summation of classified components according to the Regulation (EC) No 1272/2008 (CLP-Regulation). See details in sections 2 and 3.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

Disposal-definition No. (AVV-Code): 08 01 11* Paint and varnish waste which contains organic solvents or other dangerous substances.

Waste treatment options

Appropriate disposal / Product

Packaging with not dry uped residues have to droped at official collecting sites. Do not empty into waters or drains. Packaging with dry uped residues can be disposed together with household garbage or building site garbage.

Appropriate disposal / Package

Only empty packaging can be transfered to recycling. Uncleaned packaging must be disposed of in the same manner as the medium.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant because the product in type of delivery does not transport in bulks according to the Internationa Maritime Organization (IMO) instruments.

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture $^{15.1}$

EU legislation

Other regulations (EU)

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

Product sub-category and VOC limiting values in accordance with appendix II, letter A of the guideline: Category h, type Wb;

VOC limiting value of the category for 2010: 30 g/l.

This product contains max. 1 g/l VOC.

National regulations

Water hazard class (WGK)

Class: 1 (Slightly hazardous to water) Classification according to AwSV

Page: 9 / 11

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Fondosil 1903

Revision date : 09.08.2021 **Version (Revision) :** 2.0.1 (2.0.0) **Print date :** 09.08.2021

Additional information

The product is not classified as a solid substance according to the criteria of the Penetrometer test (ADR, part 2, section 2.3.4) and also fulfils not the criteria for solid substances according to the TRwS 779 number 2.1.1.

15.2 Chemical safety assessment

A chemical safety assessments was not carried out.

SECTION 16: Other information

16.1 Indication of changes

02. Label elements

16.2 Abbreviations and acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

ADR: European agreement concerning the international carriage of dangerous goods by road (Accord européen relatif transport des merchandises dangereuses par route)

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany) AOX: Adsorbable Organic halogen compounds

ATEmix: Calculated acute toxicity estimate of mixture

BCF: Bio-Concentration Factor CAS: Chemical Abstract Service

CLP: Classification, Labelling and Packaging

CMR: Substances classified as Carcinogenic, Mutagenic or toxic for Reproduction

CSR: Chemical Safety Report DNEL: Derived No Effect Level EC: European Commission EC50: Effective Concentration 50% ECHA: European Chemical Agency EEC: European Economic Community

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

EWC: European Waste Catalogue

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

IC50: Inhibition Concentration 50%

IMDG Code: International Maritime Dangerous Goods Code

IMO: International Maritime Organization

LC50: Lethal concentration 50%

LD50: Lethal Dose 50%

LOAEL: Lowest Observed Adverse Effect Level

LOEL: Lowest observable effect level

MAK: Treshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG)

MARPOL: Convention for the Preventation of Marine Pollution from Ships

MVZ: molar ratio n.a.: Not applicable n.d.: Not determined n.r.: Not relevant NLP: No Longer Polymers

NOAEC: No Observed Adverse Effect Concentration

NOAEL: No Observed Adverse Effect Level NOEC: No Observed Effect Concentration NOEL: No Observed Effect Level OEL: Occupational Exposure Limit

PBT: Persistent, bioaccumulative, toxic PNEC: Predicted No Effect Concentration RCP: Reciprocal calculation procedure

REACH: Registration, Evaluation and Authorization of Chemical)

RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer)

Page: 10 / 11

according to Regulation (EC) No. 1907/2006 (REACH)



2.0.1 (2.0.0)

Version (Revision):

Trade name : Fondosil 1903 **Revision date :** 09.08.2021

Print date : 09.08.2021

STEL: Short-term Exposure Limit SVHC: Substance of Very High Concern

TLV - TWA: Threshold Limit Value - Time Weighed Average

VOC: Volatile Organic Compounds

vPvB: Very persistent, very bioaccumulative.

16.3 Key literature references and sources for data

None

$^{16.4}$ Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The evaluation of hazard information of the product was carried out in accordance to Annex I of the REGULATION (EC) No 1272/2008 (CLP Regulation).

16.5 Relevant H- and EUH-phrases (Number and full text)

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page: 11 / 11