

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lignodur Xylodol 540 - Protect Quality
Lignodur Xylodol 540 - Protect-Qualität

Revision date : 10.03.2022

Print date : 10.03.2022

Version (Revision) : 2.0.0 (1.0.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Lignodur Xylodol 540 - Protect Quality
Lignodur Xylodol 540 - Protect-Qualität

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Products Category [PC]

PC 9 - Coatings and paints, fillers, putties, thinners.

Uses advised against

There are no information about relevant identified uses of the product according to the Regulation (EC) No. 1907/2006 (REACH-Regulation), which are advised against. For using the product observe the information in the Technical data sheet of the product.

1.3 Details of the supplier of the safety data sheet

Supplier

Brillux GmbH & Co KG
www.brillux.de

Street : Weseler Straße 401

Postal code/City : D - 48163 Münster

Telephone : +49 (0)251-7188-0

Telefax : +49 (0)251-7188-280

Information contact :

Electronic mail address of the well-informed person for safety data sheets:sdb@brillux.de

1.4 Emergency telephone number

Outside the business hours (9 a.m. to 5 p.m.):
(Giftinformationszentrum-Nord, Göttingen, consultation in german or english language)
Telephone: +49 (0)551-19240.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

None

Additional information

This product is not dangerous according to the regulation (EC) No. 1272/2008 (CLP).

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements

- | | |
|----------------|--|
| P102 | Keep out of reach of children. |
| P101 | If medical advice is needed, have product container or label at hand. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P261 | Avoid breathing spray. |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. |
| P501 | Dispose of contents/container to approved disposal company or local collection. |

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

Special rules for supplemental label elements for certain mixtures

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lignodur Xylodol 540 - Protect Quality
Lignodur Xylodol 540 - Protect-Qualität
Revision date : 10.03.2022
Print date : 10.03.2022

Version (Revision) : 2.0.0 (1.0.0)

EUH208 Contains 3-iodo-2-propynyl butylcarbamate. May produce an allergic reaction.
EUH210 Safety data sheet available on request.
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605. The product does not contain any substances, which fulfil the criteria for PBT or vPvB in accordance with the Annex XIII of the Regulation (EC) No 1907/2006 (REACH-Regulation).

Adverse physicochemical effects

The product is ignitable! (Category 4 of the class of risk "Flammable liquids" to UN-GHS; Hazard statement: Combustible liquid).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description

Wood care oil;

Composition:

Urethane oil, alkyl resin, titanium dioxide (depending on the shade), inorganic/organic pigments (depending on the shade), silicates, aliphatic hydrocarbons, additives and preservatives for film protection.

Hazardous ingredients

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS ; REACH No. : 01-2119457273-39 ; EC No. : 918-481-9

Weight fraction : ≥ 50 - < 55 %

Classification 1272/2008 [CLP] : Asp. Tox. 1 ; H304 EUH066

TITANIUM DIOXIDE ; EC No. : 236-675-5; CAS No. : 13463-67-7

Weight fraction : ≥ 0 - < 5 %

Classification 1272/2008 [CLP] : Carc. 2 ; H351i

(2-METHOXYMETHYLETHOXY)PROPANOL ; REACH No. : 01-2119450011-60 ; EC No. : 252-104-2; CAS No. : 34590-94-8

Weight fraction : ≥ 1 - < 5 %

Classification 1272/2008 [CLP] : Substance with a community workplace exposure limit

HYDROCARBONS, C11-C13, ISOALKANES, < 2% AROMATICS ; REACH No. : 01-2119456810-40 ; EC No. : 920-901-0

Weight fraction : ≥ 1 - < 5 %

Classification 1272/2008 [CLP] : Asp. Tox. 1 ; H304 EUH066

2-ETHYLHEXANOIC ACID, ZIRCONIUM SALT ; REACH No. : 01-2119979088-21 ; EC No. : 245-018-1; CAS No. : 22464-99-9

Weight fraction : ≥ 0,1 - < 0,5 %

Classification 1272/2008 [CLP] : Repr. 2 ; H361d

3-iodo-2-propynyl butylcarbamate ; EC No. : 259-627-5; CAS No. : 55406-53-6

Weight fraction : ≥ 0,1 - < 0,25 %

Classification 1272/2008 [CLP] : Acute Tox. 3 ; H331 STOT RE 1 ; H372 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Skin Sens. 1 ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410 (M Chronic=1) • (M Acute=10)

Additional information

The used hydrocarbons contain no benzene or benzene in concentrations less than 0.1 percent by weight and fulfil therefore the default(handicap) of the remark P to the appendix VI of the order (EC) No. 1272/2008 (GHS order).

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lignodur Xylodol 540 - Protect Quality
Lignodur Xylodol 540 - Protect-Qualität
Revision date : 10.03.2022
Print date : 10.03.2022

Version (Revision) : 2.0.0 (1.0.0)

Immediately remove all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. In case of unconsciousness: lay on side - call a doctor. Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.

Following inhalation

When symptoms persists, take the casualty into the fresh air and keep warm. Irregular breathing/no breathing: artificial respiration. Call a doctor and tell him the exactly substance.

In case of skin contact

Take off immediately all contaminated clothes. Wash away with soap and water and rinse. Do NOT use solvents or thinners. If skin irritation continues, consult a doctor.

After eye contact

Remove contact lenses, keep eyelids open. Rinse open eye immediately with plenty of running water. Seek medical advice if complaint continues.

Following ingestion

Drink water in small draught. Keep at rest. Do not induce vomiting. When swallowed immediately consult and show packing or label to physician.

4.2 Most important symptoms and effects, both acute and delayed

Potential symptoms: Headache, dizziness, giddiness, skin irritation and eye irritation are possible. Allergic symptoms.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

In case of fire: Use alcohol resistant foam, CO₂, powders or water spray for extinction.

Unsuitable extinguishing media

In case of fire: Do not use waterjet for extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters

At a fire caused by the product a breathing apparatus with an independent source of air is to have ready and to use if necessary for the firefighting.

5.4 Additional information

Cool endangered containers with water in case of fire. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Refer to protective measures listed in sections 7 and 8. Keep away from ignition sources on account of the organic solvent content and air room well. Do not inhale vapours. Avoid contact with eyes and skin.

6.2 Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations. Holding polluted washing water back and disposing of duly.

6.3 Methods and material for containment and cleaning up

For cleaning up

Absorb with suitable absorbent cleaning agents and keep them moist. Burn rags directly under supervision or let them

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lignodur Xylodol 540 - Protect Quality
Lignodur Xylodol 540 - Protect-Qualität
Revision date : 10.03.2022
Print date : 10.03.2022

Version (Revision) : 2.0.0 (1.0.0)

dry. The areas concerned cleaning with a customary water based cleaning agent, not using organic solvents if possible.

6.4 Reference to other sections

See Section 7 for information on safe handling.
You find information about the safety equipment of persons in the section 8,
information about the refuse disposal in section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Ensure a good ventilation in room and working area. Prevent the creation of inflammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit). Only use the material in places where open light, fire and other flammable sources can be kept away. For personal protection see Section 8. Avoid contact with skin and eyes. Read label before use. Use only outdoors or in a well-ventilated area.

Measures to prevent fire

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Avoid concentrations which form ignitable or explosive vapour and air mixtures. Likewise, avoid any concentration of vapour above the MAC-value. Keep away from ignition sources - No smoking. Ground/bond container and receiving equipment. Use explosion-proof pipes, electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Measures to prevent aerosol and dust generation

Do not breathe gas or spray.

Advices on general occupational hygiene

While working do not eat, drink or smoke. Wash hands and face before breaks and after work and take a shower if necessary. Immediately remove all contaminated clothing.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Do not store the product in lounge room. Keep only in the original container. Keep out of the reach of children. Store in a well-ventilated place. Keep cool.

Hints on joint storage

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. Store away from foodstuffs.

Storage class (TRGS 510) : 10

Further information on storage conditions

Keep container tightly sealed. Store at 5°-35°C. Containers should be kept dry and sealed.

7.3 Specific end use(s)

For using the product observe the information in the Technical data sheet of the product.

Industrial sector specific solutions

GISCODE : Product code in accordance with GISBAU (hazardous materials information system of the German professional associations of the building and construction industry) for surface treatment agents and other wood (GISCODE): Ö60.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

Limit value type (country of origin) : TRGS 900 (D)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lignodur Xylodol 540 - Protect Quality
Lignodur Xylodol 540 - Protect-Qualität
Revision date : 10.03.2022
Print date : 10.03.2022

Version (Revision) : 2.0.0 (1.0.0)

Parameter : Group limit for the calculation of the occupational exposure limit for hydrocarbon mixtures (see section 2.9 of Technical Rule 900).
Limit value : 300 mg/m³
Version :
(2-METHOXYMETHYLETHOXY)PROPANOL ; CAS No. : 34590-94-8
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 50 ppm / 310 mg/m³
Peak limitation : 1(I)
Version : 02.07.2021
Limit value type (country of origin) : TWA (EC)
Limit value : 50 ppm / 308 mg/m³
Remark : Skin
Version : 20.06.2019
SILICON DIOXIDE ; CAS No. : 7631-86-9
Limit value type (country of origin) : TRGS 900 (D)
Parameter : E: inhalable fraction
Limit value : 4 mg/m³
Remark : Y
Version : 02.07.2021
HYDROCARBONS, C11-C13, ISOALKANES, < 2% AROMATICS
Limit value type (country of origin) : TRGS 900 (D)
Parameter : Group limit for the calculation of the occupational exposure limit for hydrocarbon mixtures (see section 2.9 of Technical Rule 900).
Limit value : 300 mg/m³
Version :
3-IODO-2-PROPYNYL BUTYLCARBAMATE ; CAS No. : 55406-53-6
Limit value type (country of origin) : MAK - Grenzwerte in der Luft am Arbeitsplatz (D)
Limit value : 0,01 ml/m³ / 0,12 mg/m³
Version :

Remark

Short time value (STEL): Excess factor 2 (II) according to the german TRGS 900.
Taking into account the details mentioned in the TRGS 900 for the supervision of AGW.

DNEL-/PNEC-values

DNEL/DMEL

(2-METHOXYMETHYLETHOXY)PROPANOL ; CAS No. : 34590-94-8
Limit value type : DNEL Consumer (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 15 mg/kg
Assessment factor : 1 D
Limit value type : DNEL Consumer (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 37,2 mg/m³
Limit value type : DNEL Consumer (systemic)
Exposure route : Oral
Exposure frequency : Long-term
Limit value : 1,67 mg/kg
Assessment factor : 1 D
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 65 mg/kg
Assessment factor : 1 D

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lignodur Xylodol 540 - Protect Quality
Lignodur Xylodol 540 - Protect-Qualität
Revision date : 10.03.2022
Print date : 10.03.2022

Version (Revision) : 2.0.0 (1.0.0)

Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 310 mg/m³
2-ETHYLHEXANOIC ACID, ZIRCONIUM SALT ; CAS No. : 22464-99-9
Limit value type : DNEL/DMEL (Consumer)
Exposure route : Oral
Exposure frequency : Long-term
Limit value : 4,51 mg/kg
Assessment factor : 1 D
Limit value type : DNEL/DMEL (Consumer)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 8,13 mg/m³
Limit value type : DNEL/DMEL (Consumer)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 3,25 mg/kg
Assessment factor : 1 D
Limit value type : DNEL/DMEL (Professional)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 32,97 mg/m³
Limit value type : DNEL/DMEL (Professional)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 6,49 mg/kg
Assessment factor : 1 D

PNEC

(2-METHOXYMETHYLETHOXY)PROPANOL ; CAS No. : 34590-94-8
Limit value type : PNEC (Aquatic, freshwater)
Exposure route : Water (Including sewage plant)
Limit value : 19 mg/l
Limit value type : PNEC (Aquatic, marine water)
Exposure route : Water (Including sewage plant)
Limit value : 1,9 mg/l
Limit value type : PNEC (Sediment, freshwater)
Exposure route : Soil
Limit value : 70,2 mg/kg
Limit value type : PNEC (Sediment, marine water)
Exposure route : Soil
Limit value : 7,02 mg/kg
Limit value type : PNEC soil
Exposure route : Soil
Limit value : 2,74 mg/kg
Limit value type : PNEC (Sewage treatment plant)
Exposure route : Water (Including sewage plant)
Limit value : 4168 mg/l

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn. Observe data available of section 7.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lignodur Xylodol 540 - Protect Quality
Lignodur Xylodol 540 - Protect-Qualität
Revision date : 10.03.2022
Print date : 10.03.2022

Version (Revision) : 2.0.0 (1.0.0)

Personal protection equipment

Eye/face protection

Use protection glasses in case of spattering.

Skin protection

Hand protection

At use as agreed a protective gloves from nitrile rubber, tested according to EN 374, with a material thickness 0,38 mm has to be used. Notes of the manufacturer have to be taken into account. Penetration time of the glove material: > = 8 h.

By longer or repeated contact the penetration times can be considerably shorter. The protective gloves should be replaced after the first wear out or a damage of the gloves. Gloves of cotton should be used under the gloves of polychloropren or nitrile rubber. After washing hands replace lost skin fat by fat containing skin creams.

Body protection

Using protective clothing. If the product must sprayed, use a disposable protective suit.

Respiratory protection

Breathing protection equipment is not required in good ventilated places. A respiratory protection (combination filter A2-P3) is required by inadequate ventilation and by spray application. Do not breathe gas or spray.

General information

Avoid contact with eyes and skin. Immediately remove all contaminated clothing. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Ensure a good ventilation in room and working area. Do not breathe gas or spray. Do not put any product-impregnated cleaning rags into your trouser pockets.

Environmental exposure controls

The product should not reach waters and the ground. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.

Colour : conformable to product designation.

Odour

Poor, characteristic.

Safety characteristics

Melting point/freezing point :	(1013 hPa)	No data available
Initial boiling point and boiling range :	(1013 hPa)	170 - 220 °C
Decomposition temperature :	(1013 hPa)	No data available
Flash point :	>	60 °C
Auto-ignition temperature :	>	200 °C
Lower explosion limit :		0,6 Vol-%
Upper explosion limit :		7 Vol-%
Vapour pressure :	(50 °C)	4 hPa
Density :	(20 °C)	approx. 0,85 - 1 g/cm ³
Solvent separation test :	(20 °C)	< 3 %
Water solubility :	(20 °C)	practically insoluble
pH :		not applicable
log P O/W :		No data available
Flow time :	(20 °C)	No data available
Viscosity :	(20 °C)	thixotropic
Kinematic viscosity :	(40 °C)	> 20,5 mm ² /s
Relative vapour density :	(20 °C)	No data available
VOC-value :	max.	550 g/l

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lignodur Xylodol 540 - Protect Quality
Lignodur Xylodol 540 - Protect-Qualität
Revision date : 10.03.2022
Print date : 10.03.2022

Version (Revision) : 2.0.0 (1.0.0)

Flammable liquids : The product is ignitable.
Particle Characteristics : not applicable

9.2 Other information

Selfinflammability: In very fine distribution in contact with air the danger(risk) of the selfinflammability exists(consists). Watered cleaning cloths or the similar incline to the spontaneous combustion. Other physical and chemical data have not been determined.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangers connected by a possible reactivity of the product are known to proper handling and storage.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

10.4 Conditions to avoid

To avoid formation of ignitable vapour and air mixtures ensure good ventilation (inter alia extraction system). Keep away from frost, heat and direct sunlight.

In very fine distribution in contact with the air the danger(risk) of the spontaneous combustion exists(consists) under circumstances. Moistened cleaning cloths or the similar incline as a result of Autoxidation to the spontaneous combustion. These cleaning cloths only stretched out on a not ignitable base allow to dry, collect in fireproof waste containers and dispose them in a fire-proof manner.

10.5 Incompatible materials

No dangerous reaction known. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

No dangerous decomposition product are known if stored and handled correctly. When exposed to high temperatures or in case of fire hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen, may produced. Wetted rags tend to self-ignite due to autoxidation. Allow soaked cloths to dry on a non-flammable surface only spread out.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Acute toxicity:

- Acute oral toxicity: No data available;
- Acute dermal toxicity: No data available;
- Acute inhalation toxicity: No data available.

Acute oral toxicity

Parameter :	ATEmix calculated
Exposure route :	Oral
Effective dose :	not relevant
Parameter :	LD50 (HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS)
Exposure route :	Oral
Species :	Rat
Effective dose :	> 5000 mg/kg
Parameter :	LD50 (HYDROCARBONS, C11-C13, ISOALKANES, < 2% AROMATICS)
Exposure route :	Oral
Species :	Rat
Effective dose :	> 5000 mg/kg

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lignodur Xylodol 540 - Protect Quality
Lignodur Xylodol 540 - Protect-Qualität
Revision date : 10.03.2022
Print date : 10.03.2022

Version (Revision) : 2.0.0 (1.0.0)

Parameter : LD50 (3-iodo-2-propynyl butylcarbamate ; CAS No. : 55406-53-6)
Exposure route : Oral
Species : Rat
Effective dose : 1470 mg/kg

Acute dermal toxicity

Parameter : ATEmix calculated
Exposure route : Dermal
Effective dose : not relevant
Parameter : LD50 (HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS)
Exposure route : Dermal
Species : Rabbit
Effective dose : > 5000 mg/kg
Parameter : LD50 (HYDROCARBONS, C11-C13, ISOALKANES, < 2% AROMATICS)
Exposure route : Dermal
Species : Rabbit
Effective dose : > 5000 mg/kg
Parameter : LD50 (3-iodo-2-propynyl butylcarbamate ; CAS No. : 55406-53-6)
Exposure route : Dermal
Species : Rabbit
Effective dose : > 2000 mg/kg

Acute inhalation toxicity

Parameter : ATEmix calculated
Exposure route : Inhalation (vapour)
Effective dose : 5500 mg/l
Parameter : LC50 (HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS)
Exposure route : Inhalation
Species : Rat
Effective dose : > 4,951 mg/l
Exposure time : 4 h
Parameter : LC50 (HYDROCARBONS, C11-C13, ISOALKANES, < 2% AROMATICS)
Exposure route : Inhalation
Species : Rat
Effective dose : > 5000 mg/m³
Exposure time : 8 h
Parameter : LC50 (3-iodo-2-propynyl butylcarbamate ; CAS No. : 55406-53-6)
Exposure route : Inhalation
Species : Rat
Effective dose : > 6,89 mg/l
Exposure time : 4 h

Corrosion

Irritation:
- To the skin: Repeated exposure may cause skin dryness or cracking.
- At the eye: May cause mild, short-lasting discomfort to eyes.
- Respiratory tract: Irritation of the respiratory tract possible.

Respiratory or skin sensitisation

The product contains sensitizing substances, which may produce an allergic reaction (see section 2 and 3).

Repeated dose toxicity (subacute, subchronic, chronic)

Subacute oral toxicity

Parameter : NOAEL(C) (3-iodo-2-propynyl butylcarbamate ; CAS No. : 55406-53-6)
Exposure route : Oral
Species : Rat
Effective dose : 35 mg/kg

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lignodur Xylodol 540 - Protect Quality
Lignodur Xylodol 540 - Protect-Qualität
Revision date : 10.03.2022
Print date : 10.03.2022

Version (Revision) : 2.0.0 (1.0.0)

Exposure time : 90 D
Parameter : NOAEL(C) (3-iodo-2-propynyl butylcarbamate ; CAS No. : 55406-53-6)
Exposure route : Oral
Species : Rat
Effective dose : 20 mg/kg
Exposure time : 24 month(s)

Subacute dermal toxicity

Parameter : NOAEL(C) (3-iodo-2-propynyl butylcarbamate ; CAS No. : 55406-53-6)
Exposure route : Dermal
Species : Rat
Effective dose : 200 mg/kg
Exposure time : 90 D

Subacute inhalation toxicity

Parameter : NOAEL(C) (3-iodo-2-propynyl butylcarbamate ; CAS No. : 55406-53-6)
Exposure route : Inhalation
Species : Rat
Effective dose : 1,16 mg/m³
Exposure time : 90 D

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The product is not classified as human germ cell mutagenic, carcinogenic or human reproductive toxic (CMR effects).

STOT-single exposure

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation, kidneys and liver damages, as well as leading the impairment of the central nervous system.

Symptoms and signs include headache: dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.

The liquid splashed in the eyes may cause irritation and reversible damage.

STOT-repeated exposure

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Aspiration hazard

The product contains substances, which are classified as aspiration toxicity, category 1 (May be fatal if swallowed and enters airways), in accordance to the Regulation (EC) No. 1272/2008 (CLP-Regulation) in their pure form. Based on available data the classification criteria according to Regulation (EC) No 1272/2008 [CLP] are not fulfilled.

11.2 Information on other hazards

Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

Other adverse effects

This product is unlikely to harm health, given normal and proper handling and hygienic precautions.

Additional information

The product is classified in toxicological terms on the basis of the results of the calculation procedure outlined within the Regulation (EC) No 1272/2008 (CLP-Regulation), listed in sections 2 and 3.

At proper dealing and use as agreed the product does not cause any effects bad for health after our experiences and the information submitted to us.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter : NOEL (HYDROCARBONS, C11-C13, ISOALKANES, < 2% AROMATICS)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lignodur Xylodol 540 - Protect Quality
Lignodur Xylodol 540 - Protect-Qualität

Revision date : 10.03.2022

Print date : 10.03.2022

Version (Revision) : 2.0.0 (1.0.0)

Species : Pseudokirchneriella subcapitata
Effective dose : 1000 mg/l
Exposure time : 72 h
Parameter : NOELR (HYDROCARBONS, C11-C13, ISOALKANES, < 2% AROMATICS)
Species : Daphnia magna (Big water flea)
Effective dose : 1 mg/l
Exposure time : 21 D
Parameter : LC50 (3-iodo-2-propynyl butylcarbamate ; CAS No. : 55406-53-6)
Species : Oncorhynchus mykiss (Rainbow trout)
Effective dose : 0,067 mg/l
Exposure time : 96 h

Chronic (long-term) fish toxicity

Parameter : NOEC (3-iodo-2-propynyl butylcarbamate ; CAS No. : 55406-53-6)
Species : Pimephales promelas (fathead minnow)
Effective dose : 0,0084 mg/l
Exposure time : 35 D
Parameter : NOEC (3-iodo-2-propynyl butylcarbamate ; CAS No. : 55406-53-6)
Species : Oncorhynchus mykiss (Rainbow trout)
Effective dose : 0,049 mg/l
Exposure time : 96 h

Acute (short-term) toxicity to crustacea

Parameter : EC50 (3-iodo-2-propynyl butylcarbamate ; CAS No. : 55406-53-6)
Species : Daphnia magna (Big water flea)
Effective dose : 0,16 mg/l
Exposure time : 48 h

Chronic (long-term) toxicity to aquatic invertebrate

Parameter : NOEC (3-iodo-2-propynyl butylcarbamate ; CAS No. : 55406-53-6)
Species : Daphnia magna (Big water flea)
Effective dose : 0,05 mg/l
Exposure time : 21 D

Acute (short-term) toxicity to algae and cyanobacteria

Parameter : EL0 (HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS)
Species : Daphnia magna (Big water flea)
Effective dose : 1000 mg/l
Exposure time : 48 h
Parameter : EL0 (HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS)
Species : Pseudokirchneriella subcapitata
Effective dose : 1000 mg/l
Exposure time : 72 h
Parameter : EL0 (HYDROCARBONS, C11-C13, ISOALKANES, < 2% AROMATICS)
Species : Daphnia magna (Big water flea)
Effective dose : 1000 mg/l
Exposure time : 48 h
Parameter : EL0 (HYDROCARBONS, C11-C13, ISOALKANES, < 2% AROMATICS)
Species : Pseudokirchneriella subcapitata
Effective dose : 1000 mg/l
Exposure time : 72 h
Parameter : EC50 (3-iodo-2-propynyl butylcarbamate ; CAS No. : 55406-53-6)
Species : Scenedesmus subspicatus
Effective dose : 0,022 mg/l
Exposure time : 72 h
Parameter : EL50 (3-iodo-2-propynyl butylcarbamate ; CAS No. : 55406-53-6)
Species : Scenedesmus subspicatus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lignodur Xylodol 540 - Protect Quality
Lignodur Xylodol 540 - Protect-Qualität
Revision date : 10.03.2022
Print date : 10.03.2022

Version (Revision) : 2.0.0 (1.0.0)

Effective dose : 0,0046 mg/l
Exposure time : 72 h

12.2 Persistence and degradability

These are not data available about the potential of the product concerning his persistency and degradability.

12.3 Bioaccumulative potential

These are not data available about the bio accumulation potential of the product.

12.4 Mobility in soil

These are not datas available about the potential of the product concerning his mobility in the ground.
A penetrating into soil, waters and sewage system should be prevented.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

12.7 Other adverse effects

Acute or chronic damages to water organisms by the product in the aquatic environment are not expecting.

12.8 Additional ecotoxicological information

Avoid exposing into ground, waterways and drainage.

The classification of the product is based on summation of classified components according to the Regulation (EC) No 1272/2008 (CLP-Regulation). See details in sections 2 and 3.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Directive 2008/98/EC (Waste Framework Directive)

Before intended use

Dispose of contents/container to approved disposal company or local collection according to the local regulations. Packaging with not dry uped residues have to dropped at official collecting sites. Packaging with dry uped residues can be disposed together with household garbage or building site garbage. Do not empty into waters or drains.

Waste codes/waste designations according to EWC/AVV

For the product:

Disposal-definition No.: 08 01 11* - Paint and varnish waste which contains organic solvents or other dangerous substances.

After intended use

Only empty packaging can be transfered to recycling. Uncleaned packaging must be disposed of in the same manner as the medium. Moistened cleaning cloths or the similar incline as a result of Autoxidation to the spontaneous combustion. Watered cleaning cloths only stretched out on a not ignitable base allow to dry, collect in fireproof waste containers and dispose them in a fire-proof manner.

Waste codes/waste designations according to EWC/AVV

For the uncleaned packaging:

Disposal-definition No.: 15 01 10 * packings which contain dangerous substances or are polluted by dangerous substances.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lignodur Xylodol 540 - Protect Quality
Lignodur Xylodol 540 - Protect-Qualität

Revision date : 10.03.2022

Print date : 10.03.2022

Version (Revision) : 2.0.0 (1.0.0)

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant because the product in type of delivery does not transport in bulks according to the International Maritime Organization (IMO) instruments.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no. : 75

Other regulations (EU)

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

The product is not subject to the EU guideline 2004/42/EC about the limitation of the issues of brief organic connections due to the use of organic solvents in certain colours and varnishes.

This product contains max. 550 g/l VOC.

National regulations

Water hazard class

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

Additional information

The product is not classified as a solid substance according to the criteria of the Penetrometer test (ADR, part 2, section 2.3.4) and also fulfils not the criteria for solid substances according to the TRwS 779 number 2.1.1.

Maternity regulations and Young Persons Employment Act are to take into account.

15.2 Chemical Safety Assessment

A chemical safety assessments was not carried out.

SECTION 16: Other information

16.1 Indication of changes

15. Restrictions on use * 15. Water hazard class

16.2 Abbreviations and acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

ADR: European agreement concerning the international carriage of dangerous goods by road (Accord européen relatif transport des marchandises dangereuses par route)

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany) AOX: Adsorbable Organic halogen compounds

ATEmix: Calculated acute toxicity estimate of mixture

BCF: Bio-Concentration Factor

CAS: Chemical Abstract Service

CLP: Classification, Labelling and Packaging

CMR: Substances classified as Carcinogenic, Mutagenic or toxic for Reproduction

CSR: Chemical Safety Report

DNEL: Derived No Effect Level

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lignodur Xylodol 540 - Protect Quality
Lignodur Xylodol 540 - Protect-Qualität

Revision date : 10.03.2022

Print date : 10.03.2022

Version (Revision) : 2.0.0 (1.0.0)

EC: European Commission
EC50: Effective Concentration 50%
ECHA: European Chemical Agency
EEC: European Economic Community
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
EWC: European Waste Catalogue
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
IC50: Inhibition Concentration 50%
IMDG Code: International Maritime Dangerous Goods Code
IMO: International Maritime Organization
LC50: Lethal concentration 50%
LD50: Lethal Dose 50%
LOAEL: Lowest Observed Adverse Effect Level
LOEL: Lowest observable effect level
MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG)
MARPOL: Convention for the Prevention of Marine Pollution from Ships
MVZ: molar ratio
n.a.: Not applicable
n.d.: Not determined
n.r.: Not relevant
NLP: No Longer Polymers
NOAEC: No Observed Adverse Effect Concentration
NOAEL: No Observed Adverse Effect Level
NOEC: No Observed Effect Concentration
NOEL: No Observed Effect Level
OEL: Occupational Exposure Limit
PBT: Persistent, bioaccumulative, toxic
PNEC: Predicted No Effect Concentration
RCP: Reciprocal calculation procedure
REACH: Registration, Evaluation and Authorization of Chemicals
RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer)
STEL: Short-term Exposure Limit
SVHC: Substance of Very High Concern
TLV - TWA: Threshold Limit Value - Time Weighted Average
VOC: Volatile Organic Compounds
vPvB: Very persistent, very bioaccumulative.

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The evaluation of hazard information of the product was carried out in accordance to Annex I of the REGULATION (EC) No 1272/2008 (CLP Regulation).

16.5 Relevant H- and EUH-phrases (Number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H351i	Suspected of causing cancer if inhaled.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lignodur Xylodol 540 - Protect Quality
Lignodur Xylodol 540 - Protect-Qualität
Revision date : 10.03.2022
Print date : 10.03.2022

Version (Revision) : 2.0.0 (1.0.0)

EUH066

Repeated exposure may cause skin dryness or cracking.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
