

Turpentine Substitute 321

For thinning alkyd resin enamel paints



Field of application

For consistency regulation for improved application of alkyd resin enamel paints, e.g. Metal Primer 850, with brush and roller. Also suitable for cleaning the required tools.

Properties

Specially coordinated solvent, predominantly for thinning alkyd resin based synthetic enamels.

Material description

Color shade	colorless
Base material	Solvent mixture based on aliphates.
Constituent substances	Aliphatic hydrocarbons
VOC value	max.800 g/l
Flash point	+62 °C
Density	approx. 0.79–0.81 g/cm ³
Packaging	500 ml, 1 l and 5 l

Use

Add the relevant product in the specified mixing ratio depending on the individual requirements and mix thoroughly. Follow the more detailed instructions on the viscosity setting in the individual Data Sheets.

Storage

Store in a cool and dry location. Protect from direct sunlight. Reseal opened containers tightly.

Declaration

Product code M-VM01.

Comply with the specifications in the current Safety Data Sheet.

Notes

Mask surfaces Carefully mask the surrounding area and particularly sensitive materials.

Further information Follow the instructions in the data sheets of the products used.

Remark

This Data Sheet has been prepared taking into account the current applicable German laws, standards, specifications and codes of practice. All details have been translated from the current German version. The contents do not form a legal contract. The user and/or the purchaser is not released from the responsibility of checking that our products are suitable for the proposed use. In addition our Terms of Conditions and Payment apply.

When a new version of this Data Sheet with updated information is published, the previous version no longer applies. The current version is available on our website.

Brillux
Weseler Straße 401
48163 Münster
Germany
Phone +49 251 7188-0
Fax +49 251 7188-105
info@brillux.de
www.brillux.com