

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2K-Aqua Hardener 2380  
2K-Aqua Härter 2380  
**Revision date :** 13.06.2022  
**Print date :** 13.06.2022

**Version (Revision) :** 4.0.0 (3.0.1)

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier

2K-Aqua Hardener 2380  
2K-Aqua Härter 2380

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses

###### Products Category [PC]

PC 9 - Coatings and paints, fillers, putties, thinners.

##### Uses advised against

The 2K-PUR product may be used only in industrial and professional applications. A use in Do-it Yourself applications is warning.

The main component of the Hardener was registered for the splashing and spraying application in accordance with the REACH regulations.

#### 1.3 Details of the supplier of the safety data sheet

##### Supplier

Brillux GmbH & Co KG  
www.brillux.de

**Street :** Weseler Straße 401

**Postal code/City :** D - 48163 Münster

**Telephone :** +49 (0)251-7188-0

**Telefax :** +49 (0)251-7188-280

##### Information contact :

Electronic mail address of the well-informed person for safety data sheets:sdb@brillux.de

#### 1.4 Emergency telephone number

Outside the business hours (9 a.m. to 5 p.m.):

(Giftinformationszentrum-Nord, Göttingen, consultation in german or english language)

Telephone: +49 (0)551-19240.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4 ; H332 - Acute toxicity (inhalative) : Category 4 ; Harmful if inhaled.

Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

STOT SE 3 ; H335 - STOT-single exposure : Category 3 ; May cause respiratory irritation.

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Chronic 3 ; Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

###### Hazard pictograms



Exclamation mark (GHS07)

##### Signal word

Warning

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-Aqua Hardener 2380  
2K-Aqua Härter 2380  
Revision date : 13.06.2022  
Print date : 13.06.2022

Version (Revision) : 4.0.0 (3.0.1)

### Hazard components for labelling

ALIPHATIC POLYISOCYANATE ; CAS No. : 666723-27-9  
HEXAMETHYLENE-1,6-DIISOCYANATE, HOMOPOLYMER ; CAS No. : 28182-81-2  
HEXAMETHYLENE-DI-ISOCYANATE ; CAS No. : 822-06-0

### Hazard statements

H332 Harmful if inhaled.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.  
H412 Harmful to aquatic life with long lasting effects.

### Precautionary statements

P102 Keep out of reach of children.  
P261 Avoid breathing vapours.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P312 Call a POISON CENTER or a doctor if you feel unwell.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P501 Dispose of contents/container to approved disposal company or local collection.

### Special rules for supplemental label elements for certain mixtures

EUH204 Contains isocyanates. May produce an allergic reaction.

## 2.3 Other hazards

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.  
The product does not contain any substances, which fulfil the criteria for PBT or vPvB in accordance with the Annex XIII of the Regulation (EC) No 1907/2006 (REACH-Regulation).

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Description

Aliphatic polyisocyanates.

#### Hazardous ingredients

ALIPHATIC POLYISOCYANATE ; CAS No. : 666723-27-9

Weight fraction :  $\geq 40 - < 45$  %  
Classification 1272/2008 [CLP] : Acute Tox. 4 ; H332 Skin Sens. 1B ; H317 STOT SE 3 ; H335 Aquatic Chronic 3 ; H412 EUH204

HEXAMETHYLENE-1,6-DIISOCYANATE, HOMOPOLYMER ; REACH No. : 01-2119488934-20 ; EC No. : 500-060-2 ; CAS No. : 28182-81-2

Weight fraction :  $\geq 35 - < 40$  %  
Classification 1272/2008 [CLP] : Acute Tox. 4 ; H332 Skin Sens. 1 ; H317 STOT SE 3 ; H335 EUH204

HEXAMETHYLENE-DI-ISOCYANATE ; REACH No. : 01-2119457571-37 ; EC No. : 212-485-8 ; CAS No. : 822-06-0

Weight fraction :  $< 0,1$  %  
Classification 1272/2008 [CLP] : Acute Tox. 2 ; H330 Resp. Sens. 1 ; H334 Acute Tox. 4 ; H302 Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319 STOT SE 3 ; H335  
Specific Conc. Limits : Resp. Sens. 1 ; H334: C  $\geq 0,5$  % • Skin Sens. 1 ; H317: C  $\geq 0,5$  %

#### Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

## SECTION 4: First aid measures

**Trade name :** 2K-Aqua Hardener 2380  
2K-Aqua Härter 2380  
**Revision date :** 13.06.2022  
**Print date :** 13.06.2022

**Version (Revision) :** 4.0.0 (3.0.1)

#### **4.1 Description of first aid measures**

##### **General information**

In all cases of doubt, or when symptoms persist, seek medical attention. Immediately remove all contaminated clothing. In case of unconsciousness: lay on side - call a doctor. Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.

##### **Following inhalation**

When symptoms persists, take the casualty into the fresh air and keep warm. Irregular breathing/no breathing: artificial respiration. In case of unconsciousness place patient stably in side position for transportation.

##### **In case of skin contact**

Take off immediately all contaminated clothes. Wash away with soap and water and rinse. Do NOT use solvents or thinners. If skin irritation continues, consult a doctor.

##### **After eye contact**

Remove contact lenses, keep eyelids open. Rinse open eye immediately with plenty of running water. Seek medical advice if complaint continues.

##### **Following ingestion**

Keep at rest. Do not induce vomiting. When swallowed immediately consult and show packing or label to physician.

#### **4.2 Most important symptoms and effects, both acute and delayed**

Potential symptoms: Headache, dizziness, giddiness, skin irritation, eye irritation and irritation to respiratory tract are possible. Allergic symptoms.

#### **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### **SECTION 5: Firefighting measures**

#### **5.1 Extinguishing media**

##### **Suitable extinguishing media**

In case of fire: Use alcohol resistant foam, CO<sub>2</sub>, powders or water spray for extinction. Fight larger fires with water jet or alcohol-resistant foam.

##### **Unsuitable extinguishing media**

In case of fire: Do not use waterjet for extinction.

#### **5.2 Special hazards arising from the substance or mixture**

##### **Hazardous combustion products**

In case of fire carbon monoxide, oxides of nitrogen, isocyanide and hydrogen cyanide may be formed.

#### **5.3 Advice for firefighters**

##### **Special protective equipment for firefighters**

When extinguishing fires, use breathing apparatus with an independent source of air.

#### **5.4 Additional information**

Cool endangered containers with water in case of fire. Do not allow run-off from fire-fighting to enter drains or water courses.

### **SECTION 6: Accidental release measures**

#### **6.1 Personal precautions, protective equipment and emergency procedures**

Refer to protective measures listed in sections 7 and 8. Keep no protective persons away, personal should wear protective clothings. Avoid contact with eyes and skin.

#### **6.2 Environmental precautions**

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations. Holding polluted washing water back and disposing of duly.

**Trade name :** 2K-Aqua Hardener 2380  
2K-Aqua Härter 2380  
**Revision date :** 13.06.2022  
**Print date :** 13.06.2022

**Version (Revision) :** 4.0.0 (3.0.1)

### 6.3 Methods and material for containment and cleaning up

#### For cleaning up

Ensure adequate ventilation. Absorb with liquid binding material (i.e. sand, kieselgur, universal binder or sawdust). After approx. 1 hour put in waste container but do not close (CO<sub>2</sub> development). Subsequently put in the waste container. Do not seal (CO<sub>2</sub> may be given off). Keep damp and leave several days in a container in a secure area. The areas concerned cleaning with a customary water based cleaning agent, not using organic solvents if possible.

### 6.4 Reference to other sections

See Section 7 for information on safe handling.  
You find information about the safety equipment of persons in the section 8,  
information about the refuse disposal in section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Protective measures

No special measures necessary in the case of regulation storage and handling. Ensure a good ventilation in room and working area. Prevent the creation of inflammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit). Only use the material in places where open light, fire and other flammable sources can be kept away. For personal protection see Section 8. Avoid contact with skin and eyes. Read label before use.

#### Measures to prevent fire

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Avoid concentrations which form ignitable or explosive vapour and air mixtures. Likewise, avoid any concentration of vapour above the MAC-value. Keep away from ignition sources - No smoking. Ground/bond container and receiving equipment. Use explosion-proof pipes, electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### Measures to prevent aerosol and dust generation

Do not breathe gas or spray.

#### Advices on general occupational hygiene

While working do not eat, drink or smoke. Wash hands and face before breaks and after work and take a shower if necessary. Immediately remove all contaminated clothing.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Do not store the product in lounge room. Keep only in the original container. Keep out of the reach of children. in a well-ventilated place. Keep container tightly closed.

#### Hints on joint storage

Store away from foodstuffs. Avoid moisture.

**Storage class (TRGS 510) :** 10

#### Further information on storage conditions

Keep container tightly sealed. Store at 5°-35°C. Containers should be kept dry and sealed.

### 7.3 Specific end use(s)

For using the product observe the information in the Technical data sheet of the product.

#### Industrial sector specific solutions

**GISCODE :** Product code in accordance to GISBAU (hazardous materials information system of the German professional associations of the building and construction industry): PU 50.

## SECTION 8: Exposure controls/personal protection

**Trade name :** 2K-Aqua Hardener 2380  
2K-Aqua Härter 2380  
**Revision date :** 13.06.2022  
**Print date :** 13.06.2022

**Version (Revision) :** 4.0.0 (3.0.1)

## 8.1 Control parameters

### Occupational exposure limit values

HEXAMETHYLENE-DI-ISOCYANATE ; CAS No. : 822-06-0

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 0,005 ppm / 0,035 mg/m<sup>3</sup>

Peak limitation : 1/=2=(I)

Remark : Sa

Version : 02.07.2021

#### Remark

Taking into account the details mentioned in the TRGS 900 for the supervision of AGW.

### Biological limit values

HEXAMETHYLENE-DI-ISOCYANATE ; CAS No. : 822-06-0

Limit value type (country of origin) : TRGS 903 ( D )

Parameter : Hexamethylenediamine (after hydrolysis) / Urine (U) / End of exposure or end of shift

Limit value : 0,15 mg/g Creatinine

Version : 04.05.2021

### DNEL-/PNEC-values

#### DNEL/DMEL

HEXAMETHYLENE-1,6-DIISOCYANATE, HOMOPOLYMER ; CAS No. : 28182-81-2

Limit value type : DNEL/DMEL (Worker)

Exposure route : Inhalation

Exposure frequency : Short-term

Limit value : 0,7 mg/m<sup>3</sup>

Limit value type : DNEL/DMEL (Worker)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 0,35 mg/m<sup>3</sup>

HEXAMETHYLENE-DI-ISOCYANATE ; CAS No. : 822-06-0

Limit value type : DNEL/DMEL (Industrial)

Exposure route : Dermal

Exposure frequency : Short-term

Limit value type : DNEL/DMEL (Industrial)

Exposure route : Inhalation

Exposure frequency : Short-term

Limit value : 0,07 mg/m<sup>3</sup>

Limit value type : DNEL/DMEL (Industrial)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 0,035 mg/m<sup>3</sup>

#### PNEC

HEXAMETHYLENE-1,6-DIISOCYANATE, HOMOPOLYMER ; CAS No. : 28182-81-2

Limit value type : PNEC (Aquatic, freshwater)

Exposure route : Water (Including sewage plant)

Limit value : 0,1 mg/l

Limit value type : PNEC Intermittierende Einleitung

Exposure route : Water (Including sewage plant)

Limit value : 1 mg/l

Limit value type : PNEC (Aquatic, marine water)

Exposure route : Water (Including sewage plant)

Limit value : 0,01 mg/l

Limit value type : PNEC (Sediment, freshwater)

Exposure route : Soil

Limit value : 2530 mg/kg

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2K-Aqua Hardener 2380  
2K-Aqua Härter 2380  
**Revision date :** 13.06.2022  
**Print date :** 13.06.2022

**Version (Revision) :** 4.0.0 (3.0.1)

Limit value type : PNEC (Sediment, marine water)  
Exposure route : Soil  
Limit value : 253 mg/kg  
Limit value type : PNEC soil  
Exposure route : Soil  
Limit value : 505 mg/kg  
Limit value type : PNEC (Sewage treatment plant)  
Exposure route : Water (Including sewage plant)  
Limit value : 100 mg/l

## 8.2 Exposure controls

### Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn. Observe data available of section 7.

### Personal protection equipment

#### Eye/face protection

Use protection glasses in case of spattering.

#### Skin protection

##### Hand protection

Use protective gloves. For a short-term contact protective gloves made of nitrile rubber are suitable with a material thickness of 0.38 mm.

For longer or repeated contact protective gloves made of butyl rubber are used with a material thickness of  $\geq 0,7$  mm. Penetration time  $\geq 60$  min. By longer or repeated contact the penetration times can be considerably shorter. The protective gloves should be replaced after the first wear out or a damage of the gloves. Gloves of cotton should be used under the gloves of polychloropren or nitrile rubber. After washing hands replace lost skin fat by fat containing skin creams.

##### Body protection

Using protective clothing. If the product must be sprayed, use a disposable protective suit.

### Respiratory protection

Breathing protection equipment is not required in good ventilated places. A respiratory protection (combination filter A2-P2) is required by inadequate ventilation and by spray application of the 2K-Product. Do not breathe gas or spray.

### General information

Avoid contact with eyes and skin. Immediately remove all contaminated clothing. Keep away from food, drink and animal feeding stuff. Do not eat or drink during work - no smoking. Keep working clothes separately. Ensure a good ventilation in room and working area. Do not breathe gas or spray. Dealing with the product is warned against at oversensitivity of the respiratory tract and the skin (asthma, chronic bronchitis or skin suffering).

### Environmental exposure controls

The product should not reach waters and the ground. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state :** Liquid.

**Colour :** conformable to product designation.

#### Odour

Poor, characteristic.

#### Safety characteristics

**Melting point/freezing point :** ( 1013 hPa )

No data available

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-Aqua Hardener 2380  
2K-Aqua Härter 2380  
Revision date : 13.06.2022  
Print date : 13.06.2022

Version (Revision) : 4.0.0 (3.0.1)

Initial boiling point and boiling range :	( 1013 hPa )	No data available	
Decomposition temperature :	( 1013 hPa )	No data available	
Flash point :	>	61	°C
Auto-ignition temperature :		431	°C
Lower explosion limit :		No data available	
Upper explosion limit :		No data available	
Vapour pressure :	( 50 °C )	No data available	
Density :	( 20 °C )	approx. 1,09 - 1,13	g/cm <sup>3</sup>
Solvent separation test :	( 20 °C )	not applicable	
Water solubility :	( 20 °C )	practically insoluble	
pH :		not applicable	
log P O/W :		No data available	
Flow time :	( 20 °C )	No data available	DIN-cup 4 mm
Viscosity :	( 20 °C )	No data available	
Kinematic viscosity :	( 40 °C )	No data available	
Relative vapour density :	( 20 °C )	No data available	
VOC-value :	max.	100	g/l
Flammable liquids :	The product is ignitable.		
Particle Characteristics :	not applicable		

## 9.2 Other information

The mentioned VOC value refers to the mixture of the product ready for use of tribe varnish and harder.  
Other physical and chemical data have not been determined.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangers connected by a possible reactivity of the product are known to proper handling and storage. Product is hardening with moisture.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

### 10.3 Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

### 10.4 Conditions to avoid

To avoid formation of ignitable vapour and air mixtures ensure good ventilation (inter alia extraction system). Keep away from frost, heat and direct sunlight.  
Avoid moisture.

### 10.5 Incompatible materials

No dangerous reaction known. Exothermic reaction with amines and alcohols. Reaction with water separate CO<sub>2</sub>. Build-up of pressure in closed containers. Danger that they might burst.

### 10.6 Hazardous decomposition products

No dangerous decomposition product are known if stored and handled correctly. When exposed to high temperatures may produce hazardous decomposition products such as carbon dioxide, carbon monoxide, smoke, nitric oxides or thick, black smoke.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Acute toxicity:

- Acute oral toxicity: No data available;
- Acute dermal toxicity: No data available;
- Acute inhalation toxicity: No data available.

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2K-Aqua Hardener 2380  
2K-Aqua Härter 2380  
**Revision date :** 13.06.2022  
**Print date :** 13.06.2022

**Version (Revision) :** 4.0.0 (3.0.1)

### Acute oral toxicity

Parameter : ATEmix calculated  
Exposure route : Oral  
Effective dose : not relevant  
Parameter : LD50 ( ALIPHATIC POLYISOCYANATE ; CAS No. : 666723-27-9 )  
Exposure route : Oral  
Species : Rat  
Effective dose : > 5000 mg/kg  
Parameter : LD50 ( HEXAMETHYLENE-1,6-DIISOCYANATE, HOMOPOLYMER ; CAS No. : 28182-81-2 )  
Exposure route : Oral  
Species : Rat  
Effective dose : > 5665 mg/kg  
Parameter : LD50 ( HEXAMETHYLENE-DI-ISOCYANATE ; CAS No. : 822-06-0 )  
Exposure route : Oral  
Species : Rat  
Effective dose : 710 mg/kg

### Acute dermal toxicity

Parameter : ATEmix calculated  
Exposure route : Dermal  
Effective dose : not relevant  
Parameter : LD50 ( HEXAMETHYLENE-1,6-DIISOCYANATE, HOMOPOLYMER ; CAS No. : 28182-81-2 )  
Exposure route : Dermal  
Species : Rat  
Effective dose : > 2000 mg/kg  
Parameter : LD50 ( HEXAMETHYLENE-DI-ISOCYANATE ; CAS No. : 822-06-0 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : 570 mg/kg

### Acute inhalation toxicity

Parameter : ATEmix calculated  
Exposure route : Inhalation (vapour)  
Effective dose : 13,8 mg/l  
Parameter : LC50 ( ALIPHATIC POLYISOCYANATE ; CAS No. : 666723-27-9 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 1,5 mg/l  
Parameter : ATEmix calculated ( HEXAMETHYLENE-1,6-DIISOCYANATE, HOMOPOLYMER ; CAS No. : 28182-81-2 )  
Exposure route : Inhalation (dust/mist)  
Effective dose : 1,5 mg/l  
Parameter : LC50 ( HEXAMETHYLENE-DI-ISOCYANATE ; CAS No. : 822-06-0 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 0,124 mg/l  
Exposure time : 4 h  
Parameter : LC50 ( HEXAMETHYLENE-DI-ISOCYANATE ; CAS No. : 822-06-0 )  
Exposure route : Inhalation  
Species : Mouse  
Effective dose : 1,57 mg/l

### Assessment/classification

Harmful by inhalation.

### Corrosion



# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2K-Aqua Hardener 2380  
2K-Aqua Härter 2380  
**Revision date :** 13.06.2022  
**Print date :** 13.06.2022

**Version (Revision) :** 4.0.0 (3.0.1)

### Irritation:

- To the skin: Repeated exposure may cause skin dryness or cracking.
- At the eye: May cause mild, short-lasting discomfort to eyes.
- Respiratory tract: May cause respiratory irritation.

### Respiratory or skin sensitisation

The product is labeled as skin sensitizing.

### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The product is not classified as human germ cell mutagenic, carcinogenic or human reproductive toxic (CMR effects).

### STOT-single exposure

No risk expected.

### STOT-repeated exposure

No risk expected.

### Aspiration hazard

No risk expected.

## 11.2 Information on other hazards

### Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

### Other adverse effects

This product is unlikely to harm health, given normal and proper handling and hygienic precautions. In the case of over-exposure, especially during spraying without taking protective measures: Danger of irritation to eyes, nose, throat and the air passages. Delayed appearance of the complaints and development of an oversensitivity (respiratory troubles, cough, asthma) possible. With oversensitive persons reactions can already be triggered at very low isocyanate concentration also below the MAK-value. Tanning and stimulus effects are possible at a longer touch with the skin.

### Additional information

The product is classified in toxicological terms on the basis of the results of the calculation procedure outlined within the Regulation (EC) No 1272/2008 (CLP-Regulation), listed in sections 2 and 3.

At proper dealing and use as agreed the product does not cause any effects bad for health after our experiences and the information submitted to us.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity

##### Acute (short-term) fish toxicity

Parameter :	LC50 ( ALIPHATIC POLYISOCYANATE ; CAS No. : 666723-27-9 )
Species :	Danio rerio (zebrafish)
Effective dose :	35,2 mg/l
Exposure time :	96 h
Parameter :	LC50 ( HEXAMETHYLENE-1,6-DIISOCYANATE, HOMOPOLYMER ; CAS No. : 28182-81-2 )
Species :	Danio rerio (zebrafish)
Effective dose :	> 100 mg/l
Exposure time :	96 h
Parameter :	LC50 ( HEXAMETHYLENE-DI-ISOCYANATE ; CAS No. : 822-06-0 )
Species :	Danio rerio (zebrafish)
Effective dose :	22 mg/l
Exposure time :	96 h

##### Acute (short-term) toxicity to crustacea

Parameter :	EC50 ( ALIPHATIC POLYISOCYANATE ; CAS No. : 666723-27-9 )
Species :	Daphnia magna (Big water flea)

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2K-Aqua Hardener 2380  
2K-Aqua Härter 2380  
**Revision date :** 13.06.2022  
**Print date :** 13.06.2022

**Version (Revision) :** 4.0.0 (3.0.1)

Effective dose : > 100 mg/l  
Exposure time : 48 h  
Parameter : EC50 ( HEXAMETHYLENE-1,6-DIISOCYANATE, HOMOPOLYMER ; CAS No. : 28182-81-2 )  
Species : Daphnia magna (Big water flea)  
Effective dose : > 100 mg/l  
Exposure time : 48 h

### Acute (short-term) toxicity to algae and cyanobacteria

Parameter : ErC50 ( ALIPHATIC POLYISOCYANATE ; CAS No. : 666723-27-9 )  
Species : Desmodesmus subspicatus  
Effective dose : 72 mg/l  
Exposure time : 72 h  
Parameter : ErC50 ( HEXAMETHYLENE-1,6-DIISOCYANATE, HOMOPOLYMER ; CAS No. : 28182-81-2 )  
Species : Scenedesmus subspicatus  
Effective dose : 50 - 100 mg/l  
Exposure time : 72 h

### Toxicity to microorganisms

Parameter : EC50 ( ALIPHATIC POLYISOCYANATE ; CAS No. : 666723-27-9 )  
Species : Mysisopsis bahia  
Effective dose : > 10000 mg/l  
Parameter : EC50 ( HEXAMETHYLENE-1,6-DIISOCYANATE, HOMOPOLYMER ; CAS No. : 28182-81-2 )  
Species : Mysisopsis bahia  
Effective dose : 5560 mg/l

## 12.2 Persistence and degradability

These are not data available about the potential of the product concerning his persistency and degradability.

## 12.3 Bioaccumulative potential

These are not data available about the bio accumulation potential of the product.

## 12.4 Mobility in soil

These are not datas available about the potential of the product concerning his mobility in the ground.  
A penetrating into soil, waters and sewage system should be prevented.

## 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6 Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

## 12.7 Other adverse effects

Harmful to aquatic life, may cause long-term adverse effects in the aquatic environment.

## 12.8 Additional ecotoxicological information

Avoid exposing into ground, waterways and drainage.  
The classification of the product is based on summation of classified components according to the Regulation (EC) No 1272/2008 (CLP-Regulation). See details in sections 2 and 3.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Directive 2008/98/EC (Waste Framework Directive)

##### Before intended use

Dispose of contents/container to approved disposal company or local collection according to the local regulations.  
Packaging with not dry uped residues have to dropped at official collecting sites. Packaging with dry uped residues can be disposed together with household garbage or building site garbage. Do not empty into waters or drains.

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2K-Aqua Hardener 2380  
2K-Aqua Härter 2380  
**Revision date :** 13.06.2022  
**Print date :** 13.06.2022

**Version (Revision) :** 4.0.0 (3.0.1)

### Waste codes/waste designations according to EWC/AVV

For the product:  
Disposal-definition No.: 08 01 11\* - Paint and varnish waste which contains organic solvents or other dangerous substances.

### After intended use

Only empty packaging can be transferred to recycling. Uncleaned packaging must be disposed of in the same manner as the medium.

### Waste codes/waste designations according to EWC/AVV

For the uncleaned packaging:  
Disposal-definition No.: 15 01 10 \* packings which contain dangerous substances or are polluted by dangerous substances.

## SECTION 14: Transport information

### 14.1 UN number

No dangerous good in sense of these transport regulations.

### 14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

### 14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

### 14.4 Packing group

No dangerous good in sense of these transport regulations.

### 14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

### 14.6 Special precautions for user

None

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant because the product in type of delivery does not transport in bulks according to the International Maritime Organization (IMO) instruments.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

##### Authorisations and/or restrictions on use

##### Restrictions on use

##### Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions):

Use restriction according to REACH annex XVII, no. : 3, 74, 75

##### Other regulations (EU)

##### Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

Product sub-category and VOC limiting values in accordance with appendix II, letter A of the guideline:

Category j, type WB;

VOC limiting value of the category for 2010: 140 g/l.

This product contains max. 100 g/l VOC.

The mentioned VOC value refers to the mixture of the product ready for use of tribe varnish and harder.

##### National regulations

##### Water hazard class

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

##### Additional information

The product is not classified as a solid substance according to the criteria of the Penetrometer test (ADR, part 2,

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2K-Aqua Hardener 2380  
2K-Aqua Härter 2380  
**Revision date :** 13.06.2022  
**Print date :** 13.06.2022

**Version (Revision) :** 4.0.0 (3.0.1)

section 2.3.4) and also fulfils not the criteria for solid substances according to the TRwS 779 number 2.1.1.  
Maternity regulations and Young Persons Employment Act are to take into account.

### 15.2 Chemical Safety Assessment

A chemical safety assessments was not carried out.

## SECTION 16: Other information

### 16.1 Indication of changes

None

### 16.2 Abbreviations and acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)  
ADR: European agreement concerning the international carriage of dangerous goods by road (Accord européen relatif transport des marchandises dangereuses par route)  
AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany) AOX: Adsorbable Organic halogen compounds  
ATEmix: Calculated acute toxicity estimate of mixture  
BCF: Bio-Concentration Factor  
CAS: Chemical Abstract Service  
CLP: Classification, Labelling and Packaging  
CMR: Substances classified as Carcinogenic, Mutagenic or toxic for Reproduction  
CSR: Chemical Safety Report  
DNEL: Derived No Effect Level  
EC: European Commission  
EC50: Effective Concentration 50%  
ECHA: European Chemical Agency  
EEC: European Economic Community  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
EWC: European Waste Catalogue  
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organization  
IC50: Inhibition Concentration 50%  
IMDG Code: International Maritime Dangerous Goods Code  
IMO: International Maritime Organization  
LC50: Lethal concentration 50%  
LD50: Lethal Dose 50%  
LOAEL: Lowest Observed Adverse Effect Level  
LOEL: Lowest observable effect level  
MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG)  
MARPOL: Convention for the Prevention of Marine Pollution from Ships  
MVZ: molar ratio  
n.a.: Not applicable  
n.d.: Not determined  
n.r.: Not relevant  
NLP: No Longer Polymers  
NOAEC: No Observed Adverse Effect Concentration  
NOAEL: No Observed Adverse Effect Level  
NOEC: No Observed Effect Concentration  
NOEL: No Observed Effect Level  
OEL: Occupational Exposure Limit  
PBT: Persistent, bioaccumulative, toxic  
PNEC: Predicted No Effect Concentration  
RCP: Reciprocal calculation procedure  
REACH: Registration, Evaluation and Authorization of Chemical  
RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2K-Aqua Hardener 2380  
2K-Aqua Härter 2380  
**Revision date :** 13.06.2022  
**Print date :** 13.06.2022

**Version (Revision) :** 4.0.0 (3.0.1)

le transport de marchandises dangereuses par chemin de fer)  
STEL: Short-term Exposure Limit  
SVHC: Substance of Very High Concern  
TLV - TWA: Threshold Limit Value - Time Weighted Average  
VOC: Volatile Organic Compounds  
vPvB: Very persistent, very bioaccumulative.

### 16.3 Key literature references and sources for data

None

### 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The evaluation of hazard information of the product was carried out in accordance to Annex I of the REGULATION (EC) No 1272/2008 (CLP Regulation).

### 16.5 Relevant H- and EUH-phrases (Number and full text)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

### 16.6 Training advice

None

### 16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.