

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Rausan KR K2 3516 - Protect Quality
Rausan KR K2 3516 - Protect-Qualität

Revision date : 23.08.2021

Print date : 23.08.2021

Version (Revision) : 18.0.0 (17.0.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Rausan KR K2 3516 - Protect Quality
Rausan KR K2 3516 - Protect-Qualität

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Products Category [PC]

PC9 - Coatings and paints, fillers, putties, thinners

Uses advised against

There are no information about relevant identified uses of the product according to the Regulation (EC) No. 1907/2006 (REACH-Regulation), which are advised against. For using the product observe the information in the Technical data sheet of the product.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Brillux GmbH & Co KG
www.brillux.de

Street : Weseler Straße 401

Postal code/city : D - 48163 Münster

Telephone : +49 (0)251-7188-0

Telefax : +49 (0)251-7188-280

Information contact :

Electronic mail address of the well-informed person for safety data sheets:sdb@brillux.de

1.4 Emergency telephone number

Outside the business hours (9 a.m. to 5 p.m.):

(Giftinformationszentrum-Nord, Göttingen, consultation in german or english language)

Telephone: +49 (0)551-19240.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Chronic 3 ; Harmful to aquatic life with long lasting effects.

Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Exclamation mark (GHS07)

Signal word

Warning

Hazard components for labelling

1,2-BENZISOTHIAZOL-3(2H)-ONE ; CAS No. : 2634-33-5

TERBUTRYN ; CAS No. : 886-50-0

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Rausan KR K2 3516 - Protect Quality
Rausan KR K2 3516 - Protect-Qualität

Revision date : 23.08.2021

Print date : 23.08.2021

Version (Revision) : 18.0.0 (17.0.0)

2-OCTYL-2H-ISOTHIAZOL-3-ONE ; CAS No. : 26530-20-1

Hazard statements

H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
P261 Avoid breathing vapours.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P501 Dispose of contents/container to approved disposal company or local collection.

Special rules for supplemental label elements for certain mixtures

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Adverse environmental effects

The product does not contain any substances, which fulfil the criteria for PBT or vPvB in accordance with the Annex XIII of the Regulation (EC) No 1907/2006 (REACH-Regulation).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description

Dispersion plaster.

Composition:

Vinylacetate-ethylene-copolymer-dispersion, titanium dioxide (depending on the shade), inorganic/organic coloured pigments (depending on the shade), dolomite, calcium carbonate, mineral extenders, polymer extender, water, additives, preservatives for film protection and preservatives (benzisothiazolinone and pyrrithione zinc).

Hazardous ingredients

TITANIUM DIOXIDE ; EC No. : 236-675-5; CAS No. : 13463-67-7

Weight fraction : $\geq 1 - < 5 \%$
Classification 1272/2008 [CLP] : Carc. 2 ; H351i

ZINC PYRITHIONE ; REACH No. : 01-2119511196-46 ; EC No. : 236-671-3; CAS No. : 13463-41-7 (M Acute=1000) (M Chronic=10)

Weight fraction : $\geq 0,0025 - < 0,025 \%$
Classification 1272/2008 [CLP] : Acute Tox. 2 ; H330 Acute Tox. 3 ; H301 Repr. 1B ; H360D STOT RE 1 ; H372 Eye Dam. 1 ; H318 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

1,2-BENZISOTHIAZOL-3(2H)-ONE ; EC No. : 220-120-9; CAS No. : 2634-33-5 (M Acute=1)

Weight fraction : $\geq 0,005 - < 0,05 \%$
Classification 1272/2008 [CLP] : Acute Tox. 2 ; H330 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 2 ; H411

TERBUTRYN ; EC No. : 212-950-5; CAS No. : 886-50-0 (M=100)

Weight fraction : $\geq 0,0025 - < 0,025 \%$
Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Skin Sens. 1B ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

2-OCTYL-2H-ISOTHIAZOL-3-ONE ; EC No. : 247-761-7; CAS No. : 26530-20-1 (M=100)

Weight fraction : $\geq 0,0025 - < 0,025 \%$
Classification 1272/2008 [CLP] : Acute Tox. 3 ; H301 Acute Tox. 3 ; H311 Acute Tox. 3 ; H331 Skin Corr. 1 ; H314 Eye Dam. 1 ; H318 Skin Sens. 1A ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

Additional information

Full text of H- and EUH-phrases: see section 16.

Trade name : Rausan KR K2 3516 - Protect Quality
Rausan KR K2 3516 - Protect-Qualität
Revision date : 23.08.2021
Print date : 23.08.2021

Version (Revision) : 18.0.0 (17.0.0)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Immediately remove all contaminated clothing. If unconscious no administration by mouth, storage in recovery position and seek medical advice. If medical advice is needed, have product container or label at hand.

Following inhalation

When symptoms persists, take the casualty into the fresh air and keep warm. Irregular breathing/no breathing: artificial respiration.

In case of skin contact

Take off immediately all contaminated clothes. Wash away with soap and water and rinse. Do NOT use solvents or thinners. If skin irritation continues, consult a doctor.

After eye contact

Remove contact lenses, keep eyelids open. Rinse open eye immediately with plenty of running water. Seek medical advice if complaint continues.

After ingestion

Drink water in small draught. Keep at rest. Do not induce vomiting. When swallowed immediately consult and show packing or label to physician.

4.2 Most important symptoms and effects, both acute and delayed

Allergic symptoms.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

This product is not flammable. In case of a fire extinguish surroundings as indicated.

Unsuitable extinguishing media

None known.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters

When extinguishing fires, use breathing apparatus with an independent source of air.

5.4 Additional information

Cool endangered containers with water in case of fire. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Refer to protective measures listed in sections 7 and 8. The product produced in combination with water slippery surfaces.

6.2 Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations. Holding polluted washing water back and disposing of duly.

Trade name : Rausan KR K2 3516 - Protect Quality
Rausan KR K2 3516 - Protect-Qualität
Revision date : 23.08.2021
Print date : 23.08.2021

Version (Revision) : 18.0.0 (17.0.0)

6.3 Methods and material for containment and cleaning up

For cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Remove residue by rinsing thoroughly with water. Thoroughly clean contaminated objects and floors and observe environmental regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.
You find information about the safety equipment of persons in the section 8,
information about the refuse disposal in section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

No special measures necessary in the case of regulation storage and handling. Ensure a good ventilation in room and working area. For personal protection see Section 8. Keep out of reach of children. Read label before use.

Measures to prevent fire

This product is not flammable. Cool endangered containers with water.

Advices on general occupational hygiene

While working do not eat, drink or smoke. Wash hands and face before breaks and after work and take a shower if necessary. Immediately remove all contaminated clothing.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly in a dry, cool and good ventilated place. Do not store the product in lounge room. Keep only in the original container. Protect against frost. Keep out of the reach of children.

Hints on joint storage

Store away from foodstuffs.

Storage class (TRGS 510) : 12

Further information on storage conditions

Keep container tightly sealed. Store at 5°-35°C. Containers should be kept dry and sealed.

7.3 Specific end use(s)

For using the product observe the information in the Technical data sheet of the product.

Industrial sector specific solutions

GISCODE : Product code in accordance with GISBAU (hazardous materials information system of the German professional associations of the building and construction industry) for colours and varnishes (GISCODE): BSW50

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

None

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.
Observe data available of section 7.

Personal protection equipment

Eye/face protection

Use protection glasses in case of spattering.

Skin protection

Hand protection

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Rausan KR K2 3516 - Protect Quality
Rausan KR K2 3516 - Protect-Qualität

Revision date : 23.08.2021

Print date : 23.08.2021

Version (Revision) : 18.0.0 (17.0.0)

At use as agreed a protective gloves from nitrile rubber, tested according to EN 374, with a material thickness 0,38 mm has to be used. Notes of the manufacturer have to be taken into account. Penetration time of the glove material: > = 8 h.

By longer or repeated contact the penetration times can be considerably shorter. The protective gloves should be replaced after the first wear out or a damage of the gloves. Gloves of cotton should be used under the gloves of polychloropren or nitrile rubber. After washing hands replace lost skin fat by fat containing skin creams.

Body protection

Using protective clothing.

Respiratory protection

At a processing of the product a respiratory protection is not necessary. Do not inhale the vapour.

General information

Avoid contact with eyes and skin. Immediately remove all contaminated clothing. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Ensure a good ventilation in room and working area. Do not breathe vapour.

Environmental exposure controls

The product should not reach waters and the ground. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Pasty.

Colour : conformable to product designation.

Odour

Characteristic.

Safety characteristics

Initial boiling point and boiling range :	(1013 hPa)		not applicable	
Flash point :			not applicable	
Auto-ignition temperature :			not applicable	
Vapour pressure :	(50 °C)		not determined	
Density :	(20 °C)	approx.	1,85 - 1,95	g/cm ³
Solvent separation test :	(20 °C)		not applicable	
pH :		approx.	8 - 9	
Flow time :	(20 °C)		not applicable	DIN-cup 4 mm
Viscosity :	(20 °C)		pasty	
VOC-value :		max.	1	g/l

9.2 Other information

Other physical and chemical data have not been determined.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangers connected by a possible reactivity of the product are known to proper handling and storage.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

No dangerous reactions are known if stored and handled the product correctly.

10.4 Conditions to avoid

Keep away from frost, heat and direct sunlight.

10.5 Incompatible materials

Trade name : Rausan KR K2 3516 - Protect Quality
Rausan KR K2 3516 - Protect-Qualität
Revision date : 23.08.2021
Print date : 23.08.2021

Version (Revision) : 18.0.0 (17.0.0)

No dangerous reaction known. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

No dangerous decomposition product are known if stored and handled correctly. When exposed to high temperatures or in case of fire hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen, may produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute toxicity:

- Acute oral toxicity: No data available;
- Acute dermal toxicity: No data available;
- Acute inhalation toxicity: No data available.

Acute oral toxicity

Parameter :	ATEmix calculated
Exposure route :	Oral
Effective dose :	not relevant
Parameter :	LD50 (ZINC PYRITHIONE ; CAS No. : 13463-41-7)
Exposure route :	Oral
Species :	Rat
Effective dose :	200 mg/kg
Parameter :	LD50 (1,2-BENZISOTHIAZOL-3(2H)-ONE ; CAS No. : 2634-33-5)
Exposure route :	Oral
Species :	Rat
Effective dose :	532 mg/kg
Parameter :	LD50 (TERBUTRYN ; CAS No. : 886-50-0)
Exposure route :	Oral
Species :	Rat
Effective dose :	500 mg/kg
Parameter :	LD50 (2-OCTYL-2H-ISOTHIAZOL-3-ONE ; CAS No. : 26530-20-1)
Exposure route :	Oral
Species :	Rat
Effective dose :	> 500 mg/kg

Acute dermal toxicity

Parameter :	ATEmix calculated
Exposure route :	Dermal
Effective dose :	not relevant
Parameter :	LD50 (ZINC PYRITHIONE ; CAS No. : 13463-41-7)
Exposure route :	Dermal
Species :	Rat
Effective dose :	> 2000 mg/kg
Parameter :	LD50 (1,2-BENZISOTHIAZOL-3(2H)-ONE ; CAS No. : 2634-33-5)
Exposure route :	Dermal
Species :	Rat
Effective dose :	> 2000 mg/kg
Parameter :	LD50 (TERBUTRYN ; CAS No. : 886-50-0)
Exposure route :	Dermal
Species :	Rat
Effective dose :	> 2000 mg/kg
Parameter :	LD50 (2-OCTYL-2H-ISOTHIAZOL-3-ONE ; CAS No. : 26530-20-1)
Exposure route :	Dermal
Species :	Rat
Effective dose :	> 900 mg/kg

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Rausan KR K2 3516 - Protect Quality
Rausan KR K2 3516 - Protect-Qualität

Revision date : 23.08.2021

Print date : 23.08.2021

Version (Revision) : 18.0.0 (17.0.0)

Acute inhalation toxicity

Parameter : ATEmix calculated
Exposure route : Inhalation (vapour)
Effective dose : not relevant

Parameter : LC50 (ZINC PYRITHIONE ; CAS No. : 13463-41-7)
Exposure route : Inhalation
Effective dose : 0,5 mg/l
Exposure time : 4 h

Parameter : LC50 (1,2-BENZISOTHIAZOL-3(2H)-ONE ; CAS No. : 2634-33-5)
Exposure route : Inhalation
Species : Rat
Effective dose : 0,4 mg/l
Exposure time : 4 h

Parameter : LC50 (TERBUTRYN ; CAS No. : 886-50-0)
Exposure route : Inhalation
Species : Rat
Effective dose : 5,21 mg/l
Exposure time : 4 h

Parameter : LC50 (2-OCTYL-2H-ISOTHIAZOL-3-ONE ; CAS No. : 26530-20-1)
Exposure route : Inhalation
Species : Rat
Effective dose : 0,27 mg/l
Exposure time : 4 h

Corrosion

- To the skin: Not expecting any damage or irritancy.
- At the eye: Not expecting any damage or irritancy.

Respiratory or skin sensitisation

The product contains sensitizing substances, which may produce an allergic reaction (see section 2 and 3).

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The product is not classified as human germ cell mutagenic, carcinogenic or human reproductive toxic (CMR effects).

STOT-single exposure

No risk expected.

STOT-repeated exposure

No risk expected.

Aspiration hazard

No risk expected.

11.4 Other adverse effects

Other observations

This product is unlikely to harm health, given normal and proper handling and hygienic precautions.

11.5 Additional information

The product is classified in toxicological terms on the basis of the results of the calculation procedure outlined within the Regulation (EC) No 1272/2008 (CLP-Regulation), listed in sections 2 and 3.

At proper dealing and use as agreed the product does not cause any effects bad for health after our experiences and the information submitted to us.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter : LC50 (ZINC PYRITHIONE ; CAS No. : 13463-41-7)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Rausan KR K2 3516 - Protect Quality
Rausan KR K2 3516 - Protect-Qualität

Revision date : 23.08.2021

Print date : 23.08.2021

Version (Revision) : 18.0.0 (17.0.0)

Species : Brachydanio rerio (zebra-fish)
Effective dose : 0,0104 mg/l
Exposure time : 96 h
Parameter : LC50 (TERBUTRYN ; CAS No. : 886-50-0)
Species : Brachydanio rerio (zebra-fish)
Effective dose : 1,8 mg/l
Exposure time : 96 h
Parameter : LC50 (2-OCTYL-2H-ISOTHIAZOL-3-ONE ; CAS No. : 26530-20-1)
Species : Oncorhynchus mykiss (Rainbow trout)
Effective dose : 0,036 mg/l
Exposure time : 96 h

Chronic (long-term) fish toxicity

Parameter : NOEC (ZINC PYRITHIONE ; CAS No. : 13463-41-7)
Species : Brachydanio rerio (zebra-fish)
Effective dose : 0,00125 mg/l
Parameter : NOEC (2-OCTYL-2H-ISOTHIAZOL-3-ONE ; CAS No. : 26530-20-1)
Species : Oncorhynchus mykiss (Rainbow trout)
Effective dose : 0,022 mg/l
Exposure time : 28 D

Acute (short-term) toxicity to crustacea

Parameter : EC50 (ZINC PYRITHIONE ; CAS No. : 13463-41-7)
Species : Daphnia magna (Big water flea)
Effective dose : 0,051 mg/l
Exposure time : 48 h
Parameter : EC50 (TERBUTRYN ; CAS No. : 886-50-0)
Species : Daphnia magna (Big water flea)
Effective dose : 7,1 mg/l
Exposure time : 48 h
Parameter : EC50 (2-OCTYL-2H-ISOTHIAZOL-3-ONE ; CAS No. : 26530-20-1)
Species : Daphnia magna (Big water flea)
Effective dose : 0,42 mg/l
Exposure time : 48 h

Chronic (long-term) toxicity to crustacea

Parameter : NOEC (ZINC PYRITHIONE ; CAS No. : 13463-41-7)
Species : Daphnia magna (Big water flea)
Effective dose : 0,00213 mg/l
Exposure time : 21 D
Parameter : NOEC (2-OCTYL-2H-ISOTHIAZOL-3-ONE ; CAS No. : 26530-20-1)
Species : Daphnia magna (Big water flea)
Effective dose : 0,002 mg/l
Exposure time : 21 D

Acute (short-term) toxicity to aquatic algae and cyanobacteria

Parameter : EC50 (ZINC PYRITHIONE ; CAS No. : 13463-41-7)
Species : Pseudokirchneriella subcapitata
Effective dose : 0,051 mg/l
Exposure time : 72 h
Parameter : EC50 (TERBUTRYN ; CAS No. : 886-50-0)
Species : Pseudokirchneriella subcapitata
Effective dose : 0,104 mg/l
Exposure time : 72 h
Parameter : IC50 (TERBUTRYN ; CAS No. : 886-50-0)
Species : Scenedesmus capricornutum
Effective dose : 0,0055 mg/l
Exposure time : 72 h
Parameter : EC50 (2-OCTYL-2H-ISOTHIAZOL-3-ONE ; CAS No. : 26530-20-1)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Rausan KR K2 3516 - Protect Quality
Rausan KR K2 3516 - Protect-Qualität

Revision date : 23.08.2021

Print date : 23.08.2021

Version (Revision) : 18.0.0 (17.0.0)

Species : Scenedesmus subspicatus
Effective dose : 0,084 mg/l
Exposure time : 72 h

Chronic (long-term) algae toxicity

Parameter : NOEC (ZINC PYRITHIONE ; CAS No. : 13463-41-7)
Species : Pseudokirchneriella subcapitata
Effective dose : 0,0149 mg/l
Exposure time : 72 h
Parameter : NOEC (2-OCTYL-2H-ISOTHIAZOL-3-ONE ; CAS No. : 26530-20-1)
Species : Chronic (long-term) algae toxicity
Effective dose : 0,004 mg/l
Exposure time : 72 h

12.2 Persistence and degradability

These are not data available about the potential of the product concerning his persistency and degradability.

12.3 Bioaccumulative potential

These are not data available about the bio accumulation potential of the product.
No information about the individual components is available either.

12.4 Mobility in soil

These are not datas available about the potential of the product concerning his mobility in the ground.
A penetrating into soil, waters and sewage system should be prevented.

12.5 Results of PBT and vPvB assessment

This product does not contain any relevant substances which were classified as a PBT or vPvB-substance.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

Avoid exposing into ground, waterways and drainage.
The classification of the product is based on summation of classified components according to the Regulation (EC) No 1272/2008 (CLP-Regulation). See details in sections 2 and 3.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

Disposal-definition No. (AVV-Code): 08 01 12 Paint and varnish waste with the exception of the ones who come under 08 01 11 *.

Waste treatment options

Appropriate disposal / Product

Packaging with not dry uped residues have to dropped at official collecting sites. Do not empty into waters or drains.
Packaging with dry uped residues can be disposed together with household garbage or building site garbage.

Appropriate disposal / Package

Only empty packaging can be transfered to recycling. Uncleaned packaging must be disposed of in the same manner as the medium.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Rausan KR K2 3516 - Protect Quality
Rausan KR K2 3516 - Protect-Qualität

Revision date : 23.08.2021

Print date : 23.08.2021

Version (Revision) : 18.0.0 (17.0.0)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant because the product in type of delivery does not transport in bulks according to the International Maritime Organization (IMO) instruments.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Other regulations (EU)

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

The product is not subject to the EU guideline 2004/42/EC about the limitation of the emissions of volatile organic compounds due to the use of organic solvents in certain colours and varnishes.

This product contains max. 1 g/l VOC.

National regulations

Water hazard class (WGK)

Class : 2 (Obviously hazardous to water) Classification according to AWSV

Additional information

The product is classified as a solid substance according to the criteria of the Penetrometer test (ADR, part 2, section 2.3.4) and also fulfils the criteria for solid substances according to the TRwS 779 number 2.1.1.

15.2 Chemical safety assessment

A chemical safety assessment was not carried out.

SECTION 16: Other information

16.1 Indication of changes

02. Classification of the substance or mixture · 02. Label elements · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling · 02. Special rules for supplemental label elements for certain mixtures · 15. Water hazard class (WGK)

16.2 Abbreviations and acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

ADR: European agreement concerning the international carriage of dangerous goods by road (Accord européen relatif au transport des marchandises dangereuses par route)

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany) AOX: Adsorbable Organic halogen compounds

ATEmix: Calculated acute toxicity estimate of mixture

BCF: Bio-Concentration Factor

CAS: Chemical Abstract Service

CLP: Classification, Labelling and Packaging

CMR: Substances classified as Carcinogenic, Mutagenic or toxic for Reproduction

CSR: Chemical Safety Report

DNEL: Derived No Effect Level

EC: European Commission

EC50: Effective Concentration 50%

ECHA: European Chemical Agency

EEC: European Economic Community

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Rausan KR K2 3516 - Protect Quality
Rausan KR K2 3516 - Protect-Qualität

Revision date : 23.08.2021

Version (Revision) : 18.0.0 (17.0.0)

Print date : 23.08.2021

INECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
EWC: European Waste Catalogue
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
IC50: Inhibition Concentration 50%
IMDG Code: International Maritime Dangerous Goods Code
IMO: International Maritime Organization
LC50: Lethal concentration 50%
LD50: Lethal Dose 50%
LOAEL: Lowest Observed Adverse Effect Level
LOEL: Lowest observable effect level
MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG)
MARPOL: Convention for the Prevention of Marine Pollution from Ships
MVZ: molar ratio
n.a.: Not applicable
n.d.: Not determined
n.r.: Not relevant
NLP: No Longer Polymers
NOAEC: No Observed Adverse Effect Concentration
NOAEL: No Observed Adverse Effect Level
NOEC: No Observed Effect Concentration
NOEL: No Observed Effect Level
OEL: Occupational Exposure Limit
PBT: Persistent, bioaccumulative, toxic
PNEC: Predicted No Effect Concentration
RCP: Reciprocal calculation procedure
REACH: Registration, Evaluation and Authorization of Chemical)
RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer)
STEL: Short-term Exposure Limit
SVHC: Substance of Very High Concern
TLV - TWA: Threshold Limit Value - Time Weighted Average
VOC: Volatile Organic Compounds
vPvB: Very persistent, very bioaccumulative.

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The evaluation of hazard information of the product was carried out in accordance to Annex I of the REGULATION (EC) No 1272/2008 (CLP Regulation).

16.5 Relevant H- and EUH-phrases (Number and full text)

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H351i	Suspected of causing cancer if inhaled.
H360D	May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Rausan KR K2 3516 - Protect Quality
Rausan KR K2 3516 - Protect-Qualität
Revision date : 23.08.2021
Print date : 23.08.2021

Version (Revision) : 18.0.0 (17.0.0)

H411 Toxic to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
