Data Sheet

Universal Thinner 432

For thinning synthetic enamels



Field of application

For consistency regulation for improved application of synthetic enamels, e.g. MP Thick Film 229, with brush and roller. Also suitable for cleaning the required tools and for removing tough enamel soiling.

Properties

Intense-acting solvent, predominantly for thinning synthetic enamels.

Material description

Color shade colorless

Base material Solvent mixture based on hydrocarbons and esters.

Constituent substances Aromatic hydrocarbons, C9–C10 and butyl acetate

en Date: 24.04.2017

VOC value max. 880 g/l

Flash point +47 °C

Density approx. 0.78 g/cm³

Packaging 500 ml, 1 l, 5 l and 30 l

Use

Add the relevant product in the specified mixing ratio depending on the individual requirements and mix thoroughly. Follow the more detailed instructions on the viscosity setting in the individual data sheets.

Storage

Store in a cool and dry location. Protect from direct sunlight.



Declaration

Product code M-VM04.

Comply with the specifications in the current Safety Data Sheet.

Notes

Mask surfaces

Carefully mask the surrounding area and particularly sensitive materials.

Further information

Follow the instructions in the data sheets of the products used.

Remark

This Data Sheet has been prepared taking into account the current applicable German laws, standards, specifications and codes of practice. All details have been translated from the current German version. The contents do not form a legal contract. The user and/or the purchaser is not released from the responsibility of checking that our products are suitable for the proposed use. In addition our Terms of Conditions and Payment apply.

When a new version of this Data Sheet with updated information is published, the previous version no longer applies. The current version is available on our website.

Brillux Weseler Straße 401 48163 Münster Germany Phone +49 251 7188-0 Fax +49 251 7188-105 info@brillux.de www.brillux.com

