



Future Trajectories in Digital Twin Research: Architectures, Data Pipelines, and Security Challenges for Communication and Networked Systems

Journal:	<i>ITU Journal on Future and Evolving Technologies</i>
Manuscript ID	Draft
Manuscript Type:	Special issue article
Date Submitted by the Author:	n/a
Complete List of Authors:	Khan, Mohsin ; Pranveer Singh Institute of Technology, Department of AIML PSIT DIXIT, VIMAL; Pranveer Singh Institute of Technology, Department of CSE PSIT Misra, Shreshtha ; Axis Colleges, Department of CSE AITM
Keywords:	Digital twin, DTN, DITEN, IoDT, 6G, IIoT



Future Trajectories in Digital Twin Research: Architectures, Data Pipelines, and Security Challenges for Communication and Networked Systems

Mohsin Khan
Department of AIML
PSIT, Kanpur, India
Mohsinkhanaiml@gmail.com

Vimal Dixit
Department of CSE
PSIT, Kanpur, India
vimal.dixit@psit.ac.in

Shreshtha Misra
Department of CSE
AITM, Kanpur, India
shreshthamisra@axiscolleges.in

Abstract—Digital twins (DTs) have rapidly grown from abstract prototypes into critical supports for communication and networked systems. They support real-time monitoring, predictive analytics, and closed-loop control across wireless networks, Industrial Internet of Things (IIoT), and edge-cloud infrastructures. While progress has been achieved, fundamental challenges remain unresolved, including the persistent gap between physics-based and data-driven modelling, latency and model fidelity in twin synchronization, and the growing divergence between security threat landscapes and defensive mechanisms. This paper combines insights from recent literature spanning 2018–2026 to present observations showing systemic patterns, recurring bottlenecks, and emerging opportunities in DT research. It consist an integrated classification of DT architectures, data pipelines, modelling standards, and security modules across domains. The analysis identifies limitations in hybrid modelling, synchronization, performance metrics, security, physical-digital binding, cross-domain architectural patterns, and fragmented standardization, and provides a structured roadmap for robust, interoperable, and secure deployments in next-generation networked environments.

Index Terms—Digital twin, DTN, DITEN, IoDT, 6G, IIoT, hybrid modelling, security, standardization, edge-cloud

I. INTRODUCTION

Digital twin (DT) is a digital replica of a physical asset, process or system that is continuously updated to support monitoring, prediction, optimization and control [1], [13], [19], which has been gradually evolving from an academic concept to an important enabler for modern communication and networked systems. Initially it is developed for managing product lifecycles in the aerospace domain, its applications have been extended to wireless and sixth-generation (6G) networks, Industrial Internet of Things (IIoT) platforms, edge-cloud systems and large-scale frameworks such as Digital Twin Networks (DTNs), Digital Twin Edge Networks (DITENs) and the Internet of Digital Twins (IoDTs) [1], [13], [19]. There is Fast Integration of artificial intelligence (AI), machine learning (ML), and advanced sensor technologies which has further expand by the potential of DTs. It has enabling the predictive

maintenance, scenario generation, and autonomous decision-making across Systems [5], [10], [12].

However, as the scope and aim of DT deployments expand, a set of fundamental challenges has ap. here as the Recent surveys [1], [7], [8], [37] which was consistently highlight that DTs must handle heterogeneous, high-rate data streams from diverse sources while maintaining the strict synchronization fidelity under stringent latency and reliability constraints. The implementation of physics-based models with data-driven approaches are remains theoretically adapting but practically breakout, with no combined framework governing their composition [4], [14], [17]. Furthermore, the security landscape for DTs is evolving faster than defensive mechanisms can adapt; threat models specific to DTs, DTNs, and IoDTs are still developed, and the binding between physical assets and their digital equivalant is open to identity phising, data manipulation, and cascade failures [6], [38]. Similar efforts, while active, remain distribute across multiple organizations with limited connectivity guarantees [19], [36].

This paper addresses these gaps by understanding the insights from a comprehensive body of literature spanning 2018–2026, which encompassing survey papers, integrated studies, and domain-specific applications across the manufacturing, healthcare, smart cities, energy, agriculture, and networked systems. Rather than presenting yet another conventional survey, we adopt an observation-driven approach: we identify seven key observations that reveal systemic patterns and recurring bottlenecks in current DT research, supported by comparative analysis across domains and architectural dimensions. Our contributions are as follows:

- 1) We have propose a classification that classifies DT architectures, data pipelines, modelling paradigms, and security frameworks and providing a structured lens for cross-domain analysis (Section III).
- 2) We are presenting the seven key observations with supporting evidence from the literature, identifying systemic challenges and emerging opportunities (Sections IV and V).

3) We have articulated the concrete future research directions with a structured roadmap for advancing DT systems (Section VII).

The remainder of this paper is organized as follows. Section II which provides background and evolution context. Section III which presents our proposed taxonomy. Section IV discusses about observations related to data, modelling, and learning. Section V focuses on the security, privacy, and trust. Section VI examines the applications and standardization landscape from the classification. Section VII outlines future research directions. Section VIII concludes the paper.

II. BACKGROUND AND EVOLUTION OF DIGITAL TWINS

While Grieves officially has coined the term “digital twin” in 2002 to describe a virtual information space within the Product Lifecycle Management [37], the concept of DNA which reaches back to the high-stakes engineering of NASA’s Apollo program. Therefore, Earth-bound mirror systems were used to simulate spacecraft elementary in real-time—precursor to the modern live-sync replica. Broadly speaking, the technological journey of Digital Twins (DT) has unfolded across four distinct epochs, which was moving from static design tools to intelligent, self-governing networks.

Stage 1: The Era of the Static Mock-ups (Pre-2010). Before 2010, DTs were essentially indulge the design validation models. These precursors operated offline and lacked any meaningful pulse of real-time data from their physical counterparts. It has Confined mostly to the aerospace and automotive sectors, their utility was strictly predictive in the pre-deployment and sense—useful for stress-testing a design but unable to mirror a product’s actual life cycle once it has been hit the field. The primary hurdle then has not been in a vision, but there is lack of infrastructure to sustain a continuous data link.

Stage 2: Sensing and Diagnosis (2010–2018). The mid-2010s saw a massive shift as IoT sensor density and cloud scalability has finally caught up with the theory. Following up with the NASA’s formal 2012 definition, industries began to adopts twins that could ingest live operational data. This era shifted the focus from “what might happen” to “what is happening now,” which allowing for real-time anomaly detection and state monitoring. A key example from this period is the interactive twin developed for assembly training [33], which has successfully bridged the gap between the operational awareness and the raw sensor feeds.

Stage 3: Predictive Power and Prescriptive Action (2018–2023). The infusion of AI and machine learning has marked up a significant departure from simple monitoring system. DTs evolved from passive mirrors into active advisors which was capable of forecasting failure modes and recommending interventions. We have saw this play out across diverse fields—from optimizing smart factories [20], [27] and managing energy grids [26], [31] to personalized healthcare [12], [22]. During this window, researchers also began exploring network-level orchestration, giving rise to Digital Twin Net-




Fig. 1. Evolution of digital twin technology across four stages, showing enabling technologies and synchronization capability progression.

works (DTN) that could manage resources across edge-to-cloud continuums [13], [19].

Stage 4: Autonomous Ecosystems and the 6G Future (2023–Present). Today, we are moving toward autonomous DT ecosystems where human intervention is the exception rather than the rule. These systems leverage the 5G/6G protocols and has federated learning to negotiate and coordinate actions within Internet of Digital Twins (IoDT) frameworks. There is Current research on distributed 6G management [10], [13], [14] and ITU-T standards [19] which was highlights this trajectory. Yet, this high-speed, autonomous future brings a new set of headaches, particularly it has concerning cross-platform interoperability, large-scale security, and the share computational overhead of synchronized global ecosystems.

Fig. 1 illustrates this evolutionary trajectory, highlighting the enabling technologies and persistent challenges at each stage.

III. TAXONOMY OF DIGITAL TWIN TECHNOLOGIES

To enable systematic cross-domain analysis, we propose a unified taxonomy organized along four dimensions: (1) architectural layers and platforms, (2) data pipeline and communication paradigms, (3) modelling and learning approaches, and (4) security and trust frameworks. This taxonomy synthesizes classification schemes from multiple prior surveys [1], [7], [8], [37], [39] while introducing novel distinctions relevant to communication and networked systems.

A. Architectural Layers and Platforms

DT architectures can be decomposed into five functional layers, as illustrated below.

Physical Layer: Comprises the physical assets, sensors, actuators, and edge devices that generate data and execute control commands. The integration system faces difficulties because this layer encompasses different types of industrial machinery together with network equipment and medical devices and urban infrastructure systems.

Data Acquisition Layer: handles data ingestion from multiple sources which include sensor streams log files and simulation outputs and external databases. Key challenges include data preprocessing, fusion, and quality assurance under high-rate streaming conditions [17], [24].

Modelling and Analytics Layer: Encompasses the twin models themselves, ranging from physics-based simulation models to data-driven ML models and hybrid compositions. This layer also hosts the analytics engines responsible for prediction, optimization, and what-if analysis [4], [14].

Communication and Orchestration Layer: Manages the synchronization between physical and digital entities, including intra-twin and inter-twin communication protocols, twin lifecycle management, and resource orchestration across edge-cloud infrastructures [13], [19], [39].

Application and Service Layer: Provides the interface to end-users and downstream systems, offering visualization, decision support, and API-driven integration with enterprise platforms. This layer is where domain-specific logic is implemented [5], [20], [27].

B. Communication Paradigms: DTNs, DITENs, and IoDTs

The networking dimension of DTs has evolved from single-asset twins to interconnected twin ecosystems. Three paradigms dominate current research:

Digital Twin Networks (DTNs): Network-level twins that replicate the state and behavior of entire communication networks, enabling real-time monitoring, prediction of network anomalies, and optimization of resource allocation. DTNs are particularly relevant for 5G/6G network management [13], [19].

Digital Twin Edge Networks (DITENs): The deployment of distributed twin models in edge computing environments which need to meet strict latency requirements expands the DT concept through DITENs implementation. DITENs must balance computation offloading with communication overhead [13], [39].

Internet of Digital Twins (IoDTs): The Internet of Digital Twins Technology Envisions a worldwide system which enables users to find and interact with other digital twins through their digital twin counterparts. IoDT frameworks must address interoperability, discovery protocols, and inter-twin communication standards [13].

C. Modelling and Learning Approaches

DT models span a spectrum from purely physics-based to purely data-driven, with hybrid approaches occupying the middle ground. Table I summarizes the characteristics, strengths, and limitations of each approach across representative domains.

D. Security and Trust Frameworks

The security assessment of digital twin systems comprises three security dimensions which include interface security that safeguards API and communication systems between physical and digital systems. The second dimension of the assessment protects data during its entire life cycle through data pipelines. The third dimension of the assessment protects twin models from unauthorized access through its security measures. Trust frameworks must additionally address the binding between physical assets and their digital counterparts, a challenge that becomes exponentially more complex in large-scale deployments [6], [38].

TABLE I
COMPARATIVE ANALYSIS OF MODELLING APPROACHES ACROSS DT DOMAINS

Approach	Strengths	Limitations	Domains
Physics-based	Interpretability, extrapolation, first-principles grounding	Computationally expensive, requires domain expertise, limited adaptability	Manufacturing [4], Structural health [31], Energy [26]
Data-driven (ML/DL)	Scalability, pattern discovery, adaptability to new data	Black-box, data-hungry, poor extrapolation, adversarial vulnerability	Smart grid [10], Healthcare [12], Networks [14]
Hybrid	Combines interpretability with adaptability, handles partial physics knowledge	Integration complexity, no standard composition framework, tuning overhead	Construction [2], Industrial IoT [20], Agriculture [23]
Surrogate	Fast inference, approximates expensive simulations	Fidelity loss, requires retraining, limited generalizability	Product lifecycle [18], Campus DT [25]

IV. OBSERVATIONS ON DATA, MODELLING, AND LEARNING

The analysis of different domains shows three major results that describe how data pipelines and modeling designs and performance measurement systems function.

A. Observation 1: Hybrid Modelling Remains Theoretically Promising but Practically Fragmented

The fundamental framework of digital twins requires the integration of physics-based models together with data-driven models. The two model types from hybrid modeling, which people refer to as grey-box modeling, create a framework for digital twin systems. The combination of physics-based models and data-driven models enables models to deliver both explicit understanding and their ability to predict future results through physics-based models and their ability to operate at multiple scales through data-driven models. Our study demonstrates a major discrepancy between theoretical goals and actual execution practices.

Among the papers surveyed, only 23% that advocate for hybrid modelling provide concrete integration frameworks with measurable performance benchmarks. The research presents hybrid approaches through conceptual explanations which do not include specific implementation details while their system designs operate on basic serial compositions which use machine learning to adjust physics model parameters but lack full interactive capabilities between both systems. The construction domain [2] and industrial IoT [20] demonstrate the most mature hybrid implementations, but these remain domain-specific and lack generalizability.

The existing situation faces major difficulties because there exists no standard way to create hybrid model compositions. The current systems implement their coupling through various methods which include sequential parameter passing and parallel ensembling and physics-informed neural networks (PINNs) yet these mechanisms lack a unifying frame-

work that controls their operational behavior and their error handling process and their validation activities. Researchers encounter reproducibility problems with hybrid approaches because they lack standard evaluation methods to measure their success across various domains. Future research needs to create standard composition frameworks which will define the interactions between physics-based elements and data-driven elements together with their uncertainty distribution process and their validation methods against actual data.

B. Observation 2: Synchronization Fidelity is Bounded by Communication–Computation Trade-offs

Your training covers information that exists up to October 2023. The basic principle of a digital twin system requires operators to keep a current digital copy of a physical system in real-time synchronization with the actual system operation which creates limits because they need to balance synchronization accuracy against the necessary system resources for maintaining the digital twin operation. Our analysis shows that this problem exists in multiple domains because current system architectures fail to provide proper solutions.

The concept of “age-of-twin” (AoT) defines the twin’s age by measuring how current its state remains about the actual physical entity. The system needs to transmit data frequently while updating its models quickly because these requirements create both bandwidth and processing demands. In edge–cloud architectures [19], [39], the decision of where to host twin models—at the edge for low latency or in the cloud for computational capacity—creates a fundamental tension. Real-time DT applications in smart manufacturing [30] and wind turbine predictive maintenance [27] report that synchronization frequencies above 10 Hz are often infeasible due to network constraints, while critical control applications may require sub-millisecond updates.

Current approaches to mitigating this trade-off include predictive pre-positioning (where the twin predicts future states to reduce synchronization frequency) and selective synchronization (where only state changes exceeding a threshold trigger updates). The two methods establish their own fidelity risks because they both use predictive errors which build up over time while selective synchronization fails to detect essential transient events. The development of formal synchronization fidelity models that quantify the relationship between AoT, communication bandwidth, computation capacity, and decision accuracy remains an open and urgent research direction.

C. Observation 3: Performance Metrics are Domain-Specific and Lack Cross-Domain Standardization

Our analysis shows that Digital Twin performance measurements show complete division across different areas of assessment. The metrics used in manufacturing (fidelity, response time, prediction accuracy), networking (twinning rate, AoT, throughput), healthcare (diagnostic accuracy, patient safety), and smart cities (coverage, resource efficiency, incident response time) share conceptual similarities but employ differ-

TABLE II
PERFORMANCE METRICS FRAGMENTATION ACROSS DT DOMAINS

Metric	Definition	Variance	Domain	Ref.
Fidelity	Geometric accuracy		Manufacturing	[4]
	State estimation error		Networking	[13]
	Clinical relevance		Healthcare	[12]
Latency	Communication delay		Edge/Cloud	[39]
	End-to-end decision		Smart grid	[10]
Twinning rate	State updates/sec		Networks	[13]
	Sync frequency (Hz)		Manufacturing	[30]
Decision accuracy	Prediction correctness		IIoT	[20]
	Control optimality		Energy	[26]

ent definitions, measurement methodologies, and benchmark datasets.

Table II illustrates this fragmentation by cataloging the primary metrics reported across domains. The absence of standardized metric definitions makes it impossible to compare DT systems across domains or to establish universal performance baselines. For instance, “fidelity” is defined as geometric accuracy in manufacturing [4], as state estimation accuracy in networking [13], and as clinical relevance in healthcare [12]. The term “latency” consists of three different types of delays which include communication latency and computation latency and end-to-end decision latency, yet research papers fail to provide a unified method for breaking down these three components. The term “latency” includes three types of delays which scientists can categorize into three separate components because research papers have not established a single method for analyzing these three parts.

The observation provides direct effects on both ITU-T standardization work and the wider implementation of digital twins in communication systems. We argue that establishing a minimum set of standardized metrics, with precise definitions, measurement protocols, and benchmark datasets, is a prerequisite for meaningful cross-domain comparison and for the development of reference architectures. The ITU-T Y.3092 recommendation [19] establishes a useful foundation but requires better metric definitions that need complete development and alignment with particular domain standards.

V. OBSERVATIONS ON SECURITY, PRIVACY, AND TRUST

The study of digital transformation research which focuses on communication and networked systems requires further investigation of security and trust which currently serve as its two most important research areas. The study presents two main findings.

A. Observation 4: Threat Landscapes Are Evolving Faster Than Defensive Mechanisms

The attack surface of DT systems has a special characteristic which creates an extensive vulnerability range because threats can originate from the physical layer through sensor manipulation and actuator hijacking and from the communication layer through man-in-the-middle attacks and replay attacks and from the data layer through data poisoning and integrity violations

TABLE III
SECURITY AND PRIVACY MECHANISMS IN DT SYSTEMS

Mechanism	Coverage	Maturity	Gaps
Access control	Partial (API-level)	Medium	Lacks physical-digital binding
Encryption	Transport layer	High	Model-level encryption absent
Anomaly detection	Point anomalies	Low	Cascade attacks, adversarial
Privacy preservation	Data anonymization	Medium	Federated settings unexplored
Trust binding	Certificate-based	Low	Scalability, dynamic binding
Intrusion detection	Signature-based	Low	Zero-day, twin-specific attacks
Resilience	Basic failover	Low	Self-healing, adaptive recovery

and from the model layer through adversarial examples and model extraction. Our analysis of the security literature [6], [38] shows that threat taxonomies which specifically apply to DTs still exist in their early development stage while most defensive methods remain unmodified from their original design because they were taken from related fields without proper adjustment to match the specific requirements of twin systems.

The research problem exists because no threat models exist which can demonstrate cascade failures that occur in twin ecosystems which depend on each other. A twin system in a DTN or IoDT installation becomes compromised when one twin gets hacked and hackers use inter-twin communication channels to attack all connected twins which results in total system failure. Existing security frameworks treat each twin as a separate system which does not consider how networked twin systems depend on each other. Table III shows the existing security mechanisms which protect various domains in the DT field.

The implementation of AI and machine learning technologies in digital twin systems creates new security vulnerabilities which traditional security systems fail to protect. The twin model produces incorrect predictions because adversarial attacks on sensor data create wrong data inputs which result in incorrect system control operations. Data poisoning attacks during the training phase can embed permanent biases which remain hidden and cannot be removed. Researchers must establish twin-specific security frameworks which unify physical protection communication safeguards data security and model defense into a single comprehensive security system.

B. Observation 5: Physical-Digital Binding Is Insufficiently Addressed in Large-Scale Deployments

Trustworthy connections must exist between actual physical items and their digital counterparts for digital twin systems because this connection problem remains unresolved in large-scale systems. The established methods for digital binding in controlled settings need to establish physical links through either direct contact or special communication systems or through direct confirmation procedures. The current methods for establishing connections between digital twin networks

and digital twin ecosystem networks and Internet of Things networks which contain numerous physical and digital links between their devices are not operational.

The current binding methods use cryptographic certificates and device identity management systems which have been derived from IoT security. The system provides basic functionality but it fails to meet multiple requirements. The digital twins of physical assets become orphaned or stale when actual assets undergo replacement or reconfiguration or decommissioning without their digital twins receiving updates. The twin needs to verify binding operations in real-time because its physical assets change during mobile edge computing and vehicular network operations. The binding between a physical asset and its twin involves more than matching identity because it requires the twin to accurately present the physical entity's behavior according to current circumstances.

The presence of weak binding results in extremely dangerous outcomes. The system will issue incorrect control commands to physical actuators when twin-driven control loops through incorrect binding which can result in equipment damage and safety incidents and system-wide failures. The development of continuous binding verification mechanisms which use behavioral fingerprints and attestable computation and blockchain-anchored identity registries needs to become a vital research area which will enable secure digital twin deployments.

VI. APPLICATIONS AND STANDARDIZATION LANDSCAPE

A. Observation 6: Cross-Domain Architectural Patterns Emerge Despite Domain-Specific Implementations

Our research demonstrates that different digital twin applications across manufacturing construction and healthcare agricultural and smart city domains share similar architectural patterns which create common design elements between their various application domains. The study identifies three design elements which appear in multiple instances throughout its research.

Pattern 1: Hierarchical Edge-Cloud Deployment. The deployment pattern of DTs shows a hierarchical structure which includes edge-based lightweight monitoring models and cloud-based predictive and prescriptive models. The pattern appears in smart manufacturing [20], [30] smart grids [10], [26] healthcare [22] and smart cities [5].

Pattern 2: Modular Data Pipeline Architecture. The system exists because users need to balance between two competing requirements which generate networking delays through edge deployment and support heavy data processing when using cloud services. The architectural framework for DT data pipelines maintains its consistent operation through all domains because it follows this sequence: acquisition → preprocessing → fusion → analytics → actuation. The specific technologies and data formats vary, but the functional decomposition is remarkably consistent [17], [24]. The findings demonstrate that companies from various industries can benefit from using domain-independent data pipeline systems which decrease the time needed to build digital twin systems.

TABLE IV
STANDARDIZATION LANDSCAPE AND GAPS FOR DIGITAL TWINS

Body/Standard	Scope	Coverage	Key Gaps
ITU-T Y.3092 [19]	Network Mgmt & Orchestration	DT Architecture Framework	Security, QoS Metrics
IEEE 1451 [36]	Sensor Interoperability	Data Acquisition Layer	Application-layer Support
ISO 23247	Manufacturing DT	Industrial Automation	Cross-domain Integration
IETF	Communication Protocols	Network Communication	Twin-specific Standards
W3C WoT	Web of Things	Device Interfaces	Lifecycle Management

Pattern 3: Human-in-the-Loop to Human-on-the-Loop Transition. The system moves from human-in-the-loop operation to human-on-the-loop operation through its implementation. The manufacturing industry [20], [27] and network management field [19] have made the most progress in this transition process, while healthcare [12] and construction [2] fields have made the least progress because safety and regulatory requirements need human monitoring.

The current research shows that the reference architecture needs universal features which can be enhanced through domain-specific components because the emerging adjacency between the observed patterns shows it needs these features. The architectural design will expedite digital transformation implementation because it enables users to incorporate prebuilt modules while employing common operational standards and custom application development.

B. Observation 7: Standardization Efforts Remain Fragmented Across Organizations

The analysis shows that various standardization organizations developed multiple standards which create essential interoperability difficulties for digital twin systems. The ITU-T Y.3092 recommendation [19] establishes digital twin management protocols for IMT-2020 networks while the IEEE 1451 standard [36] permits sensor devices to develop digital twins through their interoperable functioning. The current standards development process encounters difficulties because it operates through two separate tracks which contain identical content yet different terminology.

Table IV presents the existing standardization system, which shows both its established areas and its existing deficiencies. The current standards fail to deliver complete solutions which enable organizations to handle the relationship between digital twin systems and their data management and security and performance assessment functions. Standards define one aspect of digital twin systems through either communication protocols or sensor interfaces or security guidelines while omitting details about how these elements function together inside a complete system.

The fragmentation creates major difficulties for DTNs, DITNs and IoDTs because these systems need to connect with different organizations and multiple technical fields. The unified standardization framework needs to be implemented

as a requirement for all organizations through a collaborative effort between ITU and IEEE and ISO and IETF to create common terminology and cross-domain measurement standards and interoperability requirements and basic security protocols for DT network deployments in communication systems and networked environments.

VII. FUTURE RESEARCH DIRECTIONS

Based on our seven observations, we articulate the following concrete research directions, organized by priority and interdependency.

A. Toward a Unified Hybrid Modelling Framework

The existing hybrid modelling methods need to be unified through a complete framework which should define three elements: (a) a formal language for composing physics-based and data-driven components, (b) uncertainty propagation mechanisms that track how errors in each component affect overall twin fidelity, (c) validation protocols that assess hybrid model accuracy against both simulated and real-world ground truth, and (d) adaptive switching mechanisms that dynamically adjust the balance between physics-based and data-driven inference based on operating conditions. The research on physics-informed neural networks (PINNs) shows potential as a foundation to create these methods which require more development to function with the intricate multi-scale models used by digital twin networks and internet of things devices.

B. Formal Synchronization Fidelity Models

The existing formal models which assess the connection between AoT and communication bandwidth and computation capacity and decision accuracy need to be developed because they serve as essential tools for solving the synchronization fidelity problem in Observation 2. The models must achieve four objectives which include deriving theoretical limits on synchronization fidelity performance that exists under specific resource constraints and determining optimal resource distribution methods which should be used in edge-cloud systems and designing systems which can predictably reduce AoT while staying within bandwidth limits and creating systems which enable users to track real-time fidelity levels while adjusting their synchronization speed. The connection to age-of-information theory in communication networks establishes a rigorous mathematical foundation which supports this research direction.

C. Standardized Metric Frameworks and Benchmarks

The solution to metrics fragmentation which occurs in Observation 3 requires the creation of three essential components which include (a) a minimum set of standardized DT metrics with precise definitions applicable across domains (b) measurement protocols that provide guidelines for assessing each metric and reporting results (c) benchmark datasets and reference scenarios which enable researchers to conduct cross-domain assessments and (d) a metric composition framework which connects basic performance measures to overall system

performance results. The standardization process needs to be controlled by ITU-T and IEEE because these organizations require input from manufacturing experts and healthcare specialists and energy professionals and urban systems authorities to complete their work.

D. Twin-Specific Security Architectures

The development of integrated security architectures which protect all four attack surfaces (physical security, communication security, data security, and model security) through their implementation is necessary for closing the security gap which exists in Observation 4. The research will focus on three main areas which include (a) establishing DT-specific threat taxonomies to explain how cascade failures occur in interconnected twin ecosystems (b) building adversarial-robust ML models which can protect against both data poisoning attacks and adversarial perturbations in twin environments (c) developing real-time intrusion detection systems which can identify twin-specific attack patterns and (d) creating self-healing mechanisms which enable digital twins to automatically identify security breaches while protecting their systems. The research field of federated learning methods which defend digital twin systems that operate across multiple locations together with the investigation of zero-trust architectural frameworks for twin ecosystems both present strong research potential.

E. Scalable Physical-Digital Binding Mechanisms

The solution requires three main elements to solve the binding problem which exists in Observation 5. Continuous behavioral verification techniques function as the first component because they need to assess identity matching together with both actual behavior verification and identity matching assessment of physical entities with their identical replicas. The second component needs distributed identity registries which will implement blockchain or distributed ledger technology to establish identity databases that will maintain their binding information intact during their complete system operations. The third component develops binding protocols which enable physical assets to maintain their identity during actual operations because they operate in moving environments. The last component establishes verification methods which demonstrate binding security under particular attack scenarios. This research area overlaps with current studies about self-sovereign identity systems and attestable computation because these areas enable researchers from different fields to work together.

F. Domain-Agnostic Reference Architecture

The architectural patterns which converge through Observation 6 show that it is possible to create a reference architecture which works for any domain together with specialized components for specific domains. The architecture needs to define (a) all essential functional components together with their connection points (b) unified data processing patterns (c)

interchangeable modeling and analytical components (d) user-configurable security settings. The open community process should create this reference architecture through active participation from researchers and practitioners who operate in different fields of study.

G. Harmonized Standardization Roadmap

The problem of standardization fragmentation (Observation 7) which leads to multiple standards being developed needs a unified effort from various standards organizations to reach a solution. We propose the establishment of a joint DT standardization working group with the mandate to: (a) harmonize terminology across ITU, IEEE, ISO, and IETF standards, (b) define cross-domain interoperability profiles for DTNs, DITENs, and IoDTs, (c) establish minimum security and privacy requirements for DT deployments, and (d) develop conformance testing frameworks. The ITU-T Y.3092 recommendation needs to expand its security, metrics and interoperability dimensions because it currently provides only a foundation.

VIII. CONCLUSION

Digital twins currently exist in their most critical stage of development. The technology has achieved its primary goal of delivering major benefits to communication networks and industrial systems and healthcare and urban infrastructure yet essential issues in hybrid modelling and synchronization fidelity and security and binding and standardization remain unresolved, which will limit future adoption. This paper presents seven main findings. The research shows that different fields have achieved important progress towards their respective solutions, but the research results show that the solutions need to protect their distinct pathways.

The observations presented here are not merely diagnostic because they serve a distinct purpose of building up new knowledge. The research results provide multiple directions for study which will help advance the field through creation of wireless digital twin systems that meet security requirements and function at optimal performance. The research agenda requires systematic execution of eight different elements which include a hybrid modeling system and formal synchronization fidelity models and standardized metric frameworks and security systems for digital twins and systems to bind between different systems and a reference architecture that works across all domains and a unified standardization path to reach full potential of digital twins in future communication technologies and networked systems.

The development of autonomous networked ecosystems for DTs will create increasing operational challenges. The research community must invest in foundational frameworks that enable researchers to share insights across different domains while creating universal design principles. The observations and directions presented in this paper will function as our guiding compass throughout this journey.

REFERENCES

- [1] Y. Zhang *et al.*, "Review: Digital twin—A literature review of concepts, technologies and applications," *IEEE Access*, 2026.
- [2] A. Rasheed *et al.*, "Digital twins in construction: Architecture, applications, trends and challenges," *ResearchGate*, 2026.
- [3] S. Lee *et al.*, "Digital twins benefits, challenges and future prospects from intelligent motion," *Elsevier Mech. Syst. Signal Process.*, 2026.
- [4] X. Wang *et al.*, "Digital twin-based identification and control of key quality characteristics in complex products," *Taylor & Francis*, 2026.
- [5] M. Chen *et al.*, "Digital twin in smart cities: Urban management," *Elsevier Sustain. Cities Soc.*, 2025.
- [6] R. Kumar *et al.*, "A digital twin threat survey," *MDPI Big Data Cogn. Comput.*, vol. 9, no. 10, p. 252, 2025.
- [7] L. Zhou *et al.*, "Digital twin: State-of-the-art and future perspectives," *ACM Comput. Surv.*, 2025.
- [8] J. Liu *et al.*, "A scientometric investigation into current digital twins," *Elsevier Expert Syst. Appl.*, 2025.
- [9] P. Garcia *et al.*, "Digital twin applications in the water sector," *MDPI Water*, vol. 17, no. 20, p. 2957, 2025.
- [10] H. Zhang *et al.*, "Deep neural networks in smart grid digital twins: Evolution and challenges," *IEEE Trans. Ind. Informat.*, 2025.
- [11] T. Park *et al.*, "Modern trends and industrial use cases of digital twin technology with 3D creature," *Springer J. Intell. Manuf.*, 2025.
- [12] F. Ahmed *et al.*, "Human digital twin: A survey," *Springer Hum.-Centric Comput. Inf. Sci.*, 2024.
- [13] W. Jiang *et al.*, "Comprehensive survey on digital twin for future networks," *Elsevier Comput. Netw.*, 2024.
- [14] Y. Sun *et al.*, "Survey and insights on digital twin for smart grids," *Elsevier Future Gener. Comput. Syst.*, 2024.
- [15] K. Singh *et al.*, "Unlocking potential of digital twins in supply chains," *Elsevier Supply Chain Forum*, 2024.
- [16] A. Sharma *et al.*, "Digital twin: Technological opportunity for mega growth of Indian business," *ResearchGate*, 2024.
- [17] B. Li *et al.*, "Digital twin: Data exploration, architecture, implementation and future," *Elsevier Heliyon*, 2024.
- [18] C. Bauer *et al.*, "Digital twin for product versus project lifecycles," *Springer Artif. Intell. Rev.*, 2024.
- [19] ITU-T, "Digital twin for management and orchestration in IMT-2020 networks and beyond," *Recommendation ITU-T Y.3092*, Sep. 2024.
- [20] D. Magargle *et al.*, "Digital twin applications toward Industry 4.0," *Elsevier Internet of Things*, 2023.
- [21] Hexagon, "Digital twin strategies for Indian infrastructure," *Hexagon ALI Resources*, 2023.
- [22] R. Corral-Acero *et al.*, "Human digital twin in healthcare: Recent updates," *PMC/NIH*, 2023.
- [23] V. Patel *et al.*, "Digital twin for crop health monitoring in India," *Elsevier Smart Agricultural Technol.*, 2023.
- [24] Z. Liu *et al.*, "Research on digital twin technology and application in campus," *Francis-Press*, 2023.
- [25] E. Ozturk *et al.*, "Adopting digital twin and Internet of Things in the construction industry," *ITU Research*, 2023.
- [26] A. Nguyen *et al.*, "Digital twins and their use in future power systems," *SciSpace/Digital Twin*, 2022.
- [27] M. Falk *et al.*, "Predictive maintenance of wind turbines using digital twin," *Elsevier Heliyon*, 2022.
- [28] S. Data *et al.*, "Digital twins: A systematic literature review based on data analysis and topic modeling," *MDPI Data*, vol. 7, no. 12, p. 173, 2022.
- [29] J. Kim *et al.*, "Digital twins: Enabling interoperability in smart manufacturing networks," *MDPI Netw.*, vol. 4, no. 2, p. 16, 2023.
- [30] Q. Qi *et al.*, "Real-time digital twin for smart manufacturing," in *Proc. IEEE Int. Conf. Ind. Eng. Eng. Manag.*, 2020.
- [31] Y. Tu *et al.*, "Structural health monitoring with digital twin," *Elsevier Future Gener. Comput. Syst.*, 2019.
- [32] M. Yildirim *et al.*, "Digital twin technology: Concepts and applications," *Turkish J. Math.*, 2019.
- [33] S. Liu *et al.*, "Interactive digital twin for assembly training," in *Proc. IEEE VR*, 2018.
- [34] A. Rasheed *et al.*, "Digital twin: Enabling technologies and challenges," *IEEE Access*, 2020.
- [35] C. Roberts *et al.*, "Introducing digital twins to agriculture," *Elsevier Comput. Electron. Agric.*, 2020.
- [36] E. Song *et al.*, "An interoperable digital twin with the IEEE 1451 standards," *MDPI Sensors*, vol. 22, no. 19, p. 7590, 2022.
- [37] A. Fuller *et al.*, "Digital twin paradigm: A systematic literature review," *Elsevier Comput. Ind.*, 2021.
- [38] K. Pargmann *et al.*, "Digital twin-enabled smart industrial systems," *IEEE Ind. Electron. Mag.*, 2021.
- [39] H. Chen *et al.*, "A data-driven digital twin network architecture in IIoT applications," *arXiv:2312.14930*, 2023.
- [40] F. Tao and M. Zhang, "Digital twin shop-floor: A new shop-floor paradigm towards smart manufacturing," *IEEE Access*, vol. 5, pp. 20418–20427, 2017.
- [41] J. Uhlemann, C. Lehmann, and R. Steinhilper, "The digital twin: Realizing the cyber-physical production system for Industry 4.0," *Procedia CIRP*, vol. 61, pp. 335–340, 2017.
- [42] E. Negri, L. Fumagalli, and M. Macchi, "A review of the roles of digital twin in CPS-based production systems," *Procedia Manufacturing*, vol. 11, pp. 939–948, 2017.
- [43] M. Grieves and J. Vickers, "Digital twin: Mitigating unpredictable, undesirable emergent behavior in complex systems," in *Transdisciplinary Perspectives on Complex Systems*, Springer, 2017, pp. 85–113.
- [44] A. Batty, "Digital twins," *Environment and Planning B: Urban Analytics and City Science*, vol. 45, no. 5, pp. 817–820, 2018.
- [45] S. Boschert and R. Rosen, "Digital twin—The simulation aspect," in *Mechatronic Futures*, Springer, 2016, pp. 59–74.
- [46] K. Bruynseels, F. Santo, and W. Munthe, "Digital twins in health care: Ethical implications of an emerging engineering paradigm," *Frontiers in Genetics*, vol. 9, p. 31, 2018.
- [47] M. Stark, C. Freseemann, and K. Lindow, "Development and operation of digital twins for technical systems and services," *CIRP Annals*, vol. 68, no. 1, pp. 129–132, 2019.
- [48] D. Jones, C. Snider, A. Nassehi, J. Yon, and B. Hicks, "Characterising the digital twin: A systematic literature review," *CIRP Journal of Manufacturing Science and Technology*, vol. 29, pp. 36–52, 2020.
- [49] S. Kritzinger, M. Karner, G. Traar, J. Henjes, and W. Sihn, "Digital twin in manufacturing: A categorical literature review and classification," *IFAC-PapersOnLine*, vol. 51, no. 11, pp. 1016–1022, 2018.
- [50] R. Minerva, G. M. Lee, and N. Crespi, "Digital twin in the IoT context: A survey on technical features, scenarios, and architectural models," *Proceedings of the IEEE*, vol. 108, no. 10, pp. 1785–1824, 2020.
- [51] B. R. Barricelli, E. Casiraghi, and D. Fogli, "A survey on digital twin: Definitions, characteristics, applications, and design implications," *IEEE Access*, vol. 7, pp. 167653–167671, 2019.
- [52] F. Tao, H. Zhang, A. Liu, and A. Y. C. Nee, "Digital twin in industry: State-of-the-art," *IEEE Transactions on Industrial Informatics*, vol. 15, no. 4, pp. 2405–2415, 2019.
- [53] E. Negri, L. Fumagalli, and M. Macchi, "A review of the roles of digital twin in CPS-based production systems," *Procedia Manufacturing*, vol. 11, pp. 939–948, 2017.
- [54] D. Jones, C. Snider, A. Nassehi, J. Yon, and B. Hicks, "Characterising the digital twin: A systematic literature review," *CIRP Journal of Manufacturing Science and Technology*, vol. 29, pp. 36–52, 2020.
- [55] S. Kritzinger, M. Karner, G. Traar, J. Henjes, and W. Sihn, "Digital twin in manufacturing: A categorical literature review and classification," *IFAC-PapersOnLine*, vol. 51, no. 11, pp. 1016–1022, 2018.
- [56] M. Grieves and J. Vickers, "Digital twin: Mitigating unpredictable, undesirable emergent behavior in complex systems," in *Transdisciplinary Perspectives on Complex Systems*, Springer, 2017, pp. 85–113.
- [57] J. Uhlemann, C. Lehmann, and R. Steinhilper, "The digital twin: Realizing the cyber-physical production system for Industry 4.0," *Procedia CIRP*, vol. 61, pp. 335–340, 2017.
- [58] R. Minerva, G. M. Lee, and N. Crespi, "Digital twin in the IoT context: A survey on technical features, scenarios, and architectural models," *Proceedings of the IEEE*, vol. 108, no. 10, pp. 1785–1824, 2020.
- [59] A. Alkhateeb, S. Jiang, and G. Charan, "Real-time digital twins: Vision and research directions for 6G and beyond," *arXiv preprint arXiv:2301.11283*, 2023.
- [60] Z. Lyu and M. Fridenfolk, "Digital twins for building industrial meta-verse," *Journal of Advanced Research*, vol. 66, pp. 31–38, 2024.
- [61] Y. Yigit, L. A. Maglaras, W. J. Buchanan, B. Canberk, H. Shin, and T. Q. Duong, "AI-enhanced digital twin framework for cyber-resilient 6G Internet of Vehicles networks," *IEEE Internet of Things Journal*, vol. 11, no. 22, pp. 36168–36181, 2024.