



**Table 1.16.b.: PEWFS on Fire Resistance rated Exterior wall -Test Requirements**

OCCUPANCY AND TYPE OF BUILDING	TEST 1 PEWFS PANEL AS PRODUCT	TEST 2 PEWFS IN WALL ASSEMBLY
<p><b>1. ANY BUILDING</b></p> <p><b>2. ANY INSTALLATION</b></p> <p><b>3. ANY AESTHETICS</b></p>	<p>i. EN 13501-1 With pass criteria A1 OR A2-s1-d0</p> <p>AND</p> <p>ii. ASTM D1929 With pass criteria PEWFS shall have self ignition temperature of not less than 343°C</p>	<p>iii. ASTM E 119 With pass criteria "1 Hr or 2 Hr OR 3 Hr as per required fire rating of the wall.</p> <p>OR</p> <p>iv. UL 263 With pass criteria "1 Hr or 2 Hr OR 3 Hr as per required fire rating of the wall.</p> <p>OR</p> <p>v. EN 1362-3 With pass criteria "1 Hr or 2 Hr OR 3 Hr as per required fire rating of the wall.</p> <p>OR</p> <p>vi. EN 1362-4 With pass criteria "1 Hr or 2 Hr OR 3 Hr as per required fire rating of the wall.</p>