


### 2.4.3. Food Truck Cylinders

**2.4.3.1.** LPG cylinders installed on Mobile Food Trucks shall comply as per **Table 11.3.** and other relevant sections of this chapter. Material requirements shall be as per **Section 2.3.** and **section 6.**

**Table 11.3: Food Truck LPG Cylinder Installation Guideline**

ITEMS	REQUIREMENTS
<b>1. LOCATION OF FOOD TRUCK CYLINDERS</b>	<p>Cylinders shall be placed in a permanent, fixed manifold at the back of the Mobile Food Truck in a metal ventilated cabinet, fully isolated from the Truck interiors. It can be single cabinet or two separate cabinets. See <b>Figure 11.5.</b></p> <ol style="list-style-type: none"> <li>Compartment shall be of steel construction with ventilation on the front side.</li> <li>Cylinders compartments are not allowed on the sides or on the Truck top.</li> </ol>
<b>2. QUANTITY ALLOWED ON FOOD TRUCKS</b>	<ol style="list-style-type: none"> <li>Maximum quantity allowed is 2 cylinders of 12 kg in one group in the enclosure. 1 cylinder shall be main and 1 cylinder shall be reserve in a common manifold with isolation valves. Additional / spare LPG cylinders are not allowed to be stored in the truck.</li> </ol>
<b>3. SAFETY PROVISIONS FOR FOOD TRUCK CYLINDERS</b>	<ol style="list-style-type: none"> <li>Food truck owners shall produce certificate from manufacturer confirming the load carrying capacity of the truck.</li> <li>There shall be twin tires for the truck rear.</li> <li>Cylinders shall be composite type only.</li> <li>Piping shall be welded steel and up to as close as possible to cylinders with flexible hose connections as minimum as possible.</li> <li>Provide emergency shut-off switch at both doors of truck interior.</li> <li>Steel guard shall be provided at the exterior of cylinder enclosure.</li> <li>LPG Leak detectors shall be installed at the enclosure and inside the truck near cooking platform.</li> <li>Battery operated Heat detectors shall be installed for the Truck interior covering cooking platform.</li> <li>All electrical wiring, lighting wiring, equipment wiring shall be concealed in a metallic containment pipe.</li> <li>Kitchenhood suppression system shall be provided for the hood.</li> <li>Civil Defence NOC shall be obtained only after inspection of the Food Truck.</li> </ol>



**Figure 11.5: LPG for Food Truck**