Table 1.9: Fire Resistance Separation and other requirement of incidental accessory /Occupancies.

INCIDENTAL ACCESSORY ROOMS AND OCCUPANCIES	REQUIRED SEPARATION WITH AUTOMATIC FIXED FIRE PROTECTION SYSTEM	REQUIRED SEPARATION WITHOUT AUTOMATIC FIXED FIRE PROTECTION SYSTEM	OTHER CONSTRUCTION AND PROTECTION REQUIREMENTS (See Chapter 9 for Fire Protection requirements Chapter 10 for smoke control requirements)
29. GROUP A STORAGE EXPLOSIVES, DETONABLE PYROPHORIC MATERIALS, BLASTING AGENTS < 100 KG More than 100 kg shall have risk assessment and shall comply with Chapter 13, NFPA 5000 and NFPA 294.	2 Hour	2 Hour	 i. Storage shall be in a separate building without basements and a maximum of one floor. ii. This dedicated building shall be minimum of 23 m away from other buildings and property line. iii. Separation and Compartmentation shall be complete with walls, floor, roof and opening protection. iv. Door shall be 90 minutes fire rated, self closing and directly outside available on Fire accessway. v. Rolling shutters shall be 90 minutes rated and shall be closed automatically upon receiving fire signal. vi. Vapor exhaust system shall be provided. vii.Steel structure fire rating shall not be required.
30. GROUP A STORAGE MATERIALS STORE ROOM (FLAMMABLE AND COMBUSTIBLE MATERIALS) > 93 M² IN AREA. Rooms exceeding MAQ, as per chapter 13, shall have risk assessment and shall comply with Chapter 13, NFPA 5000 and NFPA 30.	1 Hour	2 Hour	 i. Storage room shall be 9 m away from property line. ii. Storage room shall not be in the basement. iii. Separation and Compartmentation shall be complete with walls, floor, roof and opening protection. iv. Door shall be 90 minutes fire rated, self closing and directly outside available on Fire accessway v. Rolling shutters shall be 90 minutes rated and shall be closed automatically upon receiving fire signal. vi. Vapor exhaust system shall be provided. vii.Steel structure fire rating shall not be required.



