Table 3.13.: Occupant Load Factors and Exit Capacity Factors

OCCUPANCY	OCCUPANT LOAD FACTOR PER PERSON	STAIR CAPACITY PER PERSON	RAMP CAPACITY PER PERSON
4. HEALTHCARE GROUP A,B			
i. Inpatient treatment departments	22.3 m ²	7.6 mm	5 mm
ii. Sleeping departments	11.1 m ²	7.6 mm	5 mm
iii. Consultation departments	9.3 m ²	7.6 mm	5 mm
iv. Clinics	9.3 m ²	7.6 mm	5 mm
v. Limited Care	9.3 m ²	7.6 mm	5 mm
vi. Both sides of Smoke Compartment	2.8 m ² , net	7.6 mm	5 mm
5. HEALTHCARE GROUP C			
i. Ambulatory Health care	13 m ²	7.6 mm	5 mm
6. RESIDENTIAL GROUP A			
i. Apartments	18.6 m ²	7.6 mm	5 mm
7. RESIDENTIAL GROUP B, C			
i. Staff Accommodation, Hostels	18.6 m ²	7.6 mm	5 mm
i. Labor Accommodation	18.6 m ²	7.6 mm	5 mm
8. PRIVATE VILLA	None	None	None
9. COMMERCIAL VILLA	None	None	None
10. DETENTION , GROUP A,B,C.	11.1 m ²	7.6 mm	5 mm
11. HOTEL			
i. Hotel Apartments	18.6 m ²	7.6 mm	5 mm
i. Hotel Guest rooms	18.6 m ²	7.6 mm	5 mm
12. DAY CARE, GROUP A,B	3.3 m ² , net	10 mm	5 mm
13. MERCANTILE, GROUP A,B,C.			
i. Sales area on floor below street floor	2.8 m ²	7.6 mm	5 mm
ii. Sales area on street floor	2.8 m ²	7.6 mm	5 mm
iii. Sales area on floors above street floor	5.6 m ²	7.6 mm	5 mm
iv. Sales area on two or more street floors	3.7 m ²	7.6 mm	5 mm
v. Floors used only for offices	9.3 m ²	7.6 mm	5 mm
vi. Floors used for goods and not public	27.9 m ²	7.6 mm	5 mm