Table 8.1: General Requirements of Fire Detection and Alarm Systems		
ITEMS	REQUIREMENTS	
17. VISUAL NOTIFICATION DEVICES	 i. The spacing of Visual Notification devices in room shall be as per Manufacturer's specifications. However, number of devices shall be as per Table 8.1.a. ii. Room spacing in accordance with Table 8.1.a. and Figure 8.1. for wall- 	
SPACING IN ROOMS	mounted appliances shall be based on locating the visible notification device at the halfway distance of the wall.	

Table 8.1.a.: Spacing of Visual Notification Devices in Rooms

MAXIMUM ROOM SIZE	MAXIMUM CEILING HEIGHT	MINIMUM REQUIRED LIGHT OUTPUT (ONE LIGHT, cd)
1. 6.1 m x 6.1 m	3 m	15
2. 9.1 m x 9.1 m	3 m	30
3. 12.2 m x 12.2 m	3 m	60
4. 13.4 m x 13.4 m	3 m	75
5. 15.2 m x 15.2 m	3 m	95
6. 16.2 m x 16.2 m	3 m	110
7. 16.8 m x 16.8 m	3 m	115
8. 18 m x 18 m	3 m	135
9. 19.2 m x 19.2 m	3 m	150
10. 20.7 m x 20.7 m	3 m	177
11. 21.3 m x 21.3 m	3 m	185
12. 6.1 m x 6.1 m	6.1 m	30
13. 9.1 m x 9.1 m	6.1 m	45
14. 13.4 m x 13.4 m	6.1 m	75
15. 14 m x 14 m	6.1 m	80
16. 15.2 m x 15.2 m	6.1 m	95
17. 16.2 m x 16.2 m	6.1 m	110
18. 16.8 m x 16.8 m	6.1 m	115
19. 18 m x 18 m	6.1 m	135
20. 19.2 m x 6.1 m	6.1 m	150
21. 20.7 m x 20.7 m	6.1 m	177
22. 21.3 m x 21.3 m	6.1 m	185
23. 6.1 m x 6.1 m	9.1 m	55
24. 9.1 m x 9.1 m	9.1 m	75
25. 15.2 m x 15.2 m	9.1 m	95
26. 16.2 m x 16.2 m	9.1 m	110
27. 16.8 m x 16.8 m	9.1 m	115
28. 18 m x 18 m	9.1 m	135
29. 19.2 m x 19.2 m	9.1 m	150
30. 20.7 m x 20.7 m	9.1 m	177
31. 21.3 m x 21.3 m	9.1 m	185