5.10. Daycare, Group A, B.

5.10.1. The Day care, Group A, B. (Child day care, Old age day care, Adult day care) occupancies shall comply with **Table 3.31.** along with all other sections of this chapter. Where conflicts arise between this section and other sections of this Chapter or code, the requirements of this section shall prevail.

Table 3.31.: Day Care, Group A, B. (Child day care, Old age day care, Adult day care)

Table 3.31.: Day Care, Group A, B. (Child day care, Old age day care, Adult day care)	
ITEMS	REQUIREMENTS
1. MULTIPLE OCCUPANCY	 i. Where day care occupancies are situated in other occupancies, and if the two exit accesses from a day-care occupancy enter the same corridor as other occupancy (such as an apartment occupancy, Residential occupancy, or hotel occupancy) the exit accesses shall be separated in the corridor by a 1 hour smoke partition which is located so that it has an exit on each side. ii. No Day care room shall have its sole means of egress pass through any nonresidential occupancy of the same building, unless non residential occupancy is fully sprinklered as per chapter 9.
2. CORRIDORS	 i. Minimum common exit corridor width shall be 1200 mm. ii. Corridor shall have 1 hour fire resistance rated construction if building is not sprinklered. iii. Every Day care room shall have a door leading directly to an exit access corridor. iv. Transoms, louvers, or transfer grilles shall be prohibited in walls or doors of exit access corridors.
3. SINGLE EXIT PERMISSION	i. Single exit shall not be permitted.ii. 2 enclosed exits shall be available from every part of every floor.
4. TWO EXIT DOORS REQUIREMENTS	i. Any Day care room larger than 185 m², shall have 2 exit corridor access doors remotely located from each other as per Section 4.4.
5. RESCUE WINDOW IN NON SPRINKLERED BUILDINGS	 i. Every day care room or space, in non-sprinklered buildings, normally subject to client occupancy shall have at least one window with a fixed breakable glass, having area clear opening not less than 510 mm in width and 610 mm in height, and 0.5 m2 in area, located not more than 1120 mm above the floor for an emergency rescue. ii. Such window shall be on the exterior wall of the room, accessible from public way to the Civil Defence rescue team.
6. DOORS	 i. Balcony and terrace access shall be restricted with door having child lock or latch. ii. Window opening shall be restricted to 100 mm opening with windows safety latch. (See Chapter 1, section 2.17. Balcony, Terrace and Windows) iii. Every closet door latch shall be such that children can open the door from inside the closet. iv. Every bathroom door shall be designed to allow opening from the outside during an emergency when locked. v. At all times, the Day care occupancy is occupied, all locking devices that impede or prohibit egress or that cannot be easily disengaged shall be prohibited.
7. SMOKE COMPARTMENT	i. Child day care and old age day care (Day care, Group A) occupancies shall be located within one storey above level of exit discharge. If day care, group A occupancies are located two or more levels above the level of exit discharge, each floor shall be subdivided into minimum of 2 smoke compartments with smoke barrier having 1 hour fire resistance rated construction.