b.1.5. Where a vapour barrier does not meet the requirement of b.1.4., then the façade system(s) proposed for the project including the vapour barrier shall be required to pass the large scale façade tests in accordance with UAE Fire and Life Safety Code of Practice 2017, Chapter 1, Section 4.

b.2. Fire Access Road

- b.2.1. Minimum of ¼ (25 percent) of the building perimeter shall have fire access road in compliance to UAE Fire and Life Safety Code of Practice 2017, chapter 2. Fire Service vehicle and personnel accessibility specifications.
- b.2.2. Fire truck staging area of 6 m wide and 12 m long shall be provided in compliance to UAE Fire and Life Safety Code of Practice 2017, chapter 2. Fire Service vehicle and personnel accessibility specifications.
- b.2.3. All the water front properties which have only ¼ (25 percent) of the required Primary Fire access road in accordance with Section 2.8.10.a., a secondary fire access road, in accordance with the following shall be provided.
 - 4.5 m wide, secondary fire access road shall be provided at the entire water side of the property.
 - ii. The secondary fire access road load carrying capacity shall not be less than 40,000 kg.
 - iii. Except for b.2.3.i and b.2.3.ii., the secondary fire access road shall comply with UAE Fire and Life Safety Code of Practice 2017, chapter 2. Fire Service vehicle and personnel accessibility specifications.

