



```
A[0] = 0
A[1] = 1
A[2] = 0
A[3] = 1
A[4] = 1
```

the function should return 5, as explained above.

Write an **efficient** algorithm for the following assumptions:

- N is an integer within the range [1..100,000];
- each element of array A is an integer that can have one of the following values: 0, 1.

Copyright 2009–2019 by Codility Limited. All Rights Reserved. Unauthorized copying, publication or disclosure prohibited.

Test results - Codility

```
10         if value == prev:
11             counter += prev
12         else:
13             prev = value
14         if counter > 100000000:
15             return -1
16     return counter
```

Analysis summary

The solution obtained perfect score.

Analysis ?

Detected time complexity: **O(N)**

expand all	Example tests	
▶	example	✓ OK
	example test	
expand all	Correctness tests	
▶	single	✓ OK
	single element	
▶	double	✓ OK
	two elements	
▶	simple	✓ OK
	simple test	
▶	small_random	✓ OK
	random, length = 100	
▶	small_random2	✓ OK
	random, length = 1000	
expand all	Performance tests	
▶	medium_random	✓ OK
	random, length = ~10,000	
▶	large_random	✓ OK
	random, length = ~100,000	
▶	large_big_answer	✓ OK
	0..01..1, length = ~100,000	
▶	large_alternate	✓ OK
	0101..01, length = ~100,000	
▶	large_extreme	✓ OK
	large test with all 1s/0s, length = ~100,000	

PDF version of this report that may be downloaded on top of this site may contain sensitive data including personal information. For security purposes, we recommend you remove it from your system once reviewed.