Apply filters to SQL queries

Project description

You are a security professional at a large organization. Part of your job is to investigate security issues to help keep the system secure. You recently discovered some potential security issues that involve login attempts and employee machines.

Your task is to examine the organization's data in their employees and log_in_attempts tables. You'll need to use SQL filters to retrieve records from different datasets and investigate the potential security issues.

Retrieve after hours failed login attempts

Your team is investigating failed login attempts that were made after business hours. You want to retrieve this information from the login activity. You'll identify all unsuccessful attempts after 18:00.

Here I created a SQL query that filter all login attemps made after business hours

```
MariaDB [organization]> SELECT *
    -> FROM log_in_attempts
    -> WHERE login_time > '18:00' AND success = FALSE;
+----------+----------+------------+------------+---------+-----------------+---------+
| event_id | username | login_date | login_time | country | ip_address      | success |
+----------+----------+------------+------------+---------+-----------------+---------+
|        2 | apatel   | 2022-05-10 | 20:27:27   | CAN     | 192.168.205.12  |       0 |
|       18 | pwashing | 2022-05-11 | 19:28:50   | US      | 192.168.66.142  |       0 |
|       20 | tshah    | 2022-05-12 | 18:56:36   | MEXICO  | 192.168.109.50  |       0 |
|       28 | aestrada | 2022-05-09 | 19:28:12   | MEXICO  | 192.168.27.57   |       0 |
|       34 | drosas   | 2022-05-11 | 21:02:04   | US      | 192.168.45.93   |       0 |
|       42 | cgriffin | 2022-05-09 | 23:04:05   | US      | 192.168.4.157   |       0 |
|       52 | cjackson | 2022-05-10 | 22:07:07   | CAN     | 192.168.58.57   |       0 |
|       69 | wjaffrey | 2022-05-11 | 19:55:15   | USA     | 192.168.100.17  |       0 |
|       82 | abernard | 2022-05-12 | 23:38:46   | MEX     | 192.168.234.49  |       0 |
|       87 | apatel   | 2022-05-08 | 22:38:31   | CANADA  | 192.168.132.153 |       0 |
|       96 | ivelasco | 2022-05-09 | 22:36:36   | CAN     | 192.168.84.194  |       0 |
|      104 | asundara | 2022-05-11 | 18:38:07   | US      | 192.168.96.200  |       0 |
|      107 | bisles   | 2022-05-12 | 20:25:57   | USA     | 192.168.116.187 |       0 |
|      111 | aestrada | 2022-05-10 | 22:00:26   | MEXICO  | 192.168.76.27   |       0 |
|      127 | abellmas | 2022-05-09 | 21:20:51   | CANADA  | 192.168.70.122  |       0 |
|      131 | bisles   | 2022-05-09 | 20:03:55   | US      | 192.168.113.171 |       0 |
|      155 | cgriffin | 2022-05-12 | 22:18:42   | USA     | 192.168.236.176 |       0 |
|      160 | jclark   | 2022-05-10 | 20:49:00   | CANADA  | 192.168.214.49  |       0 |
|      199 | yappiah  | 2022-05-11 | 19:34:48   | MEXICO  | 192.168.44.232  |       0 |
+----------+----------+------------+------------+---------+-----------------+---------+
19 rows in set (0.001 sec)
```

The result is based on the log_in_attempts table where I set the filter to search for logins after 18:00 and login attemps that failed. The query "SELECT *" means that it will get every information "FROM log_in_attempts" table and the conditional statement "WHERE login_time > '18:00' AND success = FALSE" will filter any login attempts made outside business hours that failed.

Retrieve login attempts on specific dates

Your team is investigating a suspicious event that occurred on '2022-05-09'. You want to retrieve all login attempts that occurred on this day and the day before ('2022-05-08').

Here I created an SQL query to filter for dates.

```
MariaDB [organization]> SELECT *
    -> FROM log_in_attempts
    -> WHERE login_date = '2022-05-09' OR login_date = '2022-05-08';
+----------+----------+------------+------------+---------+-----------------+---------+
| event_id | username | login_date | login_time | country | ip_address      | success |
+----------+----------+------------+------------+---------+-----------------+---------+
|        1 | jrafael  | 2022-05-09 | 04:56:27   | CAN     | 192.168.243.140 |       1 |
|        3 | dkot     | 2022-05-09 | 06:47:41   | USA     | 192.168.151.162 |       1 |
|        4 | dkot     | 2022-05-08 | 02:00:39   | USA     | 192.168.178.71  |       0 |
|        8 | bisles   | 2022-05-08 | 01:30:17   | US      | 192.168.119.173 |       0 |
|       12 | dkot     | 2022-05-08 | 09:11:34   | USA     | 192.168.100.158 |       1 |
|       15 | lyamamot | 2022-05-09 | 17:17:26   | USA     | 192.168.183.51  |       0 |
|       24 | arusso   | 2022-05-09 | 06:49:39   | MEXICO  | 192.168.171.192 |       1 |
|       25 | sbaelish | 2022-05-09 | 07:04:02   | US      | 192.168.33.137  |       1 |
|       26 | apatel   | 2022-05-08 | 17:27:00   | CANADA  | 192.168.123.105 |       1 |
|       28 | aestrada | 2022-05-09 | 19:28:12   | MEXICO  | 192.168.27.57   |       0 |
|       30 | yappiah  | 2022-05-09 | 03:22:22   | MEX     | 192.168.124.48  |       1 |
|       32 | acook    | 2022-05-09 | 02:52:02   | CANADA  | 192.168.142.239 |       0 |
|       36 | asundara | 2022-05-08 | 09:00:42   | US      | 192.168.78.151  |       1 |
|       38 | sbaelish | 2022-05-09 | 14:40:01   | USA     | 192.168.60.42   |       1 |
|       39 | yappiah  | 2022-05-09 | 07:56:40   | MEXICO  | 192.168.57.115  |       1 |
|       42 | cgriffin | 2022-05-09 | 23:04:05   | US      | 192.168.4.157   |       0 |
|       43 | mcouliba | 2022-05-08 | 02:35:34   | CANADA  | 192.168.16.208  |       0 |
|       44 | daquino  | 2022-05-08 | 07:02:35   | CANADA  | 192.168.168.144 |       0 |
|       47 | dkot     | 2022-05-08 | 05:06:45   | US      | 192.168.233.24  |       1 |
|       49 | asundara | 2022-05-08 | 14:00:01   | US      | 192.168.173.213 |       0 |
|       53 | nmason   | 2022-05-08 | 11:51:38   | CAN     | 192.168.133.188 |       1 |
|       56 | acook    | 2022-05-08 | 04:56:30   | CAN     | 192.168.209.130 |       1 |
|       58 | ivelasco | 2022-05-09 | 17:20:54   | CAN     | 192.168.57.162  |       0 |
|       61 | dtanaka  | 2022-05-09 | 09:45:18   | USA     | 192.168.98.221  |       1 |
|       65 | aalonso  | 2022-05-09 | 23:42:12   | MEX     | 192.168.52.37   |       1 |
|       66 | aestrada | 2022-05-08 | 21:58:32   | MEX     | 192.168.67.223  |       1 |
|       67 | abernard | 2022-05-09 | 11:53:41   | MEX     | 192.168.118.29  |       1 |
|       68 | mrah     | 2022-05-08 | 17:16:13   | US      | 192.168.42.248  |       1 |
|       70 | tmitchel | 2022-05-09 | 10:55:17   | MEXICO  | 192.168.87.199  |       1 |
|       71 | mcouliba | 2022-05-09 | 06:57:42   | CAN     | 192.168.55.169  |       0 |
|       72 | alevitsk | 2022-05-08 | 12:09:10   | CANADA  | 192.168.139.176 |       1 |
|       79 | abernard | 2022-05-09 | 11:41:15   | MEX     | 192.168.158.170 |       0 |
|       80 | cjackson | 2022-05-08 | 02:18:10   | CANADA  | 192.168.33.140  |       1 |
|       83 | lrodriqu | 2022-05-08 | 08:10:23   | USA     | 192.168.67.69   |       1 |
|       87 | apatel   | 2022-05-08 | 22:38:31   | CANADA  | 192.168.132.153 |       0 |
|       90 | gesparza | 2022-05-09 | 00:49:05   | CANADA  | 192.168.87.201  |       0 |
|       92 | pwashing | 2022-05-08 | 00:36:12   | US      | 192.168.247.219 |       0 |
```

I used the “SELECT * FROM login_attemps” followed by my conditional statement WHERE login_date should be ‘2022-05-09’ OR ‘2022-05-08’ This query will return values based on the set parameters only.

Retrieve login attempts outside of Mexico

Now, your team is investigating logins that did not originate in Mexico, and you need to find this information.

Here I created a query that filters for logins outside of mexico.

```
MariaDB [organization]> SELECT *
    -> FROM log_in_attempts
    -> WHERE NOT country LIKE 'MEX%';
+----------+----------+------------+------------+---------+-----------------+---------+
| event_id | username | login_date | login_time | country | ip_address      | success |
+----------+----------+------------+------------+---------+-----------------+---------+
|        1 | jrafael  | 2022-05-09 | 04:56:27   | CAN     | 192.168.243.140 |       1 |
|        2 | apatel   | 2022-05-10 | 20:27:27   | CAN     | 192.168.205.12  |       0 |
|        3 | dkot     | 2022-05-09 | 06:47:41   | USA     | 192.168.151.162 |       1 |
|        4 | dkot     | 2022-05-08 | 02:00:39   | USA     | 192.168.178.71  |       0 |
|        5 | jrafael  | 2022-05-11 | 03:05:59   | CANADA  | 192.168.86.232  |       0 |
|        7 | eraab    | 2022-05-11 | 01:45:14   | CAN     | 192.168.170.243 |       1 |
|        8 | bisles   | 2022-05-08 | 01:30:17   | US      | 192.168.119.173 |       0 |
|       10 | jrafael  | 2022-05-12 | 09:33:19   | CANADA  | 192.168.228.221 |       0 |
|       11 | sgilmore | 2022-05-11 | 10:16:29   | CANADA  | 192.168.140.81  |       0 |
|       12 | dkot     | 2022-05-08 | 09:11:34   | USA     | 192.168.100.158 |       1 |
|       13 | mrah     | 2022-05-11 | 09:29:34   | USA     | 192.168.246.135 |       1 |
|       14 | sbaelish | 2022-05-10 | 10:20:18   | US      | 192.168.16.99   |       1 |
|       15 | lyamamot | 2022-05-09 | 17:17:26   | USA     | 192.168.183.51  |       0 |
|       16 | mcouliba | 2022-05-11 | 06:44:22   | CAN     | 192.168.172.189 |       1 |
|       17 | pwashing | 2022-05-11 | 02:33:02   | USA     | 192.168.81.89   |       1 |
|       18 | pwashing | 2022-05-11 | 19:28:50   | US      | 192.168.66.142  |       0 |
|       19 | jhill    | 2022-05-12 | 13:09:04   | US      | 192.168.142.245 |       1 |
|       21 | iuduike  | 2022-05-11 | 17:50:00   | US      | 192.168.131.147 |       1 |
|       25 | sbaelish | 2022-05-09 | 07:04:02   | US      | 192.168.33.137  |       1 |
|       26 | apatel   | 2022-05-08 | 17:27:00   | CANADA  | 192.168.123.105 |       1 |
|       29 | bisles   | 2022-05-11 | 01:21:22   | US      | 192.168.85.186  |       0 |
|       31 | acook    | 2022-05-12 | 17:36:45   | CANADA  | 192.168.58.232  |       0 |
|       32 | acook    | 2022-05-09 | 02:52:02   | CANADA  | 192.168.142.239 |       0 |
|       33 | zbernal  | 2022-05-11 | 02:52:10   | US      | 192.168.72.59   |       1 |
|       34 | drosas   | 2022-05-11 | 21:02:04   | US      | 192.168.45.93   |       0 |
|       36 | asundara | 2022-05-08 | 09:00:42   | US      | 192.168.78.151  |       1 |
|       37 | eraab    | 2022-05-10 | 06:03:41   | CANADA  | 192.168.152.148 |       0 |
|       38 | sbaelish | 2022-05-09 | 14:40:01   | USA     | 192.168.60.42   |       1 |
|       41 | apatel   | 2022-05-10 | 17:39:42   | CANADA  | 192.168.46.207  |       0 |
|       42 | cgriffin | 2022-05-09 | 23:04:05   | US      | 192.168.4.157   |       0 |
|       43 | mcouliba | 2022-05-08 | 02:35:34   | CANADA  | 192.168.16.208  |       0 |
|       44 | daquino  | 2022-05-08 | 07:02:35   | CANADA  | 192.168.168.144 |       0 |
|       45 | dtanaka  | 2022-05-11 | 10:28:54   | US      | 192.168.223.157 |       1 |
|       46 | eraab    | 2022-05-11 | 11:29:27   | CAN     | 192.168.24.12   |       0 |
|       47 | dkot     | 2022-05-08 | 05:06:45   | US      | 192.168.233.24  |       1 |
|       48 | asundara | 2022-05-11 | 03:18:45   | USA     | 192.168.72.10   |       1 |
|       49 | asundara | 2022-05-08 | 14:00:01   | US      | 192.168.173.213 |       0 |
```

I used the “SELECT * FROM log_in_attemps” since we want to see all logins outside of mexico and just added the conditional statement WHERE NOT country LIKE ‘MEX%’ to filter all logins attempted in Mexico.

Retrieve employees in Marketing

Your team is updating employee machines, and you need to obtain the information about employees in the 'Marketing' department who are located in all offices in the East building (such as 'East-170' or 'East-320').

Here I created an SQL query to filter employees table.

```
MariaDB [organization]> SELECT *
    -> FROM employees
    -> WHERE department = 'Marketing' AND office LIKE 'East%';
+-------------+--------------+----------+------------+----------+
| employee_id | device_id    | username | department | office   |
+-------------+--------------+----------+------------+----------+
|        1000 | a320b137c219 | elarson  | Marketing  | East-170 |
|        1052 | a192b174c940 | jdarosa  | Marketing  | East-195 |
|        1075 | x573y883z772 | fbautist | Marketing  | East-267 |
|        1088 | k8651965m233 | rgosh    | Marketing  | East-157 |
|        1103 | NULL         | randerss | Marketing  | East-460 |
|        1156 | a184b775c707 | dellery  | Marketing  | East-417 |
|        1163 | h679i515j339 | cwilliam | Marketing  | East-216 |
+-------------+--------------+----------+------------+----------+
7 rows in set (0.074 sec)
```

I used the “SELECT * FROM employees” to get all the data from the employees table. I then added the conditional statement WHERE to add a condition that the department must be in Marketing and the employee office must be in the East buildinf

Retrieve employees in Finance or Sales

Now, your team needs to perform a different update to the computers of all employees in the Finance or the Sales department, and you need to locate information on these employees. Here I created an SQL query to filter employees in the FInance or Sales Department.

```
MariaDB [organization]> SELECT *
    -> FROM employees
    -> WHERE department = 'Finance' OR department = 'Sales';
+-------------+--------------+----------+------------+-------------+
| employee_id | device_id    | username | department | office      |
+-------------+--------------+----------+------------+-------------+
|        1003 | d394e816f943 | sgilmore | Finance    | South-153   |
|        1007 | h174i497j413 | wjaffrey | Finance    | North-406   |
|        1008 | i858j583k571 | abernard | Finance    | South-170   |
|        1009 | NULL         | lrodriqu | Sales      | South-134   |
|        1010 | k2421212m542 | jlansky  | Finance    | South-109   |
|        1011 | l748m120n401 | drosas   | Sales      | South-292   |
|        1015 | p611q262r945 | jsoto    | Finance    | North-271   |
|        1017 | r550s824t230 | jclark   | Finance    | North-188   |
|        1018 | s310t540u653 | abellmas | Finance    | North-403   |
|        1022 | w237x430y567 | arusso   | Finance    | West-465    |
|        1024 | y976z753a267 | iuduike  | Sales      | South-215   |
|        1025 | z381a365b233 | jhill    | Sales      | North-115   |
|        1029 | d336e475f676 | ivelasco | Finance    | East-156    |
|        1035 | j236k3031245 | bisles   | Sales      | South-171   |
```

Here I used the “SELECT * FROM employees” to again select all the data in the employees table then I used WHERE in order to filter department based on what the team is asking for.

Retrieve all employees not in IT

Your team needs to make one more update. This update was already made to employee computers in the Information Technology department. The team needs information about employees who are not in that department. Here I created an SQL query to filter for employees ouside the IT department

```
MariaDB [organization]> SELECT *
    -> FROM employees
    -> WHERE NOT department = 'Information Technology';
+-------------+--------------+----------+-----------------+-------------+
| employee_id | device_id    | username | department      | office      |
+-------------+--------------+----------+-----------------+-------------+
|        1000 | a320b137c219 | elarson  | Marketing       | East-170    |
|        1001 | b239c825d303 | bmoreno  | Marketing       | Central-276 |
|        1002 | c116d593e558 | tshah    | Human Resources | North-434   |
|        1003 | d394e816f943 | sgilmore | Finance         | South-153   |
|        1004 | e218f877g788 | eraab    | Human Resources | South-127   |
|        1005 | f551g340h864 | gesparza | Human Resources | South-366   |
|        1007 | h174i497j413 | wjaffrey | Finance         | North-406   |
|        1008 | i858j583k571 | abernard | Finance         | South-170   |
|        1009 | NULL         | lrodriqu | Sales           | South-134   |
|        1010 | k2421212m542 | jlansky  | Finance         | South-109   |
|        1011 | l748m120n401 | drosas   | Sales           | South-292   |
|        1015 | p611q262r945 | jsoto    | Finance         | North-271   |
|        1016 | q793r736s288 | sbaelish | Human Resources | North-229   |
```

I used the query “SELECT * FROM employees” to select data from the table employees then I added a conditional statement “WHERE NOT” since this query filters employees from the department column who are not in the information technology department.

Summary

Here I applied filters to SQL queries to get information from tables and I used the AND, OR, NOT operators to filter for specific informations as well as using LIKE and % sign to filter for patterns.