

Claude Code — implementation prompts: Signals page event cards + flip

This replaces **Prompt 4** in `CLAUDE_CODE_EVENTS_PROMPTS.md`. Run Prompts 0–3 from that file first, because this assumes the `events` and `event_signal_links` tables exist.

Prototype reference (commit these so Claude Code can read them):

- `components/page-signals.jsx`: the page, view toggle, filters, flip state and jump-between-views logic
- `components/events.jsx`: `FlipCard`, `EventCard`, `SignalCardBack`, `EventCount`, `FlipHint`, `LikelihoodPill`, `eventCategory`, `looksLikeEvent`, `AddSignalModal`
- `styles.css`: `.chip-*` STEEP colours and `.badge-high/mid/low`
- `data.js`: the `events` seed, showing the shape each card expects

Paste one prompt per message.

Prompt A — Orient (read-only)

Read, then report back before changing anything:

- components/page-signals.jsx and components/events.jsx (the prototype of this feature, the source of truth for layout and behaviour)
- styles.css (.chip-* and .badge-* classes)
- data.js (the events seed)
- the production Signals page component, its data hooks, and the events / event_signal_links schema from the previous migration

Answer, no code changes:

1. Where does the production Signals page get signals from, and what's the cleanest place to also load events + event_signal_links in the same fetch?
2. Does the events table have `category` and `description` columns? The event cards need both.
3. Is there an existing Stars component and chip/badge classes in production that match the prototype's, or do they need porting?
4. How does the production app handle scroll containers on this page? (Jump-to-card scrolls the page's own scroll container, never window, and never uses scrollToView.)

Prompt B — Schema top-up

The event cards need a STEEP category and a description on each event. Write one new migration and do not edit existing ones.

- If missing, add `events.category text` with check in ('Social','Technology','Economic','Ecological','Political').
- If missing, add `events.description text` (the prototype calls it `body`; use `description` in the DB and map it in the client).
- Backfill category for existing events from the category of their first linked signal (lowest created_at on event_signal_links). Leave it null if the event has no links.
- Do not make category NOT NULL yet. The client falls back to the first linked signal's category when it's null, exactly like `eventCategory()` in components/events.jsx.

RLS is unchanged. Confirm the existing events policies still apply to the new columns.

Prompt C — Data layer

Add a hook `useSignalsWithEvents(projectId)` that returns `{ signals, events, links, loading, error, refetch }`.

- One round-trip where possible: signals, events and event_signal_links for the project, all under RLS through the Supabase client.
- Return events in the shape the prototype components expect:
`{ id, category, body, status: 'observed'|'possible', date, title, impact, likelihood, source, indicatorId, wildcard, precursor, links: [{ sigId, toward }] }`
Map from DB columns:
 - description -> body
 - occurred_on (formatted 'Mon YYYY') or window_label -> date
 - is_wildcard -> wildcard
 - likelihood lowercase -> Title Case
 - indicators.event_id reverse lookup -> indicatorId
- Subscribe to realtime changes on events and event_signal_links for the project so a news-match acceptance elsewhere updates the cards without a reload.
- No N+1 queries. No client-side joins over unbounded lists; paginate if the project has more than 500 events.

Prompt D — Port the card components

Port these components from components/events.jsx into the production codebase, matching the repo's file and styling conventions. Keep the visual output identical to the prototype.

1. FlipCard({ id, flipped, front, back, focused })
 - Both faces share a single CSS grid cell (grid-area: 1/1) so the card height = the taller face. Do not use absolute positioning.
 - rotateY(180deg) with perspective 1200px, 0.45s cubic-bezier(.2,.7,.2,1), backface-visibility hidden on both faces.
 - CRITICAL: set pointer-events: none on the hidden face, and aria-hidden on it. Without this, clicks on a flipped card hit buttons on the back of the hidden face. This was a real bug in the prototype.
 - Honour prefers-reduced-motion: swap instantly with no rotation.
 - `focused` renders a 2px #F97316 ring with a soft outer halo, used after a cross-view jump.
 - Put data-card-id={id} on the root for scroll targeting.

2. EventCard: front face must match the signal card exactly (same border #E5E7EB, radius 10, padding 14, fonts, sizes):

- Row 1: colour-coded STEEP chip (className chip chip-<category>) on the left. On the right, mono 10.5px "<STATUS> · <date>" in #9CA3AF, or #7C3AED for wildcards.
- Title 14px/600, description 12.5px #6B7280.
- Wildcards only: "EARLY SIGN <precursor>".
- IMPACT row: mono label (fixed 78px width) + Stars. Observed events show their source right-aligned on this row.
- LIKELIHOOD row, ALWAYS shown:
 - possible/wildcard: a 3-segment bar (orange for filled segments) plus a badge-high/mid/low pill reading High / Medium / Low, or "Not set".
 - observed: a neutral "Occurred" pill. Likelihood never applies once something has happened.
- Footer divider: "N linked force(s)", an INDICATOR tag if an indicator references the event, and a "FORCES ⚡" flip hint.

Back face: "LINKED FORCES", then each linked signal as a button showing its STEEP chip, title, and "pushes toward <pole> →". Clicking one jumps to that signal in the Forces view.

3. SignalCardBack: "LINKED EVENTS", the signal title, then its events (observed first, then possible), each as a button with:

- title
- date (observed) or likelihood pill (possible)
- "→ <pole>"
- a solid border for observed events, dashed for possible (orange #FDBA74), dashed purple (#C4B5FD) for wildcards

Clicking an event jumps to it in the Events view. Footer: a "Timeline & details" button that opens the existing signal detail modal, plus a "FORCE ⚡" hint.

4. EventCount: "● N evidence" (solid dot) and "○ N ahead" (dashed dot), shown on the signal card front footer next to an "EVENTS ⚡" flip hint.

Every inner button inside a face must stopPropagation so it doesn't also flip the card.

Prompt E — Rebuild the Signals page

Update the production Signals page to match components/page-signals.jsx.

Header:

- Title "Signals Library".
- Subtitle "Forces that could shape your focal question. Specific events, past or future, attach to a force. Click any card to flip it."
- Right side: segmented toggle "Forces · N" / "Events · N" (labels nowrap), Sort, and "+ Add Signal". The header row wraps on narrow widths.

Filters:

- The STEEP filter pills (All, Social, Technology, Economic, Ecological, Political) apply to BOTH views. Events filter by their category, falling back to the first linked signal's category.
- In the Events view only, a second row of status filters: All / Observed / Possible / Wildcards.

Forces view: the existing signal card grid (repeat(auto-fill, minmax(250px,1fr)), gap 12), each card wrapped in FlipCard. Front = the existing signal card plus the EventCount footer. Back = SignalCardBack. "+ Add to Matrix" and the "..." details button stay on the front.

Events view: three groups (Observed, Possible, Wildcards), each with a header "<Label> · <count>" (nowrap) and a subtitle:

- Observed: "Evidence that a force is moving"
- Possible: "Future events to watch – likelihood is per event, never per scenario"
- Wildcards: "Low-likelihood, high-impact – kept off the matrix"

Each group is the same card grid of EventCards. Show an empty-state line when a group has no events in the current filter.

Flip state: a single map keyed by card id, held in page state. Flipping one card doesn't affect others.

Cross-view jump, jump(toView, id):

1. switch the view
2. reset the STEEP filter (and the status filter when going to Events) so the target can't be hidden
3. un-flip the target card
4. set focusId
5. after layout, scroll the PAGE'S scroll container so the card sits about 80px from the top. Use container.scrollTo with a computed offset, never scrollIntoView.
6. clear focusId after about 2.6s

Add Signal: keep AddSignalModal and looksLikeEvent from the prototype.

- When the title reads like an event, default to "Add as event". Require a target force and a "pushes toward" pole, offer a likelihood for possible events, and set the event's category from the target force.
- After adding an event, jump to it in the Events view.
- The regex must match both past tense ("added") and present-tense headline verbs ("adds").

Reuse existing styles. Do not restyle anything outside what the prototype changes.

Prompt F — Verify

Verify without changing behaviour. Fix only what's broken, and report results.

1. Hidden-face clicks: flip a signal card, then click where "+ Add to Matrix" sits on the front. Assert no navigation happens. Repeat for event cards.
2. Card height: a card with a long back face (a signal with 5+ events) grows to fit. Nothing is clipped or overlaps the next row.
3. Likelihood: every possible and wildcard card shows the LIKELIHOOD row with a bar and a pill. Every observed card shows "Occurred". No observed card shows High/Medium/Low.
4. STEEP chips: every event card shows a coloured category chip, including events whose category column is null (fallback to the linked signal).
5. Jumps: signal back → event lands in the Events view with the card highlighted and scrolled into position, even when a STEEP filter was active that would have hidden it. Same for event back → signal.
6. Filters: the STEEP filter applies in both views, and the status filter only appears in Events.
7. Realtime: accept a news-match proposal in another tab, then assert the event card moves from Possible to Observed and its likelihood row changes to "Occurred", with no reload.
8. Reduced motion: with prefers-reduced-motion, flips are instant.
9. Keyboard: cards are focusable. Enter or Space flips a card. Inner buttons are reachable only on the visible face.
10. Heuristic: "US adds 14 firms to Entity List" and "Tariff hike in Q3 2027" trigger the event nudge. "Direction of SEA foreign-ownership regulation" does not.

Hold the implementer to

- **The prototype is the spec.** Card anatomy, colours and copy come from `components/events.jsx` and `components/page-signals.jsx`. Don't reinterpret them.
- **Hidden faces must not be clickable.** It's the one non-obvious bug in a flip UI, and it silently triggers the wrong action.
- **Likelihood is per event only.** It shows on event cards and nowhere on scenarios.