


Garbage collection



A *garbage collector* is part of the run-time system: it reclaims heap-allocated records that are no longer used.

A garbage collector should:


- reclaim *all* unused records;
- spend very little time per record;
- not cause significant delays; and
- allow all of memory to be used.

These are difficult and often conflicting requirements.

Life without garbage collection:

- unused records must be explicitly deallocated;
- superior if done correctly;
- but it is easy to miss some records; and
- it is dangerous to handle pointers.

Memory leaks in real life (`ical` v.2.1):



Which records are *dead*, i.e. no longer in use?

Ideally, records that will never be accessed in the future execution of the program.


But that is of course undecidable...

Basic conservative assumption:

A record is *live* if it is reachable from a stack-based program variable, otherwise dead.

Dead records may still be pointed to by other dead records.

A heap with live and dead records:



The mark-and-sweep algorithm:

- explore pointers starting from the program variables, and *mark* all records encountered;
- *sweep* through all records in the heap and reclaim the unmarked ones; also
- unmark all marked records.

Assumptions:

- we know the size of each record;
- we know which fields are pointers; and
- reclaimed records are kept in a **freelist**.



Pseudo code for mark-and-sweep:

```
function DFS( $x$ )  
  if  $x$  is a pointer into the heap then  
    if record  $x$  is not marked then  
      mark record  $x$   
      for  $i:=1$  to  $|x|$  do  
        DFS( $x.f_i$ )
```

```
function Mark()  
  for each program variable  $v$  do  
    DFS( $v$ )
```

```
function Sweep()  
   $p$  := first address in heap  
  while  $p$  < last address in heap do  
    if record  $p$  is marked then  
      unmark record  $p$   
    else  
       $p.f_1$  := freelist  
      freelist :=  $p$   
       $p$  :=  $p$  + sizeof(record  $p$ )
```

Marking and sweeping:



Analysis of mark-and-sweep:

- assume the heap has size H words; and
- assume that R words are reachable.

The cost of garbage collection is:

$$c_1 R + c_2 H$$

Realistic values are:

$$10R + 3H$$

The cost per reclaimed word is:

$$\frac{c_1 R + c_2 H}{H - R}$$

- if R is close to H , then this is expensive;
- the lower bound is c_2 ;
- increase the heap when $R > 0.5H$; then
- the cost per word is $c_1 + 2c_2 \approx 16$.

Other relevant issues:

- The DFS recursion stack could have size H (and has at least size $\log H$), which may be too much; however, the recursion stack can cleverly be embedded in the fields of marked records (pointer reversal).
- Records can be kept sorted by sizes in the **freelist**. Records may be split into smaller pieces if necessary.
- The heap may become *fragmented*: containing many small free records but none that are large enough.

The reference counting algorithm:

- maintain a counter of the references to each record;
- for each assignment, update the counters appropriately; and
- a record is dead when its counter is zero.

Advantages:

- is simple and attractive;
- catches dead records immediately; and
- does not cause long pauses.

Disadvantages:

- cannot detect cycles of dead records; and
- is much too expensive.

Pseudo code for reference counting:

```
function Increment( $x$ )  
     $x.\text{count} := x.\text{count} + 1$ 
```

```
function Decrement( $x$ )  
     $x.\text{count} := x.\text{count} - 1$   
    if  $x.\text{count} = 0$  then  
        PutOnFreelist( $x$ )
```

```
function PutOnFreelist( $x$ )  
    Decrement( $x.f_1$ )  
     $x.f_1 := \text{freelist}$   
     $\text{freelist} := x$ 
```

```
function RemoveFromFreelist( $x$ )  
    for  $i := 2$  to  $|x|$  do  
        Decrement( $x.f_i$ )
```

The stop-and-copy algorithm:

- divide the heap into two parts;
- only use one part at a time;
- when it runs full, copy live records to the other part; and
- switch the roles of the two parts.


Advantages:

- allows fast allocation (no `freelist`);
- avoids fragmentation;
- collects in time proportional to R ; and
- avoids stack and pointer reversal.

Disadvantage:

- wastes half your memory.

Before and after stop-and-copy:




- `next` and `limit` indicate the available heap space; and
- copied records are contiguous in memory.

Pseudo code for stop-and-copy:

```
function Forward( $p$ )  
  if  $p \in$  from-space then  
    if  $p.f_1 \in$  to-space then  
      return  $p.f_1$   
    else  
      for  $i:=1$  to  $|p|$  do  
         $\text{next}.f_i := p.f_i$   
       $p.f_1 := \text{next}$   
       $\text{next} := \text{next} + \text{sizeof}(\text{record } p)$   
      return  $p.f_1$   
  else return  $p$ 
```

```
function Copy()  
   $\text{scan} := \text{next} :=$  start of to-space  
  for each program variable  $v$  do  
     $v := \text{Forward}(v)$   
  while  $\text{scan} < \text{next}$  do  
    for  $i:=1$  to  $|\text{scan}|$  do  
       $\text{scan}.f_i := \text{Forward}(\text{scan}.f_i)$   
     $\text{scan} := \text{scan} + \text{sizeof}(\text{record scan})$ 
```

Snapshots of stop-and-copy:



before

after forwarding p and q and scanning 1 record

Analysis of stop-and-copy:

- assume the heap has size H words; and
- assume that R words are reachable.

The cost of garbage collection is:

$$c_3 R$$

A realistic value is:

$$10R$$

The cost per reclaimed word is:

$$\frac{c_3 R}{\frac{H}{2} - R}$$

- this has no lower bound as H grows;
- if $H = 4R$ then the cost is $c_3 \approx 10$.

Earlier assumptions:

- we know the size of each record; and
- we know which fields are pointers.

For object-oriented languages, each record already contains a pointer to a class descriptor.

For general languages, we must sacrifice a few bytes per record.

We use mark-and-sweep or stop-and-copy.

But garbage collection is still expensive:
 ≈ 100 instructions for a small object!

Each algorithm can be further extended by:

- generational collection (to make it run faster);
and
- incremental (or concurrent) collection (to make it run smoother).

Generational collection:

- observation: the young die quickly;
- hence the collector should focus on young records;
- divide the heap into generations:
 G_0, G_1, G_2, \dots ;
- all records in G_i are younger than records in G_{i+1} ;
- collect G_0 often, G_1 less often, and so on; and
- promote a record from G_i to G_{i+1} when it survives several collections.

How to collect the G_0 generation:

- roots are no longer just program variables but also pointers from G_1, G_2, \dots ;
- it might be very expensive to find those pointers;
- fortunately, they are rare; so
- we can try to remember them.

Ways to remember:

- maintain a list of all updated records (use marks to make this a set); or
- mark pages of memory that contain updated records (in hardware or software).

Incremental collection:

- garbage collection may cause long pauses;
- this is undesirable for interactive or real-time programs; so
- try to interleave the garbage collection with the program execution.

Two players access the heap:

- the *mutator*: creates records and moves pointers around; and
- the *collector*: tries to collect garbage.

Some invariants are clearly required to make this work.

The mutator will suffer some slowdown to maintain these invariants.